



TEST REPORT

No. I17D00219-MPE01

For

Client : Shanghai Simcom Ltd.

Production : LTE-FDD/HSPA MODULE

Model Name : SIM7600A

FCC ID: UDV-201709

Issued date: 2017-9-27

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of ECIT Shanghai.

Test Laboratory:

ECIT Shanghai, East China Institute of Telecommunications

Add: 7F, G Area, No.668, Beijing East Road, Huangpu District, Shanghai, P. R. China

Tel: (+86)-021-63843300, E-Mail: welcome@ecit.org.cn

Revision Version

Report Number	Revision	Date	Memo
I17D00219-MPE01	00	2017-9-27	Initial creation of test report

CONTENTS

1. TEST LABORATORY	4
1.1. TESTING LOCATION	4
1.2. PROJECT DATA	4
1.3. SIGNATURE	4
2. CLIENT INFORMATION	5
2.1. APPLICANT INFORMATION	5
2.2. MANUFACTURER INFORMATION	5
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	6
3.1. ABOUT EUT	6
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	6
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	6
4. REFERENCE DOCUMENTS	7
4.1. APPLICABLE STANDARDS	7
4.2. TEST LIMITS	7
5. TEST RESULTS	8
5.1. RF POWER OUTPUT	8
5.2. CALCULATION INFORMATION	8
5.3. RESULT OF WCDMA BAND II	8
5.4. RESULT OF WCDMA BAND V	9
5.5. RESULT OF LTE BAND2	9
5.6. RESULT OF LTE BAND4	10
5.7. RESULT OF LTE BAND12	10

1. Test Laboratory

1.1. Testing Location

Company Name:	ECIT Shanghai, East China Institute of Telecommunications
Address:	7-8F, G Area, No. 668, Beijing East Road, Huangpu District, Shanghai, P. R. China
Postal Code:	200001
Telephone:	(+86)-021-63843300
Fax:	(+86)-021-63843301
FCC Registration NO.:	489729

1.2. Project Data

Project Leader:	Zhou Yan
-----------------	----------


1.3. Signature



Yan Hang
(Prepared this test report)



Fu Erliang
(Reviewed this test report)



Zheng Zhongbin
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: Shanghai Simcom Ltd.
Address /Post: SIM Technology Building.,No.633, Jinzhong Rd,Changning District,
Shanghai, P.R.China
Telephone: 021-32523134

2.2. Manufacturer Information

Company Name: Shanghai Simcom Ltd.
Address /Post: SIM Technology Building.,No.633, Jinzhong Rd,Changning District,
Shanghai, P.R.China
Telephone: 021-32523134

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

EUT Description	LTE-FDD/HSPA MODULE
Model name	SIM7600A
WCDMA Frequency Band	WCDMA Band 850/1900
LTE Frequency Band	LTE Band2/4/12
Antenna Type	External Antenna
FCC ID:	UDV-201709

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	Date of receipt
N01	861475030055166	V1.02	2017.9.21

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	Model	SN	Manufacturer
AE1	RF cable	N/A	N/A	N/A
AE2	Dummy Battery	N/A	N/A	N/A

*AE ID: is used to identify the test sample in the lab internally.

4. Reference Documents

4.1. Applicable Standards

The MPE report was carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Part 2.1091.

The limits standard is based on the Council Recommendation 1999/519/EC.

FCC CFR 47, Part 2, FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS

Section 1.1310 Radiofrequency radiation exposure limits

4.2. Test Limits

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

Limits for Occupational / Controlled Exposure

Frequency Range [MHz]	Electric Field Strength [V/m]	Magnetic Field Strength (H) [A/m]	Power Density (S) [mW/cm ²]	Averaging Times E ² , H ² or S [minutes]
0.3 – 3.0	614	1.63	(100)*	6
3.0 – 30	1824/f	4.89/f	(900/f)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	--	--	F/300	6
1500 - 100000	--	--	5	6

Limits for General Population / Uncontrolled Exposure

Frequency Range [MHz]	Electric Field Strength [V/m]	Magnetic Field Strength (H) [A/m]	Power Density (S) [mW/cm ²]	Averaging Times E ² , H ² or S [minutes]
0.3 – 1.34	614	1.63	(100)*	30
1.34 – 30	824/f	2.19/f	(180/f)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	--	--	F/1500	30
1500 - 100000	--	--	1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

For the DUT, the limits for General Population / Uncontrolled Exposure are applicable.

5. Test Results

5.1. RF Power Output

Frequency Band	Highest Power Output(dBm)	Antenna Gain(dBi)
WCDMA Band II	25	1.87
WCDMA Band V	25	0.91
LTE Bnad2	25.7	1.87
LTE Bnad4	25.7	3.49
LTE Bnad12	25.7	1.57

5.2. Calculation Information

For conservative evaluation consideration, only maximum power of each frequency band based on the tighter limits respectively are used to calculate the boundary power density.

Based on the FCC KDB 447498 D01 and 47 CFR §2.1091, the DUT is evaluated as a mobile device.

$$\text{Given } S = \frac{P \times G}{4\pi d^2} \quad \text{Equation 1}$$

Where

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

5.3. Result of WCDMA Band II

Test Results: MPE Limit Calculation: the EUT's operating frequencies @ 1852.4 – 1907.6 MHz; as per the original test report the highest power is 316.23mW,. The maximum gain is 1.87dBi(numeric gain 1.54).The resulted power density at a distance of 20cm can be deducted as follows:

$$\text{Power Density} = P \times G \times \text{Duty Cycle} / (4 \pi R^2) = 316.23 \times 1.54 \times 1 / (4 \pi \times 20^2) = 0.0987 \text{ mW/cm}^2$$

The MPE limit for Occupational/Controlled Exposure is shown in the FCC KDB 447498 D01 and 47 CFR §2.1091, can be calculated as follows:

$$\text{MPE limit} = 1 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore the DUT

in this band is compliant with the FCC rules on RF exposure.

5.4. Result of WCDMA Band V

Test Results: MPE Limit Calculation: the EUT's operating frequencies @ 826.4 – 846.6 MHz; as per the original test report the highest power is 316.23mW,. The maximum gain is 0.91dBi(numeric gain 1.23).The resulted power density at a distance of 20cm can be deducted as follows:

$$\text{Power Density} = P * G * \text{Duty Cycle} / (4 * \pi * R^2) = 316.23 * 1.23 * 1 / (4 * \pi * 20^2) = 0.078 \text{ mW/cm}^2$$

The MPE limit for Occupational/Controlled Exposure is shown in the FCC KDB 447498 D01 and 47 CFR §2.1091, can be calculated as follows:

$$\text{MPE limit} = F / 1500 = 826.4 / 1500 = 0.551 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore the DUT in this band is compliant with the FCC rules on RF exposure.

5.5. Result of LTE Band2

Test Results: MPE Limit Calculation: the EUT's operating frequencies @ 1850 – 1910 MHz; as per the original test report the highest power is 371.54mW,. The maximum gain is 1.87dBi(numeric gain 1.54).The resulted power density at a distance of 20cm can be deducted as follows:

$$\text{Power Density} = P * G * \text{Duty Cycle} / (4 * \pi * R^2) = 371.54 * 1.54 * 1 / (4 * \pi * 20^2) = 0.105 \text{ mW/cm}^2$$

The MPE limit for Occupational/Controlled Exposure is shown in the FCC KDB 447498 D01 and 47 CFR §2.1091, can be calculated as follows:

$$\text{MPE limit} = 1 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore the DUT in this band is compliant with the FCC rules on RF exposure.

5.6. Result of LTE Band4

Test Results: MPE Limit Calculation: the EUT's operating frequencies @ 1710 – 1785 MHz; as per the original test report the highest power is 371.54mW,. The maximum gain is 3.49dBi(numeric gain 2.234).The resulted power density at a distance of 20cm can be deducted as follows:

$$\text{Power Density} = P \cdot G \cdot \text{Duty Cycle} / (4 \pi R^2) = 371.54 \cdot 2.05 \cdot 1 / (4 \pi \cdot 20^2) = 0.165 \text{ mW/cm}^2$$

The MPE limit for Occupational/Controlled Exposure is shown in the FCC KDB 447498 D01 and 47 CFR §2.1091, can be calculated as follows:

$$\text{MPE limit} = 1 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore the DUT in this band is compliant with the FCC rules on RF exposure.

5.7. Result of LTE Band12

Test Results: MPE Limit Calculation: the EUT's operating frequencies @ 698 – 716 MHz; as per the original test report the highest power is 371.54mW,. The maximum gain is 1.57dBi(numeric gain 1.435).The resulted power density at a distance of 20cm can be deducted as follows:

$$\text{Power Density} = P \cdot G \cdot \text{Duty Cycle} / (4 \pi R^2) = 371.54 \cdot 1.469 \cdot 1 / (4 \pi \cdot 20^2) = 0.106 \text{ mW/cm}^2$$

The MPE limit for Occupational/Controlled Exposure is shown in the FCC KDB 447498 D01 and 47 CFR §2.1091, can be calculated as follows:

$$\text{MPE limit} = F / 1500 = 698 / 1500 = 0.465 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore the DUT in this band is compliant with the FCC rules on RF exposure.

Note: $\pi=3.1416$

So the product is under the MPE limits. All is pass.

*******End The Report*******