



Engineering and Testing for EMC and Safety Compliance

TYPE CERTIFICATION REPORT

Vertex Standard Co., LTD.
4-8-8, Nakameguro, Meguro-ku, Tokyo 153-8644, Japan
81-(0) 3-5725-6122
MODEL: VX_900U/600U
FCC ID: K66VX-900U

December 8, 2000

STANDARDS REFERENCED FOR THIS REPORT	
PART 2: 1999	FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS
PART 15: 1999	§15.109: RADIATED EMISSIONS LIMITS
PART 22: 1998	PUBLIC MOBILE SERVICES
PART 74: 1998	LOW POWER AUXILIARY STATION
PART 90: 1998	PRIVATE LAND MOBILE RADIO SERVICES
PART 95 (A): 1998	GENERAL MOBILE RADIO SERVICES
ANSI C63.4-1992	STANDARD FORMAT MEASUREMENT/TECHNICAL REPORT PERSONAL COMPUTER AND PERIPHERALS
ANSI/TIA/EIA603- 1992	LAND MOBILE FM OR PM COMMUNICATIONS EQUIPMENT MEASUREMENT AND PERFORMANCE STANDARDS
ANSI/TIA/EIA 603-1-1998	ADDENDUM TO ANSI/TIA/EIA 603-1992
RSS-119, Issue 5: 1996	LAND MOBILE AND FIXED RADIO TRANSMITTERS AND RECEIVERS.27.41 TO 960.0 MHz

FCC Rules Parts	Frequency Range	Output Power (W)	Freq. Tolerance	Emission Designator
90.210	450-485 MHz	5	2.5 ppm	11K0F3E
90, 22, 74, 95	450-485 MHz	5	2.5 ppm	16K0F3E
90.210	450-485 MHz	2.5	2.5 ppm	11K0F3E
90, 22, 74, 95	450-485 MHz	2.5	2.5 ppm	16K0F3E
90.210	450-485 MHz	1.0	2.5 ppm	11K0F3E
90, 22, 74, 95	450-485 MHz	1.0	2.5 ppm	16K0F3E
90.210	450-485 MHz	0.25	2.5 ppm	11K0F3E
90, 22, 74, 95	450-485 MHz	0.25	2.5 ppm	16K0F3E
Canadian	Frequency Range	Output Power (W)	Freq. Tolerance	
RSS-119	450-485 MHz	5	2.5 ppm	16K0F3E
RSS-119	450-485 MHz	5	2.5 ppm	11K0F3E

REPORT PREPARED BY:

EMC Engineer: Desmond Fraser
Technical Writer: Melissa Fleming

Document Number: 2000468

No part of this report may be reproduced without the full written approval of Rhein Tech Laboratories, Inc.

360 Herndon Parkway, Suite 1400
Herndon, VA 20170
Phone: 703-689-0368; Fax: 703-689-2056; Metro: 703-471-6441



TABLE OF CONTENTS

1	GENERAL INFORMATION.....	4
1.1	TEST FACILITY	4
1.2	1.2 RELATED SUBMITTAL(S)/GRANT(S)	4
2	CONFORMANCE STATEMENT	5
3	TESTED SYSTEM DETAILS	6
3.2	CONFIGURATION OF TESTED SYSTEM	6
4	FIELD STRENGTH CALCULATION	7
5	CONDUCTED MEASUREMENT	8
5.1	CONDUCTED MEASUREMENT TEST RESULTS.....	9
6	RADIATED MEASUREMENT.....	10
7	FCC RULES AND REGULATIONS PART 2 §2.1046 (A): RF POWER OUTPUT: CONDUCTED.....	11
7.1	TEST PROCEDURE	11
7.2	TEST DATA.....	11
7.3	TEST EQUIPMENT	11
8	PART 2.1046 (A) RF POWER OUTPUT: RADIATED - ERP.....	12
8.1	TEST PROCEDURE	12
8.2	TEST DATA.....	13
8.3	TEST EQUIPMENT	13
9	FCC RULES AND REGULATIONS PART 2 §2.1051: SPURIOUS EMISSIONS AT ANTENNA TERMINALS	14
9.1	TEST PROCEDURE	14
9.2	TEST DATA.....	14
9.2.1	CFR Part 90 Requirements.....	14
10	FCC RULES AND REGULATIONS PART 2 §2.1053 (A): FIELD STRENGTH OF SPURIOUS RADIATION	16
10.1	TEST PROCEDURE	16
10.2	TEST DATA.....	16
10.3	TEST EQUIPMENT	16
11	FCC RULES AND REGULATIONS PART 2 §2.1049 (C) (1): OCCUPIED BANDWIDTH.....	17
11.1	TEST PROCEDURE	17
11.2	TEST DATA.....	17
11.2.1	Channel 1: 5W for 25 kHz Channel Bandwidth: Mask B (Audio Modulation: 2,500 Hz).....	17
11.2.2	Channel 4: 5 W for 12.5 kHz Channel Bandwidth: Mask D (Audio Modulation: 2,500 Hz).....	18
11.3	TEST EQUIPMENT	18
12	FCC RULES AND REGULATION PART 2 §2.1055: FREQUENCY STABILITY	19
12.1	TEST PROCEDURE	19
12.2	TEST DATA.....	19
12.2.1	Frequency stability/Temperature variation	19
12.2.2	Frequency Stability/Voltage Variation.....	22
12.3	7.3 TEST EQUIPMENT	23



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

13	FCC RULES AND REGULATIONS PART 2 §2.1047 (A): MODULATION CHARACTERISTICS - AUDIO FREQUENCY RESPONSE	24
13.1	TEST PROCEDURE	24
13.2	TEST DATA.....	24
13.2.1	Channel 1 – 25 kHz Audio Frequency Response.....	24
13.2.2		24
13.2.3	Channel 4 – 12.5 kHz Audio Frequency Response.....	25
13.3	TEST EQUIPMENT	25
14	FCC RULES AND REGULATIONS PART 2 §2.1047 (A): MODULATION CHARACTERISTICS - AUDIO LOW PASS FILTER RESPONSE.....	26
14.1	TEST PROCEDURE	26
14.2	TEST DATA.....	26
14.3	TEST EQUIPMENT	27
15	FCC RULES AND REGULATIONS PART 2 §2.1047 (B): MODULATION CHARACTERISTICS - MODULATION LIMITING	28
15.1	TEST PROCEDURE	28
15.2	TEST DATA.....	28
15.3	TEST EQUIPMENT	31
16	FCC RULES AND REGULATIONS PART 90 §90.214 : TRANSIENT FREQUENCY BEHAVIOR.....	32
16.1	TEST PROCEDURE	32
16.2	TEST DATA WIDE BAND.....	32
16.3	TEST EQUIPMENT	44
17	FCC RULES AND REGULATIONS PART 2.202: NECESSARY BANDWIDTH AND EMISSION BANDWIDTH	45
18	RECEIVER DATA	46

APPENDIX LISTING

APPENDIX A: TEST CONFIGURATION PHOTOGRAPHS	47
APPENDIX B: LABEL INFORMATION	49
APPENDIX C: PRODUCT DESCRIPTION	50
APPENDIX D: SCHEMATICS	51
APPENDIX E: USER'S MANUAL	52
APPENDIX F: INTERNAL PHOTOGRAPHS	53
APPENDIX G: EXTERNAL PHOTOGRAPHS	54



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

1 GENERAL INFORMATION

The following Report of a Type Certification is prepared on behalf of **Vertex Standard Co., LTD** in accordance with the Federal Communications Commissions and Industry Canada Rules and Regulations. The Equipment Under Test (EUT) was the **VX_900U/600U**. The test results reported in this document relate only to the item that was tested. **The VX-900U and the VX-600U are identical both electrically and mechanically. The only difference between both units is an LCD display that is removed from the VX-900U to form the VX-600U. The VX-900U/600U supports 5 watt, 2.5 watt, 1 watt, and 0.25 watt. It was determined during testing that the VX-900U 5 watt and 2.5 watt were the worst-case. Hence through out this report the VX-900U was used for testing. The manufacturer intends to remove the LCD display measured at 1 inch by 0.5 inch leaving all other electronic and mechanical supporting components.**

All measurements contained in this application were conducted in accordance with FCC Rules and Regulations CFR 47, Industry Canada RSS-119, and ANSI C63.4 Methods of Measurement of Radio Noise Emissions, 1992. The instrumentation utilized for the measurements conforms to the ANSI C63.4 standard for EMI and Field Strength Instrumentation. Calibration checks are performed regularly on the instruments, and all accessories including high pass filter, coaxial attenuator, preamplifier and cables.

1.1 TEST FACILITY

The open area test site and conducted measurement facility used to collect the radiated data is located on the parking lot of Rhein Tech Laboratories, Inc. 360 Herndon Parkway, Suite 1400, Herndon, Virginia 20170. This site has been fully described in a report dated March 3, 1994, submitted to and approved by the Federal Communication Commission to perform AC line conducted and radiated emissions testing (ANSI C63.4 1992).

1.2 1.2 RELATED SUBMITTAL(S)/GRANT(S)

This is an original application report.




COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

2 CONFORMANCE STATEMENT

We, the undersigned, hereby declare that the equipment tested and referenced in this report conforms to the identified standard(s) as described in this attached test record. No modifications were made to the equipment during testing in order to achieve compliance with these standards.


Furthermore, there was no deviation from, additions to or exclusions from the FCC Part 2, FCC Part 90 and Industry Canada RSS-119 Certification methodology.

Signature: 

Date: December 8, 2000

Typed/Printed Name: Desmond A. Fraser

Position: President
(NVLAP Signatory)



Accredited by the National Voluntary Accreditation Program for the specific scope of accreditation under Lab Code 200061-0.

Note: This report may not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.




COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

3 TESTED SYSTEM DETAILS

Listed below are the identifiers and descriptions of all equipment, cables, and internal devices used with the EUT for this test, as applicable.

PART	MANUFACTURER	MODEL	SERIAL NUMBER	FCC ID
RADIO	VERTEX	VX-900U/600U	N/A	K66VX-900U
ANTENNA WHIP	VERTEX	N/A	N/A	N/A
AUDIO TEST CABLE	VERTEX	N/A	N/A	N/A
AUDIO TEST BOX	VERTEX	TUNING I/F	N/A	N/A
BATTERY	VERTEX	FNB-V68L1	N/A	N/A
MICROPHONE / SPEAKER	VERTEX	MH-50E7A	N/A	N/A

3.1 CONFIGURATION OF TESTED SYSTEM





COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

4 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FI(\text{dBuV/m}) = SAR(\text{dBuV}) + SCF(\text{dB/m})$$

FI = Field Intensity

SAR = Spectrum Analyzer Reading

SCF = Site Correction Factor

The Site Correction Factor (SCF) used in the above equation is determined empirically, and is expressed in the following equation:

$$SCF(\text{dB/m}) = -PG(\text{dB}) + AF(\text{dB/m}) + CL(\text{dB})$$

SCF = Site Correction Factor

PG = Pre-amplifier Gain

AF = Antenna Factor

CL = Cable Loss

The field intensity in microvolts per meter can then be determined according to the following equation:

$$FI(\text{uV/m}) = 10^{FI(\text{dBuV/m})/20}$$

For example, assume a signal at a frequency of 125 MHz has a received level measured as 49.3 dBuV. The total Site Correction Factor (antenna factor plus cable loss minus preamplifier gain) for 125 MHz is -11.5 dB/m. The actual radiated field strength is calculated as follows:

$$49.3 \text{ dBuV} - 11.5 \text{ dB/m} = 37.8 \text{ dBuV/m}$$

$$10^{37.8/20} = 10^{1.89} = 77.6 \text{ uV/m}$$



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

5 CONDUCTED MEASUREMENT

The power line conducted emission measurements were performed in a Series 81 type shielded enclosure manufactured by Rayproof. The EUT was assembled on a wooden table 80 centimeters high. Power was fed to the EUT through a 50 ohm / 50 microhenry Line Impedance Stabilization Network (EUT LISN). The EUT LISN was fed power through an A.C. filter box on the outside of the shielded enclosure. The filter box and EUT LISN housing are bonded to the ground plane of the shielded enclosure. A second LISN, the peripheral LISN, provides isolation for the EUT test peripherals. This peripheral LISN was also fed A.C. power. A metal power outlet box, which is bonded to the ground plane and electrically connected to the peripheral LISN, powers the EUT host peripherals.

The spectrum analyzer was connected to the A.C. line through an isolation transformer. The 50-ohm output of the EUT LISN was connected to the spectrum analyzer input through a Solar 400 kHz high-pass filter. The filter is used to prevent overload of the spectrum analyzer from noise below 400 kHz. Conducted emission levels were measured on each current-carrying line with the spectrum analyzer operating in the CISPR quasi-peak mode (or peak mode if applicable). The analyzer's 6 dB bandwidth was set to 9 kHz. No video filter less than 10 times the resolution bandwidth was used. Average measurements are performed in linear mode using a 10 kHz resolution bandwidth, a 1 Hz video bandwidth, and by increasing the sweep time in order to obtain a calibrated measurement. The emission spectrum was scanned from (150/450) kHz to 30 MHz. The highest emission amplitudes relative to the appropriate limit were measured and have been recorded in this report.



COMPANY NAME: COM NET ERICSSON
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

5.1 CONDUCTED MEASUREMENT TEST RESULTS

Mode: 467.525MHz High Wide band
NEUTRAL SIDE (Line 1)

Temperature: 74°F					Humidity: 34%				
Emission Frequency (MHz)	Test Detector	Analyzer Reading (dBuV)	Site Correction Factor (dB)	Emission Level (dBuV)	FCC B QP Limit (dBuV)	FCC B QP Margin (dBuV)	FCC B AV Limit (dBuV)	FCC B AV Margin (dBuV)	Pass/Fail
0.464	Pk	23.3	0.8	24.1	48.0	-23.9	48.0	-23.9	Pass
0.596	Pk	23.1	0.9	24.0	48.0	-24.0	48.0	-24.0	Pass
0.798	Pk	21.0	0.9	21.9	48.0	-26.1	48.0	-26.1	Pass
2.698	Pk	19.3	1.5	20.8	48.0	-27.2	48.0	-27.2	Pass
8.490	Pk	16.2	2.3	18.5	48.0	-29.5	48.0	-29.5	Pass
15.700	Pk	18.6	3.0	21.6	48.0	-26.4	48.0	-26.4	Pass
27.810	Pk	16.4	3.4	19.8	48.0	-28.2	48.0	-28.2	Pass

Hot Side (L2)

Mode: 467.525 MHz high power wide band

HOT SIDE (Line 2)

Temperature: 74°F					Humidity: 34%				
Emission Frequency (MHz)	Test Detector	Analyzer Reading (dBuV)	Site Correction Factor (dB)	Emission Level (dBuV)	FCC B QP Limit (dBuV)	FCC B QP Margin (dBuV)	FCC B AV Limit (dBuV)	FCC B AV Margin (dBuV)	Pass/Fail
0.613	Pk	21.1	0.8	21.9	48.0	-26.1	48.0	-26.1	Pass
0.795	Pk	19.4	0.9	20.3	48.0	-27.7	48.0	-27.7	Pass
0.984	Pk	20.1	0.9	21.0	48.0	-27.0	48.0	-27.0	Pass
2.130	Pk	20.2	1.3	21.5	48.0	-26.5	48.0	-26.5	Pass
11.440	Pk	18.9	2.6	21.5	48.0	-26.5	48.0	-26.5	Pass
22.050	Pk	17.8	3.4	21.2	48.0	-26.8	48.0	-26.8	Pass

Pk = Peak; QP = Quasi-Peak; Av = Average

TEST PERSONNEL:

Signature: 

Date: November 29, 2000

Typed/Printed Name: Daniel Baltzell



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

6 RADIATED MEASUREMENT

Before final measurements of radiated emissions were made on the open-field three meter range, the EUT was scanned indoors at a three meter distance in order to determine its emissions spectrum signature. The physical arrangement of the test system and associated cabling was varied in order to determine the effect on the EUT's emissions in amplitude, direction and frequency. This process was repeated during final radiated emissions measurements on the open-field range, at each frequency, in order to insure that maximum emission amplitudes were attained.

Final radiated emissions measurements were made on the three-meter, open-field test site. The EUT was placed on a nonconductive turntable approximately 0.8 meters above the ground plane.

At each frequency, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters in order to determine the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarizations.

Note: Rhein Tech Laboratories, Inc. has implemented procedures to minimize errors that occur from test instruments, calibration, procedures, and test setups. Test instrument and calibration errors are documented from the manufacturer or calibration lab. Other errors have been defined and calculated within the Rhein Tech quality manual, section 6.1. Rhein Tech implements the following procedures to minimize errors that may occur: yearly as well as daily calibration methods, technician training, and emphasis to employees on avoiding error.



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

7 FCC RULES AND REGULATIONS PART 2 §2.1046 (A): RF POWER OUTPUT: CONDUCTED

7.1 TEST PROCEDURE

ANSI/TIA/EIA-603-1992, section 2.2.1

The EUT was connected to a coaxial attenuator having a 50 Ω load impedance.

7.2 TEST DATA

The following channel (in MHz) were tested: 450.025, 469.975, 487.975

The worst-case Output Power (highest) levels are shown.

CARRIER OUTPUT POWER (UNMODULATED)

Power Setting	RF Power measured (Watt)*
Low1	2.5
High	5

*Measurement accuracy: +/- 3%

Rated Power:

Power Setting	Rated Power (W)
Low1	2.5
High	5

7.3 TEST EQUIPMENT

Power Meter	HP437B	s/n 2949A02966
	HP 8901A	s/n 2545A04102 (power mode)
Power Sensor	HP8481B	s/n 2702A05059
Frequency Counter	HP8901A	s/n 2545A04102 (Frequency mode)



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

8 PART 2.1046 (A) RF POWER OUTPUT: RADIATED - ERP

8.1 TEST PROCEDURE

Substitution Method:

The EUT was setup at an antenna to EUT distance of 3 meters on an open area test site. The EUT was placed on a nonconductive turntable approximately 0.8 meters above the ground plane.

The physical arrangement of the EUT and associated cabling was varied in order to determine the effect on the EUT's emissions in amplitude, direction and frequency. At each frequency, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters in order to determine the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarizations.

The worst-case, maximum radiated emission was recorded and used as reference for the ERP measurement.

The EUT was then replaced by an $\frac{1}{2}$ wave dipole antenna and polarized in accordance with the EUT's antenna polarization. The $\frac{1}{2}$ wave dipole antenna was connected to a RF signal generator with a coaxial cable.

The search antenna height, and search antenna polarity was set to levels that produced the maximum reading obtained in step 3. The signal generator was adjusted to a level that produced the radiated emission level obtained in step 3.

The signal generator level was recorded and corrected by the power loss in the cable between the generator and the antenna and further corrected for the gain of the substitution antenna used relative to an ideal $\frac{1}{2}$ wave dipole antenna. The signal generator corrected level is the ERP level

Calculation Method:

$$P_{Watt} = \frac{E_{v/m}^2 \times d_m^2}{30 \times 1.64}$$



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

8.2 TEST DATA

Settings:

- High Power: 5 Watt delivered to antenna
- 5W VX-900U/600U radiated power measurements (3 meter)

Frequency (MHz)	Level Measured (dBμV)	Site Factor (dB/m)	ERP Calculated (Watt)	ERP Substitution Method (dBm)
450.025	106.0	30.8	5.0	37.0
469.975	104.5	31.7	6.0	37.8
487.975	102.6	31.8	5.0	37.0

*Antenna as specified by manufacturer (unity gain)

**Measurement accuracy is +/- 1.5 dB

8.3 TEST EQUIPMENT

Spectrum Analyzer HP8566B
Antenna Roberts 1/2wave dipoles



9 FCC RULES AND REGULATIONS PART 2 §2.1051: SPURIOUS EMISSIONS AT ANTENNA TERMINALS

9.1 TEST PROCEDURE

ANSI/TIA/EIA-603-1992, Section 2.2.13

The transmitter is terminated with a 50Ω load and interfaced with a spectrum analyzer.

The transmitter is modulated with a 2,500 Hz sine wave at an input level 16 dB greater than that required to produce 50% of the rated system deviation at 1000 Hz.

9.2 TEST DATA

9.2.1 CFR PART 90 REQUIREMENTS

Frequency range of measurement per Part 2.1057: 9kHz to $10 \times F_c$

Limits: Mask B (dBm): $P(\text{dBm}) - (43 + 10 \times \log P(\text{W}))$
Mask D (dBm): $P(\text{dBm}) - (50 + 10 \times \log P(\text{W}))$

The following channel (in MHz) was investigated: 450.025, 467.525, and 484.975 in 5W, 2.5W, 1W and 0.25W mode for both 25KHz and 12.5 KHz channel spacing.

The worst case (unwanted emissions) channels are shown. The magnitude of emissions attenuated more than 20 dB below the FCC limit need not be recorded.

Channel 4 (450.025 MHz) – 5 Watt and 12.5 kHz Channel Bandwidth: Mask D

Frequency (MHz)	Level Measured (dBm)	Limit (dBm)	Margin (dB)
830.050	Noise floor		
1245.075	Noise floor		
1660.100	Noise floor		
2075.125	Noise floor		
2490.150	Noise floor		
2513.000	-26.3	-20.0	-6.3
2905.175	Noise floor		
3320.200	Noise floor		
3735.225	Noise floor		
4150.250	Noise floor		



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

Channel 5 (467.525 MHz) – 5 Watt and 12.5 kHz Channel Bandwidth: Mask D

Frequency (MHz)	Level Measured (dBm)	Limit (dBm)	Margin (dB)
830.050	Noise floor		
1245.075	Noise floor		
1660.100	Noise floor		
2075.125	Noise floor		
2490.150	Noise floor		
2905.175	Noise floor		
3073.333	-24.7	-20.0	-4.7
3320.200	Noise floor		
3735.225	Noise floor		
4150.250	Noise floor		

Channel 1 (484.975MHz) – 5 Watt and 12.5 kHz Channel Bandwidth: Mask D

Frequency (MHz)	Level Measured (dBm)	Limit (dBm)	Margin (dB)
969.952	Noise floor		
1454.928	Noise floor		
1939.9050	Noise floor		
2424.882	Noise floor		
2909.856	Noise floor		
3394.835	Noise floor		
3467.000	-26.0	-20	-6.0
3879.812	Noise floor		

4.3 Test Equipment

Audio Generator:

Synthesized Level Generator	HP3336B	s/n 2127A00559
Selective Level Meter	HP3585	s/n B032374

Spectrum Analyzer:

HP8564E	s/n 3943A01719
HP8546A	s/n 3525A00159



COMPANY NAME: COM NET ERICSSON
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

10 FCC RULES AND REGULATIONS PART 2 §2.1053 (A): FIELD STRENGTH OF SPURIOUS RADIATION

10.1 TEST PROCEDURE

ANSI/TIA/EIA-603-1992, section 2.2.12

The transmitter is terminated with a 50 Ω load and is modulated with a 2,500 Hz sine wave at an input level 16 dB greater than that required to produce 50% of the rated system deviation at 1000 Hz.

Refer to section "Radiated Measurement" in this report for further information.

10.2 TEST DATA

The worst-case emissions test data are shown. The magnitude of emissions attenuated more than 20 dB below the FCC limit need not be recorded.

5Watt at 12.5 kHz channel spacing						
Radiated Emissions (Channel 5 at 467.525 MHz) Substitution Method						
Frequency	ERP S/G level (dBm)	Cable Loss*	Difference in gain (ref. to 1/2 wave dipole)	Emission level (dBm)	Limit (dBm) Mask D	Margin (dB)
935.050	-27.3	4.2	1.1	-24.2	-20	-4.2
1402.575	-38.0	6.7	-3.7	-27.6	-20	-7.6
1870.100	-38.0	7.7	-4.8	-25.5	-20	-5.5
2337.625	-40.7	10.5	-5.1	-25.1	-20	-5.1
2805.15	-68.8	12.0	-5.8	-51.0	-20	-31.0
3272.675	-57.4	13.5	-6.2	-37.7	-20	-17.7
3740.2	-69.1	15.9	-5.9	-47.3	-20	-27.3
4207.725	-66.0	17.8	-6.4	-41.8	-20	-21.8
4675.25	-61.7	20.1	-7.0	-34.6	-20	-14.6

*This insertion loss corresponds to the cable connecting the RF Signal Generator to the $\frac{1}{2}$ wave dipole antenna.

10.3 TEST EQUIPMENT

Antenna: CHASE CBL6112 s/n 2099
Amplifier: HP8449B s/n 3008A00505
Spectrum analyzer: HP8564E s/n 3943A01719

RF Signal Generator: HP8648C s/n 3537A01741
Synthesized Sweeper: HP83752A s/n 3610A00846



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

11 FCC RULES AND REGULATIONS PART 2 §2.1049 (C) (1): OCCUPIED BANDWIDTH

OCCUPIED BANDWIDTH - COMPLIANCE WITH THE EMISSION MASKS

11.1 TEST PROCEDURE


ANSI/TIA/EIA-603-1992, section 2.2.11

Device with audio modulation: Transmitter is modulated with a 2500 Hz sine wave at an input level of 16 dB greater than that required to produce 50% of rated system deviation at 1000 Hz.

Device with digital modulation: N/A

11.2 TEST DATA


11.2.1 CHANNEL 1: 5W FOR 25 kHz CHANNEL BANDWIDTH: MASK B (AUDIO MODULATION: 2,500 Hz)





COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

11.2.2 CHANNEL 4: 5 W FOR 12.5 kHz CHANNEL BANDWIDTH: MASK D (AUDIO MODULATION: 2,500 Hz)



11.3 TEST EQUIPMENT

Spectrum Analyzer HP8564E s/n 3943A01719



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

12 FCC RULES AND REGULATION PART 2 §2.1055: FREQUENCY STABILITY

12.1 TEST PROCEDURE

ANSI/TIA/EIA-603-1992, section 2.2.2

The carrier frequency stability is the ability of the transmitter to maintain an assigned carrier frequency.

The EUT was evaluated over the temperature range -30°C to +50°C.

The temperature was initially set to -30°C and a 2-hour period was observed for stabilization of the EUT.

The frequency stability was measured within one minute after application of primary power to the transmitter. The temperature was raised at intervals of 10 degrees centigrade through the range. A ½ an hour period was observed to stabilize the EUT at each measurement step and the frequency stability was measured within one minute after application of primary power to the transmitter.

Additionally, the power supply voltage of the EUT was varied from 85% to 115% of the nominal voltage.

The worst-case test data are shown.

12.2 TEST DATA

12.2.1 FREQUENCY STABILITY/TEMPERATURE VARIATION

Limit is 2.5 ppm for device with a 12.5 kHz channel bandwidth


Limit is 5 ppm for device with a 25 kHz channel bandwidth

The VX-900U/600U 5Watt radios was tested with 12.5 kHz and 25 kHz channel bandwidth. The worst-case temperature deviation on the following plots.



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

Temperature Frequency Stability; 467.525 MHz; 12.5 kHz channel spacing




Temperature (C)	Frequency (MHz)	ppm
-30.00000	467.52517	0.36362
-20.00000	467.52465	-0.74862
-10.00000	467.52495	-0.10695
0.00000	467.52583	1.77531
10.00000	467.52597	2.07476
20.00000	467.52565	1.39030
30.00000	467.52508	0.17111
40.00000	467.52463	-0.79140
50.00000	467.52448	-1.11224



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

Temperature Frequency Stability; 467,525 MHz; 25KHz channel spacing



Temperature (C)	Frequency (MHz)	ppm
-30.00000	467.52500	0.00000
-20.00000	467.52453	-1.00529
-10.00000	467.52493	-0.14972
0.00000	467.52583	1.77531
10.00000	467.52597	2.07476
20.00000	467.52565	1.39030
30.00000	467.52505	0.10695
40.00000	467.52463	-0.79140
50.00000	467.52452	-1.03310




COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

12.2.2 FREQUENCY STABILITY/VOLTAGE VARIATION

Assigned Frequency 467.525 MHz

Voltage Frequency Stability 467.525MHz; 12.5KHz channel spacing




Voltage (7.2V +/- 85-115%)	Frequency (MHz)	ppm
5.15	467.525087	0.18609
6.12	467.525225	0.48126
7.2	467.525337	0.72082
8.38	467.525337	0.72082

Battery end point = 5.15V



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

Voltage Frequency Stability 467.525MHz; 25KHz channel spacing



Voltage (7.2V +/- 85-115%)	Frequency (MHz)	ppm
5.15	467.525087	0.18609
6.12	467.525225	0.48126
7.2	467.525337	0.72082
8.38	467.525337	0.72082

Battery end point = 5.15

12.3 7.3 TEST EQUIPMENT

Temperature Chamber Tenney TH65 s/n 11380

Frequency Counter HP8901A (Frequency Mode) s/n 2545A04102



13 FCC RULES AND REGULATIONS PART 2 §2.1047 (A): MODULATION CHARACTERISTICS - AUDIO FREQUENCY RESPONSE

13.1 TEST PROCEDURE

ANSI/TIA/EIA-603-1992, section 2.2.6

The audio frequency response is the degree of closeness to which the frequency deviation of the transmitter follows a prescribed characteristic.

The input audio level at 1000 Hz is set to produce 20% of the rated system deviation. This point is shown as the 0 dB reference level, noted DEVref.

The audio signal generator was varied from 100Hz to 5kHz with the input level held constant.

The deviation in kHz was recorded using a modulation analyzer as DEVfreq.


The response in dB relative to 1 kHz was calculated as follows:

$$\text{Audio Frequency Response} = 20 \text{ LOG } (\text{DEVfreq}/\text{DEVref})$$

13.2 TEST DATA

13.2.1 CHANNEL 1 – 25 kHz AUDIO FREQUENCY RESPONSE

Audio Frequency Response (467.525 MHz; 25 kHz channel spacing)




13.2.2



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

13.2.3 CHANNEL 4 – 12.5 kHz AUDIO FREQUENCY RESPONSE



13.3 TEST EQUIPMENT

Audio generator	HP3336B	s/n 2127A00559
Modulation analyzer	HP8901A	s/n 2545A04102



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

14 FCC RULES AND REGULATIONS PART 2 §2.1047 (A): MODULATION CHARACTERISTICS - AUDIO LOW PASS FILTER RESPONSE


14.1 TEST PROCEDURE

ANSI/TIA/EIA-603-1992, 2.2.15

The Audio Low Pass Filter Response is the frequency response of the post limiter low pass filter circuit above 3000 Hz.

14.2 TEST DATA


Audio Low Pass Filter Response (25 kHz channel spacing)





COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

Audio Low Pass Filter Response (12.5 kHz channel spacing)



14.3 TEST EQUIPMENT

Audio generator	HP3336B	s/n 2127A00559
Modulation analyzer	HP8901A	s/n 2545A04102
Selective level meter	HP3586B	s/n 1928A01892
Synthesizer/Level generator	HP3336B	s/n 2514A02585



15 FCC RULES AND REGULATIONS PART 2 §2.1047 (B): MODULATION CHARACTERISTICS - MODULATION LIMITING


15.1 TEST PROCEDURE

ANSI/TIA/EIA-603-1992, section 2.2.3

The transmitter is adjusted for full rated system deviation. The audio input level is adjusted for 60% of rated system deviation at 1000Hz. Using this level as a reference (0dB) the audio input level is varied from the reference to a level +20 dB above it and -20 dB under it, for modulation frequencies of 300Hz, 1,000Hz, and 2,500Hz. The system deviation obtained as a function of the input level is recorded. Both Positive and Negative Peak deviations were recorded.

15.2 TEST DATA


Modulation Limiting (467.525 MHz; 12.5 kHz channel spacing; Positive Peak)





COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U


Modulation Limiting (467.525 MHz; 12.5 kHz channel spacing; Negative Peak)





COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U


Modulation Limiting (467.525 MHz; H power 25 kHz channel spacing; Positive Peak)





COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

Modulation Limiting (467.525 MHz; H power
25 kHz channel spacing; Negative Peak)



15.3 TEST EQUIPMENT

Audio generator	HP3336B	s/n 2127A00559
Modulation analyzer	HP8901A	s/n 2545A04102
Selective level meter	HP3586B	s/n 1928A01892
Synthesizer/Level generator	HP3336B	s/n 2514A02585




COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

16 FCC RULES AND REGULATIONS PART 90 §90.214 : TRANSIENT FREQUENCY BEHAVIOR

16.1 TEST PROCEDURE

ANSI/TIA/EIA-603-1992, section 2.2.19

16.2 TEST DATA WIDE BAND






COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

25KHz channel spacing off time 450.025 MHz

Tek **Stop** 5.00kS/s

3 Acqs




29 Nov 2000
13:25:29

25KHz channel spacing on time 450.025 MHz




COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U





COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U


25KHz channel spacing off time 484.975 MHz



25KHz channel spacing on time 484.975 MHz




COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U





COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

25KHz channel spacing off time 467.525 MHz




25KHz channel spacing on time 467.525 MHz



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U


Test Data Narrow Band





COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U


12.5KHz channel spacing off time 450.025 MHz





COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U


12.5KHz channel spacing on time 450.025 MHz





COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U


12.5KHz channel spacing off time 484.975 MHz





COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U


12.5KHz channel spacing on time 484.975 MHz





COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

12.5KHz channel spacing off time 450.025 MHz



12.5KHz channel spacing on time 450.025 MHz



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

Limits:

Requirements for EUT with 25 kHz channel spacing:

Time Intervals (*)(**)	Maximum Frequency Difference(***)	150-174 MHz	421-512 MHz
t1(****)	± 25 kHz	5.0 mSec	10.0 mSec
t2	± 12.5 kHz	20.0 mSec	25.0 mSec
t3(****)	± 25 kHz	5.0 mSec	10.0 mSec

Requirements for EUT with 12.5 kHz channel spacing:

Time Intervals (*)(**)	Maximum Frequency Difference(***)	150-174 MHz	421-512 MHz
t1(****)	± 12.5 kHz	5.0 mSec	10.0 mSec
t2	± 6.25 kHz	20.0 mSec	25.0 mSec
t3(****)	± 12.5 kHz	5.0 mSec	10.0 mSec

(*) t on is the instant when a 1 kHz test signal is completely suppressed, including any capture time due to phasing.

t 1 is the time period immediately following ton.

t2 is the time period immediately following t1.

t3 is the time period from the instant when the transmitter is turned off until toff.

toff is the instant when the 1 kHz test signal starts to rise.

(**) During the time from the end of t2 to the beginning of t3, the frequency difference must not exceed the limits specified in § 90.213.

(***) Difference between the actual transmitter frequency and the assigned transmitter frequency.

(****) If the transmitter carrier output power rating is 6 watts or less, the frequency difference during this time period may exceed the maximum frequency difference for this time period.

Maximum frequency difference between time T2 and T3: Calculation for Channel 6:

The frequency stability is required to be 2.5ppm.

Calculation for Channel 6:

4 div. on scope represent 12.5kHz for narrow band channel.

Therefore, 487.975M times 2.5 ppm times +/- 4 Divisions divided by 12.5kHz equals about +/- 0.4 division. 0.4 Div. correspond to 1.2 19 kHz

16.3 TEST EQUIPMENT

Detector: HP8471D s/n 2952A
RF signal generator: HP8648C s/n 3537A01741
Modulation Analyzer: HP8901A s/n 2545A04102
Oscilloscope: Tektronix TDS540B s/n B020129
Receiver: HP 8546A s/n 3525A00159



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

17 FCC RULES AND REGULATIONS PART 2.202: NECESSARY BANDWIDTH AND EMISSION BANDWIDTH

Type of Emission: F3E

Necessary Bandwidth and Emission Bandwidth:

12.5kHz (NB channel) : $B_n = 11K0F3E$

25kHz (WB channel): $B_n = 16K0F3E$

Calculation:

Max modulation(M) in kHz : 3

Max deviation (D) in kHz: 2.5 (NB) and 5 (BB)

Constant factor (K) : 1

$B_n = 2xM + 2xDK$



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

18 RECEIVER DATA

Radiated Test Data - OATS 1

Test Date: December 01, 2000 - 4:28:14 PM

Work Order: 1

Customer Reference: 1

Model: 900U

Mode: 900U

Name: DB

Limit/Distance: FCC B/3M

Notes: IF 423.275

Temperature: 1°F Humidity: 1%									
Emission Frequency (MHz)	Test Detector	Antenna Polarity (H/V)	Turntable Azimuth (deg)	Antenna Height (m)	Analyzer Reading (dBuV/m)	Site Correction Factor (dB/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
160.600	Qp	H	0	1.0	11.5	-17.5	-6.0	43.5	-49.5
233.600	Qp	H	0	1.0	14.5	-16.2	-1.7	46.0	-47.7
306.600	Qp	H	0	1.0	13.7	-13.1	0.6	46.0	-45.4
379.600	Qp	H	0	1.0	9.6	-10.6	-1.0	46.0	-47.0
423.275	Qp	H	30	1.0	42.2	-8.6	33.6	46.0	-12.4
423.275	Qp	V	30	1.0	36.7	-8.9	27.8	46.0	-18.2
846.550	Qp	H	30	1.8	42.9	-3.0	39.9	46.0	-6.1
846.550	Qp	V	90	1.0	41.6	-3.6	38.0	46.0	-8.0




COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

APPENDIX A

TEST CONFIGURATION PHOTOGRAPHS



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U



Radiated Back View



Radiated Front View



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

APPENDIX B

LABEL INFORMATION

Please see the following page



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

APPENDIX C

PRODUCT DESCRIPTION

Please see the following page



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

APPENDIX D

SCHEMATICS

Please see the following page.



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

APPENDIX E

OPERATOR'S MANUAL

Please see the following page



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

APPENDIX F

INTERNAL PHOTOGRAPHS



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U

APPENDIX G

EXTERNAL PHOTOGRAPHS



COMPANY NAME: COM NET ERICSSON.
EUT: VX_900U/600U
WORK ORDER NUMBER: 2000468
FCC ID: K66VX-900U