



**YAESU MUSEN CO., LTD.**

Omori Bellport Building D-3F

6-26-3 Minami-Oi, Shinagawa-ku, Tokyo, 140-0013, Japan

Tel: +81-3-6410-8121 • Fax: +81-3-5753-5123

18 Oct 2024

Federal Communications Commission  
Authorization and Evaluation Division,  
7435 Oakland Mills Road  
Columbia, MD 21046  
USA

Re: FTM-510DR                      FCC ID: K6620895X50

Gentlemen:

The scanner receiver equipment meets the requirements of the FCC Rules, 15.121(a) and (b).

Compliance is achieved through the following methods:

The scanner receiver in this equipment is incapable of tuning, or readily being altered, by the User to operate within the frequency bands allocated to the Domestic Public Cellular Telecommunications Service in Part 22. Blocking of the cellular frequencies is implemented in the firmware of the unit's main control central processing unit (CPU). Coverage of 824 - 849 MHz and 869 - 894 MHz is completely blocked, since it is done in the microprocessor, and cannot be re-enabled by any user-accessible procedure, including diode, resistor, or jumper changes, nor by connection of any external device such as a personal computer, nor by installation of any "special" enabling semiconductor device.

The scanning receiver is designed so that the tuning, control and filtering circuitry is inaccessible.

The scanning receiver is reject any signals from the Cellular Radiotelephone Service frequency bands that are 38 dB or lower based upon a 12 dB SINAD measurement.

Sincerely,

YAESU MUSEN CO., LTD.

Masatoshi Muraishi  
Engineering Division