

TEST REPORT

Reference No..... : WTX20X07043541W-2
FCC ID : 2AG5CWMSOUNDPOD
Applicant : Shenzhen Xinglong new plastic products limited company
Address : 1-3 floor, No.10, quanwei, xikeng Community, henggang, longgang District,
Shenzhen,China
Product Name : Bluetooth Earbuds
Test Model. : SOUNDPOD
Standards : FCC Part 15.247
Date of Receipt sample : Jul.08, 2020
Date of Test..... : Jul.08, 2020 to Jul.24, 2020
Date of Issue : Jul.24, 2020
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308

Fax.: +86-755-33663309

Tested by:

Reviewed By:

Approved & Authorized By:

Jack Huang

Lion Cai

Silin Chen

Jack Huang / Project Engineer

Lion Cai / RF Manager

Silin Chen / Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY.....	5
1.4 TEST FACILITY	5
1.5 EUT SETUP AND TEST MODE	6
1.6 MEASUREMENT UNCERTAINTY	7
1.7 TEST EQUIPMENT LIST AND DETAILS	8
2. SUMMARY OF TEST RESULTS	10
3. RF EXPOSURE	11
3.1 STANDARD APPLICABLE.....	11
3.2 TEST RESULT.....	11
4. ANTENNA REQUIREMENT	12
4.1 STANDARD APPLICABLE.....	12
4.2 EVALUATION INFORMATION	12
5. POWER SPECTRAL DENSITY	13
5.1 STANDARD APPLICABLE.....	13
5.2 TEST SETUP BLOCK DIAGRAM	13
5.3 TEST PROCEDURE.....	13
5.4 SUMMARY OF TEST RESULTS/PLOTS	13
6. DTS BANDWIDTH.....	17
6.1 STANDARD APPLICABLE.....	17
6.2 TEST SETUP BLOCK DIAGRAM	17
6.3 TEST PROCEDURE.....	17
6.4 SUMMARY OF TEST RESULTS/PLOTS	17
7. RF OUTPUT POWER	21
7.1 STANDARD APPLICABLE.....	21
7.2 TEST SETUP BLOCK DIAGRAM	21
7.3 TEST PROCEDURE.....	21
7.4 SUMMARY OF TEST RESULTS/PLOTS	21
8. FIELD STRENGTH OF SPURIOUS EMISSIONS	25
8.1 STANDARD APPLICABLE.....	25
8.2 TEST PROCEDURE.....	25
8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	27
8.4 SUMMARY OF TEST RESULTS/PLOTS	27
9. OUT OF BAND EMISSIONS.....	35
9.1 STANDARD APPLICABLE.....	35
9.2 TEST PROCEDURE.....	35
9.3 SUMMARY OF TEST RESULTS/PLOTS	36
10. CONDUCTED EMISSIONS	42
10.1 TEST PROCEDURE.....	42
10.2 BASIC TEST SETUP BLOCK DIAGRAM.....	42
10.3 TEST RECEIVER SETUP	42
10.4 SUMMARY OF TEST RESULTS/PLOTS	42

Report version

Version No.	Date of issue	Description
Rev.00	Jul.24, 2020	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shenzhen Xinglong new plastic products limited company
Address of applicant: 1-3 floor, No.10, quanwei, xikeng Community, henggang, longgang District, Shenzhen,China

Manufacturer: Shenzhen Xinglong new plastic products limited company
Address of manufacturer: 1-3 floor, No.10, quanwei, xikeng Community, henggang, longgang District, Shenzhen,China

General Description of EUT	
Product Name:	Bluetooth Earbuds
Trade Name	/
Model No.:	SOUNDPOD
Adding Model(s):	WMSOUNDPOD-BK, WMSOUNDPOD-W, WMSOUNDPOD
	WLGSOUNDPOD-W, ASOTV-TWS, PBT151WH-CSG,
	ARBT10WH, P2G-SP7, PNS-AP4, WLGSOUNDPOD
Rated Voltage:	Battery DC 3.7V
Battery Capacity:	Earbud: 40mAh Charging Box: 400mAh
Power Adapter:	/
Software Version:	SDK_V013
Hardware Version:	V1.2
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model SOUNDPOD but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Bluetooth Version:	V5.1 (BLE mode)
Frequency Range:	2402-2480MHz
RF Output Power:	-4.64dBm (Conducted)
Data Rate:	1Mbps, 2Mbps
Modulation:	GFSK
Quantity of Channels:	40
Channel Separation:	2MHz
Type of Antenna:	PCB Antenna
Antenna Gain:	-0.58dBi

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under section 15.247 of the Fcc rules.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low	2402MHz
TM2	Middle	2440MHz
TM3	High	2480MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
USB Cable	0.5	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Adapter	/	KA1517-0502000CNU	/
Notebook	Lenovo	E445	EB12648265
Mobile phone	HUAWEI	VOG-AL00	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2020-04-28	2021-04-27
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2020-04-28	2021-04-27
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2020-04-28	2021-04-27
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2020-04-28	2021-04-27
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2020-04-28	2021-04-27
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2019-05-05	2021-05-04
SEMT-1042	Horn Antenna	ETS	3117	00086197	2019-05-05	2021-05-04
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2019-05-05	2021-05-04
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2019-05-05	2021-05-04
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2020-04-28	2021-04-27
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2020-04-28	2021-04-27
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2020-04-28	2021-04-27
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2020-04-28	2021-04-27
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2020-04-28	2021-04-27
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2020-04-28	2021-04-27
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2019-05-05	2021-05-04
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2020-04-28	2021-04-27
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2020-04-28	2021-04-27
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2020-04-28	2021-04-27
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2020-03-17	2021-03-16
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2020-03-17	2021-03-16
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2020-03-17	2021-03-16
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2020-03-17	2021-03-16
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2020-03-17	2021-03-16
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2020-03-17	2021-03-16

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

*Remark: indicates software version used in the compliance certification testing

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§2.1093	RF Exposure	Compliant
§15.203; §15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	DTS Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: Not applicable

3. RF Exposure

3.1 Standard Applicable

According to §1.1307 and §2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information


This product has a PCB antenna, fulfill the requirement of this section.

5. Power Spectral Density

5.1 Standard Applicable

According to 15.247(a)(1)(iii), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Setup Block Diagram



5.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.2, the test method of power spectral density as below:




- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.




5.4 Summary of Test Results/Plots

Test Mode	Test Channel	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
GFSK(BLE) -1M	Low	-27.79	8
	Middle	-25.98	8
	High	-24.69	8

Test Mode	Test Channel	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
GFSK(BLE) -2M	Low	-27.73	8
	Middle	-26.04	8
	High	-24.65	8

Please refer to the following test plots:

GFSK(BLE)-1M	
Low	 Ref: 10 dBm, Att: 20 dB, RBW: 3 kHz, VBW: 10 kHz, SWT: 225 ms, Marker 1 [T1]: -27.79 dBm, Center: 2.402 GHz, Span: 2 MHz Date: 21.JUL.2020 14:13:13
Middle	 Ref: 10 dBm, Att: 20 dB, RBW: 3 kHz, VBW: 10 kHz, SWT: 225 ms, Marker 1 [T1]: -25.98 dBm, Center: 2.44 GHz, Span: 2 MHz Date: 21.JUL.2020 14:13:33
High	 Ref: 10 dBm, Att: 20 dB, RBW: 3 kHz, VBW: 10 kHz, SWT: 225 ms, Marker 1 [T1]: -24.69 dBm, Center: 2.48 GHz, Span: 2 MHz Date: 21.JUL.2020 14:13:50


Low	GFSK(BLE)-2M  Ref: 10 dBm Att: 20 dB RBW: 3 kHz VBW: 10 kHz SWT: 225 ms Marker 1 [T1]: -27.73 dBm 2.402015000 GHz Center 2.402 GHz 200 kHz/ Span 2 MHz Date: 21.JUL.2020 14:14:52
Middle	 Ref: 10 dBm Att: 20 dB RBW: 3 kHz VBW: 10 kHz SWT: 225 ms Marker 1 [T1]: -26.04 dBm 2.440030000 GHz Center 2.44 GHz 200 kHz/ Span 2 MHz Date: 21.JUL.2020 14:14:28
High	 Ref: 10 dBm Att: 20 dB RBW: 3 kHz VBW: 10 kHz SWT: 225 ms Marker 1 [T1]: -24.65 dBm 2.480030000 GHz Center 2.48 GHz 200 kHz/ Span 2 MHz Date: 21.JUL.2020 14:14:10

6. DTS Bandwidth

6.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Setup Block Diagram



6.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.4 Summary of Test Results/Plots

Test Mode	Test Channel	6 dB Bandwidth MHz	Limit kHz
GFSK(BLE) -1M	Low	0.516	≥ 500
	Middle	0.516	≥ 500
	High	0.504	≥ 500

Test Mode	Test Channel	6 dB Bandwidth MHz	Limit kHz
GFSK(BLE) -2M	Low	0.512	≥ 500
	Middle	0.510	≥ 500
	High	0.510	≥ 500

Please refer to the following test plots:

	GFSK(BLE)-1M Date: 21.JUL.2020 14:20:43
Middle	Date: 21.JUL.2020 14:23:00
High	Date: 21.JUL.2020 14:23:40


[illegible]

7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

7.2 Test Setup Block Diagram



7.3 Test Procedure




According to the KDB-558074 D01 v05r02 Subclause 8.3.1.1 and ANSI C63.10-2013 Subclause 11.9.1.1, this procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.




- a) Set the $RBW \geq DTS$ bandwidth.
- b) Set $VBW \geq 3 \times RBW$.
- c) Set $span \geq 3 \times RBW$
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

7.4 Summary of Test Results/Plots

Test Mode	Test Channel	Reading dBm	Output Power mW	Limit mW
GFSK(BLE)-1M	Low	-7.71	0.17	1000
	Middle	-5.99	0.25	1000
	High	-4.66	0.34	1000

Test Mode	Test Channel	Reading dBm	Output Power mW	Limit mW
GFSK(BLE)-2M	Low	-7.70	0.17	1000
	Middle	-5.98	0.25	1000
	High	-4.64	0.34	1000

Low	GFSK(BLE)-1M  Date: 21.JUL.2020 14:05:47
Middle	 Date: 21.JUL.2020 14:06:15
High	 Date: 21.JUL.2020 14:06:51

Low	GFSK(BLE)-2M  Date: 21.JUL.2020 14:08:48
Middle	 Date: 21.JUL.2020 14:09:06
High	 Date: 21.JUL.2020 14:09:39

8. Field Strength of Spurious Emissions

8.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.


The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.


The test setup for emission measurement below 30MHz..



The test setup for emission measurement from 30 MHz to 1 GHz..



The test setup for emission measurement above 1 GHz..



Frequency :9kHz-30MHz
RBW=10KHz,
VBW =30KHz
Sweep time= Auto
Trace = max hold
Detector function = peak

Frequency :30MHz-1GHz
RBW=120KHz,
VBW=300KHz
Sweep time= Auto
Trace = max hold
Detector function = peak, QP

Frequency :Above 1GHz
RBW=1MHz,
VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto
Trace = max hold
Detector function = peak, AV

8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$


8.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

All test modes (different data rate and different modulation) are performed, but only the worst case (GFSK(BLE)-1M) is recorded in this report.


➤ Spurious Emissions Below 1GHz

Test Channel	Low	Polarity:	Horizontal
--------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	119.8556	46.94	-14.28	32.66	43.50	-10.84	-	-	peak
2	167.8243	49.29	-15.14	34.15	43.50	-9.35	-	-	peak
3	191.7450	44.20	-12.99	31.21	43.50	-12.29	-	-	peak
4	263.8190	43.35	-10.83	32.52	46.00	-13.48	-	-	peak
5	348.0274	43.03	-7.55	35.48	46.00	-10.52	-	-	peak
6	793.3960	38.81	-1.23	37.58	46.00	-8.42	-	-	peak

Test Channel	Low	Polarity:	Vertical
--------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.1616	36.39	-12.30	24.09	40.00	-15.91	-	-	peak
2	61.1316	34.69	-13.20	21.49	40.00	-18.51	-	-	peak
3	119.8556	45.01	-14.28	30.73	43.50	-12.77	-	-	peak
4	192.4186	37.26	-12.94	24.32	43.50	-19.18	-	-	peak
5	312.1794	33.88	-8.95	24.93	46.00	-21.07	-	-	peak
6	414.7223	37.58	-6.12	31.46	46.00	-14.54	-	-	peak

Test Channel	Middle	Polarity:	Horizontal
--------------	--------	-----------	------------




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	119.8556	47.32	-14.28	33.04	43.50	-10.46	-	-	peak
2	167.8243	49.44	-15.14	34.30	43.50	-9.20	-	-	peak
3	216.0240	44.19	-12.24	31.95	46.00	-14.05	-	-	peak
4	300.3673	43.90	-8.92	34.98	46.00	-11.02	-	-	peak
5	360.4477	41.05	-7.34	33.71	46.00	-12.29	-	-	peak
6	793.3960	40.09	-1.23	38.86	46.00	-7.14	-	-	peak

Test Channel	Middle	Polarity:	Vertical
--------------	--------	-----------	----------




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	39.2991	35.88	-12.24	23.64	40.00	-16.36	-	-	peak
2	63.0916	34.32	-13.57	20.75	40.00	-19.25	-	-	peak
3	119.8556	44.95	-14.28	30.67	43.50	-12.83	-	-	peak
4	216.0240	37.51	-12.24	25.27	46.00	-20.73	-	-	peak
5	420.5803	35.60	-5.99	29.61	46.00	-16.39	-	-	peak
6	793.3960	32.97	-1.23	31.74	46.00	-14.26	-	-	peak

Test Channel	High	Polarity:	Horizontal
--------------	------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	96.0986	39.87	-13.96	25.91	43.50	-17.59	-	-	peak
2	119.8556	47.36	-14.28	33.08	43.50	-10.42	-	-	peak
3	167.8243	49.06	-15.14	33.92	43.50	-9.58	-	-	peak
4	216.0240	44.48	-12.24	32.24	46.00	-13.76	-	-	peak
5	348.0274	42.82	-7.55	35.27	46.00	-10.73	-	-	peak
6	793.3960	38.98	-1.23	37.75	46.00	-8.25	-	-	peak

Test Channel	High	Polarity:	Vertical
--------------	------	-----------	----------



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	96.0986	38.07	-13.96	24.11	43.50	-19.39	-	-	peak
2	119.8556	45.81	-14.28	31.53	43.50	-11.97	-	-	peak
3	167.8243	40.06	-15.14	24.92	43.50	-18.58	-	-	peak
4	216.0240	36.42	-12.24	24.18	46.00	-21.82	-	-	peak
5	360.4477	36.14	-7.34	28.80	46.00	-17.20	-	-	peak
6	768.7482	32.93	-1.14	31.79	46.00	-14.21	-	-	peak

Remark: ‘-’Means’ the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

➤ Spurious Emissions Above 1GHz

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2402MHz							
4149.351	52.72	-6.13	46.59	74.00	-27.41	H	PK
6577.753	51.97	-2.28	49.69	74.00	-24.31	H	PK
9441.913	51.41	1.48	52.89	74.00	-21.11	H	PK
4332.852	52.99	-5.39	47.60	74.00	-26.40	V	PK
6527.712	52.77	-2.29	50.48	74.00	-23.52	V	PK
9181.198	52.24	1.09	53.33	74.00	-20.67	V	PK
Middle Channel-2440MHz							
4321.837	52.68	-5.44	47.24	74.00	-26.76	H	PK
6921.301	51.34	-2.27	49.07	74.00	-24.93	H	PK
9417.909	51.33	1.45	52.78	74.00	-21.22	H	PK
4908.444	51.85	-4.44	47.41	74.00	-26.59	V	PK
6868.647	51.85	-2.28	49.57	74.00	-24.43	V	PK
8747.716	51.97	0.29	52.26	74.00	-21.74	V	PK
High Channel-2480MHz							
4213.211	53.31	-5.87	47.44	74.00	-26.56	H	PK
6140.854	51.00	-2.79	48.21	74.00	-25.79	H	PK
8814.774	51.93	0.43	52.36	74.00	-21.64	H	PK
4299.890	52.18	-5.52	46.66	74.00	-27.34	V	PK
6251.257	51.80	-2.63	49.17	74.00	-24.83	V	PK
9228.060	50.61	1.17	51.78	74.00	-22.22	V	PK

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9. Out of Band Emissions

9.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

9.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement

KDB publication number: 913591 may be used for the radiated bandedge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9.
- b) $VBW \geq [3 \times RBW]$.
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

RBW as a function of frequency

Frequency	RBW
9kHz to 150kHz	200Hz to 300Hz
0.15MHz to 30MHz	9kHz to 10kHz
30MHz to 1000MHz	100kHz to 120kHz
>1000MHz	1MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.


Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

9.3 Summary of Test Results/Plots

Note: All test modes (different data rate and different modulation) are performed, but only the worst case (GFSK (BLE)- 1M) is recorded in this report.


➤ Radiated test

Test Channel	Low	Polarity:	Horizontal worst case)
--------------	-----	-----------	------------------------





No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	39.07	-9.66	29.41	54.00	-24.59	Average Detector
	2310.000	52.20	-9.66	42.54	74.00	-31.46	Peak Detector
2	2390.000	38.93	-9.50	29.43	54.00	-24.57	Average Detector
	2390.000	52.27	-9.50	42.77	74.00	-31.23	Peak Detector
3	2400.000	47.82	-9.48	38.34	Delta=22.26dBc		Average Detector
4	2402.100	70.07	-9.47	60.60			Average Detector

Test Channel	High	Polarity:	Horizontal worst case)
--------------	------	-----------	------------------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2480.000	72.76	-9.32	63.44	/	/	Average Detector
	2479.775	79.74	-9.32	70.42	74.00	-3.58	Peak Detector
2	2483.500	40.41	-9.31	31.10	54.00	-22.90	Average Detector
	2483.500	54.19	-9.31	44.88	74.00	-29.12	Peak Detector
3	2500.000	38.07	-9.28	28.79	54.00	-25.21	Average Detector
	2500.000	51.21	-9.28	41.93	74.00	-32.07	Peak Detector


Low



Middle




Date: 21.JUL.2020 14:41:41




Date: 21.JUL.2020 14:44:15

High



Date: 21.JUL.2020 14:45:09



Date: 21.JUL.2020 14:45:42

10. Conducted Emissions


10.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

10.2 Basic Test Setup Block Diagram




10.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency	150 kHz
Stop Frequency	30 MHz
Sweep Speed	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth	9 kHz
Quasi-Peak Adapter Mode	Normal


10.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.5380	38.45	10.03	48.48	56.00	-7.52	QP
2*	0.5380	28.55	10.03	38.58	46.00	-7.42	AVG
3	0.7980	27.87	10.17	38.04	56.00	-17.96	QP
4	0.8180	17.27	10.18	27.45	46.00	-18.55	AVG
5	1.0740	26.72	10.37	37.09	56.00	-18.91	QP
6	1.0740	16.74	10.37	27.11	46.00	-18.89	AVG

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.4740	25.00	10.02	35.02	46.44	-11.42	AVG
2	0.4780	31.83	10.02	41.85	56.37	-14.52	QP
3	0.5380	37.59	10.03	47.62	56.00	-8.38	QP
4*	0.5380	32.08	10.03	42.11	46.00	-3.89	AVG
5	1.0740	27.51	10.37	37.88	56.00	-18.12	QP
6	1.1500	19.22	10.38	29.60	46.00	-16.40	AVG

***** END OF REPORT *****