

# **Test Report**

Product	Telematics unit for mounting on forklifts				
Name and address of the applicant	Toyota Material Handling Manufacturing Sweden AB Svarvargatan 8 SE-59581 Mjölby, Sweden				
Name and address of the manufacturer	Toyota Material Handling Manufacturing Sweden AB Svarvargatan 8 SE-59581 Mjölby, Sweden				
Model	DHU4				
Rating	External DC supply (12-48 V <sub>DC</sub> )				
Trademark	ΤΟΥΟΤΑ				
Serial number	202205REVBZ02404				
Additional information	WiFi, BT Classic, BLE, GSM, WCDMA, LTE				
Tested according to	Parts of FCC Part 15.407 Unlicensed National Information Infrastructure Devices (U-NII) Parts of Industry Canada RSS-247, Issue 2 Licence-Exempt Local Area Network (LE-LAN) Devices				
Order number	433049				
Tested in period	2022-05-23 to 2022-05-24				
Issue date	2022-06-08				
Name and address of the testing laboratory	Instituttveien 6 Kjeller, Norway www.nemko.com CAB Number FCC: NO0001 ISED: NO0470 Image: Cab Structure of Struct				
	France Svorz G. Subathahmer. Prepared by [Frode Sveinsen] Approved by [G.Suhanthakumar]				
This report shall not be reproduced except in	full without the written approval of Nemko. Opinions and interpretations expressed within this report are not part of the				
current accreditation. This report was origina	ally distributed electronically with digital signatures. For more information contact Nemko.				



### **Revision history**

Revision	Date	Comment	Sign
00	2022-06-08	First edition	FS



#### THIS TEST REPORT APPLIES ONLY TO THE ITEM(S) AND CONFIGURATIONS TESTED.

Deviations from, additions to, or exclusions from the test specifications are described in "Summary of Test Data".

Nemko Group authorizes the above named entity to reproduce this report provided it is reproduced in its entirety and for use by the entity's employees only. Any reproduction of parts of this report requires approval in writing from Nemko Group.

Any use that a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Group accepts no responsibility for damages suffered by any third party caused by decisions made or actions based on this report.



## CONTENTS

1		4
1.1	Test Item	4
1.2	Normal test conditions	5
1.3	Test Engineer	5
1.4	Antenna Requirement	5
1.5	Worst-Case Configuration	5
1.6	EUT Operating Modes	5
1.7	Radio Modules	5
1.8	EUT Power Levels	6
1.9	Comments	6
2	TEST REPORT SUMMARY	7
2.1	General	7
2.2	Test Summary	7
2	TEST RESULTS	•
<b>3</b>		. <b>o</b>
3.1		0
4	Measurement Uncertainty1	1
5	LIST OF TEST EQUIPMENT1	2
6		3
6.1	Test Site Radiated Emission	3



## 1 INFORMATION

## 1.1 Test Item

Name	Toyota
Model	DHU4
FCC ID	2A24D-DHU4
ISED ID	27803-DHU4
Serial number	202205REVBZ02404
Hardware identity and/or version	BZ1
Software identity and/or version	dv_b1_2021-05-05
Frequency Ranges	U-NII 1 : 5180 – 5240 MHz: 4 channels U-NII 2A : 5260 – 5320 MHz: 4 channels U-NII 2C : 5500 – 5720 MHz: 12 channels U-NII 3 : 5745 – 5825 MHz: 5 channels
Operating Modes	802.11a 802.11n (20/40 MHz BW) 802.11ac (40/80 MHz BW)
Type of Modulation	Digital (OFDM - Orthogonal frequency-division multiplexing)
Conducted Output Power	5180 – 5240 MHz: 16.4 mW 5260 – 5320 MHz: 16.6 mW 5500 – 5720 MHz: 12.9 mW 5745 – 5825 MHz: 13.3 mW
Antenna Connector	Quad MiniFakra
Antenna Type	Smarteq SmartDisc Combi (4-in-1 antenna, 2xLTE, GNSS, WIFi/BT/BLE) P/N: 550237 (tested with 200mm cable, longer cables may also be used) Antenna element LTE1: Rx/Tx Antenna element LTE2: Rx Only Antenna element WiFi/BT: Rx/Tx 2.4GHz WiFi/BT/BLE and 5GHz WiFi Antenna element GNSS: Rx Only GNSS/GPS
Antenna Diversity Supported	Not for WiFi
Smart Antennas Supported	No
TPC Supported	Not implemented. Not required when EIRP is below 500 mW
DFS Supported	Client Device without Radar Detection
Ad-hoc Mode	EUT does not support Ad-hoc Mode in DFS bands
Hotspot Mode	EUT does not support Hotspot Mode in DFS bands
Power Source	External DC Supply (12-48V <sub>DC</sub> , supplied through MX23 connector)
Interfaces	MX23 Connector
	HSD Connector (100TX Ethernet)

#### **Description of Test Item**

The EUT is a telematics unit with radio modules for BT/BLE/WiFi and Mobile (GSM/WCDMA/LTE). Both radio modules are certified radio modules. The EUT also contains a GPS receiver.

This test report covers tests to verify Output Power after change of WiFi Module from FC20-Q73 to FC20-Q93.



### 1.2 Normal test conditions

Temperature:	20 - 24 °C
Relative humidity:	20 - 50 %
Normal test voltage:	24V DC (2x 12V lead acid batteries, Fiamm FG20451)

The EUT was powered from two fully charged batteries during all tests.

The values are the limit registered during the test period.

### 1.3 Test Engineer

Frode Sveinsen

## 1.4 Antenna Requirement

Does the EUT have detachable antenna(s)?	⊠ YES			
If detachable, is the antenna connector(s) non-standard?	⊠ YES			
Antenna Connector: Quad MiniFakra				

Requirement: FCC 15.203, 15.204

## 1.5 Worst-Case Configuration

Radiated Emissions and Power Line Conducted Emissions were performed with the EUT set to transmit at the channel with the highest output power as worst-case scenario.

## 1.6 EUT Operating Modes

Description of operating modes	Continuous TX, 5 GHz 20/40/80 MHz Mode		
Additional information	EUT was controlled from a computer and programmed with the Qualcomm Test App.		
	All tests were performed with the default power levels.		

### 1.7 Radio Modules

Data for radio modules					
Manufacturer	Model No	Identification	Technology		
Quectel	FC20	FCC ID: XMR201703FC20 IC: 10224A-201703FC20 P/N: FC20-Q93	BT Classic BT Low Energy WiFi 2.4 GHz WiFi 5GHz		
Quectel	EG25	FCC ID: XMR201903EG25G IC: 10224A-201903EG25G P/N: EG25GGB-256-SGNS	GSM WCDMA LTE		



### 1.8 EUT Power Levels

The default values from the module manufacturer were used for all channels and modulations.

No power levels were modified for any of the tests.

### 1.9 Comments

The measurements were done with the EUT powered from fully charged batteries.

All ports were populated during spurious emission measurements.

This test report covers only selected tests for new antennas, all other tests are covered by the original Test Reports.



## 2 TEST REPORT SUMMARY

## 2.1 General

All measurements are tracable to national standards.

The tests were conducted for demonstrating compliance with FCC CFR 47 Part 15, paragraph 15.407 and ISED RSS-247 Issue 2.

Tests were performed in accordance with ANSI C63.4-2014 and ANSI C63.10-2013.

Radiated tests were performed in a semi-anechoic chamber at measuring distances of 1m and 3m.

□ New Submission	Production Unit
🛛 Class II Permissive Change	Pre-production Unit
NII Equipment Code	Family Listing

## 2.2 Test Summary

Name of test	FCC Part 15 ref.	RSS-247 Issue 2 RSS-GEN Issue 5 reference	Result
Maximum Output Power	15.407(a)	6.2	Complies



## 3 TEST RESULTS

## 3.1 Maximum Output Power, EIRP

#### FCC 15.407 (a)

ISED RSS-247, Issue 2, Clause 6.2

Measurement procedure: ANSI C63.10-2013 Clause 12.3, method SA-1

**Test Results: Complies** 

#### Measurement Data:

Ch. No.	Nominal Frequency	Maximum Field Strength (dBµV/m)			Maximum e.i.r.p. (dBm)				
	(MHz)	802.11a		802.11n HT20		802.11a		802.11n HT20	
		6M	54M	MCS0	MCS7	6M	54M	MCS0	MCS7
48	5240	96.9	92.8	94.9	91.7	1.7	-2.4	-0.4	-3.5
116	5580	99.7	95.6	97.5	94.4	4.5	0.4	2.3	-0.8

The EUT operates continuously; therefore, method SA-1 of ANSI C63.10-2013 clause 12.3 was used.

EIRP values were calculated from Field Strength values using the method described in KDB 412172 D01.

This is an indoor device with directional Antenna Gain less than 6 dBi.

#### Limits for Indoor Device:

Frequency Band	FCC 15.407(a)	ISED RSS-247 Issue 2
5150 – 5250 MHz	Less than 250 mW (24 dBm) for client device Less than 1 W (30 dBm) for master device	Less than the lesser of 200 mW e.i.r.p. or 10 + 10 log <sub>10</sub> <i>B</i> dBm e.i.r.p.
5250 – 5350 MHz 5470 – 5725 MHz	Less than the lesser of 250 mW (24 dBm) or 11 + 10 log <sub>10</sub> <i>B</i> dBm	Less than the lesser of 250 mW or 11 + 10 log <sub>10</sub> B dBm, and Less than the lesser of 1 W e.i.r.p. or 17 + 10 log <sub>10</sub> B dBm e.i.r.p. Devices with e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W
5725 – 5825 MHz	Less than 1 Watt If Antenna Gain is more than 6 dBi the Power Limit is reduced by the amount exceeding 6 dBi	Less than 1 Watt If Antenna Gain is more than 6 dBi the Power Limit is reduced by the amount exceeding 6 dBi
	<i>B</i> is the 26dB emission bandwidth in MHz	B is the 99% emission bandwidth in MHz







#### Date: 24.MAY.2022 09:32:08

Maximum EIRP, Ch048, 802.11a, 6M



Date: 24.MAY.2022 09:33:21

Maximum EIRP, Ch048, 802.11a, 54M



Date: 24.MAY.2022 09:27:52

Maximum EIRP, Ch048, 802.11n, HT20, MCS0

Date: 24.MAY.2022 09:26:31

Maximum EIRP, Ch048, 802.11n, HT20, MCS7







#### Date: 24.MAY.2022 09:34:54

Maximum EIRP, Ch116, 802.11a, 6M



Date: 24.MAY.2022 09:36:05

Maximum EIRP, Ch116, 802.11a, 54M



Date: 24.MAY.2022 09:37:51

Maximum EIRP, Ch116, 802.11n, HT20, MCS0

Date: 24.MAY.2022 09:40:02

Maximum EIRP, Ch116, 802.11n, HT20, MCS7



## 4 Measurement Uncertainty

Measurement Uncertainty Values		
Test Item	Uncertainty	
Output Power	±0.5 dB	
Power Spectral Density	±0.5 dB	
Out of Band Emissions, Conducted	< 3.6 GHz	±0.6 dB
	> 3.6 GHz	±0.9 dB
Spurious Emissions, Radiated	< 1 GHz	±2.5 dB
	> 1 GHz	±2.2 dB
Emission Bandwidth	±4 %	
Power Line Conducted Emissions		+2.9 / -4.1 dB
Spectrum Mask Measurements	Frequency	±5 %
	Amplitude	±1.0 dB
Frequency Error	±0.6 ppm	
Temperature Uncertainty	±1 °C	

All uncertainty values are expanded standard uncertainty to give a confidence level of 95%, based on coverage factor k=2



## 5 LIST OF TEST EQUIPMENT

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment and ancillaries are identified (numbered) by the Test Laboratory.

No.	Model number	Description	Manufacturer	Ref. no.	Cal. date	Cal. Due
1	ESU40	Measuring Receiver	Rohde & Schwarz	LR 1639	2022-01	2023-01
2	6810-17B	Attenuator	Suhner	LR 1669	2021-08	2022-08
3	3117-PA	Horn Antenna +PreAmp	EMCO	LR 1717	2021-08	2022-08

Note: COU – calibrate on use; N/A – Not Applicable

The software listed below has been used for one or more tests.

No.	Manufacturer	Name	Version	Comment
1	Nemko AS	RSPlot	1.0.8.0	Screenshots from R&S Spectrum Analyzers



## 6 BLOCK DIAGRAM

## 6.1 Test Site Radiated Emission



This test setup is used for all radiated emissions tests. Measuring distance is 3m for all frequencies.

Emissions above 1 GHz are measured with a Spectrum Analyzer and Horn Antenna.

All measurements at 1GHz and above were performed with turntable height 1.5m and with the ground plane covered by absorbers.

A pre-amplifier is used for all measurements, and High-Pass filter is used for all harmonics.