



**CFR 47 FCC PART 15 SUBPART C  
ISED RSS-247 ISSUE 2**

**CERTIFICATION TEST REPORT**

*For*

**Television**

**MODEL NUMBER: V655-J04**

**FCC ID: 2AYT5-V655J04**

**IC: 26954-V655J04**

**REPORT NUMBER: 4789898884.1-1**

**ISSUE DATE: May 6, 2021**

*Prepared for*

**Hefei BOE Vision-electronic Technology Co.,Ltd.  
NO.2177 Dongfang RD, Xinzhan General Pilot Zone HeFei, Anhui, 230012,  
P.R.China**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch  
Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-  
Tech Development Zone Dongguan, 523808, People's Republic of China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	05/06/2021	Initial Issue	

Note: The host product television installed the module SKI.WB7638U.1\_MT7638BUB which had already applied for the limited single module and the FCC ID is 2AYT5-SKIWB7638U2 (IC: 26954-SKIWB7638U2). Since the installation of the module in the host does not change those parameters, full radiated testing was conducted and the original conducted data from the module is being leveraged. The conducted data contained within is taken directly from the module reports. The module reports were listed as followed. For other data, please refer to the original module reports.

## Module Reports Details:

Equipment Class	Application Type	Test Report Number	Exhibit Type	FCC / ISED
DTS	Limited Single Module	SEFI2001042	Test Report	FCC
	Limited Single Module	SEDL2001042	Test Report	ISED
	Limited Single Module	4789787344.1-3	Test Report	FCC / ISED
NII	Limited Single Module	SEDL2001042	Test Report	FCC
	Limited Single Module	SEDM2001042	Test Report	ISED
	Limited Single Module	4789787344.1-4	Test Report	FCC / ISED
BLE	Limited Single Module	4789787344.1-1	Test Report	FCC / ISED
BT	Limited Single Module	4789787344.1-2	Test Report	FCC / ISED



Summary of Test Results			
Clause	Test Items	FCC/ISED Rules	Test Results
1	Peak Conducted Output Power Spot Check	FCC Part 15.247 (b) (3) RSS-247 Clause 5.4 (d)	Pass
2	Conducted Bandedge and Spurious Emission Spot Check	FCC Part 15.247 (d) RSS-247 Clause 5.5	Pass
3	Radiated Bandedge and Spurious Emission	FCC Part 15.247 (d) FCC Part 15.209 FCC Part 15.205 RSS-247 Clause 5.5 RSS-GEN Clause 8.9	Pass
4	Conducted Emission Test for AC Power Port	FCC Part 15.207 RSS-GEN Clause 8.8	Pass
5	Antenna Requirement	FCC Part 15.203 RSS-GEN Clause 6.8	Pass
<p>Note:</p> <p>1. This test report is only published to and used by the applicant, and it is not for evidence purpose in China.</p> <p>2. The measurement result for the sample received is &lt;Pass&gt; according to &lt; CFR 47 FCC PART 15 SUBPART C &gt;&lt; ISED RSS-247 &gt; when &lt;Accuracy Method&gt; decision rule is applied.</p>			

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS</b>	<b>5</b>
<b>2. TEST METHODOLOGY</b>	<b>6</b>
<b>3. FACILITIES AND ACCREDITATION</b>	<b>6</b>
<b>4. CALIBRATION AND UNCERTAINTY</b>	<b>7</b>
4.1. MEASURING INSTRUMENT CALIBRATION	7
4.2. MEASUREMENT UNCERTAINTY	7
<b>5. EQUIPMENT UNDER TEST</b>	<b>8</b>
5.1. DESCRIPTION OF EUT	8
5.2. CHANNEL LIST	8
5.3. TEST CHANNEL CONFIGURATION	8
5.4. DESCRIPTION OF AVAILABLE ANTENNAS	9
5.5. DESCRIPTION OF TEST SETUP	10
<b>6. MEASURING INSTRUMENT AND SOFTWARE USED</b>	<b>12</b>
<b>7. ANTENNA PORT TEST RESULTS</b>	<b>14</b>
7.1. ON TIME AND DUTY CYCLE	14
7.2. CONDUCTED OUTPUT POWER	16
7.3. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS	18
<b>8. RADIATED TEST RESULTS</b>	<b>21</b>
8.1. RESTRICTED BANDEDGE	27
8.1.1. LE 1M MODE	27
8.1.2. LE 2M MODE	29
8.2. SPURIOUS EMISSIONS (1 GHz ~ 3 GHz)	31
8.2.1. LE 1M MODE	31
8.3. SPURIOUS EMISSIONS (3 GHz ~ 18 GHz)	37
8.3.1. LE 1M MODE	37
8.3.2. LE 2M MODE	43
8.4. SPURIOUS EMISSIONS 18 GHz ~ 26 GHz	49
8.4.1. LE 1M MODE	49
8.5. SPURIOUS EMISSIONS 30 MHz ~ 1 GHz	51
8.5.1. LE 1M MODE	51
8.6. SPURIOUS EMISSIONS BELOW 30 MHz	53
8.6.1. LE 1M MODE	53
<b>9. AC POWER LINE CONDUCTED EMISSIONS</b>	<b>56</b>
9.1. LE 1M MODE	57

**10. ANTENNA REQUIREMENTS.....59****1. ATTESTATION OF TEST RESULTS****Applicant Information**

Company Name: Hefei BOE Vision-electronic Technology Co.,Ltd.  
Address: NO.2177 Dongfang RD, Xinzhan General Pilot Zone HeFei,  
Anhui, 230012, P.R.China

**Manufacturer Information**

Company Name: Hefei BOE Vision-electronic Technology Co.,Ltd.  
Address: NO.2177 Dongfang RD, Xinzhan General Pilot Zone HeFei,  
Anhui, 230012, P.R.China

**EUT Information**

EUT Name: Television  
Model: V655-J04  
Brand: VIZIO  
Sample Received Date: February 25, 2021  
Sample Status: Normal  
Date of Tested: March 1, 2021 ~ May 6, 2021

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS
ISED RSS-247 Issue 2	PASS
ISED RSS-GEN Issue 5	PASS

Prepared By:

Denny Huang  
Project Engineer  
Approved By:

Stephen Guo

Laboratory Manager

Checked By:

Shawn Wen  
Laboratory Leader



## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15, ANSI C63.10-2013, KDB 996369 D04 Module Integration Guide V02, ISED RSS-247 Issue 2 and ISED RSS-GEN Issue 5.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>ISED (Company No.: 21320)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p><b>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793.</p> <p>Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	---

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognize national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction Emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Maximum Conducted Output Power	$\pm 0.766$ dB
Conducted Band-edge Compliance	$\pm 1.328$ dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	$\pm 0.746$ dB (9 kHz ~ 1 GHz)
	$\pm 1.328$ dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

EUT Name	Television	
Model	V655-J04	
Technology	Bluetooth - Low Energy	
Transmit Frequency Range	2402 MHz ~ 2480 MHz	
Modulation	GFSK	
Data Rate	LE 1M	1 Mbps
	LE 2M	2 Mbps
Ratings	AC 120 V, 60 Hz	

### 5.2. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	11	2424	22	2446	33	2468
1	2404	12	2426	23	2448	34	2470
2	2406	13	2428	24	2450	35	2472
3	2408	14	2430	25	2452	36	2474
4	2410	15	2432	26	2454	37	2476
5	2412	16	2434	27	2456	38	2478
6	2414	17	2436	28	2458	39	2480
7	2416	18	2438	29	2460	/	/
8	2418	19	2440	30	2462	/	/
9	2420	20	2442	31	2464	/	/
10	2422	21	2444	32	2468	/	/

### 5.3. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
LE 1M	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz
LE 2M	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz





#### 5.4. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
0	2402-2480	PIFA	1.5

Test Mode	Transmit and Receive Mode	Description
LE 1M	<input checked="" type="checkbox"/> 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
LE 2M	<input checked="" type="checkbox"/> 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.

Note: The value of the antenna gain was declared by customer.



## 5.5. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remarks
1	Laptop	Dell	Vostro 3902	/
2	USB Disk	/	/	/
3	DVD	/	DV-410V-K	/
4	Laptop	Lenovo	E42-80	/
5	Laptop	Lenovo	E42-80	/
6	Speaker	/	MS20	/
7	50 $\Omega$ Load	/	MS20	/
8	Test fixture	/	/	/
9	Switching Adapter	FLYPOWER	PS65IBCAY5000H	Input: AC 100-240 V, 50/60 Hz, 1.5A Output: DC 12.0 V, 5000 mA

### I/O CABLES

Cable No	Port	Cable Type	Cable Length(m)	Remarks
1	USB	Unshielded	1	/
2	HDMI 1	Shielded	1.5	/
3	HDMI 2	Shielded	1.5	/
4	HDMI 3	Shielded	1.5	/
5	OPTICAL	Unshielded	1	/
6	COMPOSITE INPUT	Unshielded	2	/
7	AUDIO OUT	Unshielded	2	/
8	ANTENNA	Unshielded	1	/
9	ETHERNET	Unshielded	1	/

### ACCESSORIES


Item	Accessory	Brand Name	Model Name	Description
1	Remote Controller	/	/	/

## TEST SETUP


The EUT can work in engineering mode with a software through a Laptop.

## SETUP DIAGRAM FOR TESTS

For Conducted Test:



For Radiated Test:





## 6. MEASURING INSTRUMENT AND SOFTWARE USED

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Nov. 12, 2020	Nov. 11, 2021
Two-Line V-Network	R&S	ENV216	101983	Nov. 12, 2020	Nov. 11, 2021
Software					
Description			Manufacturer	Name	Version
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1
Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Nov. 12, 2020	Nov. 11, 2021
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	Aug. 11, 2018	Aug. 10, 2021
Preamplifier	HP	8447D	2944A09099	Nov. 12, 2020	Nov. 11, 2021
EMI Measurement Receiver	R&S	ESR26	101377	Nov. 12, 2020	Nov. 11, 2021
Horn Antenna	TDK	HRN-0118	130939	Sept. 17, 2018	Sept. 17, 2021
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Nov. 20, 2020	Nov. 19, 2021
Horn Antenna	Schwarzbeck	BBHA9170	#691	Aug. 11, 2018	Aug. 11, 2021
Preamplifier	TDK	PA-02-2	TRS-307-00003	Nov. 12, 2020	Nov. 11, 2021
Loop antenna	Schwarzbeck	1519B	00008	Jan.17, 2019	Jan.17,2022
Preamplifier	Mini-Circuits	ZX60-83LN-S+	SUP01201941	Nov. 20, 2020	Nov. 19, 2021
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Nov. 12, 2020	Nov. 11, 2021
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Nov. 12, 2020	Nov. 11, 2021
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1



Other Instruments					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Spectrum Analyzer	Keysight	N9020A	MY49100060	Nov. 20, 2020	Nov. 19, 2021
Dual Channel Power Meter	Keysight	N1912A	MY55416024	Nov. 20, 2020	Nov. 19, 2021
Power Sensor	Keysight	USB Wideband Power Sensor	MY5100022	Nov. 20, 2020	Nov. 19, 2021



## 7. ANTENNA PORT TEST RESULTS

### 7.1. ON TIME AND DUTY CYCLE


#### LIMITS

None; for reporting purposes only.

#### PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	22.8 °C	Relative Humidity	64.3 %
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V

#### RESULTS

Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (db)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
LE 1M	0.375	0.625	0.600	60.00	2.22	2.67	3
LE 2M	0.325	0.625	0.520	52.00	2.84	3.08	5



Note:

Duty Cycle Correction Factor= $10\log(1/x)$ .

Where: x is Duty Cycle(Linear)

Where: T is On Time (transmit duration)

If that calculated VBW is not available on the analyzer then the next higher value should be used.





## 7.2. CONDUCTED OUTPUT POWER

### LIMITS


CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3) ISED RSS-247 5.4 (d)	Peak Conducted Output Power	1 watt or 30 dBm	2400-2483.5

### TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

### TEST SETUP



### TEST ENVIRONMENT

Temperature	23.6 °C	Relative Humidity	67.2 %
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V

### RESULTS





## Spot Check Verification Result:

Test Item	Test Mode	Frequency	Worst Case Test Result	
			Original Model	Spot Check Model
			dBm	dBm
Conducted Peak Power	LE 1M	2402 MHz	5.94	5.89
		2440 MHz	5.24	5.21
		2480 MHz	4.51	4.55
	LE 2M	2402 MHz	5.94	5.88
		2440 MHz	5.26	5.23
		2480 MHz	4.52	4.46

## Conclusion:

The spot check test result show that the new devices still comply with the standard and the new test result was close to the original test result, so it can demonstrate that the original test data remains valid for the new device.



### 7.3. CONDUCTED BANDEGE AND SPURIOUS EMISSIONS

#### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d) ISED RSS-247 5.5	Conducted Bandedge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

#### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.


Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.



## TEST SETUP



## TEST ENVIRONMENT

Temperature	23.6 °C	Relative Humidity	67.2 %
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V



## RESULTS

### Spot Check Verification Summery

Test Item	Test Mode	Test Channel	Worst Case Test Result	
			Original Model	Spot Check Model
		MHz	dBm	
Conducted Bandedge	LE 2M	2402	-29.39	-28.83
Spurious Emission	LE 2M	2402	-54.44	-61.50

### Conclusion:

The spot check test result show that the new devices still comply with the standard and the new test result was close to the original test result, so it can demonstrate that the original test data remains valid for the new device.



## 8. RADIATED TEST RESULTS

### LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (9 kHz-1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (μA/m)	Measurement distance (m)
9 - 490 kHz <sup>Note 1</sup>	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

**Note 1:** The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.



ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

**Note 1:** Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup>Above 38.6c

## TEST SETUP AND PROCEDURE

Below 30 MHz




The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz) / 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz) / 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 11.11 & 11.12.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

Below 1 GHz and above 30 MHz




The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 11.11 & 11.12.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.



Above 1 GHz



The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 11.11 and 11.12.
2. The EUT was arranged to its worst case and then tune the antenna tower (1.5 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.



Note: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

#### **TEST ENVIRONMENT**


Temperature	22.6 °C	Relative Humidity	64.4 %
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V

#### **RESULTS**

## 8.1. RESTRICTED BANDEDGE

### 8.1.1. LE 1M MODE


#### RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2370.605	14.24	33.21	47.45	74.00	-26.55	peak
2	2390.000	12.34	33.35	45.69	74.00	-28.31	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
5. For the transmitting duration, please refer to clause 7.1.  
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	14.08	33.71	47.79	74.00	-26.21	peak
2	2485.825	16.05	33.71	49.76	74.00	-24.24	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. AVG:  $VBW=1/T_{on}$ , where:  $T_{on}$  is the transmitting duration.  
5. For the transmitting duration, please refer to clause 7.1.  
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: Both the horizontal and vertical polarities had been tested, only the worst data was recorded in the report.

## 8.1.2. LE 2M MODE


### RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.970	13.69	33.34	47.03	74.00	-26.97	peak
2	2390.000	11.72	33.35	45.07	74.00	-28.93	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
5. For the transmitting duration, please refer to clause 7.1.  
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	19.63	33.71	53.34	74.00	-20.66	peak
2	2483.550	19.81	33.71	53.52	74.00	-20.48	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
5. For the transmitting duration, please refer to clause 7.1.  
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: Both the horizontal and vertical polarities had been tested, only the worst data was recorded in the report.

## 8.2. SPURIOUS EMISSIONS (1 GHz ~ 3 GHz)

### 8.2.1. LE 1M MODE


#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1194.000	45.58	-13.02	32.56	74.00	-41.44	peak
2	1724.000	44.85	-10.62	34.23	74.00	-39.77	peak
3	1920.000	50.22	-10.13	40.09	74.00	-33.91	peak
4	2402.000	50.66	-8.39	42.27	/	/	fundamental
5	2772.000	43.25	-6.74	36.51	74.00	-37.49	peak
6	2964.000	42.77	-5.76	37.01	74.00	-36.99	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1254.000	45.74	-12.91	32.83	74.00	-41.17	peak
2	1724.000	44.20	-10.62	33.58	74.00	-40.42	peak
3	1920.000	52.30	-10.13	42.17	74.00	-31.83	peak
4	2402.000	43.94	-8.39	35.55	/	/	fundamental
5	2758.000	43.55	-6.82	36.73	74.00	-37.27	peak
6	2826.000	43.68	-6.43	37.25	74.00	-36.75	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1542.000	44.19	-11.94	32.25	74.00	-41.75	peak
2	1814.000	44.39	-10.06	34.33	74.00	-39.67	peak
3	1920.000	48.90	-10.13	38.77	74.00	-35.23	peak
4	2270.000	43.75	-8.82	34.93	74.00	-39.07	peak
5	2440.000	48.94	-8.33	40.61	/	/	fundamental
6	2842.000	43.00	-6.35	36.65	74.00	-37.35	peak

- Note:
1. Peak Result = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. Peak: Peak detector.
  4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses
  5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1174.000	46.23	-13.13	33.10	74.00	-40.90	peak
2	1736.000	44.90	-10.52	34.38	74.00	-39.62	peak
3	1920.000	53.23	-10.13	43.10	74.00	-30.90	peak
4	2440.000	45.29	-8.33	36.96	/	/	fundamental
5	2782.000	43.23	-6.67	36.56	74.00	-37.44	peak
6	2972.000	42.69	-5.73	36.96	74.00	-37.04	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1550.000	44.64	-11.90	32.74	74.00	-41.26	peak
2	1720.000	45.16	-10.65	34.51	74.00	-39.49	peak
3	1920.000	49.91	-10.13	39.78	74.00	-34.22	peak
4	2370.000	44.56	-8.49	36.07	74.00	-37.93	peak
5	2480.000	46.48	-8.26	38.22	/	/	fundamental
6	2764.000	43.42	-6.79	36.63	74.00	-37.37	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1548.000	45.75	-11.91	33.84	74.00	-40.16	peak
2	1724.000	45.29	-10.62	34.67	74.00	-39.33	peak
3	1920.000	53.20	-10.13	43.07	74.00	-30.93	peak
4	2374.000	44.02	-8.48	35.54	74.00	-38.46	peak
5	2480.000	45.35	-8.26	37.09	/	/	fundamental
6	2778.000	43.36	-6.69	36.67	74.00	-37.33	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


Note: All the modes and channels have been tested, only the worst data was recorded in the report.



### 8.3. SPURIOUS EMISSIONS (3 GHz ~ 18 GHz)

#### 8.3.1. LE 1M MODE

##### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7005.000	35.49	7.60	43.09	74.00	-30.91	peak
2	8145.000	37.31	10.01	47.32	74.00	-26.68	peak
3	11730.000	34.54	15.32	49.86	74.00	-24.14	peak
4	12675.000	35.17	15.66	50.83	74.00	-23.17	peak
5	14745.000	33.27	17.84	51.11	74.00	-22.89	peak
6	17655.000	29.23	23.14	52.37	74.00	-21.63	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	38.41	4.00	42.41	74.00	-31.59	peak
2	8025.000	38.26	9.01	47.27	74.00	-26.73	peak
3	10395.000	35.28	12.20	47.48	74.00	-26.52	peak
4	12210.000	34.11	15.97	50.08	74.00	-23.92	peak
5	14775.000	33.25	17.95	51.20	74.00	-22.80	peak
6	17295.000	29.68	22.58	52.26	74.00	-21.74	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. AVG:  $VBW=1/T_{on}$ , where:  $T_{on}$  is the transmitting duration.  
5. For the transmitting duration, please refer to clause 7.1.  
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5655.000	39.58	3.04	42.62	74.00	-31.38	peak
2	7815.000	37.53	9.28	46.81	74.00	-27.19	peak
3	9240.000	37.37	10.10	47.47	74.00	-26.53	peak
4	11835.000	35.34	15.34	50.68	74.00	-23.32	peak
5	14760.000	33.38	17.90	51.28	74.00	-22.72	peak
6	17085.000	30.71	21.80	52.51	74.00	-21.49	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5865.000	38.52	4.16	42.68	74.00	-31.32	peak
2	8115.000	37.21	10.13	47.34	74.00	-26.66	peak
3	9375.000	36.37	10.83	47.20	74.00	-26.80	peak
4	11925.000	34.92	15.52	50.44	74.00	-23.56	peak
5	14310.000	33.50	18.05	51.55	74.00	-22.45	peak
6	17670.000	28.84	23.24	52.08	74.00	-21.92	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
5. For the transmitting duration, please refer to clause 7.1.  
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.




### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.000	39.87	1.33	41.20	74.00	-32.80	peak
2	5865.000	38.18	4.16	42.34	74.00	-31.66	peak
3	7815.000	38.52	9.28	47.80	74.00	-26.20	peak
4	11745.000	34.29	15.30	49.59	74.00	-24.41	peak
5	13530.000	33.89	17.19	51.08	74.00	-22.92	peak
6	17070.000	30.44	21.71	52.15	74.00	-21.85	peak

Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	38.69	4.00	42.69	74.00	-31.31	peak
2	8250.000	38.09	9.75	47.84	74.00	-26.16	peak
3	10260.000	36.24	11.68	47.92	74.00	-26.08	peak
4	12510.000	35.05	15.69	50.74	74.00	-23.26	peak
5	14820.000	33.10	17.91	51.01	74.00	-22.99	peak
6	17295.000	29.83	22.58	52.41	74.00	-21.59	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
5. For the transmitting duration, please refer to clause 7.1.  
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### 8.3.2. LE 2M MODE

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5880.000	37.19	4.31	41.50	74.00	-32.50	peak
2	8235.000	37.62	9.76	47.38	74.00	-26.62	peak
3	8970.000	37.11	10.70	47.81	74.00	-26.19	peak
4	11505.000	35.89	14.66	50.55	74.00	-23.45	peak
5	14820.000	32.90	17.91	50.81	74.00	-23.19	peak
6	17280.000	29.23	22.48	51.71	74.00	-22.29	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5925.000	38.15	4.38	42.53	74.00	-31.47	peak
2	8115.000	37.40	10.13	47.53	74.00	-26.47	peak
3	11820.000	34.88	15.29	50.17	74.00	-23.83	peak
4	13590.000	33.24	17.11	50.35	74.00	-23.65	peak
5	14805.000	32.83	18.00	50.83	74.00	-23.17	peak
6	17670.000	28.51	23.24	51.75	74.00	-22.25	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.  
5. For the transmitting duration, please refer to clause 7.1.  
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5895.000	38.61	4.46	43.07	74.00	-30.93	peak
2	8295.000	37.71	9.69	47.40	74.00	-26.60	peak
3	11730.000	34.41	15.32	49.73	74.00	-24.27	peak
4	13515.000	33.44	17.19	50.63	74.00	-23.37	peak
5	14730.000	32.86	17.79	50.65	74.00	-23.35	peak
6	17550.000	29.81	22.38	52.19	74.00	-21.81	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7050.000	36.32	7.63	43.95	74.00	-30.05	peak
2	7755.000	39.03	8.94	47.97	74.00	-26.03	peak
3	11835.000	35.10	15.34	50.44	74.00	-23.56	peak
4	12600.000	35.19	15.78	50.97	74.00	-23.03	peak
5	13890.000	34.10	17.53	51.63	74.00	-22.37	peak
6	17085.000	30.84	21.80	52.64	74.00	-21.36	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.  
5. For the transmitting duration, please refer to clause 7.1.  
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5925.000	38.46	4.38	42.84	74.00	-31.16	peak
2	8115.000	38.36	10.13	48.49	74.00	-25.51	peak
3	9390.000	36.97	10.92	47.89	74.00	-26.11	peak
4	11865.000	34.80	15.42	50.22	74.00	-23.78	peak
5	13890.000	33.00	17.53	50.53	74.00	-23.47	peak
6	16920.000	30.45	21.51	51.96	74.00	-22.04	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8220.000	37.55	9.79	47.34	74.00	-26.66	peak
2	9330.000	36.76	10.57	47.33	74.00	-26.67	peak
3	12645.000	34.17	15.71	49.88	74.00	-24.12	peak
4	13530.000	33.41	17.19	50.60	74.00	-23.40	peak
5	14820.000	33.37	17.91	51.28	74.00	-22.72	peak
6	17100.000	30.26	21.90	52.16	74.00	-21.84	peak


- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.  
5. For the transmitting duration, please refer to clause 7.1.  
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.



## 8.4. SPURIOUS EMISSIONS 18 GHz ~ 26 GHz

### 8.4.1. LE 1M MODE

#### SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18608.000	47.87	-5.33	42.54	74.00	-31.46	peak
2	19952.000	47.46	-5.41	42.05	74.00	-31.95	peak
3	21032.000	47.65	-4.87	42.78	74.00	-31.22	peak
4	23304.000	47.13	-3.32	43.81	74.00	-30.19	peak
5	24008.000	45.64	-2.75	42.89	74.00	-31.11	peak
6	24912.000	44.42	-2.18	42.24	74.00	-31.76	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

### SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19432.000	47.60	-5.57	42.03	74.00	-31.97	peak
2	20272.000	47.77	-5.60	42.17	74.00	-31.83	peak
3	21288.000	47.29	-4.75	42.54	74.00	-31.46	peak
4	22792.000	46.11	-3.65	42.46	74.00	-31.54	peak
5	24192.000	45.71	-2.81	42.90	74.00	-31.10	peak
6	25032.000	44.94	-2.04	42.90	74.00	-31.10	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


Note: All the modes have been tested, only the worst data was recorded in the report.



## 8.5. SPURIOUS EMISSIONS 30 MHz ~ 1 GHz

### 8.5.1. LE 1M MODE


#### SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	101.7800	52.66	-21.00	31.66	43.50	-11.84	QP
2	353.0100	47.92	-14.25	33.67	46.00	-12.33	QP
3	398.6000	50.60	-13.37	37.23	46.00	-8.77	QP
4	455.8300	49.67	-12.27	37.40	46.00	-8.60	QP
5	556.7100	46.55	-10.38	36.17	46.00	-9.83	QP
6	575.1400	45.49	-10.03	35.46	46.00	-10.54	QP

- Note: 1. Result Level = Read Level + Correct Factor.  
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

### SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	40.6699	55.34	-20.05	35.29	40.00	-4.71	QP
2	194.9000	48.60	-16.49	32.11	43.50	-11.39	QP
3	355.9200	46.08	-14.19	31.89	46.00	-14.11	QP
4	554.7700	47.06	-10.41	36.65	46.00	-9.35	QP
5	660.5000	45.72	-8.68	37.04	46.00	-8.96	QP
6	704.1500	42.47	-8.29	34.18	46.00	-11.82	QP

Note: 1. Result Level = Read Level + Correct Factor.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto

Note: All the modes have been tested, only the worst data was recorded in the report.




## 8.6. SPURIOUS EMISSIONS BELOW 30 MHz

### 8.6.1. LE 1M MODE

#### SPURIOUS EMISSIONS (LOW CHANNEL, LOOP ANTENNA FACE ON TO THE EUT, WORST-CASE CONFIGURATION)

9 kHz~ 150 kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.0094	72.66	-101.35	-28.69	48.05	-80.19	-3.45	-76.74	peak
2	0.0131	71.75	-101.38	-29.63	45.25	-81.13	-6.25	-74.88	peak
3	0.0160	68.91	-101.37	-32.46	43.52	-83.96	-7.98	-75.98	peak
4	0.0258	63.96	-101.37	-37.41	39.37	-88.91	-12.13	-76.78	peak
5	0.0587	59.98	-101.52	-41.54	32.23	-93.04	-19.27	-73.77	peak
6	0.1058	55.96	-101.78	-45.82	27.11	-97.32	-24.39	-72.93	peak

Note: 1. Measurement = Reading Level + Correct Factor (dBuA/m= dBuV/m- 20Log10[120π] = dBuV/m- 51.5).

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

150 kHz ~ 490 kHz


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.1517	74.25	-101.63	-27.38	23.98	-78.88	-27.52	-51.36	peak
2	0.1800	72.12	-101.68	-29.56	22.5	-81.06	-29.00	-52.06	peak
3	0.2091	66.82	-101.73	-34.91	21.19	-86.41	-30.31	-56.10	peak
4	0.2782	63.29	-101.83	-38.54	18.71	-90.04	-32.79	-57.25	peak
5	0.3234	62.48	-101.88	-39.4	17.41	-90.90	-34.09	-56.81	peak
6	0.4047	58.41	-101.96	-43.55	15.46	-95.05	-36.04	-59.01	peak

Note: 1. Measurement = Reading Level + Correct Factor (dBuA/m= dBuV/m- 20Log10[120 $\pi$ ] = dBuV/m- 51.5).

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

### 490 kHz ~ 30 MHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.5127	60.77	-62.08	-1.31	33.41	-52.81	-18.09	-34.72	peak
2	1.0212	57.99	-62.25	-4.26	27.42	-55.76	-24.08	-31.68	peak
3	3.4704	56.85	-61.46	-4.61	29.54	-56.11	-21.96	-34.15	peak
4	3.9786	54.44	-61.34	-6.9	29.54	-58.40	-21.96	-36.44	peak
5	8.0151	51.34	-61.07	-9.73	29.54	-61.23	-21.96	-39.27	peak
6	15.3925	50.50	-61.00	-10.5	29.54	-62.00	-21.96	-40.04	peak

Note: 1. Measurement = Reading Level + Correct Factor (dBuA/m= dBuV/m- 20Log10[120π] = dBuV/m- 51.5).

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

Note: All the modes have been tested, only the worst data was recorded in the report.

## 9. AC POWER LINE CONDUCTED EMISSIONS


### LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

### TEST SETUP AND PROCEDURE

Refer to ANSI C63.10-2013 clause 6.2.




The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

### TEST ENVIRONMENT

Temperature	24.1 °C	Relative Humidity	57.1 %
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V



**TEST RESULTS****9.1. LE 1M MODE****LINE L RESULTS (LOW CHANNEL, WORST-CASE CONFIGURATION)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1717	43.60	9.59	53.19	64.88	-11.69	QP
2	0.1717	30.75	9.59	40.34	54.88	-14.54	AVG
3	0.3840	29.80	9.59	39.39	58.19	-18.80	QP
4	0.3840	21.79	9.59	31.38	48.19	-16.81	AVG
5	0.7456	26.42	9.60	36.02	56.00	-19.98	QP
6	0.7456	11.77	9.60	21.37	46.00	-24.63	AVG
7	1.0800	24.88	9.61	34.49	56.00	-21.51	QP
8	1.0800	10.40	9.61	20.01	46.00	-25.99	AVG
9	15.0148	31.83	9.66	41.49	60.00	-18.51	QP
10	15.0148	28.09	9.66	37.75	50.00	-12.25	AVG
11	20.2497	17.28	9.84	27.12	60.00	-32.88	QP
12	20.2497	12.03	9.84	21.87	50.00	-28.13	AVG


Note: 1. Result = Reading +Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).

4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

### LINE N RESULTS (LOW CHANNEL, WORST-CASE CONFIGURATION)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1720	40.67	9.59	50.26	64.86	-14.60	QP
2	0.1720	3.37	9.59	12.96	54.86	-41.90	AVG
3	0.3818	29.81	9.59	39.40	58.24	-18.84	QP
4	0.3818	18.79	9.59	28.38	48.24	-19.86	AVG
5	0.5522	27.30	9.60	36.90	56.00	-19.10	QP
6	0.5522	10.18	9.60	19.78	46.00	-26.22	AVG
7	0.7093	28.92	9.60	38.52	56.00	-17.48	QP
8	0.7093	13.88	9.60	23.48	46.00	-22.52	AVG
9	0.9857	26.54	9.61	36.15	56.00	-19.85	QP
10	0.9857	9.18	9.61	18.79	46.00	-27.21	AVG
11	14.9548	32.81	9.66	42.47	60.00	-17.53	QP
12	14.9548	29.37	9.66	39.03	50.00	-10.97	AVG

Note: 1. Result = Reading +Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).

4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.



## 10. ANTENNA REQUIREMENTS

### APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### RESULTS

Complies

---

**END OF REPORT**