



## RF Exposure evaluation

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$
$$f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz}$$

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

### EDR:

Worse case output power is as below: [2480MHz: 5.28dBm]

Maximum output power is 5.28dBm (3.37mW).

$(3.37\text{mW} / 5\text{mm}) \cdot [\sqrt{2.480(\text{GHz})}] = 1.06 < 3.0$  for 1-g SAR.

### BLE:

Worse case output power is as below: [2440MHz: 4.70dBm]

Maximum output power is 4.70dBm (2.95 mW).

$(2.95\text{mW} / 5\text{mm}) \cdot [\sqrt{2.440(\text{GHz})}] = 0.92 < 3.0$  for 1-g SAR.

Then SAR evaluation is not required.