



849 NW STATE ROAD 45
NEWBERRY, FL 32669 USA
PH: 888.472.2424 OR
352.472.5500
FAX: 352.472.2030
EMAIL: INFO@TIMCOENGR.COM
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

RF Exposure Evaluation Report

APPLICANT	FIPLEX COMMUNICATIONS INC.
	7331 N.W. 54TH STREET MIAMI FL 33166
FCC ID	P3TDHS40-HG-SCH
MODEL NUMBER	DHS40-HG-SCH
PRODUCT DESCRIPTION	PS800 SINGLE CARRIER AMPLIFIER
STANDARD APPLIED	CFR 47 Part 2.1091
PREPARED BY	Sid Sanders

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

GENERAL REMARKS

Attestations

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, FL 32669

Authorized Signatory Name:



Sid Sanders, Engineer

Date: 7/20/2017

Applicant: FIPLEX COMMUNICATIONS INC.

FCC ID: P3TDHS40-HG-SCH

Report: F\FIPLEX_P3T\1087AUT17\1087AUT17RF Exp MPE Rpt_Rev.docx

RF Exposure Requirements

General information

Device type: PS800 SINGLE CARRIER AMPLIFIER

Antenna

The manufacturer does not specify an antenna, but a typical antenna has a gain of 0 dBi.

Configuration	Antenna p/n	Type	Max. Gain (dBi)
Fixed mounted	Any		0

MPE Calculation:

The minimum separation distance is calculated as follows:

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power density: } P_d(mW/cm^2) = \frac{E^2}{3770}$$

The limit for general uncontrolled exposure environment is shown in FCC rule Part 1.11310, Table 1.

Applicant: FIPLEX COMMUNICATIONS INC.

FCC ID: P3TDHS40-HG-SCH

Report: F\FIPLEX_P3T\1087AUT17\1087AUT17RF Exp MPE Rpt_Rev.docx

Insert values in yellow highlighted boxes to determine Minimum Separation Distance

Max Power	10	W	<i>equals</i>	Max Power	10000	mW
Duty Cycle	100	%	<i>equals</i>	Duty Factor	1	numeric
Antenna Gain	0	dBi	<i>equals</i>	Gain numeric	1	numeric
Coax Loss	0	dB		Gain - Coax Los	1	numeric
Power Density	0.5	mW/cm ²				
Frequency	824	MHz				

Enter power Density from the chart to the right

Rule Part 1.1310, Table 1 (B)

Frequency range	Power der	Enter this value
MHz	mW/cm ²	mW/cm ²
0.3-1.34	100	100
1.34-30	180/f ²	0.0
30-300	0.2	0.2
300-1,500	f/1500	0.5
1,500-100,000	1	1

f = frequency in MHz

Minimum Separation Distance	40 cm	0.40 m
------------------------------------	--------------	---------------

Minimum Separation in Inches 15.69439 Inches

Applicant: FIPLEX COMMUNICATIONS INC.

FCC ID: P3TDHS40-HG-SCH

Report: F\FIPLEX_P3T\1087AUT17\1087AUT17RF Exp MPE Rpt_Rev.docx