



REPORT No. : SZ19050235E01

TEST REPORT

APPLICANT : Jiangsu SEUIC Technology Co.,Ltd.

PRODUCT NAME : Industrial Handheld Terminal

MODEL NAME : AUTOID Q7

BRAND NAME : Seuic

FCC ID : 2AC68-AUTOIDQ7

STANDARD(S) : 47 CFR Part 15 Subpart B

RECEIPT DATE : 2019-05-20

TEST DATE : 2019-05-30 to 2019-06-03

ISSUE DATE : 2019-08-30

Edited by:

Zeng Jianqing

Zeng Jianqing(Rapporteur)

Approved by:

Andy Yeh

Andy Yeh(Technical Director)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Technical Information	3
1.1. Applicant and Manufacturer Information	3
1.2. Equipment Under Test (EUT) Description	3
2. Test Results	5
2.1. Applied Reference Documents	5
2.2. EUT Setup and Operating Conditions	6
3. 47 CFR Part 15B Requirements	7
3.1. Conducted Emission	7
3.2. Radiated Disturbance	11
Annex A Photographs of Test Setup	18
Annex B Test Uncertainty	20
Annex C Testing Laboratory Information	21

Change History		
Version	Date	Reason for change
1.0	2019-08-30	First edition



1. Technical Information

Note: Provide by applicant

1.1. Applicant and Manufacturer Information

Applicant:	Jiangsu SEUIC Technology Co.,Ltd.
Applicant Address:	NO.15 Xinghuo Road, Nanjing New & High Technology Industry Development Zone, Nanjing 210061, China
Manufacturer:	Jiangsu SEUIC Technology Co.,Ltd.
Manufacturer Address:	NO.15 Xinghuo Road, Nanjing New & High Technology Industry Development Zone, Nanjing 210061, China

1.2. Equipment Under Test (EUT) Description

Product Name:	Industrial Handheld Terminal	
Serial No:	(N/A, marked #1 by test site)	
Hardware Version:	D310PA_V3_MB	
Software Version:	D310P_20190412_V142	
Frequency Range:	802.11b/g/n: 2412 MHz ~ 2472 MHz 802.11a/ac/n: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5700 MHz;5745MHz ~ 5825 MHz; Bluetooth: 2402 MHz ~ 2480 MHz NFC:13.56MHz	
Ancillary Equipment:	Battery 1	
	Brand Name:	N/A
	Model No.:	BT01310AIQ7
	Serial No.:	(N/A, marked #1 by test site)
	Capacity:	5000mAh
	Rated Voltage:	3.63V
	Charge Limit:	4.20V
	Battery 2	
	Brand Name:	N/A
	Model No.:	351322
	Serial No.:	(N/A, marked #1 by test site)
	Capacity:	90mAh
	Rated Voltage:	3.7V
	Charge Limit:	4.2V



REPORT No. : SZ19050235E01

	AC Adapter	
	Brand Name:	SZTY
	Model No.:	TPA-23A050200UU01
	Serial No.:	(N/A, marked #1 by test site)
	Rated Input:	100-240V ~ 50/60Hz 0.3A
	Rated Output:	5V $\overline{\text{---}}$ 2A

Note:

1. The product has two shipping modes, one is a separate Industrial Handheld Terminal, and the other is an Industrial Handheld Terminal without a PISTOL GRIP.
2. For a more detailed description, please refer to specification or user's manual supplied by the applicant and/or manufacturer.



2. Test Results

2.1. Applied Reference Documents

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method determination Remark
1	15.107	Conducted Emission	2019.06.13	Ya Xinhou	PASS	No deviation
2	15.109	Radiated Emission	2019.05.30	Ya Xinhou	PASS	No deviation

NOTE 1: The tests were performed according to the method of measurements prescribed in ANSI C63.4-2014.

NOTE 2: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.



2.2. EUT Setup and Operating Conditions

Test Item	
Radiated Emission	
Mode 1 :	EUT + USB Cable + Adapter + Camera
Mode 2 :	EUT + USB Cable + PC (Transmitting Data)
Conducted Emission	
Mode 1 :	EUT + USB Cable + Adapter + Camera
Mode 2 :	EUT + USB Cable + PC (Transmitting Data)
Remark: The above test modes (mode 2) in boldface were the worst cases of conducted emission, radiated emission; only the test data of these modes was reported. only the result in the boldface mode (mode 2) is recorded in this report.	

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 - 60
Atmospheric Pressure (kPa):	86 - 106

3. 47 CFR Part 15B Requirements

3.1. Conducted Emission

3.1.1. Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- The limit subjects to the Class B digital device.
- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.1.2. Test Setup

Please refer to Annex A for the photographs of the Test Configuration.






The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides 50Ω/50μH of coupling impedance for the measuring instrument. A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

The power strip or extension cord has been investigated to make sure that the LISN integrity is maintained with respect to the impedance characteristics as prescribed in ANSI C63.4-2014 at Clause 4.3.


3.1.3. Test Result

The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.

A. Test Plot and Suspicious Points:



NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.2040	57.66	39.59	63.45	53.45	Line	PASS
2	0.2536	50.65	30.86	61.64	51.64		PASS
3	0.3166	42.48	25.93	59.80	49.80		PASS
4	0.6186	37.49	26.28	56.00	46.00		PASS
5	0.9247	31.78	22.57	56.00	46.00		PASS
6	1.3390	31.79	23.31	56.00	46.00		PASS



NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1903	56.68	37.55	64.02	54.02	Neutral	PASS
2	0.2582	48.08	32.05	61.49	51.49		PASS
3	0.3162	40.16	26.24	59.81	49.81		PASS
4	0.5374	41.68	29.96	56.00	46.00		PASS
5	0.7842	36.36	25.38	56.00	46.00		PASS
6	1.5839	34.83	25.23	56.00	46.00		PASS

3.2. Radiated Disturbance

3.2.1. Requirement

According to FCC section 15.109 (a), the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range (MHz)	Field Strength Limitation at 3m Measurement Dist	
	($\mu\text{V/m}$)	(dB $\mu\text{V/m}$)
30.0 - 88.0	100	20log 100
88.0 - 216.0	150	20log 150
216.0 - 960.0	200	20log 200
Above 960.0	500	20log 500

As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in dB $\mu\text{V/m}$ is calculated by 20log Emission Level($\mu\text{V/m}$).


3.2.2. Frequency range of measurement

According to 15.33(b)(1), the frequency range of radiated measurement for the EUT is listed in the following table:


Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30.
1.705–108	1000.
108–500	2000.
500–1000	5000.
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

3.2.3. Test Setup

- 1) For radiated emissions from 30MHz to 1GHz



- 2) For radiated emissions above 1GHz





The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

For the test Antenna:


In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

3.2.4. Test Result


The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of emissions which (6GHz-12.5GHz) are attenuated more than 20 dB below the permissible value need not be reported.


Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.




No.	Fre. MHz	Pk dBμV/m	QP dBμV/m	AV dBμV/m	Limit-PK dBμV/m	Limit-QP dBμV/m	Limit-AV dBμV/m	ANT	Verdict
1	34.8549	34.00	N.A	N.A	N.A	40.00	N.A	V	PASS
2	103.7938	24.82	N.A	N.A	N.A	43.50	N.A	V	PASS
3	132.9229	25.13	N.A	N.A	N.A	43.50	N.A	V	PASS
4	237.7878	24.46	N.A	N.A	N.A	46.00	N.A	V	PASS
5	464.9950	28.47	N.A	N.A	N.A	46.00	N.A	V	PASS
6	997.0871	37.47	N.A	N.A	N.A	54.00	N.A	V	PASS



No.	Fre. MHz	Pk dBμV/m	QP dBμV/m	AV dBμV/m	Limit-PK dBμV/m	Limit-QP dBμV/m	Limit-AV dBμV/m	ANT	Verdict
1	1337.6688	35.80	N.A	N.A	74.00	N.A	54.00	V	PASS
2	1892.9465	36.41	N.A	N.A	74.00	N.A	54.00	V	PASS
3	2288.1441	37.58	N.A	N.A	74.00	N.A	54.00	V	PASS
4	3226.1131	40.18	N.A	N.A	74.00	N.A	54.00	V	PASS
5	3961.4807	43.48	N.A	N.A	74.00	N.A	54.00	V	PASS
6	5449.7249	43.59	N.A	N.A	74.00	N.A	54.00	V	PASS



No.	Fre. MHz	Pk dBμV/m	QP dBμV/m	AV dBμV/m	Limit-PK dBμV/m	Limit-QP dBμV/m	Limit-AV dBμV/m	ANT	Verdict
1	35.8258	34.84	N.A	N.A	N.A	40.00	N.A	H	PASS
2	103.7938	24.52	N.A	N.A	N.A	43.50	N.A	H	PASS
3	126.1261	24.05	N.A	N.A	N.A	43.50	N.A	H	PASS
4	237.7878	28.35	N.A	N.A	N.A	46.00	N.A	H	PASS
5	330.0300	30.44	N.A	N.A	N.A	46.00	N.A	H	PASS
6	823.2833	27.76	N.A	N.A	N.A	46.00	N.A	H	PASS



No.	Fre. MHz	Pk dBμV/m	QP dBμV/m	AV dBμV/m	Limit-PK dBμV/m	Limit-QP dBμV/m	Limit-AV dBμV/m	ANT	Verdict
1	1142.5713	34.75	N.A	N.A	74.00	N.A	54.00	H	PASS
2	1630.3152	35.61	N.A	N.A	74.00	N.A	54.00	H	PASS
3	2360.6803	38.11	N.A	N.A	74.00	N.A	54.00	H	PASS
4	3148.5743	40.41	N.A	N.A	74.00	N.A	54.00	H	PASS
5	4034.0170	44.00	N.A	N.A	74.00	N.A	54.00	H	PASS
6	5814.9075	44.71	N.A	N.A	74.00	N.A	54.00	H	PASS

Annex A Photographs of Test Setup


1. Mains Terminal Disturbance Voltage Measurement




2. Conducted emission main's port side view



3. Radiated Field Strength Measurement(30MHz-1GHz)



4. Radiated Field Strength Measurement(above 1GHz)





Annex B Test Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission Measurement

Measuring Uncertainty for a Level of Confidence of 95%(U=2Uc(y))	9kHz-150kHz	±4.1 dB
	150kHz-30MHz	±3.7dB

Uncertainty of Radiated Emission Measurement

Measuring Uncertainty for a Level of Confidence of 95%(U=2Uc(y))	30MHz-200MHz	±5.06dB
	200MHz-1000MHz	±5.24dB
	1GHz-6GHz	±5.18dB
	6GHz-18GHz	±5.48dB



Annex C Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

3. Accreditation Certificate

Accredited Testing Laboratory:	The FCC designation number is CN1192. Test firm registration number is 226174. (Shenzhen Morlab Communications Technology Co., Ltd.)
---------------------------------------	--

4. Test Software Utilized

Model	Version Number	Producer
JS32-RE	Version 2.0.2.0	Tonscend
TS+ -[JS32-CE]	Version 2.5.0.0	Tonscend

**5. Test Equipments Utilized**

Description	Manufacturer	Model	Serial No.	Cal. Date	Due. Date
MXE EMI Receiver	Agilent	N9038A	MY54130016	2019.04.09	2020.04.08
Test Receiver	R&S	ESPI	101052	2018.08.04	2019.08.03
LISN	Schwarzbeck	NSLK 8127	812744	2019.05.08	2020.05.07
Pulse Limiter (20dB)	VTSD	9561D	9537	2019.05.08	2020.05.07
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-519	2019.05.08	2020.05.07
Test Antenna - Horn	Schwarzbeck	BBHA 9120D	1774	2019.05.08	2020.05.07
Radiated Disturbance Preamplifier	rflight	S020180L3203	61171/61172	2018.07.12	2019.07.11
Radiated Disturbance Preamplifier	rflight	S10M100L3802	46732	2018.07.12	2019.07.11
Semi-Anechoic Chamber	CRT	9m*6m*6m	N/A	2017.01.12	2020.01.11
Mobile Phone	Huawei Technologies Co., Ltd	PLK-AL10	2015CP1986	N/A	N/A
PC	Apple	A1370	C02FQ2PYDQW	N/A	N/A

_____ END OF REPORT _____