


OmPlecs®-TOP 90 RAIL WiFi 2.4-5.8 MIMO

- Antenne für den Zuginnenbereich / Antenna for indoor use -










WLAN 2.4 - WLAN 5.8 (MIMO) – WiFi-6E

100-57-61-02.4

Verwendungszweck	Dualband MIMO Sende- und Empfangsantenne für die Verwendung im Innenbereich von Schienenfahrzeugen	
Purpose	Dualband MIMO transmitting and receiving train antenna for indoor use	

Technical data / Technische Daten		
RF-Port	a	b
Spectrum	WLAN / WiFi-6E	WLAN / WiFi-6E
Frequency [MHz]	2400 - 2500 5180 - 5835	2400 - 2500 5180 - 5835
Polarization	vertical / horizontal	vertical / horizontal
Pattern	omnidirectional	omnidirectional
Gain	8,4 dBi (WLAN 2.4) 9,1 dBi (WLAN 5.8)	8,4 dBi (WLAN 2.4) 9,1 dBi (WLAN 5.8)
Efficiency	88 %	88 %
VSWR	≤ 1,8 typ.	≤ 1,8 typ.
Impedance	50 Ω	50 Ω
Antenna type	Patch antenna	Patch antenna
Power / DC Voltage	50 W	50 W
RF-Connection	SMA(f)	SMA(f)
Ground-plane	integrated	integrated

Radiation Diagrams / Richtdiagramme		
	a / b	a / b
Frequency range	WLAN 2.4	WLAN 5.8
3D-Pattern		
2D-Pattern (vertical)		
2D-Pattern (horizontal)		



Mechanical Properties / Mechanische Eigenschaften			3D Overview / 3D Übersicht	
Size	Mounting	Color		
D: 96 mm H: 23 mm	1 x M8 bolt	RAL 7035 light gray (or other RAL types)		
Weight	Temp. range	Max. torque		
ca. 137 g	-40°C to + 80°C	8 Nm		
Degree of Protection				
Plastic case UV-resistance; IP 60				
Conformity / Konformität				
EN 50155, IEC 61373, EN 45545-2, ECE R118				
Drilling pattern	BO-90.028			
Drilling template	-			
Article number	100-57-61-02.4			
Accessories	Recommend RF-cable: OmProCab-5			

ANTONICS
ANTONICS GmbH•Ameisenweg 5•16727 Velten
Telefon +49 3304 25 42 04•Telefax +49 3304 25 43 48•HRB 7807NP, Neuruppin
Internet: <http://www.antonics.de>•E-Mail: info@antonics.de

Die vorstehenden Daten wurden mit Standard-Prüfverfahren an einer Probe aus der Serienproduktion auf einer 1,0 x 1,0 m Massefläche aus Aluminium erstellt. Die Ergebnisse sind daher als allgemeine Anhaltswerte für Materialeigenschaften unter optimalen Bedingungen anzusehen, nicht als Spezifikationsdaten unter davon abweichenden Bedingungen, insbesondere geringerer Masseflächen. Die von Antonics empfohlenen Größen für elektrische Gegengewichte kann der Montageanleitung entnommen werden. Die gemachten Angaben zum Richtdiagramm stellen das typische Abstrahl-/Empfangsverhalten für eine für die Antenne spezifische Frequenz dar. Richtdiagramme weiterer Frequenzen können auf Anfrage zur Verfügung gestellt werden. Sofern nicht ausdrücklich etwas Anderweitiges vereinbart wird, kann keinerlei Garantie für die Eignung des Materials für einen bestimmten Anwendungszweck übernommen werden. Es ist Sache des Käufers, ausreichend zu prüfen, ob sich das Material für seine Zwecke eignet, und das volle Risiko für die Verwendung des Materials zu übernehmen. Trotz aller Sorgfalt bei der Erstellung dieses Dokumentes können sich Daten inzwischen verändert haben. Eine Haftung oder Garantie für die Aktualität, Richtigkeit und Vollständigkeit der zur Verfügung gestellten Informationen kann daher nicht übernommen werden. Desweiteren behält sich die Antonics-ICP GmbH das Recht vor, Änderungen oder Ergänzungen der bereitgestellten Informationen vorzunehmen. Für etwaige Fehler wird keine Haftung übernommen. *Bei fehlerhafter Montage ist die Gewährleistungspflicht ausgeschlossen. Es gelten ausschließlich unsere [AGB](#), die wir Ihnen auf Anforderung zusenden.

The above data were generated using standard test procedures on a specimen from the series production on a 1.0 x 1.0 m ground plane made from aluminum. The results are therefore regarded as a general reference for material properties under optimal conditions, not as a specification data for alternative conditions, especially smaller ground planes. The recommended dimensions of the ground plane can be taken from the installation instruction. The statements made to the radiation diagram represent the typical radiating / receiving behavior for a specific frequency for the antenna. Radiation patterns of the other frequencies can be provided on request. Unless expressly otherwise agreed, no guarantee regarding the suitability of the material for a particular application can be granted. It is up to the buyer to adequately consider whether the material is suitable for his purposes, and to assume the entire risk of the use of the material. Despite all the care taken in the preparation of this document, some information may have changed. A liability or guarantee for the topicality, correctness and completeness of the information provided cannot therefore be accepted. Furthermore, the Antonics-ICP GmbH reserves the right to change or supplement the information provided. No liability is accepted for any errors. * In case of incorrect mounting, the warranty is excluded. Regarding entirely to Antonics-ICP [General Terms and Conditions](#), which we send to you on request.