





802.11n -5G


Test specification:	Body_Low_802.11n-5180_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5180 (Channel 36)		
Relative permittivity (real part)	48.3		
Conductivity (S/m)	5.29		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.839		
			
Area and Zoom Scan Plot			

Test specification:	Body_Mid_802.11n-5200_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power: N/A			
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5200 (Channel 40)		
Relative permittivity (real part)	48.2		
Conductivity (S/m)	5.40		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.728		
			
Area and Zoom Scan Plot			

Test specification:	Body_High_802.11n-5240_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5240 (Channel 48)		
Relative permittivity (real part)	48.2		
Conductivity (S/m)	5.40		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.742		
			
Area and Zoom Scan Plot			


Test specification:	Body_Low_802.11n-5260_ Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5260 (Channel 52)		
Relative permittivity (real part)	48.2		
Conductivity (S/m)	5.40		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.778		
			
Area and Zoom Scan Plot			

Test specification:	Body_Mid_802.11n-5280_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5280 (Channel 56)		
Relative permittivity (real part)	48.1		
Conductivity (S/m)	5.42		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.774		





Area and Zoom Scan Plot


Test specification:	Body_High_802.11n-5320_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5320 (Channel 64)		
Relative permittivity (real part)	48.1		
Conductivity (S/m)	5.47		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.802		




Area and Zoom Scan Plot


Test specification:	Body_Low_802.11n-5500_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5500 (Channel 100)		
Relative permittivity (real part)	47.7		
Conductivity (S/m)	5.74		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.65		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.815		
			
Area and Zoom Scan Plot			

Test specification:	Body_Mid_802.11n-5580_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5580 (Channel 116)		
Relative permittivity (real part)	47.6		
Conductivity (S/m)	5.84		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.65		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.865		
			
Area and Zoom Scan Plot			

Test specification:	Body_Mid_802.11n-5700_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5700 (Channel 140)		
Relative permittivity (real part)	47.6		
Conductivity (S/m)	5.84		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.65		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0.09		
SAR 1g (W/Kg)	0.849		
			
Area and Zoom Scan Plot			


Test specification:	Body_Low_802.11n-5745_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5745 (Channel 149)		
Relative permittivity (real part)	47.2		
Conductivity (S/m)	6.11		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.90		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.898		
			
Area and Zoom Scan Plot			

Test specification:	Body_Mid_802.11n-5785_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5785 (Channel 157)		
Relative permittivity (real part)	47.1		
Conductivity (S/m)	6.16		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.90		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.821		




Area and Zoom Scan Plot

Test specification:	Body_High_802.11n-5825_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)		5825 (Channel 165)	
Relative permittivity (real part)		47.1	
Conductivity (S/m)		6.16	
Probe SN		EX3DV4 - SN7525	
DAE SN		DAE4 Sn1522	
Conversion Factor (dB)		4.90	
Area Scan Resolution (mm)		14x14	
Zoom Scan Resolution (mm)		4.0x4.0x1.4	
Zoom Scan Size (mm)		22.0x22.0x22.0	
Power Drift (dB)		0	
SAR 1g (W/Kg)		0.842	




Area and Zoom Scan Plot

802.11n HT-40


Test specification:	Body_Low_802.11n HT40-5190_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5190 (Channel 38)		
Relative permittivity (real part)	48.3		
Conductivity (S/m)	5.30		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0.11		
SAR 1g (W/Kg)	0.655		
			
Area and Zoom Scan Plot			

Test specification:	Body_High_802.11n HT40-5230_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5230 (Channel 46)		
Relative permittivity (real part)	48.3		
Conductivity (S/m)	5.30		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.66		




Area and Zoom Scan Plot

Test specification:	Body_Low_802.11n HT40-5270_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5270 (Channel 54)		
Relative permittivity (real part)	48.1		
Conductivity (S/m)	5.42		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.712		





Area and Zoom Scan Plot

Test specification:	Body_High_802.11n HT40-5310_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5310 (Channel 62)		
Relative permittivity (real part)	48.1		
Conductivity (S/m)	5.47		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0.05		
SAR 1g (W/Kg)	0.702		




Area and Zoom Scan Plot

Test specification:	Body_Low_802.11n HT40-5510_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5510 (Channel 102)		
Relative permittivity (real part)	47.7		
Conductivity (S/m)	5.76		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.65		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0.01		
SAR 1g (W/Kg)	0.838		
			
Area and Zoom Scan Plot			


Test specification:	Body_Mid_802.11n HT40-5550_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power: N/A			
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5550 (Channel 110)		
Relative permittivity (real part)	47.5		
Conductivity (S/m)	5.87		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.65		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.898		
			
Area and Zoom Scan Plot			

Test specification:	Body_High_802.11n HT40-5670_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5670 (Channel 142)		
Relative permittivity (real part)	47.4		
Conductivity (S/m)	5.99		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.65		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0.05		
SAR 1g (W/Kg)	0.913		




Area and Zoom Scan Plot


Test specification:	Body_Low_802.11n HT40-5755_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5775 (Channel 151)		
Relative permittivity (real part)	47.2		
Conductivity (S/m)	6.12		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.9		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.911		




Area and Zoom Scan Plot

Test specification:	Body_High_802.11n HT40-5795_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5795 (Channel 159)		
Relative permittivity (real part)	47.1		
Conductivity (S/m)	6.18		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.9		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.883		
			
Area and Zoom Scan Plot			

802.11ac VHT-80


Test specification:	Body_Low_802.11ac VHT80-5210_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power: N/A			
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5210 (Channel 42)		
Relative permittivity (real part)	48.3		
Conductivity (S/m)	5.33		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.778		
			
Area and Zoom Scan Plot			

Test specification:	Body_High_802.11ac VHT80-5290_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)		5290 (Channel 58)	
Relative permittivity (real part)		48.1	
Conductivity (S/m)		5.44	
Probe SN		EX3DV4 - SN7525	
DAE SN		DAE4 Sn1522	
Conversion Factor (dB)		5.41	
Area Scan Resolution (mm)		14x14	
Zoom Scan Resolution (mm)		4.0x4.0x1.4	
Zoom Scan Size (mm)		22.0x22.0x22.0	
Power Drift (dB)		0	
SAR 1g (W/Kg)		0.774	




Area and Zoom Scan Plot

Test specification:	Body_Low_802.11ac VHT80-5530_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5530 (Channel 106)		
Relative permittivity (real part)	47.6		
Conductivity (S/m)	5.78		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.65		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.748		




Area and Zoom Scan Plot

Test specification:	Body_Mid_802.11ac VHT80-5610_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5610 (Channel 122)		
Relative permittivity (real part)	47.5		
Conductivity (S/m)	5.91		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.65		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0.04		
SAR 1g (W/Kg)	0.868		




Area and Zoom Scan Plot


Test specification:	Body_Mid_802.11ac VHT80-5775_Left Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5775 (Channel 155)		
Relative permittivity (real part)	47.5		
Conductivity (S/m)	5.91		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.65		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.911		





Area and Zoom Scan Plot


802.11a-5G:


Test specification:	Body_Low_802.11a-5180_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5180 (Channel 36)		
Relative permittivity (real part)	48.3		
Conductivity (S/m)	5.29		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0.05		
SAR 1g (W/Kg)	0.608		
			
Area and Zoom Scan Plot			


Test specification:	Body_Mid_802.11a-5200_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5200 (Channel 40)		
Relative permittivity (real part)	48.2		
Conductivity (S/m)	5.40		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.616		
			
Area and Zoom Scan Plot			


Test specification:	Body_High_802.11a-5240_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5240 (Channel 48)		
Relative permittivity (real part)	48.2		
Conductivity (S/m)	5.40		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0.01		
SAR 1g (W/Kg)	0.636		
			
Area and Zoom Scan Plot			


Test specification:	Body_Low_802.11a-5260_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power: N/A			
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5260 (Channel 52)		
Relative permittivity (real part)	48.2		
Conductivity (S/m)	5.40		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.639		
			
Area and Zoom Scan Plot			


Test specification:	Body_Mid_802.11a-5280_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5280 (Channel 56)		
Relative permittivity (real part)	48.1		
Conductivity (S/m)	5.42		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0.04		
SAR 1g (W/Kg)	0.643		
			
Area and Zoom Scan Plot			


Test specification:	Body_High_802.11a-5320_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5320 (Channel 64)		
Relative permittivity (real part)	48.1		
Conductivity (S/m)	5.47		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0.02		
SAR 1g (W/Kg)	0.661		
			
Area and Zoom Scan Plot			


Test specification:	Body_Low_802.11a-5500_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power: N/A			
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5500 (Channel 100)		
Relative permittivity (real part)	47.7		
Conductivity (S/m)	5.74		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.65		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0.01		
SAR 1g (W/Kg)	0.781		
			
Area and Zoom Scan Plot			

Test specification:	Body_Mid_802.11a-5580_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power: N/A			
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5580 (Channel 116)		
Relative permittivity (real part)	47.6		
Conductivity (S/m)	5.84		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.65		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.823		
			
Area and Zoom Scan Plot			


Test specification:	Body_Mid_802.11a-5700_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5580 (Channel 140)		
Relative permittivity (real part)	47.6		
Conductivity (S/m)	5.84		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.65		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0.02		
SAR 1g (W/Kg)	0.809		
			
Area and Zoom Scan Plot			


Test specification:	Body_Low_802.11a-5745_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5745 (Channel 149)		
Relative permittivity (real part)	47.2		
Conductivity (S/m)	6.11		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.90		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.841		
			
Area and Zoom Scan Plot			


Test specification:	Body_Mid_802.11a-5785_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5785 (Channel 157)		
Relative permittivity (real part)	47.1		
Conductivity (S/m)	6.16		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.90		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.857		
			
Area and Zoom Scan Plot			


Test specification:	Body_High_802.11a-5825_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5825 (Channel 165)		
Relative permittivity (real part)	47.1		
Conductivity (S/m)	6.16		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.90		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.879		
			
Area and Zoom Scan Plot			


802.11n -5G

Test specification:	Body_Low_802.11n-5180_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power: N/A			
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5180 (Channel 36)		
Relative permittivity (real part)	48.3		
Conductivity (S/m)	5.29		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0.01		
SAR 1g (W/Kg)	0.614		
			
Area and Zoom Scan Plot			


Test specification:	Body_Mid_802.11n-5200_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5200 (Channel 40)		
Relative permittivity (real part)	48.2		
Conductivity (S/m)	5.40		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0.02		
SAR 1g (W/Kg)	0.63		
			
Area and Zoom Scan Plot			

Test specification:	Body_High_802.11n-5240_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power: N/A			
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5240 (Channel 48)		
Relative permittivity (real part)	48.2		
Conductivity (S/m)	5.40		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0.01		
SAR 1g (W/Kg)	0.643		
			
Area and Zoom Scan Plot			


Test specification:	Body_Low_802.11n-5260_ Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5260 (Channel 52)		
Relative permittivity (real part)	48.2		
Conductivity (S/m)	5.40		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.662		
			
Area and Zoom Scan Plot			


Test specification:	Body_Mid_802.11n-5280_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5280 (Channel 56)		
Relative permittivity (real part)	48.1		
Conductivity (S/m)	5.42		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.788		
			
Area and Zoom Scan Plot			


Test specification:	Body_High_802.11n-5320_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5320 (Channel 64)		
Relative permittivity (real part)	48.1		
Conductivity (S/m)	5.47		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.814		




Area and Zoom Scan Plot


Test specification:	Body_Low_802.11n-5500_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5500 (Channel 100)		
Relative permittivity (real part)	47.7		
Conductivity (S/m)	5.74		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.65		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0.01		
SAR 1g (W/Kg)	0.781		
			
Area and Zoom Scan Plot			

Test specification:	Body_Mid_802.11n-5580_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power: N/A			
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5580 (Channel 116)		
Relative permittivity (real part)	47.6		
Conductivity (S/m)	5.84		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.65		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.823		
			
Area and Zoom Scan Plot			


Test specification:	Body_Mid_802.11n-5700_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power: N/A			
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5700 (Channel 140)		
Relative permittivity (real part)	47.6		
Conductivity (S/m)	5.84		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.65		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0.02		
SAR 1g (W/Kg)	0.809		
			
Area and Zoom Scan Plot			

Test specification:	Body_Low_802.11n-5745_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5745 (Channel 149)		
Relative permittivity (real part)	47.2		
Conductivity (S/m)	6.11		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.90		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.814		
			
Area and Zoom Scan Plot			


Test specification:	Body_Mid_802.11n-5785_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5785 (Channel 157)		
Relative permittivity (real part)	47.1		
Conductivity (S/m)	6.16		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.90		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.867		





Area and Zoom Scan Plot

Test specification:	Body_High_802.11n-5825_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5825 (Channel 165)		
Relative permittivity (real part)	47.1		
Conductivity (S/m)	6.16		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.90		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.889		
			
Area and Zoom Scan Plot			


802.11n HT-40

Test specification:	Body_Low_802.11n HT40-5190_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power: N/A			
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5190 (Channel 38)		
Relative permittivity (real part)	48.3		
Conductivity (S/m)	5.30		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0.03		
SAR 1g (W/Kg)	0.612		
			
Area and Zoom Scan Plot			


Test specification:	Body_High_802.11n HT40-5230_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power: N/A			
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5230 (Channel 46)		
Relative permittivity (real part)	48.3		
Conductivity (S/m)	5.30		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.629		
			
Area and Zoom Scan Plot			


Test specification:	Body_Low_802.11n HT40-5270_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5270 (Channel 54)		
Relative permittivity (real part)	48.1		
Conductivity (S/m)	5.42		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.798		
			
Area and Zoom Scan Plot			


Test specification:	Body_High_802.11n HT40-5310_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5310 (Channel 62)		
Relative permittivity (real part)	48.1		
Conductivity (S/m)	5.47		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.662		





Area and Zoom Scan Plot

Test specification:	Body_Low_802.11n HT40-5510_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power: N/A			
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5510 (Channel 102)		
Relative permittivity (real part)	47.7		
Conductivity (S/m)	5.76		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.65		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.787		
			
Area and Zoom Scan Plot			


Test specification:	Body_Mid_802.11n HT40-5550_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power: N/A			
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5550 (Channel 110)		
Relative permittivity (real part)	47.5		
Conductivity (S/m)	5.87		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.65		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.812		
			
Area and Zoom Scan Plot			


Test specification:	Body_High_802.11n HT40-5670_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5670 (Channel 142)		
Relative permittivity (real part)	47.4		
Conductivity (S/m)	5.99		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.65		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.839		
			
Area and Zoom Scan Plot			

Test specification:	Body_Low_802.11n HT40-5755_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power:	N/A		
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5775 (Channel 151)		
Relative permittivity (real part)	47.2		
Conductivity (S/m)	6.12		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.9		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0.02		
SAR 1g (W/Kg)	0.821		
			
Area and Zoom Scan Plot			

Test specification:	Body_High_802.11n HT40-5795_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power: N/A			
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5795 (Channel 159)		
Relative permittivity (real part)	47.1		
Conductivity (S/m)	6.18		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	4.9		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.809		
			
Area and Zoom Scan Plot			

802.11ac VHT-80

Test specification:	Body_Low_802.11ac VHT80-5210_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power: N/A			
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5210 (Channel 42)		
Relative permittivity (real part)	48.3		
Conductivity (S/m)	5.33		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.842		
			
Area and Zoom Scan Plot			

Test specification:	Body_High_802.11ac VHT80-5290_Right Side_0mm		
Environ Conditions:	Temp(oC): 23	Result:	Pass
	Humidity (%): 44		
	Atmospheric(mPa): 1015		
Mains Power: N/A			
Test Date:	09/17/2019-09/30/2019		
Tested by:	Deon Dai		
Remarks:	-		
Frequency (MHz)	5290 (Channel 58)		
Relative permittivity (real part)	48.1		
Conductivity (S/m)	5.44		
Probe SN	EX3DV4 - SN7525		
DAE SN	DAE4 Sn1522		
Conversion Factor (dB)	5.41		
Area Scan Resolution (mm)	14x14		
Zoom Scan Resolution (mm)	4.0x4.0x1.4		
Zoom Scan Size (mm)	22.0x22.0x22.0		
Power Drift (dB)	0		
SAR 1g (W/Kg)	0.833		
			
Area and Zoom Scan Plot			