

Test Report

Report No. : CQASZ20211202241E-02
Applicant: Shenzhen DO Intelligent Technology Co., Ltd
Address of Applicant: 11th Floor, 3# Building, Guole Tech Park, Lirong Road, Dalang, Longhua District, Shenzhen, China
Equipment Under Test (EUT):
Product: Smart Watch
Model No.: GT02
Test Model No.: GT02
Brand Name: IDO
FCC ID: 2AHFT440
Standards: 47 CFR Part 15, Subpart C
Date of Receipt: 2021-12-27
Date of Test: 2021-12-27 to 2022-1-13
Date of Issue: 2022-04-12
Test Result : PASS*

*In the configuration tested, the EUT complied with the standards specified above.

Tested By:

Lewis Zhou

(Lewis Zhou)

Reviewed By:

Rock Huang

(Rock Huang)

Approved By:

Jack Ai

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20211202241E-02	Rev.01	Initial report	2022-04-12

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 (2013)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2013)	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2013)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Carrier Frequencies Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Hopping Channel Number	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)&TCB Exclusion List (7 July 2002)	ANSI C63.10 (2013)	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS

3 Contents

	Page
1 VERSION	2
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF EUT	5
4.3 ADDITIONAL INSTRUCTIONS	7
4.4 TEST ENVIRONMENT	8
4.5 DESCRIPTION OF SUPPORT UNITS	8
4.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY	9
4.7 TEST LOCATION	10
4.8 TEST FACILITY	10
4.9 ABNORMALITIES FROM STANDARD CONDITIONS	10
4.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	10
4.11 EQUIPMENT LIST	11
5 TEST RESULTS AND MEASUREMENT DATA	12
5.1 ANTENNA REQUIREMENT	12
5.2 CONDUCTED EMISSIONS	13
5.3 CONDUCTED PEAK OUTPUT POWER	18
<i>Test Result</i>	19
<i>Test Graphs</i>	20
5.4 20DB OCCUPY BANDWIDTH	25
<i>Test Result</i>	25
<i>Test Graphs</i>	26
5.5 CARRIER FREQUENCIES SEPARATION	31
<i>Test Result</i>	32
<i>Test Graphs</i>	32
5.6 HOPPING CHANNEL NUMBER	34
<i>Test Result</i>	34
<i>Test Graphs</i>	35
5.7 DWELL TIME	37
<i>Test Result</i>	38
<i>Test Graphs</i>	39
5.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS	48
<i>Test Result</i>	49
<i>Test Graphs</i>	50
5.9 SPURIOUS RF CONDUCTED EMISSIONS	56
<i>Test Result</i>	57
<i>Test Graphs</i>	58
5.10 OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM	72
5.11 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS	74
5.11.1 Radiated Emission below 1GHz	77
5.11.2 Transmitter Emission above 1GHz	81
6 PHOTOGRAPHS - EUT TEST SETUP	84
6.1 RADIATED EMISSION	84
6.2 CONDUCTED EMISSION	85
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	86

4 General Information

4.1 Client Information

Applicant:	Shenzhen DO Intelligent Technology Co., Ltd
Address of Applicant:	11th Floor, 3# Building, Guole Tech Park, Lirong Road, Dalang, Longhua District, Shenzhen, China
Manufacturer:	Shenzhen DO Intelligent Technology Co., Ltd
Address of Manufacturer:	11th Floor, 3# Building, Guole Tech Park, Lirong Road, Dalang, Longhua District, Shenzhen, China
Factory:	Shenzhen DO Intelligent Technology Co., Ltd
Address of Factory:	11th Floor, 3# Building, Guole Tech Park, Lirong Road, Dalang, Longhua District, Shenzhen, China

4.2 General Description of EUT

Product Name:	Smart Watch
Model No.:	GT02
Test Model No.:	GT02
Trade Mark:	IDO
Software Version:	V14
Hardware Version:	GT02_MB_V1.3
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.1
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Transfer Rate:	1Mbps/2Mbps/3Mbps
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Product Type:	☐ Mobile ☒ Portable ☐ Fix Location
Test Software of EUT:	CBT · BLUETOOTH TESTER
Antenna Type:	FPC antenna
Antenna Gain:	2.28 dBi
Power Supply:	lithium battery:DC3.85V, 300mAh, 1.155Wh, Charge by DC5.0V 0.5A

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
6	2408MHz	26	2428MHz	46	2448MHz	66	2468MHz
7	2409MHz	27	2429MHz	47	2449MHz	67	2469MHz
8	2410MHz	28	2430MHz	48	2450MHz	68	2470MHz
9	2411MHz	29	2431MHz	49	2451MHz	69	2471MHz
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
12	2414MHz	32	2434MHz	52	2454MHz	72	2474MHz
13	2415MHz	33	2435MHz	53	2455MHz	73	2475MHz
14	2416MHz	34	2436MHz	54	2456MHz	74	2476MHz
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		

Note:


In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz

4.3 Additional Instructions

EUT Test Software Settings:		
Mode:	☒ Special software is used. ☐ Through engineering command into the engineering mode. engineering command: *##3646633#**	
EUT Power level:	Class2 (Power level is built-in set parameters and cannot be changed and selected)	
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.		
Mode	Channel	Frequency(MHz)
DH1/DH3/DH5	CH0	2402
	CH39	2441
	CH78	2480
2DH1/2DH3/2DH5	CH0	2402
	CH39	2441
	CH78	2480
3DH1/3DH3/3DH5	CH0	2402
	CH39	2441
	CH78	2480

Run Software:



4.4 Test Environment

Operating Environment:	
Temperature:	26 °C
Humidity:	59% RH
Atmospheric Pressure:	1009mbar
Test Mode:	Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.

4.5 Description of Support Units

The EUT has been tested with associated equipment below.

1) Support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
Adapter	HUAWEI	HW-0502000C01	/	CQA
Bluetooth tester description	R&S	BJ-04692	/	CQA

2) Cable

Cable No.	Description	Manufacturer	Cable Type/Length	Supplied by
/	/	/	/	/

4.6 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty	Notes
1	Radiated Emission (Below 1GHz)	±5.12dB	(1)
2	Radiated Emission (Above 1GHz)	±4.60dB	(1)
3	Conducted Disturbance (0.15~30MHz)	±3.34dB	(1)
4	Radio Frequency	3×10^{-8}	(1)
5	Duty cycle	0.6 %	(1)
6	Occupied Bandwidth	1.1%	(1)
7	RF conducted power	0.86dB	(1)
8	RF power density	0.74	(1)
9	Conducted Spurious emissions	0.86dB	(1)
10	Temperature test	0.8℃	(1)
11	Humidity test	2.0%	(1)
12	Supply voltages	0.5 %	(1)
13	time	0.6 %	(1)
14	Frequency Error	5.5 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.7 Test Location

all tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

4.8 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 22984-1

The 3m Semi-anechoic chamber of Shenzhen Huaxia Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

The test facility is recognized, certified, or accredited by the following organizations:

• **CNAS (No. CNAS L5785)**

CNAS has accredited Shenzhen Huaxia Testing Technology Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.9 Abnormalities from Standard Conditions

None.

4.10 Other Information Requested by the Customer

None.

4.11 Equipment List

Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2021/9/10	2021/9/9
Spectrum analyzer	R&S	FSU26	CQA-038	2021/9/10	2021/9/9
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2021/9/10	2021/9/9
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2021/9/10	2021/9/9
Loop antenna	Schwarzbeck	FMZB1516	CQA-087	2021/9/16	2024/9/15
Bilog Antenna	R&S	HL562	CQA-011	2021/9/16	2024/9/15
Horn Antenna	R&S	HF906	CQA-012	2021/9/16	2024/9/15
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2021/9/16	2024/9/15
Coaxial Cable (Above 1GHz)	CQA	N/A	C019	2021/9/10	2021/9/9
Coaxial Cable (Below 1GHz)	CQA	N/A	C020	2021/9/10	2021/9/9
Antenna Connector	CQA	RFC-01	CQA-080	2021/9/10	2021/9/9
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2021/9/10	2021/9/9
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2021/9/10	2021/9/9
EMI Test Receiver	R&S	ESPI3	CQA-013	2021/9/10	2021/9/9
LISN	R&S	ENV216	CQA-003	2021/9/10	2021/9/9
Coaxial cable	CQA	N/A	CQA-C009	2021/9/10	2021/9/9

Note:

The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

5 Test results and Measurement Data

5.1 Antenna Requirement


Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
	15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
EUT Antenna:	
	The antenna is FPC antenna. The best case gain of the antenna is 2.28 dBi.

Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type at the lowest, middle, high channel.
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation at the lowest channel is the worst case. Only the worst case is recorded in the report.
Test Voltage:	AC 120V/60Hz
Test Results:	Pass

Measurement Data


#1

Live line:



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.165	23.06	9.67	32.73	55.21	-22.48	Average	Line
2	0.165	30.36	9.67	40.03	65.21	-25.18	QP	Line
3	0.315	22.36	9.51	31.87	49.84	-17.97	Average	Line
4	0.315	29.61	9.51	39.12	59.84	-20.72	QP	Line
5	0.450	22.35	9.66	32.01	46.88	-14.87	Average	Line
6	0.450	29.31	9.66	38.97	56.88	-17.91	QP	Line
7	0.585	21.06	9.79	30.85	46.00	-15.15	Average	Line
8	0.585	29.25	9.79	39.04	56.00	-16.96	QP	Line
9 PP	1.625	23.04	11.06	34.10	46.00	-11.90	Average	Line
10 QP	1.625	31.13	11.06	42.19	56.00	-13.81	QP	Line
11	3.100	13.26	10.72	23.98	46.00	-22.02	Average	Line
12	3.100	21.15	10.72	31.87	56.00	-24.13	QP	Line


Neutral line:



	Freq	Read		Limit	Over		
	MHz	Level	Factor	Line	Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dB		
1	0.155	23.30	9.69	32.99	55.73	-22.74	Average
2	0.155	31.49	9.69	41.18	65.73	-24.55	QP
3	0.320	22.89	9.51	32.40	49.71	-17.31	Average
4	0.320	30.89	9.51	40.40	59.71	-19.31	QP
5	0.450	23.98	9.65	33.63	46.88	-13.25	Average
6	0.450	30.85	9.65	40.50	56.88	-16.38	QP
7	0.865	21.33	9.79	31.12	46.00	-14.88	Average
8	0.865	30.24	9.79	40.03	56.00	-15.97	QP
9	1.205	21.78	9.71	31.49	46.00	-14.51	Average
10	1.205	29.91	9.71	39.62	56.00	-16.38	QP
11 PP	1.545	24.28	9.73	34.01	46.00	-11.99	Average
12 QP	1.545	30.47	9.73	40.20	56.00	-15.80	QP


#2

Live line:



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.160	23.08	9.68	32.76	55.46	-22.70	Average	Line
2	0.160	28.20	9.68	37.88	65.46	-27.58	QP	Line
3	0.280	23.17	9.51	32.68	50.82	-18.14	Average	Line
4	0.280	27.34	9.51	36.85	60.82	-23.97	QP	Line
5	0.565	19.34	9.77	29.11	46.00	-16.89	Average	Line
6	0.565	26.30	9.77	36.07	56.00	-19.93	QP	Line
7	1.090	20.91	9.94	30.85	46.00	-15.15	Average	Line
8	1.090	25.63	9.94	35.57	56.00	-20.43	QP	Line
9 PP	1.660	20.19	11.12	31.31	46.00	-14.69	Average	Line
10 QP	1.660	27.23	11.12	38.35	56.00	-17.65	QP	Line
11	2.030	17.77	11.62	29.39	46.00	-16.61	Average	Line
12	2.030	25.08	11.62	36.70	56.00	-19.30	QP	Line

Neutral line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.180	21.35	9.64	30.99	54.49	-23.50	Average	Neutral
2	0.180	28.34	9.64	37.98	64.49	-26.51	QP	Neutral
3	0.223	21.69	9.57	31.26	52.71	-21.45	Average	Neutral
4	0.223	27.90	9.57	37.47	62.71	-25.24	QP	Neutral
5	0.542	18.53	9.74	28.27	46.00	-17.73	Average	Neutral
6	0.542	27.99	9.74	37.73	56.00	-18.27	QP	Neutral
7	1.155	19.74	9.71	29.45	46.00	-16.55	Average	Neutral
8	1.155	26.84	9.71	36.55	56.00	-19.45	QP	Neutral
9 PP	1.575	20.44	9.73	30.17	46.00	-15.83	Average	Neutral
10 QP	1.575	28.15	9.73	37.88	56.00	-18.12	QP	Neutral
11	3.280	9.60	9.77	19.37	46.00	-26.63	Average	Neutral
12	3.280	17.82	9.77	27.59	56.00	-28.41	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.


5.3 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	21dBm
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass


Test Result

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH5	Ant1	2402	4.02	≤ 21	PASS
		2441	4.66	≤ 21	PASS
		2480	4.33	≤ 21	PASS
2DH5	Ant1	2402	4.15	≤ 21	PASS
		2441	5.43	≤ 21	PASS
		2480	5.71	≤ 21	PASS
3DH5	Ant1	2402	2.79	≤ 21	PASS
		2441	3.59	≤ 21	PASS
		2480	5.56	≤ 21	PASS

Test Graphs




DH5_Ant1_2480




Date: 12 JAN 2022 03:02:37

2DH5_Ant1_2402



Date: 12 JAN 2022 03:02:56


2DH5_Ant1_2441



2DH5_Ant1_2480




3DH5_Ant1_2402




Date: 12 JAN 2022 06:30:26

3DH5_Ant1_2441




Date: 12 JAN 2022 06:31:07

3DH5_Ant1_2480



Date: 12 JAN 2022 03:04:25

5.4 20dB Occupy Bandwidth


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	NA
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass

Test Result

TestMode	Antenna	Channel	20db EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	0.882	2401.547	2402.429	---	PASS
		2441	0.882	2440.547	2441.429	---	PASS
		2480	0.903	2479.526	2480.429	---	PASS
2DH5	Ant1	2402	1.290	2401.334	2402.624	---	PASS
		2441	1.314	2440.334	2441.648	---	PASS
		2480	1.311	2479.334	2480.645	---	PASS
3DH5	Ant1	2402	1.311	2401.337	2402.648	---	PASS
		2441	1.308	2440.340	2441.648	---	PASS
		2480	1.311	2479.337	2480.648	---	PASS


Test Graphs

DH5_Ant1_2402




Date: 11. JAN 2022 13:10:00

DH5_Ant1_2441




Date: 11. JAN 2022 13:17:11

DH5_Ant1_2480




Date: 11 JAN 2022 13:19:25

2DH5_Ant1_2402




Date: 12 JAN 2022 01:42:50

2DH5_Ant1_2441




Date: 12 JAN 2022 01:46:10

2DH5_Ant1_2480




Date: 12 JAN 2022 01:48:15

3DH5_Ant1_2402




Date: 12 JAN 2022 01:50:48


3DH5_Ant1_2441



Date: 12 JAN 2022 01:55:56



5.5 Carrier Frequencies Separation


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	2/3 of the 20dB bandwidth
	Remark: the transmission power is less than 0.125W.
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass

Test Result


TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH5	Ant1	Hop	0.841	≥0.602	PASS
2DH5	Ant1	Hop	1	≥0.876	PASS
3DH5	Ant1	Hop	1	≥0.874	PASS

Test Graphs






5.6 Hopping Channel Number


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	At least 15 channels
Exploratory Test Mode:	hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass

Test Result


TestMode	Antenna	Channel	Result[Num]	Limit[Num]	Verdict
DH5	Ant1	Hop	79	≥ 15	PASS
2DH5	Ant1	Hop	79	≥ 15	PASS
3DH5	Ant1	Hop	79	≥ 15	PASS

Test Graphs





5.7 Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.
Limit:	0.4 Second
Test Results:	Pass

Test Result

TestMode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.38	320	0.121	≤0.4	PASS
DH3	Ant1	Hop	1.63	160	0.26	≤0.4	PASS
DH5	Ant1	Hop	2.89	130	0.376	≤0.4	PASS
2DH1	Ant1	Hop	0.39	320	0.124	≤0.4	PASS
2DH3	Ant1	Hop	1.63	190	0.31	≤0.4	PASS
2DH5	Ant1	Hop	2.87	120	0.345	≤0.4	PASS
3DH1	Ant1	Hop	0.38	320	0.12	≤0.4	PASS
3DH3	Ant1	Hop	1.62	170	0.275	≤0.4	PASS
3DH5	Ant1	Hop	2.86	120	0.344	≤0.4	PASS

Remark:


The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

DH1/2DH1/3DH1 Dwell time = Burst Width(ms)*[1600/ (2*79)]*31.6


DH3/2DH3/3DH3 Dwell time = Burst Width (ms)*[1600/ (4*79)]*31.6

DH5/2DH5/3DH5 Dwell time = Burst Width (ms)*[1600/ (6*79)]*31.6


Test Graphs



DH3_Ant1_Hop




Date: 12 JAN 2022 02:23:42




Date: 12 JAN 2022 02:23:48

DH5_Ant1_Hop




Date: 13.JAN.2022 07:58:51




Date: 13.JAN.2022 07:58:56

2DH1_Ant1_Hop




Date: 12 JAN 2022 02:47:39




Date: 12 JAN 2022 02:47:44

2DH3_Ant1_Hop




Date: 12 JAN 2022 02:48:02




Date: 12 JAN 2022 02:48:07

2DH5_Ant1_Hop




Date: 12 JAN 2022 02:46:47




Date: 12 JAN 2022 02:46:52

3DH1_Ant1_Hop




Date: 20.APR.2022 10:23:24




Date: 20.APR.2022 10:23:30

3DH3_Ant1_Hop




Date: 20.APR.2022 10:23:48




Date: 20.APR.2022 10:23:54

3DH5_Ant1_Hop




Date: 20.APR.2022 10:11:17



Date: 20.APR.2022 10:11:23

5.8 Band-edge for RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 <i>Remark: Offset=cable loss+ attenuation factor.</i>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass

Test Result

TestMode	Antenna	ChName	Channel	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	-1.42	-46.7	≤-21.42	PASS
		High	2480	-0.31	-47.01	≤-20.31	PASS
		Low	Hop_2402	-1.69	-48.37	≤-21.69	PASS
		High	Hop_2480	-0.28	-48.14	≤-20.28	PASS
2DH5	Ant1	Low	2402	-1.41	-47.43	≤-21.41	PASS
		High	2480	0.41	-47.13	≤-19.59	PASS
		Low	Hop_2402	-1.85	-48.82	≤-21.85	PASS
		High	Hop_2480	0.20	-46.68	≤-19.8	PASS
3DH5	Ant1	Low	2402	-1.11	-46.84	≤-21.11	PASS
		High	2480	0.54	-47.48	≤-19.46	PASS
		Low	Hop_2402	-4.18	-47.32	≤-24.18	PASS
		High	Hop_2480	0.12	-47.07	≤-19.88	PASS


Test Graphs

DH5_Ant1_Low_2402



Date: 11.JAN.2022 13:10:20

DH5_Ant1_High_2480



Date: 11.JAN.2022 13:19:46