



Conforms to
UL Std. 1993
Certified to
CSA Std. C22.2 No. 1993
Model: BLB-A19-RGBW
100-132Vac, 50/60Hz ,0.15A ,8W
FCC ID: 2AQSN-A19-RGBW
IC: 10733A-A19RGBW

Font requirements: Silk-screen

1. ETL logo shall be at least 8mm high. "US" shall be at least 2mm high, "Intertek" shall be at least 3mm high, control number shall be at least 2mm high. Other letters shall be at least 1.6mm high.



Conforms to
UL Std. 1993
Certified to
CSA Std. C22.2 No. 1993
Model: I-WFRGBWBLB
100-132Vac, 50/60Hz ,0.15A ,8W
FCC ID: 2AQSN-A19-RGBW
IC: 10733A-A19RGBW

Font requirements: Silk-screen

1. ETL logo shall be at least 8mm high. "US" shall be at least 2mm high, "Intertek" shall be at least 3mm high, control number shall be at least 2mm high. Other letters shall be at least 1.6mm high.



Conforms to
UL Std. 1993
Certified to
CSA Std. C22.2 No. 1993
Model: I-K4WFRGBWBLB
100-132Vac, 50/60Hz ,0.15A ,8W
FCC ID: 2AQSN-A19-RGBW
IC: 10733A-A19RGBW

Font requirements: Silk-screen

1. ETL logo shall be at least 8mm high. "US" shall be at least 2mm high, "Intertek" shall be at least 3mm high, control number shall be at least 2mm high. Other letters shall be at least 1.6mm high.