

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



Report No.: AGC10232220302FE05

Page 52 of 80

11. RADIATED EMISSION


11.1. MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.




11.2. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz





Report No.: AGC10232220302FE05

Page 54 of 80

11.3. LIMITS AND MEASUREMENT RESULT

15.209(a) Limit in the below table has to be followed

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|----------------------|-----------------------------------|-------------------------------|
| 0.009~0.490 | 2400/F(kHz) | 300 |
| 0.490~1.705 | 24000/F(kHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

Note: All modes were tested for restricted band radiated emission,

the test records reported below are the worst result compared to other modes.

11.4. TEST RESULT


Radiated emission below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.




Radiated emission from 30MHz to 1000MHz

| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 58% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11n20 with date rate 1 2462MHz | Antenna | Horizontal |




| NO. | Freq. [MHz] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
|-----|----------------|-------------------|----------------|-------------------|----------------|----------------|--------------|------------|
| 1 | 49.4 | 23.94 | 11.61 | 40.00 | 16.06 | 100 | 281 | Horizontal |
| 2 | 94.99 | 21.18 | 9.32 | 43.50 | 22.32 | 100 | 123 | Horizontal |
| 3 | 129.91 | 38.30 | 13.13 | 43.50 | 5.20 | 100 | 117 | Horizontal |
| 4 | 191.02 | 25.57 | 11.58 | 43.50 | 17.93 | 100 | 254 | Horizontal |
| 5 | 400.54 | 23.71 | 17.29 | 46.00 | 22.29 | 100 | 51 | Horizontal |
| 6 | 787.57 | 31.64 | 25.79 | 46.00 | 14.36 | 100 | 94 | Horizontal |

RESULT: PASS





| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 58% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11n20 with date rate 1 2462MHz | Antenna | Vertical |



| NO. | Freq. [MHz] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
|-----|----------------|-------------------|----------------|-------------------|----------------|----------------|--------------|----------|
| 1 | 49.4 | 22.89 | 11.61 | 40.00 | 17.11 | 100 | 289 | Vertical |
| 2 | 106.63 | 22.92 | 12.07 | 43.50 | 20.58 | 100 | 145 | Vertical |
| 3 | 153.19 | 23.65 | 14.91 | 43.50 | 19.85 | 100 | 161 | Vertical |
| 4 | 187.14 | 22.94 | 12.30 | 43.50 | 20.56 | 100 | 148 | Vertical |
| 5 | 261.83 | 22.16 | 14.71 | 46.00 | 23.84 | 100 | 309 | Vertical |
| 6 | 500.45 | 29.75 | 18.89 | 46.00 | 16.25 | 100 | 35 | Vertical |

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

- 2. The "Factor" value can be calculated automatically by software of measurement system.
- 3. All test modes had been pre-tested. The 802.11n20 at high channel is the worst case and recorded in the report.



Report No.: AGC10232220302FE05

Page 57 of 80

Radiated emission above 1GHz


| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 58% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11n20 with date rate 1 2412MHz | Antenna | Horizontal |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|---------------|------------------|-----------------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | value Type |
| 4824.000 | 56.34 | 0.08 | 56.42 | 74 | -17.58 | peak |
| 4824.000 | 47.24 | 0.08 | 47.32 | 54 | -6.68 | AVG |
| 7236.000 | 50.13 | 2.21 | 52.34 | 74 | -21.66 | peak |
| 7236.000 | 41.38 | 2.21 | 43.59 | 54 | -10.41 | AVG |
| | | | | | | |
| Remark: | • | | • | | | • |
| actor = Anter | nna Factor + Cab | le Loss – Pre-a | mplifier. | | | |

| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 58% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11n20 with date rate 1 2412MHz | Antenna | Vertical |

| Meter Reading | Factor | Emission Level | Limits | Margin | Value Tree |
|---------------|----------------------------------|---|--|---|--|
| (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | Value Type |
| 55.26 | 0.08 | 55.34 | 74 | -18.66 | peak |
| 46.28 | 0.08 | 46.36 | 54 | -7.64 | AVG |
| 50.27 | 2.21 | 52.48 | 74 | -21.52 | peak |
| 41.16 | 2.21 | 43.37 | 54 | -10.63 | AVG |
| | | | | | |
| | | | | | |
| | 55.26 46.28 50.27 41.16 | 55.26 0.08 46.28 0.08 50.27 2.21 41.16 2.21 | 55.26 0.08 55.34 46.28 0.08 46.36 50.27 2.21 52.48 | 55.26 0.08 55.34 74 46.28 0.08 46.36 54 50.27 2.21 52.48 74 41.16 2.21 43.37 54 | 55.26 0.08 55.34 74 -18.66 46.28 0.08 46.36 54 -7.64 50.27 2.21 52.48 74 -21.52 41.16 2.21 43.37 54 -10.63 |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.






| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 58% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11n20 with date rate 1 2437MHz | Antenna | Horizontal |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|----------------|------------------|---------------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | value Type |
| 4874.000 | 56.34 | 0.14 | 56.48 | 74 | -17.52 | peak |
| 4874.000 | 45.28 | 0.14 | 45.42 | 54 | -8.58 | AVG |
| 7311.000 | 51.07 | 2.36 | 53.43 | 74 | -20.57 | peak |
| 7311.000 | 41.37 | 2.36 | 43.73 | 54 | -10.27 | AVG |
| | | | | | | |
| Remark: | | | | | | 1 |
| Factor = Anter | na Factor + Cabl | e Loss – Pre- | amplifier. | | | |

| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 58% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11n20 with date rate 1 2437MHz | Antenna | Vertical |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|---|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | value Type |
| 4874.000 | 55.38 | 0.14 | 55.52 | 74 | -18.48 | peak |
| 4874.000 | 46.35 | 0.14 | 46.49 | 54 | -7.51 | AVG |
| 7311.000 | 50.18 | 2.36 | 52.54 | 74 | -21.46 | peak |
| 7311.000 | 40.33 | 2.36 | 42.69 | 54 | -11.31 | AVG |
| | | | | | | |
| Remark: | | | | | | |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |





| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 58% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11n20 with date rate 1 2462MHz | Antenna | Horizontal |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|---|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | value Type |
| 4924.000 | 55.46 | 0.22 | 55.68 | 74 | -18.32 | peak |
| 4924.000 | 46.39 | 0.22 | 46.61 | 54 | -7.39 | AVG |
| 7386.000 | 49.62 | 2.64 | 52.26 | 74 | -21.74 | peak |
| 7386.000 | 38.64 | 2.64 | 41.28 | 54 | -12.72 | AVG |
| | | | | | | |
| Remark: | | | | | | |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 58% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11n20 with date rate 1 2462MHz | Antenna | Vertical |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|---------------|-------------------|---------------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | value Type |
| 4924.000 | 56.49 | 0.22 | 56.71 | 74 | -17.29 | peak |
| 4924.000 | 46.58 | 0.22 | 46.8 | 54 | -7.2 | AVG |
| 7386.000 | 50.27 | 2.64 | 52.91 | 74 | -21.09 | peak |
| 7386.000 | 32.57 | 2.64 | 35.21 | 54 | -18.79 | AVG |
| | | | | | | |
| Remark: | | | | | | |
| actor = Anter | nna Factor + Cabl | e Loss – Pre- | amplifier. | | | |

Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

All test modes had been pre-tested. The 802.11n20 mode is the worst case and recorded in the report.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.




Test result for band edge emission at restricted bands

| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 60% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11b with data rate 1 2412MHz | Antenna | Horizontal |

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: PASS




| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 60% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11b with data rate 1 2412MHz | Antenna | Vertical |

Test Graph for Peak Measurement



Test Graph for Average Measurement



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.




| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 60% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11b with data rate 1 2462MHz | Antenna | Horizontal |

Test Graph for Peak Measurement



Test Graph for Average Measurement



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.




| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 60% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11b with data rate 1 2462MHz | Antenna | Vertical |

Test Graph for Peak Measurement



Test Graph for Average Measurement






| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 60% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11g with data rate 6 2412MHz | Antenna | Horizontal |

Test Graph for Peak Measurement



Test Graph for Average Measurement






| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 60% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11g with data rate 6 2412MHz | Antenna | Vertical |

Test Graph for Peak Measurement



Test Graph for Average Measurement



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 60% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11g with data rate 6 2462MHz | Antenna | Horizontal |

Test Graph for Peak Measurement



Test Graph for Average Measurement



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



| | <u> </u> | | |
|-------------|--|-------------------|-------------------|
| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
| Temperature | 25°C | Relative Humidity | 60% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11g with data rate 6 2462MHz | Antenna | Vertical |

Test Graph for Peak Measurement



Test Graph for Average Measurement



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.




| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 60% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11n20 with data rate 6.5 2412MHz | Antenna | Horizontal |

Test Graph for Peak Measurement



Test Graph for Average Measurement



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.




| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II | |
|-------------|--|-------------------|-------------------|--|
| Temperature | 25°C | Relative Humidity | 60% | |
| Pressure | 960hPa | Test Voltage | Normal Voltage | |
| Test Mode | 802.11n20 with data rate 6.5 2412MHz | Antenna | Vertical | |

Test Graph for Peak Measurement



Test Graph for Average Measurement






| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 60% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11n20 with data rate 6.5 2462MHz | Antenna | Horizontal |

Test Graph for Peak Measurement



Test Graph for Average Measurement





| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 60% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11n20 with data rate 6.5 2462MHz | Antenna | Vertical |

Test Graph for Peak Measurement



Test Graph for Average Measurement



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 60% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11n40 with data rate 13.5 2422MHz | Antenna | Horizontal |

Test Graph for Peak Measurement



Test Graph for Average Measurement






| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 60% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11n40 with data rate 13.5 2422MHz | Antenna | Vertical |

Test Graph for Peak Measurement



Test Graph for Average Measurement






| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 60% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11n40 with data rate 13.5 2452MHz | Antenna | Horizontal |

Test Graph for Peak Measurement



Test Graph for Average Measurement






| EUT | RODECASTER PRO II (Integrated Audio Production Studio) | Model Name | RODECASTER PRO II |
|-------------|--|-------------------|-------------------|
| Temperature | 25°C | Relative Humidity | 60% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | 802.11n40 with data rate 13.5 2452MHz | Antenna | Vertical |

Test Graph for Peak Measurement



Test Graph for Average Measurement





12. LINE CONDUCTED EMISSION TEST


12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

| Francisco | Maximum RF Line Voltage | | | |
|---------------|-------------------------|----------------|--|--|
| Frequency | Q.P (dBµV) | Average (dBμV) | | |
| 150kHz~500kHz | 66-56 | 56-46 | | |
| 500kHz~5MHz | 56 | 46 | | |
| 5MHz~30MHz | 60 | 50 | | |

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





Report No.: AGC10232220302FE05 Page 77 of 80

12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 15V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 Ohm load; the second scan had Line 1 connected to a 50 Ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case was reported on the Summary Data page.



12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

Line Conducted Emission Test Line 1-L



MEASUREMENT RESULT: "agc fin"

2022/3/28 16:21

| 4 | 022/3/20 10: | 21 | | | | | |
|---|------------------|---------------|--------------|---------------|--------------|----------|------|
| | Frequency MHz | Level dBµV | Transd dB | Limit dBµV | Margin dB | Detector | Line |
| | 0.162000 | 51.90 | 6.8 | 65 | 13.5 | QP | L1 |
| | 0.170000 | 51.60 | 6.8 | 65 | 13.4 | QP | L1 |
| | 0.178000 | 45.20 | 6.7 | 65 | 19.4 | QP | L1 |
| | 0.206000 | 47.60 | 6.5 | 63 | 15.8 | QP | L1 |
| | 0.250000 | 46.60 | 6.3 | 62 | 15.2 | QP | L1 |
| | 24.434000 | 51.20 | 9.1 | 60 | 8.8 | QP | L1 |

MEASUREMENT RESULT: "agc_fin2"


2022/3/28 16:21

| 2022 | ./3/20 10. | 21 | | | | | |
|------|-----------------|---------------|--------------|---------------|--------------|----------|------|
| F | requency MHz | Level dBµV | Transd dB | Limit dBµV | Margin dB | Detector | Line |
| | 0.214000 | 40.50 | 6.5 | 53 | 12.5 | AV | L1 |
| | 0.250000 | 41.50 | 6.3 | 52 | 10.3 | AV | L1 |
| | 0.294000 | 39.70 | 6.1 | 50 | 10.7 | AV | L1 |
| | 0.426000 | 34.80 | 5.6 | 47 | 12.5 | AV | L1 |
| | 0.522000 | 34.30 | 5.4 | 46 | 11.7 | AV | L1 |
| 2 | 4.434000 | 46.20 | 9.1 | 50 | 3.8 | AV | L1 |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



Line Conducted Emission Test Line 2-N



MEASUREMENT RESULT: "agc_fin"


| 2022/3/28 16:27 | | | | | | |
|------------------|---------------|--------------|---------------|--------------|----------|------|
| Frequency MHz | Level dBµV | Transd dB | Limit dBµV | Margin dB | Detector | Line |
| 0.154000 | 46.70 | 6.9 | 66 | 19.1 | QP | N |
| 0.202000 | 46.40 | 6.5 | 64 | 17.1 | QP | N |
| 0.238000 | 45.40 | 6.3 | 62 | 16.8 | QP | N |
| 0.282000 | 46.50 | 6.1 | 61 | 14.3 | QP | N |
| 0.510000 | 47.50 | 5.4 | 56 | 8.5 | QP | N |
| 24.418000 | 49.80 | 9.1 | 60 | 10.2 | QP | N |

MEASUREMENT RESULT: "agc_fin2"

2022/3/28 16:26 Frequency Level Transd Limit Margin Detector Line dΒμ∇ dΒ dΒμV MHzdΒ ΑV 0.154000 43.20 6.9 56 12.6 Ν 0.234000 52 42.60 6.3 9.7 ΑV N 0.278000 39.60 6.1 51 11.3 ΑV Ν 0.318000 34.00 6.0 50 15.8 ΑV Ν 0.506000 42.00 5.4 46 4.0 ΑV Ν 3.5 24.414000 46.50 9.1 50 N ΑV

RESULT: PASS

Note: All test modes had been pre-tested. The 802.11n20 at high channel is the worst case and recorded in the report





APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC10232220302AP02

APPENDIX B: PHOTOGRAPHS OF EUT

Refer to the Report No.: AGC10232220302AP03

----END OF REPORT----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.