

# FCC Test Report

Report No.: AGC16626241102FR01

FCC ID	:	2AW3IA102
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	Smart OBD II Dongle
BRAND NAME	:	XTOOL, AutoProPAD, XADVANCER
MODEL NAME	:	A102, AD20, AD20 Pro
APPLICANT	:	Shenzhen Xtooltech Intelligent Co., Ltd.
DATE OF ISSUE	:	Dec. 12, 2024
STANDARD(S)	:	FCC Part 15 Subpart C §15.247
<b>REPORT VERSION</b>	:	V1.0







# **Report Revise Record**

<b>Report Version</b>	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Dec. 12, 2024	Valid	Initial Release




# **Table of Contents**

1. General Information	5
2. Product Information	6
2.1 Product Technical Description	6
2.2 Test Frequency List	6
2.3 Related Submittal(S) / Grant (S)	7
2.4 Test Methodology	7
2.5 Special Accessories	7
2.6 Equipment Modifications	7
2.7 Antenna Requirement	7
3. Test Environment	8
3.1 Address of the Test Laboratory	8
3.2 Test Facility	8
3.3 Environmental Conditions	9
3.4 Measurement Uncertainty	9
3.5 List of Equipment Use	
4.System Test Configuration	
4.1 EUT Configuration	
4.2 EUT Exercise	
4.3 Configuration of Tested System	
4.4 Equipment Used In Tested System	
4.5 Summary of Test Results	
5. Description of Test Modes	
6. Duty Cycle Measurement	
7. RF Output Power Measurement	
7.1 Provisions Applicable	
7.2 Measurement Procedure	
7.3 Measurement Setup (Block Diagram of Configuration)	
7.4 Measurement Result	
8. 6dB Bandwidth Measurement	
8.1 Provisions Applicable	
8.2 Measurement Procedure	
8.3 Measurement Setup (Block Diagram of Configuration)	
8.4 Measurement Results	
9. Power Spectral Density Measurement	
9.1 Provisions Applicable	
9.2 Measurement Procedure	
9.3 Measurement Setup (Block Diagram of Configuration)	
9.4 Measurement Results	
10. Conducted Band Edge and Out-of-Band Emissions	



	10.1 Provisions Applicable	28
	10.2 Measurement Procedure	28
	10.3 Measurement Setup (Block Diagram of Configuration)	28
	10.4 Measurement Results	29
11	. Radiated Spurious Emission	35
	11.1 Measurement Limit	35
	11.2 Measurement Procedure	35
	11.3 Measurement Setup (Block Diagram of Configuration)	38
	11.4 Measurement Result	39
12	AC Power Line Conducted Emission Test	48
	12.1 Measurement Limit	48
	12.2 Measurement Setup (Block Diagram of Configuration)	48
	12.3 Preliminary Procedure of Line Conducted Emission Test	49
	12.4 Final Procedure of Line Conducted Emission Test	49
	12.5 Measurement Results	49
Ap	opendix I: Photographs of Test Setup	50
Ap	opendix II: Photographs of Test EUT	50





# **1. General Information**

Applicant	Shenzhen Xtooltech Intelligent Co., Ltd.
Address	17&18/F, A2 Building, Creative City, Liuxian Avenue, Nanshan District, Shenzhen
Manufacturer	Shenzhen Xtooltech Intelligent Co., Ltd.
Address	17&18/F, A2 Building, Creative City, Liuxian Avenue, Nanshan District, Shenzhen
Factory	Bao'an Branch of Shenzhen Xtooltech Intelligent Co., Ltd.
Address	2, 3, 4/F, Building 12, Tangtou Third Industrial Zone, Shiyan street, Bao'an District, Shenzhen
Product Designation	Smart OBD II Dongle
Brand Name	XTOOL, AutoProPAD, XADVANCER
Test Model	A102
Series Model(s)	AD20, AD20 Pro
Difference Description	A102: OBD engine diagnostics only, but without maintenance and test related functions; AD20: Only OBD engine diagnostics are supported AD20 Pro: Support full vehicle diagnostics and OBD engine diagnostics.
Date of receipt of test item	Nov. 22, 2024
Date of Test	Nov. 22, 2024 – Dec. 12, 2024
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER-FCC-BLE-V1

Note: The test results of this report relate only to the tested sample identified in this report.

Bibo zhang Prepared By Bibo Zhang Dec. 12, 2024 (Project Engineer) Calvin Lin **Reviewed By** Calvin Liu Dec. 12, 2024 (Reviewer) Approved By

Angela Li (Authorized Officer)

Dec. 12, 2024



# 2. Product Information

# 2.1 Product Technical Description

Frequency Band	2400MHz-2483.5MHz
Operation Frequency Range	2402MHz-2480MHz
Bluetooth Version	V5.0
Modulation Type	BLE GFSK 1Mbps GFSK 2Mbps
Number of channels	40
Carrier Frequency of Each Channel	40 Channels (37 Data channels + 3 advertising channels)
Channel Separation	2 MHz
Maximum Transmitter Power	-2.139dBm
Hardware Version	A102_MB_V0.1
Software Version	N/A
Antenna Designation	PCB Antenna
Antenna Gain	-1.867dBi
Power Supply	DC 9-36V

# 2.2 Test Frequency List

Frequency Band	Channel Number	Test Frequency		
	0	2402 MHz		
	1	2404 MHz		
	:	:		
2400~2483.5MHz	19	2440MHz		
	:	:		
	38	2478 MHz		
	39	2480 MHz		
Note: f = 2402 + 2*k MHz, k = 0,, 39 f is the operating frequency (MHz); k is the operating channel.				



# 2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: 2AW3IA102, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

## 2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
4	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules

#### 2.5 Special Accessories

Not available for this EUT intended for grant.

#### 2.6 Equipment Modifications

Not available for this EUT intended for grant.

#### 2.7 Antenna Requirement

Standard Requirement

## 15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

#### 15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi

## EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is -1.867dBi.



# 3. Test Environment

## 3.1 Address of the Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

## 3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories).

#### A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

#### IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



# **3.3 Environmental Conditions**

	Normal Conditions
Temperature range (°C)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106
Power supply	DC 12V

#### 3.4 Measurement Uncertainty

The reported uncertainty of measurement y  $\pm U$ , where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty		
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$		
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$		
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$		
Uncertainty of total RF Power, Conducted	$U_c = \pm 0.8 \text{ dB}$		
Uncertainty of RF Power Density, Conducted	$U_c = \pm 2.6 \text{ dB}$		
Uncertainty of Spurious Emissions, Conducted	$U_c = \pm 2 \%$		
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$		
Uncertainty of Dwell Time	$U_c = \pm 2 \%$		



## 3.5 List of Equipment Use

• R	RF Conducted Test System							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
$\boxtimes$	AGC-ER-E036	Spectrum Analyzer	Agilent	N9020A	MY49100060	2024-05-24	2025-05-23	
$\boxtimes$	AGC-ER-E062	Power Sensor	Agilent	U2021XA	MY54110007	2024-02-01	2025-01-31	
$\boxtimes$	AGC-ER-E063	Power Sensor	Agilent	U2021XA	MY54110009	2024-02-01	2025-01-31	
$\boxtimes$	AGC-ER-A001	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-09-21	2025-09-20	
$\boxtimes$	AGC-ER-E083	Signal Generator	Agilent	E4421B	US39340815	2024-05-23	2025-05-22	
$\boxtimes$	N/A	RF Connection Cable	N/A	1#	N/A	Each time	N/A	
$\boxtimes$	N/A	RF Connection Cable	N/A	2#	N/A	Each time	N/A	

• F	Radiated Spurious Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2024-02-01	2025-01-31	
$\boxtimes$	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23	
$\boxtimes$	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2024-05-28	2025-05-27	
$\boxtimes$	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04	
$\boxtimes$	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10	
	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2024-03-31	2025-03-30	
$\square$	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-09-24	2025-09-23	
$\square$	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2024-07-24	2026-07-23	
$\boxtimes$	AGC-EM-A119	2.4G Filter	SongYi	N/A	N/A	2024-05-23	2025-05-22	
$\boxtimes$	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08	
	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08	

• A	AC Power Line Conducted Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
$\boxtimes$	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2024-05-28	2025-05-27	
$\boxtimes$	AGC-EM-A130	6dB Attenuator	Eeatsheep	LM-XX-6-5W	DC-6GZ	2023-06-09	2025-06-08	
$\square$	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2024-05-28	2025-05-27	



• Tes	Test Software					
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information	
	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71	
$\boxtimes$	AGC-EM-S003	RE Test System	FARA	EZ-EMC	VRA-03A	
	AGC-EM-S004	RE Test System	Tonscend	TS+Ver2.1(JS32-RE)	4.0.0.0	
$\boxtimes$	AGC-ER-S012	BT/WIFI Test System	Tonscend	JS1120-2	2.6	
	AGC-EM-S011	RSE Test System	Tonscend	TS+-Ver2.1(JS36-RSE)	4.0.0.0	



# **4.System Test Configuration**

## **4.1 EUT Configuration**


The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

## 4.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

## 4.3 Configuration of Tested System

Radiated Emission Configure:



## 4.4 Equipment Used In Tested System

The following peripheral devices and interface cables were connected during the measurement:

☐ Test Accessories Come From The Laboratory

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1	Xiaomi Phone	Xiaomi	MI 10		
2	Control Box	RISYM	USB-TTL		
3	DC power supply	MaiSheng	1088		

# ☐ Test Accessories Come From The Manufacturer

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1					



# 4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	§15.203&15.247(b)(4)	Antenna Equipment	Pass
2	§15.247 (b)(3)	RF Output Power	Pass
3	§15.247 (a)(2)	6 dB Bandwidth	Pass
4	§15.247 (e)	Power Spectral Density	Pass
5	§15.247 (d)	Conducted Band Edge and Out-of-Band Emissions	Pass
6	§15.209	Radiated Emission& Band Edge	Pass
7	§15.207	AC Power Line Conducted Emission Not ap	

Note: The conducted emission tests at AC port are not required for devices which only employ DC power supply for operation.



# 5. Description of Test Modes

	Summary Table of Test Cases						
Test Item	Data Rate / Modulation						
Test tieffi	Bluetooth–LE(1Mbps)/GFSK	Bluetooth–LE(1Mbps)/GFSK					
Dedicted & Conducted	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps(D	C source powered)					
Radiated & Conducted Test Cases	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps(D	C source powered)					
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps(D	C source powered)					
AC Conducted Emission	N/A						
Note:							
<ol> <li>For Radiated Emission</li> <li>For Conducted Test n</li> </ol>	worst case was recorded in the report, if no other cases. on, 3axis were chosen for testing for each applicable mode nethod, a temporary antenna connector is provided by the supplied by DC 12V and DC 24V. Only the worst mode te	manufacture.					
Rhietooth RE Test Too	I (RtlBluetoothMP.dll Version :5.3.1.11 RTLBTAPP Version :5.2.2.44)	- 🗆 x					
Mode About							
COM UAR							
No KeyWo	,	Hot Key HCI Reset					
Non Link Mode Hopping L LE PKT TX (for MP) ▼		Test Mode Read Thermal					
Channel 39	<b>.</b>						
Data Len 0x25	Le Tx Gain Index 6	GetChipInfo					
Payload Type Pseuc	lo-Random bit sequence 9 🔍	ShowTxPower					
Start Sta	qu	C OFF					
LE Rx Count		PHY_STAGE					
Message		Dynamic Log					
>>p8 Tinfo is NULLUnknow >>Dpen device successfully >>Get Crystal value = 0x0 >>XTAL Tracking function (N- >>HCI Reset Success!!		Load Script					
>>LeTest_Start : PKT TX	,						
		J					




# 6. Duty Cycle Measurement

The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = Peak. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Operating mode	T(µs)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/ T Minimum VBW (kHz)
BLE_1Mbps	383	60.51	2.18	2.61
BLE_2Mbps	N/A	N/A	N/A	N/A

Remark:

- 1. Duty Cycle factor = 10 \* log (1/ Duty cycle)
- 2. The duty cycle of each frequency band mode reflects the determination requirements of the low channel measurement value
- The test plots as follows:





# 7. RF Output Power Measurement

## 7.1 Provisions Applicable

For DTSs employing digital modulation techniques operating in the bands 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W.


# 7.2 Measurement Procedure

For Peak Power, the testing follows ANSI C63.10 Section 11.9.1.1 Method Max peak power:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the RBW≥DTS bandwidth
- 3. Set the VBW  $\geq$  [3 × RBW].
- 4. Span≥[3 × RBW].
- 5. Sweep= auto couple.
- 6. Detector Function= Peak.
- 7. Trace mode= Max hold.
- 8. Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.
- For Average power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G:
- 1. The RF output of EUT was connected to the power meter by RF cable and attenuator.
- 2. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Measure the conducted output power and record the results in the test report.


#### 7.3 Measurement Setup (Block Diagram of Configuration)

For Average power test setup






# For peak power test setup



## 7.4 Measurement Result

Test Data of Conducted Output Power						
Test Mode	Test Frequency (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail		
	2402	-2.296	≪30	Pass		
GFSK_1Mbps	2440	-2.359	≪30	Pass		
	2480	-2.139	≤30	Pass		





# Test Graphs of Conducted Output Power



LXI RL	ctrum Analyzer - Swept SA RF 50 Ω AC req 2.48000000	CORREC 0 GHZ PNO: Fast IFGain:Low	SENSE: → Trig: Free Ri #Atten: 40 d	Avg un Avg l	ALIGN AUTO Type: Log-Pwr Hold: 100/100	TRAC TYL	MDec 04, 2024 DE <b>1 2 3 4 5 6</b> PE MWWWW ET PNNNNN	Frequency
10 dB/div Log	Ref 30.00 dBm				Mkr1		717 GHz 39 dBm	Auto Tune
20.0								Center Freq 2.480000000 GHz
0.00			<b>↓</b> 1					<b>Start Freq</b> 2.477500000 GHz
-10.0								<b>Stop Freq</b> 2.482500000 GHz
-30.0								CF Step 500.000 kHz <u>Auto</u> Man
-50.0								<b>Freq Offset</b> 0 Hz
-60.0	80000 GHz					Snap	000 MHz	
	Center 2.480000 GHz         Span 5.000 MHz           #Res BW 1.5 MHz         #VBW 5.0 MHz         Sweep         1.066 ms (1000 pts)           Asg         status         status         Status							
	Test_Graph_LE1M_ANT1_2480_1Mbps_Peak Power							



# 8. 6dB Bandwidth Measurement

#### 8.1 Provisions Applicable


The minimum 6dB bandwidth shall be 500 kHz.

## 8.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).

- 1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
- For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the OBW and set the Video bandwidth (VBW) ≥ 3 \* RBW.
- 5. Measure and record the results in the test report.


## 8.3 Measurement Setup (Block Diagram of Configuration)






#### **8.4 Measurement Results**

Test Data of Occupied Bandwidth and DTS Bandwidth						
Test Mode	Test Frequency (MHz)	Occupied Bandwidth (MHz)	DTS BW (MHz)	DTS BW Limits	Pass or Fail	
GFSK_1Mbps	2402	1.036	0.706	≥0.5	Pass	
	2440	1.052	0.729	≥0.5	Pass	
	2480	1.074	0.744	≥0.5	Pass	




# Test Graphs of Occupied Bandwidth










## Test Graphs of DTS Bandwidth







# 9. Power Spectral Density Measurement

## 9.1 Provisions Applicable


The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

# 9.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.

- 1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz in order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
- 4. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
- 5. Measure and record the results in the test report.
- 6. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

# 9.3 Measurement Setup (Block Diagram of Configuration)






#### 9.4 Measurement Results

Test Data of Conducted Output Power Spectral Density						
Test Mode	Test Frequency (MHz)	Power density (dBm/3kHz)	Limit (dBm/3kHz)	Pass or Fail		
	2402	-18.864	≪8	Pass		
GFSK_1Mbps	2440	-18.893	≪8	Pass		
	2480	-18.786	≪8	Pass		

#### Test Graphs of Conducted Output Power Spectral Density









# 10. Conducted Band Edge and Out-of-Band Emissions


#### **10.1 Provisions Applicable**

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure.

#### **10.2 Measurement Procedure**

- Reference level measurement
- 1. Set instrument center frequency to DTS channel center frequency
- 2. Set the span to  $\geq$  1.5 times the DTS bandwidth
- 3. Set the RBW = 100 kHz
- 4. Set the VBW  $\ge$  3 x RBW
- 5. Detector = peak
- 6. Sweep time = auto couple
- 7. Trace mode = max hold
- 8. Allow trace to fully stabilize
- Emission level measurement
- 1. Set the center frequency and span to encompass frequency range to be measured
- 2. RBW = 100kHz
- 3. VBW = 300kHz
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep time = auto couple
- 7. The trace was allowed to stabilize

#### 10.3 Measurement Setup (Block Diagram of Configuration)






#### **10.4 Measurement Results**




#### Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands
























## Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands



# 11. Radiated Spurious Emission

# **11.1 Measurement Limit**

# FCC Part 15.209 Limit in the below table to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

# **11.2 Measurement Procedure**

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds.



- 8. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 9. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 10. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 11. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

Spectrum Parameter	Setting
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/3MHz for Average

The following table is the setting of spectrum analyzer and receiver.

Receiver Parameter	Setting
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP



#### • Quasi-Peak Measurements below 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

#### Peak Measurements above 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize


#### <u>Average Measurements above 1GHz</u>

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW ≥ [3 × RBW]
- 4. Detector = Power averaging (rms)
- 5. Averaging type = power (i.e., rms)
- 6. Sweep time = auto
- 7. Perform a trace average of at least 100 traces.
- 8. The applicable correction factor is [10\*log (1 / D)], where D is the duty cycle. The factor had been edited in the "Input Correction" of the Spectrum Analyzer.




#### 11.3 Measurement Setup (Block Diagram of Configuration)






Radiated Emission Test Setup 30MHz-1000MHz



#### Radiated Emission Test Setup Above 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com




#### **11.4 Measurement Result**

#### Radiated Emission Below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

		Radi	ated Emiss	ion Test R	esults at 3	80MHz-1GH	Ιz		
EUT Name	Sm	art OBD II Dor	ngle		Mod	lel Name		A102	
Temperature	22.4°C   Relative Humidity			57.2%					
Pressure	960	hPa			Test	Voltage		DC 12V	
Test Mode	Мо	de 3			Ante	enna Polar	ity	Horizonta	I
72.0	dBuV/m								
32		Meriline publice of the	with when the second	with and we wanted out				Limit: — Margin: —	
-8 30.00	00 40 No. N		80 Reading Level	(MH2) Correct Factor	Measure	300 400 e- Limit	500 60 Over	0 700 100	0.000
-		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	
-	1	40.1347	5.81	13.89	19.70	40.00	-20.30	peak	
-	2	110.9571	5.61	16.31	21.92	43.50	-21.58	peak	
-	3	336.0352	6.75	16.98	23.73	46.00	-22.27	peak	
-	4	444.8514	6.92	24.93	31.85	46.00	-14.15	peak	
-	5	614.2142		25.17			-14.64	· · · ·	
	6 *	896.9965	6.01	31.42	37.43	46.00	-8.57	peak	





		Radia	ated Emissi	ion Test Re	esults at 3	0MHz-1GH	Ηz		
EUT Name	Sma	rt OBD II Don	gle		Mod	lel Name		A102	
Temperature	22.4°C R			Rela	Relative Humidity 57.2%		57.2%		
Pressure	960h	IPa			Test	Test Voltage			
Test Mode	Mode	e 3			Ante	enna Polar	rity	Vertical	
72.0 d	BuV/m								
								Limit: — Margin: —	
									-
				3				6	
32		×	2	1	4 X	an war	a contraction	mahad	
		L. Mary	Wega water and the	W" My work	Marke I and	Hort W. Marker and	a verski ser se		
ndhim.	danstrand	worker the ter	in a standard		. Mr. Anna Marcas				-
									-
-8									
30.000	) 40	50 60 70	80	(MHz)		300 400	500 600	0 700 1000	.000
N	lo. M	k. Freq.	Reading Level	Correct Factor	Measure ment	- Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	
	1 *	61.9951	19.30	17.08	36.38	40.00	-3.62	peak	
	2	91.4949	18.38	15.35	33.73	43.50	-9.77	peak	
	3 !	135.0319	20.27	18.08	38.35	43.50	-5.15	peak	
	4	217.5443	16.81	16.58	33.39	46.00	-12.61	peak	
	5	443.2943	6.78	25.95	32.73	46.00	-13.27	peak	

#### **RESULT: Pass**

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. All test modes had been pre-tested. The mode 3 is the worst case and recorded in the report.



UT Name		Smart OBD	II Donale		Mode	I Name	A102		
			II Doligie						
emperature		<b>22.4</b> ℃			Relative Humidity		57.2%	57.2%	
ressure		960hPa		Test Voltage		DC 12V			
est Mode		Mode 1		Anter	nna Polarity	Horizont	al		
							·		
Frequency	Met	ter Reading	Factor	Emissior	n Level	Limits	Margin	Value Type	
(MHz)		(dBµV)	(dB)	(dBµV	//m)	(dBµV/m)	(dB)	value Type	
4804.000		47.53	0.08	47.6	61	74	-26.39	peak	
4804.000		38.54	0.08	38.6	52	54	-15.38	AVG	
7206.000		42.16	2.21	44.3	37	74	-29.63	peak	
7206.000	$\square$	31.29	2.21	33.	5	54	-20.5	AVG	
	┥								
Demonstr	<u> </u>							ļ	
Remark:				a una un life a un					
Factor = Anter	ina Fa	actor + Cable	e Loss – Pre-	ampliller.					
UT Name		Smart OBD	II Dongle		Mode	I Name	A102		
emperature		<b>22.4</b> °C			Relat	ive Humidity	57.2%		
ressure		960hPa			Test \	Voltage	DC 12V		
est Mode		Mode 1			Anter	nna Polarity	Vertical		
<b>F</b>			<b>F</b> actor			1 : :	NA	1	
Frequency	Met	ter Reading	Factor	Emission		Limits	Margin	Value Type	
( \ / \   - \		(dBµV) 48.61	(dB)	(dBµ∨		(dBµV/m)	(dB)	pack	
(MHz)		48 h 1	0.08	48.6		74 54	-25.31 -16.38	peak AVG	
4804.000			0.00	07.0		54	-16 48		
4804.000 4804.000	<u> </u>	37.54	0.08	37.6		-		_	
4804.000 4804.000 7206.000		37.54 42.19	2.21	44.4	4	74	-29.6	peak	
4804.000 4804.000		37.54			4	-		_	
4804.000 4804.000 7206.000 7206.000		37.54 42.19	2.21	44.4	4	74	-29.6	peak	
4804.000 4804.000 7206.000		37.54 42.19 32.34	2.21 2.21	44	4	74	-29.6	peak	

## Radiated Emissions Test Results for Above 1GHz

## **RESULT: Pass**



UT Name	Smart OBI	D II Dongle	Мо	del Name	A102											
emperature	<b>22.4</b> °C	22.4°C Relative Humidity		22.4°C Relative Humidity		22.4°C Relative Humidity		22.4°C Relative Humidity		22.4°C Relative Humidity		2.4°C Relative Humidity		57.2%	57.2%	
ressure	960hPa		Tes	t Voltage	/oltage DC 12V											
est Mode	Mode 2	Mode 2		enna Polarity	Horizon	tal										
Frequency	Meter Reading	Factor	Emission Leve	Limits	Margin	Value Type										
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type										
4880.000	48.53	0.14	48.67	74	-25.33	peak										
4880.000	37.42	0.14	37.56	54	-16.44	AVG										
7320.000	42.16	2.36	44.52	74	-29.48	peak										
7320.000	32.34	2.36	34.7	54	-19.3	AVG										
Davaarla																
Remark:																
	nna Factor + Cab	le Loss – Pre-	amplifier.													
		le Loss – Pre- D II Dongle		del Name	A102											
Factor = Anter		-	Мо	del Name ative Humidity	A102 57.2%											
Factor = Anter	Smart OBI	-	Mo													
Factor = Anter UT Name emperature	Smart OBI 22.4℃	-	Moo Rel Tes	ative Humidity	57.2%											
Factor = Anter UT Name emperature ressure est Mode	Smart OBI 22.4℃ 960hPa Mode 2	D II Dongle	Moo Rel Tes Ant	ative Humidity t Voltage enna Polarity	57.2% DC 12V Vertical											
Factor = Anter UT Name emperature ressure est Mode	Smart OBI 22.4°C 960hPa Mode 2 Meter Reading	D II Dongle	Moo Rel Tes Ant Emission Leve	ative Humidity t Voltage enna Polarity	57.2% DC 12V Vertical Margin	Value Type										
Factor = Anter	Smart OBI 22.4℃ 960hPa Mode 2 Meter Reading (dBµV)	D II Dongle Factor (dB)	Mod Rel Tes Ant Emission Leve (dBµV/m)	ative Humidity t Voltage enna Polarity	57.2% DC 12V Vertical Margin (dB)	- Value Type										
Factor = Anter	Smart OBI           22.4 °C           960hPa           Mode 2           Meter Reading           (dBµV)           47.53	D II Dongle Factor (dB) 0.14	Moo Rel Tes Ant Emission Leve (dBµV/m) 47.67	ative Humidity t Voltage enna Polarity	57.2% DC 12V Vertical Margin (dB) -26.33	Value Type										
Factor = Anter UT Name emperature ressure est Mode Frequency (MHz) 4880.000	Smart OBI           22.4 °C           960hPa           Mode 2           Meter Reading           (dBµV)           47.53           37.59	Factor (dB) 0.14 0.14	Мос Rel Тез Апt Еmission Leve (dBµV/m) 47.67 37.73	t Voltage enna Polarity Limits (dBµV/m) 74 54	57.2% DC 12V Vertical Margin (dB) -26.33 -16.27	Value Type peak AVG										
Factor = Anter UT Name emperature ressure est Mode Frequency (MHz) 4880.000 4880.000 7320.000	Smart OBI         22.4 °C         960hPa         Mode 2         Meter Reading         (dBµV)         47.53         37.59         41.62	D II Dongle Factor (dB) 0.14 0.14 2.36	Мос Rel Тез Апт Еmission Leve (dBµV/m) 47.67 37.73 43.98	t Voltage enna Polarity Limits (dBµV/m) 74 54 74	57.2% DC 12V Vertical Margin (dB) -26.33 -16.27 -30.02	- Value Type peak AVG peak										
Factor = Anter UT Name emperature ressure est Mode Frequency (MHz) 4880.000	Smart OBI           22.4 °C           960hPa           Mode 2           Meter Reading           (dBµV)           47.53           37.59	Factor (dB) 0.14 0.14	Мос Rel Тез Апt Еmission Leve (dBµV/m) 47.67 37.73	t Voltage enna Polarity Limits (dBµV/m) 74 54	57.2% DC 12V Vertical Margin (dB) -26.33 -16.27	Value Type peak AVG										
Factor = Anter UT Name emperature ressure est Mode Frequency (MHz) 4880.000 4880.000 7320.000	Smart OBI         22.4 °C         960hPa         Mode 2         Meter Reading         (dBµV)         47.53         37.59         41.62	D II Dongle Factor (dB) 0.14 0.14 2.36	Мос Rel Тез Апт Еmission Leve (dBµV/m) 47.67 37.73 43.98	t Voltage enna Polarity Limits (dBµV/m) 74 54 74	57.2% DC 12V Vertical Margin (dB) -26.33 -16.27 -30.02	- Value Type peak AVG peak										

# Radiated Emissions Test Results for Above 1GHz

## **RESULT: Pass**



UT Name	Smart OBD	II Dongle	Mode	el Name	A102	
emperature	<b>22.4</b> °C		Relat	ive Humidity	57.2%	
Pressure	960hPa		Test	Voltage	DC 12V	
est Mode	Mode 3	Mode 3		nna Polarity	Horizonta	al
			·		·	
Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
4960.000	48.62	0.22	48.84	74	-25.16	peak
4960.000	37.53	0.22	37.75	54	-16.25	AVG
7440.000	42.16	2.64	44.8	74	-29.2	peak
7440.000	32.69	2.64	35.33	54	-18.67	AVG
Remark:						
INCINAIN.						
	nna Factor + Cabl	e Loss – Pre-	amplifier.			
	nna Factor + Cabl			el Name	A102	
Factor = Ante			Mode	el Name ive Humidity	A102 57.2%	·
Factor = Ante	Smart OBD		Mode			
Factor = Ante	Smart OBD		Mode Relat Test	ive Humidity	57.2%	
Factor = Anter	Smart OBD 22.4 °C 960hPa Mode 3	II Dongle	Mode Relat Test Ante	ive Humidity Voltage nna Polarity	57.2% DC 12V Vertical	
Factor = Anter	Smart OBD 22.4°C 960hPa Mode 3 Meter Reading	II Dongle	Mode Relat Test Ante Emission Level	ive Humidity Voltage nna Polarity Limits	57.2% DC 12V Vertical Margin	Value Type
Factor = Anter	Smart OBD 22.4℃ 960hPa Mode 3 Meter Reading (dBµV)	II Dongle Factor (dB)	Mode Relat Test Ante Emission Level (dBµV/m)	ive Humidity Voltage nna Polarity Limits (dBµV/m)	57.2% DC 12V Vertical Margin (dB)	
Factor = Anter	Smart OBD           22.4 °C           960hPa           Mode 3           Meter Reading           (dBµV)           47.53	II Dongle Factor (dB) 0.22	Mode Relat Test Ante Emission Level (dBµV/m) 47.75	ive Humidity Voltage nna Polarity Limits (dBµV/m) 74	57.2% DC 12V Vertical Margin (dB) -26.25	peak
Factor = Anter EUT Name Temperature Pressure Test Mode Frequency (MHz) 4960.000 4960.000	Smart OBD           22.4 °C           960hPa           Mode 3           Meter Reading           (dBµV)           47.53           37.54	II Dongle Factor (dB) 0.22 0.22	Mode Relat Test Ante Emission Level (dBµV/m) 47.75 37.76	ive Humidity Voltage nna Polarity Limits (dBµV/m) 74 54	57.2% DC 12V Vertical Margin (dB) -26.25 -16.24	peak AVG
Factor = Anter           EUT Name           Temperature           Pressure           Test Mode           Frequency           (MHz)           4960.000           7440.000	Smart OBD           22.4 °C           960hPa           Mode 3           Meter Reading           (dBµV)           47.53           37.54           42.16	II Dongle Factor (dB) 0.22 0.22 2.64	Моde Relat Test Ante Emission Level (dBµV/m) 47.75 37.76 44.8	ive Humidity Voltage nna Polarity Limits (dBµV/m) 74 54 74	57.2% DC 12V Vertical Margin (dB) -26.25 -16.24 -29.2	peak AVG peak
Factor = Anter EUT Name Temperature Pressure Test Mode Frequency (MHz) 4960.000 4960.000	Smart OBD           22.4 °C           960hPa           Mode 3           Meter Reading           (dBµV)           47.53           37.54	II Dongle Factor (dB) 0.22 0.22	Mode Relat Test Ante Emission Level (dBµV/m) 47.75 37.76	ive Humidity Voltage nna Polarity Limits (dBµV/m) 74 54	57.2% DC 12V Vertical Margin (dB) -26.25 -16.24	peak AVG
Factor = Anter           EUT Name           Temperature           Pressure           Test Mode           Frequency           (MHz)           4960.000           7440.000	Smart OBD           22.4 °C           960hPa           Mode 3           Meter Reading           (dBµV)           47.53           37.54           42.16	II Dongle Factor (dB) 0.22 0.22 2.64	Моde Relat Test Ante Emission Level (dBµV/m) 47.75 37.76 44.8	ive Humidity Voltage nna Polarity Limits (dBµV/m) 74 54 74	57.2% DC 12V Vertical Margin (dB) -26.25 -16.24 -29.2	peak AVG peak

# **Radiated Emissions Test Results for Above 1GHz**

#### **RESULT: Pass**


Note:

- 1. The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Pre-amplifier gain, Margin = Emission Level-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.




EUT Name	Smart OBD II Dongle	Model Name	A102
Temperature	<b>22.5</b> ℃	Relative Humidity	48%
Pressure	960hPa	Test Voltage	DC 12V
Test Mode	Mode 1	Antenna Polarity	Horizontal

#### Test Graph for Peak Measurement




Test Graph for Average Measurement



# **RESULT: Pass**




EUT Name	Smart OBD II Dongle	Model Name	A102
Temperature	<b>22.5</b> ℃	Relative Humidity	48%
Pressure	960hPa	Test Voltage	DC 12V
Test Mode	Mode 1	Antenna Polarity	Vertical



Test Graph for Average Measurement




## **RESULT: Pass**






EUT Name	Smart OBD II Dongle	Model Name	A102
Temperature	<b>22.5</b> ℃	Relative Humidity	48%
Pressure	960hPa	Test Voltage	DC 12V
Test Mode	Mode 3	Antenna Polarity	Horizontal

# Test Graph for Peak Measurement



Test Graph for Average Measurement




# **RESULT: Pass**




EUT Name	Smart OBD II Dongle	Model Name	A102
Temperature	<b>22.5</b> ℃	Relative Humidity	48%
Pressure	960hPa	Test Voltage	DC 12V
Test Mode	Mode 3	Antenna Polarity	Vertical

#### Test Graph for Peak Measurement



Test Graph for Average Measurement



## **RESULT: Pass**

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



# 12. AC Power Line Conducted Emission Test

# 12.1 Measurement Limit


<b>Francisco</b>	Maximum RF Line Voltage				
Frequency	Q.P. (dBµV)	Average (dBµV)			
150kHz~500kHz	66-56	56-46			
500kHz~5MHz	56	46			
5MHz~30MHz	60	50			

Note:

1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

## 12.2 Measurement Setup (Block Diagram of Configuration)





# 12.3 Preliminary Procedure of Line Conducted Emission Test

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

## 12.4 Final Procedure of Line Conducted Emission Test

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

## **12.5 Measurement Results**

N/A

Note: The conducted emission tests at AC port are not required for devices which only employ DC power supply for operation.



Report No.: AGC16626241102FR01 Page 50 of 50

# Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC16626241102AP02

# Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC16626241102AP03

-----End of Report-----



# Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.