

## G4 Doorbell Pro PoE



## UVC-G4 Doorbell Pro PoE

### Mechanical

|                     |   |
|---------------------|---|
| Dimensions          | Device: 160.6 x 51.7 x 35.1 mm (6.3 x 2 x 1.4")<br>Wall mount: 159.3 x 50.3 x 17.5 mm (6.3 x 1.9 x 0.7")<br>Wedge: 161.1 x 52.1 x 25.7 mm (6.3 x 2.1 x 1")<br>On-wall mount: 161.1 x 52.1 x 25.75 mm (6.3 x 2.1 x 1") |
| Weight              | Device: 264 g (9.3 oz)<br>Wall mount: 56 g (2 oz)<br>Wedge: 33 g (1.2 oz)<br>On-wall mount: 53 g (1.9 oz)   |
| Enclosure materials | Aluminum alloy, polycarbonate   |
| Mount materials     | WALL MOUNT: Aluminum Alloy<br>WEDGE: Polycarbonate<br>ON WALL MOUNT: Polycarbonate  |
| Weatherproofing     | IPX4  |

### Optics

|            |  |
|------------|--|
| Sensor     | 5 MP CMOS sensor                               |
| Lens       | Fixed focal length                             |
| View angle | H: 138°, V: 114°, D: 155°                      |
| Night mode | Built-in IR LED illumination and IR cut filter |

### Video

|                    |                   |
|--------------------|-------------------|
| Video compression  | H.264             |
| Resolution         | 1600 x 1200 (4:3) |
| Maximum frame rate | 30 FPS            |

### System

|                         |                                      |
|-------------------------|--------------------------------------|
| Processor specs         | Ambarella® S5L55m                    |
| Memory information      | 512 MB                               |
| Networking interface    | (1) 10/100/1000 MbE RJ45 port        |
| Flash memory support    | 256 MB                               |
| Power method            | PoE                                  |
| Supported voltage range | 37–57V DC                            |
| Max. power consumption  | 10W                                  |
| Link/activity LED       | Yes, LED ring                        |
| Buttons                 | (1) Ring button<br>(1) Factory reset |
| Operating temperature   | -30 to 40° C (-22 to 104° F)         |
| Operating humidity      | 0 to 90% noncondensing               |
| Certifications          | CE, FCC, IC                          |

## Audio

|            |                                   |
|------------|-----------------------------------|
| Microphone | Yes (can be disabled in software) |
| Speaker    | Yes                               |

## Software

|                      |                                   |
|----------------------|-----------------------------------|
| UniFi OS application | UniFi Protect                     |
| Mobile app           | UniFi Protect (iOS™ and Android™) |

## FCC

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions.

1. This device may not cause harmful interference, and
2. This device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This radio transmitter (FCC ID: SWX-UVCG4DPP) has been approved by FCC.



## **ISED Canada**

### **CAN ICES-3(B)/NMB-3(B)**

This device complies with ISED Canada licence-exempt RSS standard(s).

Operation is subject to the following two conditions:

1. This device may not cause interference, and
2. This device must accept any interference, including interference that may cause undesired operation of the device.

This radio transmitter (IC: 6545A-UVCG4DPP) has been approved by ISED Canada.

### **CAN ICES-3(B)/NMB-3(B)**

Le présent appareil est conforme aux CNR d'ISDE Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes :

1. l'appareil ne doit pas produire de brouillage;
2. l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

Le présent émetteur radio (IC : 6545A-UVCG4DPP) a été approuvé par ISDE Canada.

### **IMPORTANT NOTE:**

#### **Radiation Exposure Statement:**

- This equipment complies with radiation exposure limits set forth for an uncontrolled environment.
- This equipment should be installed and operated with minimum distance 20 cm between the radiator and your body.
- This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.