

# FCC PART 95 MEASUREMENT AND TEST REPORT

For

## Shenzhen Jizhida Technology Co., Ltd

1902E., BLDG.C6, HENGFENG IND. CITY, NO.739, ZHOUSHI RD., HEZHOU  
COMMUNITY, BAOAN DIST., SHENZHEN, China

**FCC ID: 2AQJJB T900**

|                                        |                                                                                                                                                                                                                                                       |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Report Type:</b><br>Original Report | <b>Product Type:</b><br>Walkie Talkie (FRS)                                                                                                                                                                                                           |
| <b>Report Number:</b> RDG181029004-00B |                                                                                                                                                                                                                                                       |
| <b>Report Date:</b> 2018-11-12         |                                                                                                                                                                                                                                                       |
| <b>Reviewed By:</b>                    | Jerry Zhang<br>EMC Manager                                                                                                                                                                                                                            |
| <b>Test Laboratory:</b>                | Bay Area Compliance Laboratories Corp. (Dongguan)<br>No.69 Pulongcun, Puxinhu Industry Area,<br>Tangxia, Dongguan, Guangdong, China<br>Tel: +86-769-86858888<br>Fax: +86-769-86858891<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA\* or any agency of the Federal Government. \* This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “\*”.

## **TABLE OF CONTENTS**

|                                                                                     |           |
|-------------------------------------------------------------------------------------|-----------|
| <b>GENERAL INFORMATION.....</b>                                                     | <b>3</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                            | 3         |
| OBJECTIVE .....                                                                     | 3         |
| RELATED SUBMITTAL(S)/GRANT(S).....                                                  | 3         |
| TEST METHODOLOGY .....                                                              | 3         |
| MEASUREMENT UNCERTAINTY.....                                                        | 4         |
| TEST FACILITY .....                                                                 | 4         |
| <b>SYSTEM TEST CONFIGURATION.....</b>                                               | <b>5</b>  |
| DESCRIPTION OF TEST CONFIGURATION .....                                             | 5         |
| EQUIPMENT MODIFICATIONS .....                                                       | 5         |
| EUT EXERCISE SOFTWARE .....                                                         | 5         |
| BLOCK DIAGRAM OF TEST SETUP .....                                                   | 6         |
| <b>SUMMARY OF TEST RESULTS .....</b>                                                | <b>7</b>  |
| <b>FCC §2.1093 - RF EXPOSURE INFORMATION .....</b>                                  | <b>8</b>  |
| APPLICABLE STANDARD .....                                                           | 8         |
| TEST RESULT .....                                                                   | 8         |
| <b>FCC §2.1046, §95.567 - RF OUTPUT POWER.....</b>                                  | <b>9</b>  |
| APPLICABLE STANDARD .....                                                           | 9         |
| TEST PROCEDURE .....                                                                | 9         |
| TEST EQUIPMENT LIST AND DETAILS.....                                                | 9         |
| TEST DATA .....                                                                     | 9         |
| <b>FCC §2.1047 &amp; §95.575 - MODULATION CHARACTERISTIC .....</b>                  | <b>11</b> |
| APPLICABLE STANDARD .....                                                           | 11        |
| TEST EQUIPMENT LIST AND DETAILS.....                                                | 11        |
| TEST PROCEDURE .....                                                                | 11        |
| TEST DATA .....                                                                     | 11        |
| <b>FCC §2.1049, §95.573, §95.579 - AUTHORIZED BANDWIDTH AND EMISSION MASK .....</b> | <b>15</b> |
| APPLICABLE STANDARD .....                                                           | 15        |
| TEST PROCEDURE .....                                                                | 15        |
| TEST EQUIPMENT LIST AND DETAILS.....                                                | 15        |
| TEST DATA .....                                                                     | 16        |
| <b>FCC §2.1053 &amp; §95.579 - RADIATED SPURIOUS EMISSION .....</b>                 | <b>19</b> |
| APPLICABLE STANDARD .....                                                           | 19        |
| TEST PROCEDURE .....                                                                | 19        |
| TEST EQUIPMENT LIST AND DETAILS.....                                                | 19        |
| TEST DATA .....                                                                     | 20        |
| <b>FCC §2.1055 (d), §95.565- FREQUENCY STABILITY .....</b>                          | <b>22</b> |
| APPLICABLE STANDARD .....                                                           | 22        |
| TEST PROCEDURE .....                                                                | 22        |
| TEST EQUIPMENT LIST AND DETAILS.....                                                | 22        |
| TEST DATA .....                                                                     | 23        |

## GENERAL INFORMATION

### Product Description for Equipment Under Test (EUT)

|                             |                                            |
|-----------------------------|--------------------------------------------|
| <b>EUT Name:</b>            | Walkie Talkie (FRS)                        |
| <b>EUT Model:</b>           | BT900                                      |
| <b>Multiple Models:</b>     | RT46, CB100                                |
| <b>FCC ID:</b>              | 2AQJJB T900                                |
| <b>Rated Input Voltage:</b> | 3.7VDC from battery and 5VDC from USB port |
| <b>External Dimension:</b>  | 60mm(L)*37mm(W)*122mm(H)                   |
| <b>Serial Number:</b>       | 181029004                                  |
| <b>EUT Received Date:</b>   | 2018-10-31                                 |

*Note: The series product, model RT46, CB100, BT900 are electrically identical, we selected BT900 for fully testing, the differences details was explained in the declaration letter.*

### Objective

This report is prepared on behalf of **Shenzhen Jizhida Technology Co., Ltd** in accordance with Part 2 and Part 95, Subpart A and B of the Federal Communication Commissions rules.

### Related Submittal(s)/Grant(s)

No related submittal(s).

### Test Methodology

All tests and measurements indicated in this document were performed in accordance with Part 95 Subpart B and Subpart E of the Federal Communication Commissions rules with TIA-603-D, Land Mobile FM or PM-Communications Equipment-Measurement and Performance Standards.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

**Measurement Uncertainty**

| Parameter                     | Measurement Uncertainty                      |
|-------------------------------|----------------------------------------------|
| Occupied Channel Bandwidth    | $\pm 5\%$                                    |
| RF output power, conducted    | $\pm 0.61\text{dB}$                          |
| Unwanted Emissions, radiated  | 30MHz ~ 1GHz: 5.85 dB<br>1G~26.5GHz: 5.23 dB |
| Unwanted Emissions, conducted | $\pm 1.5\text{ dB}$                          |
| Temperature                   | $\pm 1^\circ\text{C}$                        |
| Humidity                      | $\pm 5\%$                                    |
| DC and low frequency voltages | $\pm 0.4\%$                                  |
| Duty Cycle                    | 1%                                           |

**Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062D.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in a typical fashion (as normally used by a typical user).

EUT Specification:

|                             |                                               |
|-----------------------------|-----------------------------------------------|
| <b>Frequency Band:</b>      | 462.5500-462.7250MHz;<br>467.5625-467.7125MHz |
| <b>Modulation Mode:</b>     | FM                                            |
| <b>Channel Spacing:</b>     | 12.5kHz                                       |
| <b>Emission Designator:</b> | 11K0F3E                                       |

The device uses total 22 FRS channels as below:

| Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) |
|-------------|-----------------|-------------|-----------------|
| 1           | 462.5625        | 12          | 467.6625        |
| 2           | 462.5875        | 13          | 467.6875        |
| 3           | 462.6125        | 14          | 467.7125        |
| 4           | 462.6375        | 15          | 462.5500        |
| 5           | 462.6625        | 16          | 462.5750        |
| 6           | 462.6875        | 17          | 462.6000        |
| 7           | 462.7125        | 18          | 462.6250        |
| 8           | 467.5625        | 19          | 462.6500        |
| 9           | 467.5875        | 20          | 462.6750        |
| 10          | 467.6125        | 21          | 462.7000        |
| 11          | 467.6375        | 22          | 462.7250        |


### Equipment Modifications

No modification was made to the EUT tested.

### EUT Exercise Software

No Software was used in test.

Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

| FCC Rules                 | Description of Test                  | Results    |
|---------------------------|--------------------------------------|------------|
| §2.1093                   | RF Exposure                          | Compliance |
| §2.1046, §95.567          | RF Output Power                      | Compliance |
| §2.1047, §95.575          | Modulation Characteristic            | Compliance |
| §2.1049, §95.573, §95.579 | Authorized Bandwidth & Emission Mask | Compliance |
| §2.1053, §95.579          | Spurious Radiated Emissions          | Compliance |
| §2.1055(d), §95.565       | Frequency Stability                  | Compliance |

## **FCC §2.1093 - RF EXPOSURE INFORMATION**

---

### **Applicable Standard**

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

### **Test Result**

Please refer to SAR Report Number: RDG181029004-20.



## FCC §2.1046, §95.567 - RF OUTPUT POWER

### Applicable Standard

According to FCC §95.567

Each FRS transmitter type must be designed such that the effective radiated power (ERP) on channels 8 through 14 does not exceed 0.5 Watts and the ERP on channels 1 through 7 and 15 through 22 does not exceed 2.0 Watts.

### Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the emissions were measured by the substitution.

### Test Equipment List and Details

| Manufacturer   | Description               | Model     | Serial Number | Calibration Date | Calibration Due Date |
|----------------|---------------------------|-----------|---------------|------------------|----------------------|
| Agilent        | Signal Generator          | E8247C    | MY43321350    | 2017-12-11       | 2018-12-11           |
| EMCO           | Adjustable Dipole Antenna | 3121C     | 9109-753      | N/A              | N/A                  |
| Sunol Sciences | Antenna                   | JB3       | A060611-1     | 2017-11-10       | 2020-11-10           |
| R&S            | EMI Test Receiver         | ESCI      | 100224        | 2017-12-11       | 2018-12-11           |
| Unknown        | Coaxial Cable             | C-NJNJ-50 | C-0400-01     | 2018-09-05       | 2019-09-05           |
| Unknown        | Coaxial Cable             | C-NJNJ-50 | C-0075-01     | 2018-09-05       | 2019-09-05           |
| Unknown        | Coaxial Cable             | C-NJNJ-50 | C-1000-01     | 2018-09-05       | 2019-09-05           |

**\* Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

|                    |          |
|--------------------|----------|
| Temperature:       | 26.9 °C  |
| Relative Humidity: | 54%      |
| ATM Pressure:      | 100.8kPa |

The testing was performed by Neil Liao and Vern Shen on 2018-11-07.

*Test Mode: Transmitting***ERP:**

| Frequency<br>(MHz)    | Polar<br>(H/V) | Receiver<br>Reading<br>(dBμV) | Substituted Method            |                              |                    | Absolute<br>Level<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) |
|-----------------------|----------------|-------------------------------|-------------------------------|------------------------------|--------------------|----------------------------|----------------|----------------|
|                       |                |                               | Substituted<br>Level<br>(dBm) | Antenna<br>Gain<br>(dBd/dBi) | Cable Loss<br>(dB) |                            |                |                |
| Frequency:462.6375MHz |                |                               |                               |                              |                    |                            |                |                |
| 462.6375              | H              | 97.50                         | 15.67                         | 0.00                         | 0.65               | 15.02                      | 33.00          | 17.98          |
| 462.6375              | V              | 109.44                        | 30.44                         | 0.00                         | 0.65               | 29.79                      | 33.00          | 3.21           |
| Frequency:467.6375MHz |                |                               |                               |                              |                    |                            |                |                |
| 467.6375              | H              | 87.06                         | 5.86                          | 0.00                         | 0.68               | 5.18                       | 27.00          | 21.82          |
| 467.6375              | V              | 100.04                        | 21.81                         | 0.00                         | 0.68               | 21.13                      | 27.00          | 5.87           |

**Test Result:** Compliance.

**FCC §2.1047 & §95.575 - MODULATION CHARACTERISTIC****Applicable Standard**

Per FCC §2.1047 and §95.575:

Each FRS transmitter type must be designed such that the peak frequency deviation does not exceed 2.5 kHz, and the highest audio frequency contributing substantially to modulation must not exceed 3.125 kHz.

**Test Equipment List and Details**

| Manufacturer | Description                | Model No.   | Serial No. | Calibration Date | Calibration Due Date |
|--------------|----------------------------|-------------|------------|------------------|----------------------|
| HP           | RF Communications Test Set | 8920A       | 00 235     | 2018-07-11       | 2019-07-11           |
| LEADER       | Millivoltmeter             | LMV-181A    | 601788     | 2018-08-11       | 2019-08-10           |
| Unknown      | Coaxial Cable              | C-SJ00-0010 | C0010/04   | Each time        | N/A                  |
| Weinschel    | Coaxial Attenuators        | 53-20-34    | LN749      | 2018-09-05       | 2019-09-05           |

**\* Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Procedure**

Test Method: TIA/EIA-603-D

**Test Data****Environmental Conditions**

|                    |           |
|--------------------|-----------|
| Temperature:       | 26.9 °C   |
| Relative Humidity: | 54 %      |
| ATM Pressure:      | 100.8 kPa |

*The testing was performed by Harry yang on 2018-11-07.*


Please refer to the following tables and plots.

*Test Mode: Transmitting*

**MODULATION LIMITING**

Carrier Frequency: 462.6375 MHz


| Audio Frequency (Hz) | Instantaneous            |                          | Steady-state             |                          | Limit [kHz] |
|----------------------|--------------------------|--------------------------|--------------------------|--------------------------|-------------|
|                      | Deviation (@+20dB) [kHz] | Deviation (@-20dB) [kHz] | Deviation (@+20dB) [kHz] | Deviation (@-20dB) [kHz] |             |
| 300                  | 0.674                    | 0.190                    | 0.687                    | 0.185                    | 2.5         |
| 400                  | 0.940                    | 0.202                    | 0.933                    | 0.196                    | 2.5         |
| 500                  | 1.280                    | 0.233                    | 1.237                    | 0.229                    | 2.5         |
| 600                  | 1.540                    | 0.251                    | 1.513                    | 0.234                    | 2.5         |
| 700                  | 1.575                    | 0.256                    | 1.563                    | 0.242                    | 2.5         |
| 800                  | 1.706                    | 0.247                    | 1.692                    | 0.236                    | 2.5         |
| 900                  | 1.847                    | 0.270                    | 1.834                    | 0.255                    | 2.5         |
| 1000                 | 1.904                    | 0.299                    | 1.887                    | 0.278                    | 2.5         |
| 1200                 | 2.043                    | 0.307                    | 2.035                    | 0.296                    | 2.5         |
| 1400                 | 2.096                    | 0.342                    | 2.087                    | 0.329                    | 2.5         |
| 1600                 | 2.106                    | 0.367                    | 2.093                    | 0.345                    | 2.5         |
| 1800                 | 2.102                    | 0.367                    | 2.096                    | 0.347                    | 2.5         |
| 2000                 | 2.105                    | 0.399                    | 2.094                    | 0.383                    | 2.5         |
| 2200                 | 2.094                    | 0.410                    | 2.083                    | 0.376                    | 2.5         |
| 2400                 | 2.101                    | 0.416                    | 2.090                    | 0.374                    | 2.5         |
| 2600                 | 2.111                    | 0.432                    | 2.095                    | 0.412                    | 2.5         |
| 2800                 | 2.108                    | 0.447                    | 2.103                    | 0.413                    | 2.5         |
| 3000                 | 2.089                    | 0.432                    | 2.095                    | 0.407                    | 2.5         |



**Audio Frequency Response**

Carrier Frequency: 462.6375 MHz


| Audio Frequency (Hz) | Response Attenuation (dB) |
|----------------------|---------------------------|
| 300                  | -11.01                    |
| 400                  | -8.31                     |
| 500                  | -6.12                     |
| 600                  | -4.54                     |
| 700                  | -3.34                     |
| 800                  | -2.25                     |
| 900                  | -1.01                     |
| 1000                 | 0.00                      |
| 1200                 | 1.06                      |
| 1400                 | 2.31                      |
| 1600                 | 3.29                      |
| 1800                 | 3.71                      |
| 2000                 | 4.65                      |
| 2200                 | 4.80                      |
| 2400                 | 5.44                      |
| 2600                 | 5.80                      |
| 2800                 | 5.92                      |
| 3000                 | 5.90                      |
| 3125                 | 2.48                      |



**Audio Low Pass Filter Response**

Carrier Frequency: 462.6375 MHz

| Audio Frequency (kHz) | Response Attenuation (dB) | Limit (dB) |
|-----------------------|---------------------------|------------|
| 3.0                   | -2.2                      | 0.0        |
| 3.5                   | -8.1                      | -6.7       |
| 4.0                   | -13.6                     | -12.5      |
| 5.0                   | -24.6                     | -22.2      |
| 7.0                   | -38.5                     | -36.8      |
| 10.0                  | -56.1                     | -52.3      |
| 15.0                  | -71.9                     | -69.9      |
| 20.0                  | -84.6                     | -82.5      |
| 30.0                  | -85.6                     | -82.5      |
| 50.0                  | -84.7                     | -82.5      |
| 70.0                  | -85.2                     | -82.5      |



## FCC §2.1049, §95.573, §95.579 - AUTHORIZED BANDWIDTH AND EMISSION MASK

### Applicable Standard

According to §95.573

Each FRS transmitter type must be designed such that the occupied bandwidth does not exceed 12.5 kHz.

According to §95.579

Each FRS transmitter type must be designed to satisfy the applicable unwanted emissions limits in this paragraph.

(a) Attenuation requirements. The power of unwanted emissions must be attenuated below the carrier power output in Watts (P) by at least:

- (1) 25 dB (decibels) in the frequency band 6.25 kHz to 12.5 kHz removed from the channel center frequency.
- (2) 35 dB in the frequency band 12.5 kHz to 31.25 kHz removed from the channel center frequency.
- (3)  $43 + 10 \log (P)$  dB in any frequency band removed from the channel center frequency by more than 31.25 kHz.

### Test Procedure

TIA-603-D, section 2.2.11

### Test Equipment List and Details

| Manufacturer    | Description                | Model No.   | Serial No. | Calibration Date | Calibration Due Date |
|-----------------|----------------------------|-------------|------------|------------------|----------------------|
| Rohde & Schwarz | Signal Analyzer            | FSIQ26      | 831929/005 | 2018-08-31       | 2019-08-31           |
| HP              | RF Communications Test Set | 8920A       | 00 235     | 2018-07-11       | 2019-07-11           |
| Unknown         | Coaxial Cable              | C-SJ00-0010 | C0010/04   | Each time        | N/A                  |
| Weinschel       | Coaxial Attenuators        | 53-20-34    | LN749      | Each time        | N/A                  |

**\* Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 26.9 °C   |
| <b>Relative Humidity:</b> | 54 %      |
| <b>ATM Pressure:</b>      | 100.8 kPa |

*The testing was performed by Harry yang on 2018-11-07.*

Test Mode: Transmitting

| <b>fc<br/>(MHz)</b> | <b>99% Occupied<br/>Bandwidth<br/>(kHz)</b> | <b>20 dB<br/>Bandwidth<br/>(kHz)</b> | <b>Limit<br/>(kHz)</b> |
|---------------------|---------------------------------------------|--------------------------------------|------------------------|
| 462.6375            | 9.62                                        | 10.02                                | 12.50                  |
| 467.6375            | 9.62                                        | 10.22                                | 12.50                  |

Note: Emission bandwidth was based on calculation method instead of measurement.

Emission Designator

Per CFR 47 §2.201& §2.202,  $BW = 2M + 2D$

**For FM Mode (Channel Spacing: 12.5 kHz)**

Emission Designator 11K0F3E

In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation.



$BW = 2(M+D) = 2*(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz} = 11K0$

F3E portion of the designator represents an FM voice transmission



Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.



462.6375 MHz



467.6375 MHz



## FCC §2.1053 & §95.579 - RADIATED SPURIOUS EMISSION

### Applicable Standard

FCC §2.1053 and §95.579

### Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = 10 lg (TXpwr in Watts/0.001)-the absolute level  
Spurious attenuation limit in dB = 43+10 Log<sub>10</sub> (power out in Watts)

### Test Equipment List and Details

| Manufacturer   | Description               | Model                | Serial Number    | Calibration Date | Calibration Due Date |
|----------------|---------------------------|----------------------|------------------|------------------|----------------------|
| Agilent        | Signal Generator          | E8247C               | MY43321350       | 2017-12-11       | 2018-12-11           |
| EMCO           | Adjustable Dipole Antenna | 3121C                | 9109-753         | N/A              | N/A                  |
| Sunol Sciences | Antenna                   | JB3                  | A060611-1        | 2017-11-10       | 2020-11-10           |
| HP             | Amplifier                 | 8447D                | 2727A05902       | 2018-09-05       | 2019-09-05           |
| R&S            | EMI Test Receiver         | ESCI                 | 100224           | 2017-12-11       | 2018-12-11           |
| Unknown        | Coaxial Cable             | C-NJNJ-50            | C-0400-01        | 2018-09-05       | 2019-09-05           |
| Unknown        | Coaxial Cable             | C-NJNJ-50            | C-0075-01        | 2018-09-05       | 2019-09-05           |
| Unknown        | Coaxial Cable             | C-NJNJ-50            | C-1000-01        | 2018-09-05       | 2019-09-05           |
| Unknown        | Coaxial Cable             | C-NJNJ-50            | C-0200-02        | 2018-09-05       | 2019-09-05           |
| TDK RF         | Horn Antenna              | HRN-0118             | 130 084          | 2016-01-05       | 2019-01-04           |
| ETS-Lindgren   | Horn Antenna              | 3115                 | 000 527 35       | 2016-01-05       | 2019-01-04           |
| MICRO-COAX     | Coaxial Cable             | UFA147-1-2362-100100 | 64639 231029-001 | 2018-02-24       | 2019-02-28           |
| Mini           | Pre-amplifier             | ZVA-183-S+           | 5969001149       | 2018-09-05       | 2019-09-05           |
| R&S            | Spectrum Analyzer         | FSP 38               | 100478           | 2017-12-08       | 2018-12-08           |

**\* Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

|                           |          |
|---------------------------|----------|
| <b>Temperature:</b>       | 26.9 °C  |
| <b>Relative Humidity:</b> | 54%      |
| <b>ATM Pressure:</b>      | 100.8kPa |

The testing was performed by Neil Liao and Vern Shen on 2018-11-07.

Test Mode: Transmitting

**30MHz-5GHz:**

| Frequency<br>(MHz)        | Polar<br>(H/V) | Receiver<br>Reading<br>(dBμV) | Substituted Method            |                              |                    | Absolute<br>Level<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) |
|---------------------------|----------------|-------------------------------|-------------------------------|------------------------------|--------------------|----------------------------|----------------|----------------|
|                           |                |                               | Substituted<br>Level<br>(dBm) | Antenna<br>Gain<br>(dBd/dBi) | Cable Loss<br>(dB) |                            |                |                |
| FM, frequency:462.6375MHz |                |                               |                               |                              |                    |                            |                |                |
| 925.2750                  | H              | 34.75                         | -38.96                        | 0.00                         | 1.09               | -40.05                     | -13.00         | 27.05          |
| 925.2750                  | V              | 42.75                         | -27.67                        | 0.00                         | 1.09               | -28.76                     | -13.00         | 15.76          |
| 1387.9125                 | H              | 65.66                         | -38.01                        | 9.53                         | 1.21               | -29.69                     | -13.00         | 16.69          |
| 1387.9125                 | V              | 72.64                         | -31.14                        | 9.53                         | 1.21               | -22.82                     | -13.00         | 9.82           |
| 1850.5500                 | H              | 64.48                         | -39.72                        | 11.05                        | 1.20               | -29.87                     | -13.00         | 16.87          |
| 1850.5500                 | V              | 68.62                         | -35.51                        | 11.05                        | 1.20               | -25.66                     | -13.00         | 12.66          |
| 2313.1875                 | H              | 58.71                         | -44.55                        | 11.94                        | 1.20               | -33.81                     | -13.00         | 20.81          |
| 2313.1875                 | V              | 54.95                         | -49.17                        | 11.94                        | 1.20               | -38.43                     | -13.00         | 25.43          |
| 2775.8250                 | H              | 58.23                         | -44.04                        | 12.31                        | 1.38               | -33.11                     | -13.00         | 20.11          |
| 2775.8250                 | V              | 51.33                         | -51.51                        | 12.31                        | 1.38               | -40.58                     | -13.00         | 27.58          |
| 3238.4625                 | H              | 56.54                         | -44.85                        | 12.30                        | 1.55               | -34.10                     | -13.00         | 21.10          |
| 3238.4625                 | V              | 49.94                         | -50.68                        | 12.30                        | 1.55               | -39.93                     | -13.00         | 26.93          |
| 3701.1000                 | H              | 46.90                         | -53.47                        | 12.24                        | 1.55               | -42.78                     | -13.00         | 29.78          |
| 3701.1000                 | V              | 45.88                         | -53.91                        | 12.24                        | 1.55               | -43.22                     | -13.00         | 30.22          |
| 4163.7375                 | H              | 40.70                         | -58.38                        | 12.66                        | 1.48               | -47.20                     | -13.00         | 34.20          |
| 4163.7375                 | V              | 39.25                         | -60.49                        | 12.66                        | 1.48               | -49.31                     | -13.00         | 36.31          |
| 4626.3750                 | H              | 46.40                         | -51.26                        | 13.30                        | 1.51               | -39.47                     | -13.00         | 26.47          |
| 4626.3750                 | V              | 42.44                         | -55.40                        | 13.30                        | 1.51               | -43.61                     | -13.00         | 30.61          |

| Frequency<br>(MHz)        | Polar<br>(H/V) | Receiver<br>Reading<br>(dBμV) | Substituted Method            |                              |                    | Absolute<br>Level<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) |
|---------------------------|----------------|-------------------------------|-------------------------------|------------------------------|--------------------|----------------------------|----------------|----------------|
|                           |                |                               | Substituted<br>Level<br>(dBm) | Antenna<br>Gain<br>(dBd/dBi) | Cable Loss<br>(dB) |                            |                |                |
| FM, frequency:467.6375MHz |                |                               |                               |                              |                    |                            |                |                |
| 935.2750                  | H              | 45.57                         | -27.85                        | 0.00                         | 1.11               | -28.96                     | -13.00         | 15.96          |
| 935.2750                  | V              | 54.28                         | -15.85                        | 0.00                         | 1.11               | -16.96                     | -13.00         | 3.96           |
| 1402.9125                 | H              | 65.66                         | -38.13                        | 9.59                         | 1.23               | -29.77                     | -13.00         | 16.77          |
| 1402.9125                 | V              | 74.38                         | -29.50                        | 9.59                         | 1.23               | -21.14                     | -13.00         | 8.14           |
| 1870.5500                 | H              | 60.95                         | -43.22                        | 11.11                        | 1.19               | -33.30                     | -13.00         | 20.30          |
| 1870.5500                 | V              | 67.61                         | -36.50                        | 11.11                        | 1.19               | -26.58                     | -13.00         | 13.58          |
| 2338.1875                 | H              | 54.93                         | -48.26                        | 11.97                        | 1.20               | -37.49                     | -13.00         | 24.49          |
| 2338.1875                 | V              | 53.87                         | -50.27                        | 11.97                        | 1.20               | -39.50                     | -13.00         | 26.50          |
| 2805.8250                 | H              | 60.65                         | -41.56                        | 12.32                        | 1.40               | -30.64                     | -13.00         | 17.64          |
| 2805.8250                 | V              | 53.26                         | -49.43                        | 12.32                        | 1.40               | -38.51                     | -13.00         | 25.51          |
| 3273.4625                 | H              | 54.04                         | -47.29                        | 12.29                        | 1.56               | -36.56                     | -13.00         | 23.56          |
| 3273.4625                 | V              | 47.45                         | -53.01                        | 12.29                        | 1.56               | -42.28                     | -13.00         | 29.28          |
| 3741.1000                 | H              | 47.56                         | -52.70                        | 12.25                        | 1.53               | -41.98                     | -13.00         | 28.98          |
| 3741.1000                 | V              | 45.32                         | -54.55                        | 12.25                        | 1.53               | -43.83                     | -13.00         | 30.83          |
| 4208.7375                 | H              | 41.57                         | -57.37                        | 12.76                        | 1.49               | -46.10                     | -13.00         | 33.10          |
| 4208.7375                 | V              | 39.19                         | -60.38                        | 12.76                        | 1.49               | -49.11                     | -13.00         | 36.11          |
| 4676.3750                 | H              | 45.45                         | -52.04                        | 13.26                        | 1.50               | -40.28                     | -13.00         | 27.28          |
| 4676.3750                 | V              | 42.47                         | -55.13                        | 13.26                        | 1.50               | -43.37                     | -13.00         | 30.37          |

**FCC§2.1055 (d), §95.565- FREQUENCY STABILITY****Applicable Standard**

According to FCC §2.1055(a) (1),

The frequency stability shall be measured with variation of ambient temperature from  $-30^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$ , and according to FCC 2.1055(d) (2), the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point which is specified by the manufacturer.

According to FCC §95.565

Each FRS transmitter type must be designed such that the carrier frequencies remain within  $\pm 2.5$  parts-per-million of the channel center frequencies specified in § 95.563 during normal operating conditions.

**Test Procedure**

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to a Frequency Counter via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the Frequency Counter.

Frequency Stability vs. Voltage:

1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.

The output frequency was recorded for each voltage.

**Test Equipment List and Details**

| Manufacturer   | Description                   | Model No.   | Serial No.  | Calibration Date | Calibration Due Date |
|----------------|-------------------------------|-------------|-------------|------------------|----------------------|
| Dongzhixu      | High Temperature Test Chamber | DP1000      | 201105083-4 | 2018-08-28       | 2019-08-28           |
| UNI-T          | Multimeter                    | UT39A       | M130199938  | 2018-05-09       | 2019-05-09           |
| HP             | RF Communications Test Set    | 8920A       | 00 235      | 2018-07-11       | 2019-07-11           |
| Unknown        | Coaxial Cable                 | C-SJ00-0010 | C0010/04    | Each time        | N/A                  |
| Weinschel      | Coaxial Attenuators           | 53-20-34    | LN749       | Each time        | N/A                  |
| Pro instrument | DC Power Supply               | pps3300     | 001         | N/A              | N/A                  |

**\* Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 26.9 °C   |
| <b>Relative Humidity:</b> | 54 %      |
| <b>ATM Pressure:</b>      | 100.8 kPa |

The testing was performed by Harry yang on 2018-11-07.

Test Mode: Transmitting

| Reference Frequency: 462.6375 MHz |         |          |                 |       |
|-----------------------------------|---------|----------|-----------------|-------|
| Temperature                       | Voltage | Reading  | Frequency Error | Limit |
| °C                                | Vdc     | MHz      | ppm             | ppm   |
| -30                               | 3.7     | 462.6373 | -0.43           | 2.5   |
| -20                               |         | 462.6374 | -0.22           |       |
| -10                               |         | 462.6374 | -0.22           |       |
| 0                                 |         | 462.6373 | -0.43           |       |
| 10                                |         | 462.6374 | -0.22           |       |
| 20                                |         | 462.6374 | -0.22           |       |
| 30                                |         | 462.6374 | -0.22           |       |
| 40                                |         | 462.6374 | -0.22           |       |
| 50                                |         | 462.6373 | -0.43           |       |
| 20                                | 3.3     | 462.6374 | -0.22           | 2.5   |
| 20                                | 4.5     | 462.6374 | -0.22           |       |

| Reference Frequency: 467.6375 MHz |         |          |                 |       |
|-----------------------------------|---------|----------|-----------------|-------|
| Temperature                       | Voltage | Reading  | Frequency Error | Limit |
| °C                                | Vdc     | MHz      | ppm             | ppm   |
| -30                               | 3.7     | 467.6374 | -0.21           | 2.5   |
| -20                               |         | 467.6374 | -0.21           |       |
| -10                               |         | 467.6373 | -0.43           |       |
| 0                                 |         | 467.6374 | -0.21           |       |
| 10                                |         | 467.6374 | -0.21           |       |
| 20                                |         | 467.6374 | -0.21           |       |
| 30                                |         | 467.6374 | -0.21           |       |
| 40                                |         | 467.6374 | -0.21           |       |
| 50                                |         | 467.6373 | -0.43           |       |
| 20                                | 3.3     | 467.6374 | -0.21           | 2.5   |
| 20                                | 4.5     | 467.6373 | -0.43           |       |

Note: The extreme voltage was declared by applicant.

**\*\*\*\*\* END OF REPORT \*\*\*\*\***