



June 03, 2016

TUV SUD BABT
Octagon House, Concorde Way
Segensworth Rd N, Fareham
PO15 5RL

Attention: Director of Certification

RE: Analysis of RF Exposure for Portable and Mobile use per KDB 447498 D01 Mobile Portable RF Exposure v05r02 and RSS-102 Issue 5 March 2015.

FCC ID: YETD32-21266NU and YETD32-21266CU
IC: 9298A-D3221266NU and 9298A-D3221266CU

1. Limits

Limits for General Population/Uncontrolled Exposure (Title 47 Subpart J §2.1091 and KDB 447498 D01 referring to limits under §1.1310)

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Electric Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time (minutes)
0.3 - 1.34	614	1.63	*(100)	30
1.34 - 30	824/f	2.19/f	*(180/f ²)	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	-	-	f/1500	30
1500 - 100,000	-	-	1.0	30

f = frequency in MHz

**Plane-wave equivalent power density*



Limits for Devices Used by the General Public (Uncontrolled Environment (RSS-102 Issue 5 March 2015))

Frequency Range (MHz)	Electric Field Strength (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003 - 10 ²¹	83	90	-	Instantaneous
0.1 - 10	-	0.73/f	-	6**
1.1 - 10	87/f ^{0.5}	-	-	6**
10 - 20	27.46	0.0728	2	6
20 - 48	-58.07/f ^{0.25}	0.1540/f ^{0.25}	8.944/f ^{0.5}	6
48 - 300	22.06	0.05852	1.291	6
300 - 6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000 - 15000	61.4	0.163	10	6
15000 - 150000	61.4	0.163	10	616000/f ^{1.2}
150000 - 300000	0.158f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000/f ^{1.2}

f is frequency in MHz

*Based on nerve stimulation (NS)

** Based on specific absorption rate (SAR)

2. Mobile MPE Calculation Summary using a 20cm separation distance:

Downlink (CU)					
Mode	Output Power (dBm)*	Power Density (mW/cm ²)	Power Density (W/m ²)	FCC Limit (mW/cm ²)	ISED Limit (W/m ²)
LTE Band 2	15.30	0.01068	0.1068	1	4.624
LTE Band 12	13.80	0.00756	0.0756	0.4873	2.374
LTE Band 4	15.64	0.01155	0.1155	1	4.901
2.4G BLE	-4.31	0.000037	0.00037	1	5.351
5G HB	21.21	0.0262863	0.262863	1	9.455

Uplink (NU)					
Mode	Output Power (dBm)*	Power Density (mW/cm ²)	Power Density (W/m ²)	FCC Limit (mW/cm ²)	ISED Limit (W/m ²)
LTE Band 2	21.76	0.04729	0.4729	1	4.559
LTE Band 12	23.73	0.07443	0.7443	0.4673	2.307
LTE Band 4	21.77	0.04739	0.4739	1	4.246
5G LB	21.45	0.03497	0.3497	1	9.059

*Since the IC limit is related to the frequency, limit was calculated based from the Low Channel Frequency.



3. Co-Located Transmitters transmission table:

Downlink	
Transmitter type	Transmitter type that can transmit at the same time
LTE B2	2.4G BLE, 5G HB
LTE B12	2.4G BLE, 5G HB
LTE B4	2.4G BLE, 5G HB
2.4G BLE	LTE B2/B12/B4
5G HB	LTE B2/B12/B4

Uplink	
Transmitter type	Transmitter type that can transmit at the same time
LTE B2	5G LB
LTE B12	5G LB
LTE B4	5G LB
5G LB	LTE B2/B12/B4

4. Simultaneous Transmission MPE:

Downlink					
Transmitter type	MPE (mw/cm ²)	FCC Limit (mW/cm ²)	IC Limit (W/m ²)	FCC MPE ratio (MPE/Limit)	ISED MPE ratio (MPE/Limit)
LTE Band 4	0.01155	1	4.901	0.01155	0.023566
2.4G BLE	0.000037	1	5.351	0.000037	0.000069
5G HB	0.0262863	1	9.455	0.0262863	0.0278
Sum of the ratios (should be <1.0)				0.037	0.05143

Uplink					
Transmitter type	MPE (mw/cm ²)	FCC Limit (mW/cm ²)	IC Limit (W/m ²)	FCC MPE ratio (MPE/Limit)	ISED MPE ratio (MPE/Limit)
LTE Band 12	0.07443	0.4673	2.307	0.15927	0.3226
5G LB	0.03497	1	9.4059	0.03497	0.0372
Sum of the ratios (should be <1.0)					0.3598



5. Mobile MPE Calculation using a 20cm separation distance

Using Power Density formula:

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to isotropic

R = distance to the center of radiation of the antenna

LTE Band 2 Downlink:

Maximum peak output power at antenna input terminal:	15.30	(dBm)
Maximum peak output power at antenna input terminal:	33.88	(mW)
Antenna gain(typical):	2.0	(dBi)
Maximum antenna gain:	1.585	(numeric)
Prediction distance:	20	(cm)
Source Based Time Average Duty Cycle:	100	(%)
Prediction frequency:	1940	(MHz)
FCC MPE limit for uncontrolled exposure at prediction frequency:	1.00	(mW/cm ²)
ISED MPE limit for uncontrolled exposure at prediction frequency:	4.624	(W/m ²)
Power density at prediction frequency:	0.0106839	(mW/cm ²)
Power density at prediction frequency:	0.106839	(W/m ²)
FCC Margin of Compliance:	-19.71	(dB)
IC Margin of Compliance:	-16.36	(dB)

LTE Band 12 Downlink:

Maximum peak output power at antenna input terminal:	13.80	(dBm)
Maximum peak output power at antenna input terminal:	11.67	(mW)
Antenna gain(typical):	2.0	(dBi)
Maximum antenna gain:	1.585	(numeric)
Prediction distance:	20	(cm)
Source Based Time Average Duty Cycle:	100	(%)
Prediction frequency:	731.5	(MHz)
FCC MPE limit for uncontrolled exposure at prediction frequency:	0.4873	(mW/cm ²)
ISED MPE limit for uncontrolled exposure at prediction frequency:	2.374	(W/m ²)
Power density at prediction frequency:	0.00756	(mW/cm ²)
Power density at prediction frequency:	0.0756	(W/m ²)
FCC Margin of Compliance:	-18.09	(dB)
IC Margin of Compliance:	-14.97	(dB)



LTE Band 4 Downlink:

Maximum peak output power at antenna input terminal:	15.64	(dBm)
Maximum peak output power at antenna input terminal:	36.64	(mW)
Antenna gain(typical):	2.0	(dBi)
Maximum antenna gain:	1.585	(numeric)
Prediction distance:	20	(cm)
Source Based Time Average Duty Cycle:	100	(%)
Prediction frequency:	2112.5	(MHz)
FCC MPE limit for uncontrolled exposure at prediction frequency:	1.00	(mW/cm ²)
ISED MPE limit for uncontrolled exposure at prediction frequency:	4.901	(W/m ²)
Power density at prediction frequency:	0.01155	(mW/cm ²)
Power density at prediction frequency:	0.1155	(W/m ²)
FCC Margin of Compliance:	-19.37	(dB)
IC Margin of Compliance:	-16.28	(dB)

2.4GHz BLE:

Maximum peak output power at antenna input terminal:	-4.31	(dBm)
Maximum peak output power at antenna input terminal:	0.37	(mW)
Antenna gain(typical):	-3.0	(dBi)
Maximum antenna gain:	0.501	(numeric)
Prediction distance:	20	(cm)
Source Based Time Average Duty Cycle:	100	(%)
Prediction frequency:	2402	(MHz)
FCC MPE limit for uncontrolled exposure at prediction frequency:	1.00	(mW/cm ²)
ISED MPE limit for uncontrolled exposure at prediction frequency:	5.351	(W/m ²)
Power density at prediction frequency:	0.000037	(mW/cm ²)
Power density at prediction frequency:	0.00037	(W/m ²)
FCC Margin of Compliance:	-44.32	(dB)
IC Margin of Compliance:	-41.64	(dB)



5GHzUNII High Band

Maximum peak output power at antenna input terminal:	21.21	(dBm)
Maximum peak output power at antenna input terminal:	132.13	(mW)
Antenna gain(typical):	0	(dBi)
Maximum antenna gain:	1.00	(numeric)
Prediction distance:	20	(cm)
Source Based Time Average Duty Cycle:	100	(%)
Prediction frequency:	5525	(MHz)
FCC MPE limit for uncontrolled exposure at prediction frequency:	1.00	(mW/cm ²)
ISED MPE limit for uncontrolled exposure at prediction frequency:	9.455	(W/m ²)
Power density at prediction frequency:	0.0262863	(mW/cm ²)
Power density at prediction frequency:	0.262863	(W/m ²)
FCC Margin of Compliance:	-15.8	(dB)
IC Margin of Compliance:	-15.56	(dB)

LTE Band 2 Uplink:

Maximum peak output power at antenna input terminal:	21.76	(dBm)
Maximum peak output power at antenna input terminal:	149.97	(mW)
Antenna gain(typical):	2.0	(dBi)
Maximum antenna gain:	1.585	(numeric)
Prediction distance:	20	(cm)
Source Based Time Average Duty Cycle:	100	(%)
Prediction frequency:	1900	(MHz)
FCC MPE limit for uncontrolled exposure at prediction frequency:	1.00	(mW/cm ²)
ISED MPE limit for uncontrolled exposure at prediction frequency:	4.559	(W/m ²)
Power density at prediction frequency:	0.0472857	(mW/cm ²)
Power density at prediction frequency:	0.472857	(W/m ²)
FCC Margin of Compliance:	-13.25	(dB)
IC Margin of Compliance:	-9.84	(dB)



LTE Band 12 Uplink:

Maximum peak output power at antenna input terminal:	23.73	(dBm)
Maximum peak output power at antenna input terminal:	236.05	(mW)
Antenna gain(typical):	2.0	(dBi)
Maximum antenna gain:	1.585	(numeric)
Prediction distance:	20	(cm)
Source Based Time Average Duty Cycle:	100	(%)
Prediction frequency:	701.5	(MHz)
FCC MPE limit for uncontrolled exposure at prediction frequency:	0.4673	(mW/cm ²)
ISED MPE limit for uncontrolled exposure at prediction frequency:	2.307	(W/m ²)
Power density at prediction frequency:	0.07443	(mW/cm ²)
Power density at prediction frequency:	0.7443	(W/m ²)
FCC Margin of Compliance:	-7.98	(dB)
IC Margin of Compliance:	-4.91	(dB)

LTE Band 4 Uplink:

Maximum peak output power at antenna input terminal:	21.77	(dBm)
Maximum peak output power at antenna input terminal:	150.31	(mW)
Antenna gain(typical):	2.0	(dBi)
Maximum antenna gain:	1.585	(numeric)
Prediction distance:	20	(cm)
Source Based Time Average Duty Cycle:	100	(%)
Prediction frequency:	1712.5	(MHz)
FCC MPE limit for uncontrolled exposure at prediction frequency:	1.00	(mW/cm ²)
ISED MPE limit for uncontrolled exposure at prediction frequency:	4.246	(W/m ²)
Power density at prediction frequency:	0.04739	(mW/cm ²)
Power density at prediction frequency:	0.4739	(W/m ²)
FCC Margin of Compliance:	-13.24	(dB)
IC Margin of Compliance:	-9.52	(dB)



5GHz UNII Low Band:

Maximum peak output power at antenna input terminal:	21.45	(dBm)
Maximum peak output power at antenna input terminal:	139.64	(mW)
Antenna gain(typical):	1	(dBi)
Maximum antenna gain:	1.259	(numeric)
Prediction distance:	20	(cm)
Source Based Time Average Duty Cycle:	100	(%)
Prediction frequency:	5190	(MHz)
FCC MPE limit for uncontrolled exposure at prediction frequency:	1.00	(mW/cm ²)
ISED MPE limit for uncontrolled exposure at prediction frequency:	9.059	(W/m ²)
Power density at prediction frequency:	0.0349728	(mW/cm ²)
Power density at prediction frequency:	0.349728	(W/m ²)
FCC Margin of Compliance:	-14.56	(dB)
IC Margin of Compliance:	-14.13	(dB)

Sincerely,

A handwritten signature in blue ink, appearing to read 'Xiaoying Zhang', written over a horizontal line.

Xiaoying Zhang

Name

Authorized Signatory

Title: EMC/Wireless Test Engineer