

TEST REPORT

Reference No...... : WTS16S0550259-4E V1
FCC ID : 2AC7IEKOG50
Applicant..... : Interglobe Connection Corp
Address..... : 7500 NW 25th Street 112 Miami, Florida 33122 USA
Manufacturer : Interglobe Connection Corp
Address..... : 7500 NW 25th Street 112 Miami, Florida 33122 USA
Product Name..... : Smart Phone
Model No : EKO Novy G50, EKO Novy
Brand..... : EKO
Standards..... : FCC CFR47 Part 27: 2015
Date of Receipt sample : May. 12, 2016
Date of Test : May. 15 – 19, 2016
Date of Issue..... : Jul. 05, 2016
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Tel :+86-755-83551033


Fax:+86-755-83552400

Compiled by:



Zero Zhou / Test Engineer

Approved by:



Philo Zhong / Manager

2 Test Summary

Test Items	Test Requirement	Result
RF Output Power	2.1046 27.50(c) 27.50(d)	PASS
Peak-to-Average Ratio	27.50(d)	PASS
Bandwidth	2.1049 27.53(a)	PASS
Spurious Emissions at Antenna Terminal	2.1051 27.53(h)	PASS
Field Strength of Spurious Radiation	2.1053 27.53(h) 27.53(m)	PASS
Out of band emission	27.53(h), 27.53(m)	PASS
Frequency Stability	2.1055 27.5(h) 27.54	PASS
Maximum Permissible Exposure (SAR)	1.1307 2.1093	PASS

3 Contents

	Page
1 COVER PAGE.....	1
2 TEST SUMMARY	2
3 CONTENTS	3
4 REPORT REVISION HISTORY.....	5
5 GENERAL INFORMATION.....	6
5.1 GENERAL DESCRIPTION OF E.U.T.	6
5.2 DETAILS OF E.U.T.	6
5.3 TEST MODE	8
5.4 TEST FACILITY	9
6 EQUIPMENT USED DURING TEST	10
6.1 EQUIPMENTS LIST	10
6.2 MEASUREMENT UNCERTAINTY	11
6.3 TEST EQUIPMENT CALIBRATION	11
7 RF OUTPUT POWER	12
7.1 EUT OPERATION.....	12
7.2 TEST PROCEDURE	12
7.3 TEST RESULT	13
CONDUCTED POWER.....	13
8 PEAK-TO-AVERAGE RATIO.....	28
8.1 EUT OPERATION.....	28
8.2 TEST PROCEDURE	28
8.3 TEST RESULT	28
9 BANDWIDTH.....	29
9.1 EUT OPERATION.....	29
9.2 TEST PROCEDURE	29
9.3 TEST RESULT	30
10 SPURIOUS EMISSIONS AT ANTENNA TERMINALS	43
10.1 EUT OPERATION.....	43
10.2 TEST PROCEDURE.....	43
10.3 TEST RESULT	43
11 SPURIOUS RADIATED EMISSIONS.....	44
11.1 EUT OPERATION.....	44
11.2 TEST SETUP	44
11.3 SPECTRUM ANALYZER SETUP	45
11.4 TEST PROCEDURE.....	46
11.5 SUMMARY OF TEST RESULTS	47
12 BAND EDGE MEASUREMENT	49
12.1 EUT OPERATION.....	49
12.2 TEST PROCEDURE.....	49
12.3 TEST RESULT	50
13 FREQUENCY STABILITY.....	51
13.1 EUT OPERATION.....	51
13.2 TEST PROCEDURE.....	51
13.3 TEST RESULT	52

14 RF EXPOSURE.....62

4 Report Revision History

Report No.	Report Version	Description	Issue Date
WTS16S0550259-4E	NONE	Original	May. 26, 2016
WTS16S0550259-4E	V1	Version 1	Jul. 05, 2016

5 General Information

5.1 General Description of E.U.T.

Product Name	: Smart Phone
Model No.	: EKO Novy G50, EKO Novy
Model Description	: Only the model names are different.
GSM Band(s)	: GSM 850/900/1800/1900MHz
GPRS/EGPRS Class	: 12
WCDMA Band(s)	: FDD Band II/V
LTE Bnad(s)	: LTE Band 4/7
Wi-Fi Specification	: 2.4G: 802.11b/g/n HT20/n HT40
Bluetooth Version	: Bluetooth V4.1 with BLE
GPS	: Support
NFC	: N/A
Hardware Version	: 5097_M1_V03
Software Version	: WAO50MTK6735HD1280720IPS_160111
Storage Location	: Internal Storage

5.2 Details of E.U.T.

Operation Frequency	: GSM/GPRS/EDGE 850: 824~849MHz GSM/GPRS/EDGE1900: 1850~1910MHz WCDMA Band II: 1850~1910MHz WCDMA Band V: 824~849MHz LTE Band 4: 1710~1755MHz LTE Band 7: 2500-2570MHz WiFi: 802.11b/g/n HT20: 2412~2462MHz 802.11n HT40: 2422~2452MHz Bluetooth: 2402~2480MHz
Max. RF output power	: GSM 850: 32.59dBm PCS1900:29.61dBm WCDMA Band II: 22.14dBm WCDMA Band V: 22.36dBm LTE Band 4: 22.99dBm LTE Band 7: 24.13dBm WiFi(2.4G): 9.55dBm Bluetooth: 4.61dBm
Type of Modulation	: GS GSM,GPRS: GMSK EDGE: GMSK, 8PSK WCDMA: BPSK

	LTE: QPSK, 16QAM
	WiFi: CCK, OFDM
	Bluetooth: GFSK, Pi/4 DQPSK, 8DPSK
Antenna installation	: GSM/WCDMA/LTE: internal permanent antenna WiFi/Bluetooth: internal permanent antenna
Antenna Gain	G GSM 850: -1dBi PCS1900: -1dBi WCDMA Band II: -1dBi WCDMA Band V: -1dBi LTE Band 4: 0dBi LTE Band 7: -1 dBi WiFi(2.4G): -1dBi Bluetooth: -1 dBi
Technical Data	: Battery DC 3.8V 2000mAh DC 5V, 1000mA, charging from adapter (Adapter Input: 100-240V~50/60Hz 0.2A)
Adapter	: Manufacture: Shenzhen xin chenming technology co., LTD Model No.: YHA-6W-05FUS YZ
Type of Emission	:LTE Band 4 1.4MHz: 1M16G7D(QPSK), 1M15W7D(16QAM) LTE Band 4 3MHz: 2M73G7D(QPSK), 2M72W7D(16QAM) LTE Band 4 5MHz: 4M50G7D(QPSK), 4M50W7D(16QAM) LTE Band 4 10 MHz: 8M93G7D(QPSK), 8M92W7D(16QAM) LTE Band 4 15MHz: 13M4G7D(QPSK), 13M4W7D(16QAM) LTE Band 4 20MHz: 17M9G7D(QPSK), 17M8W7D(16QAM) LTE Band 7 5MHz: 4M51G7D(QPSK), 4M50W7D(16QAM) LTE Band 7 10 MHz: 8M94G7D(QPSK), 8M93W7D(16QAM) LTE Band 7 15MHz: 13M4G7D(QPSK), 13M4W7D(16QAM) LTE Band 7 20MHz: 17M9G7D(QPSK), 17M9W7D(16QAM)

5.3 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

Support Band	Test Mode BW(MHz)	Channel Frequency	Channel Number
LTE Band 4	1.4	1710.7 MHz	19957
		1732.5 MHz	20175
		1754.3 MHz	20393
	3	1711.5 MHz	19965
		1732.5 MHz	20175
		1753.5 MHz	20385
	5	1712.5 MHz	19975
		1732.5 MHz	20175
		1752.5 MHz	20375
	10	1715.0 MHz	20000
		1732.5 MHz	20175
		1750.0 MHz	20350
	15	1717.5 MHz	20025
		1732.5 MHz	20175
		1747.5 MHz	20325
	20	1720.0 MHz	20050
		1732.5 MHz	20175
		1745.0 MHz	20300
LTE Band 7	5	2502.5 MHz	20775
		2535 MHz	21100
		2567.5 MHz	21425
	10	2505.0 MHz	20800
		2535 MHz	21100
		2565.0 MHz	21400
	15	2507.5 MHz	20825
		2535 MHz	21100
		2562.5 MHz	21375
	20	2510.0 MHz	20850
		2535 MHz	21100
		2560.0 MHz	21350
Remark: All mode(s) were tested and the worst data was recorded.			

5.4 Test Facility

The test facility has a test site registered with the following organizations:

- **IC – Registration No.: 7760A**

Waltek Services(Shenzhen) Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration number 7760A, October 15, 2015.

- **FCC Test Site 1#– Registration No.: 880581**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 880581, April 29, 2014.

- **FCC Test Site 2#– Registration No.: 328995**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 328995, December 3, 2014.

6 Equipment Used during Test

6.1 Equipments List

RF Conducted Test						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMC Analyzer (9k~26.5GHz)	Agilent	E7405A	MY45114943	Sep.15,2015	Sep.14,2016
2.	Spectrum Analyzer (9k-6GHz)	R&S	FSL6	100959	Sep.15,2015	Sep.14,2016
3.	Humidity Chamber	GF	GTH-225-40-1P	IAA061213	Sep.15,2015	Sep.14,2016
4.	Universal Radio Communication Tester	R&S	CMU 200	112461	Apr.10,2016	Apr.09,2017
3m Semi-anechoic Chamber for Radiated Emissions						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	EMC Analyzer	Agilent	E7405A	MY45114943	Sep.15,2015	Sep.14,2016
2	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	Sep.15,2015	Sep.14,2016
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	Apr.18,2016	Apr.17,2017
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	Sep.15,2015	Sep.14,2016
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	Apr.18,2016	Apr.17,2017
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	669	Apr.18,2016	Apr.17,2017
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	Mar.17,2016	Mar.16,2017
8	Coaxial Cable (above 1GHz)	Top	1000MHZ- 25GHz	EW02014-7	Apr.09,2016	Apr.08,2017
9	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	Sep.15,2015	Sep.14,2016
10	Universal Radio Communication Tester	R&S	CMU 200	112461	Apr.10,2016	Apr.09,2017
11	Signal Generator	R&S	SMR20	100046	Sep.15,2015	Sep.14,2016
12	Smart Antenna	SCHWARZBECK	HA08	-	Apr.18,2016	Apr.17,2017

6.2 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)
Conducted Spurious Emissions test	± 3.64 dB (AC mains 150KHz~30MHz)

6.3 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

7 RF OUTPUT POWER

Test Requirement:	FCC Part 2.1046, 27.50(c),27.50(d)
Test Method:	TIA/EIA-603-D:2010
Test Mode:	Transmitting

7.1 EUT Operation


Operating Environment :

Temperature:	22.5 °C
Humidity:	52.1 % RH
Atmospheric Pressure:	101.2kPa

7.2 Test Procedure

Conducted method:

The RF output of the transmitter was connected to the wireless test set and the spectrum analyzer through sufficient attenuation.



Radiated method:

1. The setup of EUT is according with per TIA/EIA Standard 603D:2010.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

7.3 Test Result

Conducted Power LTE Band 4:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
1.4MHz	19957	1710.7	QPSK	1	0	22.97	22.0±1	0
				1	2	22.9	22.0±1	0
				1	5	22.64	22.0±1	0
				3	0	21.36	22.0±1	0
				3	1	21.91	22.0±1	0
				3	2	21.81	22.0±1	0
				6	0	21.64	22.0±1	0
			16QAM	1	0	22.81	22.0±1	0
				1	2	22.81	22.0±1	0
				1	5	22.61	22.0±1	0
				3	0	21.54	22.0±1	0
				3	1	21.84	22.0±1	0
				3	2	21.85	22.0±1	0
				6	0	21.15	22.0±1	0
	20175	1732.5	QPSK	1	0	22.84	22.0±1	0
				1	2	22.82	22.0±1	0
				1	5	22.84	22.0±1	0
				3	0	21.87	22.0±1	0
				3	1	21.85	22.0±1	0
				3	2	21.86	22.0±1	0
				6	0	21.83	22.0±1	0
			16QAM	1	0	22.16	22.0±1	0
				1	2	22.12	22.0±1	0
				1	5	22.15	22.0±1	0
				3	0	22.04	22.0±1	0
				3	1	21.98	22.0±1	0
				3	2	22.01	22.0±1	0
				6	0	21.74	22.0±1	0
	20393	1754.3	QPSK	1	0	22.79	22.0±1	0
				1	2	22.76	22.0±1	0
				1	5	22.76	22.0±1	0
				3	0	21.84	22.0±1	0
				3	1	21.87	22.0±1	0
				3	2	21.83	22.0±1	0
				6	0	21.85	22.0±1	0
			16QAM	1	0	21.85	22.0±1	0
				1	2	21.81	22.0±1	0
				1	5	21.85	22.0±1	0
				3	0	22.03	22.0±1	0
				3	1	22.03	22.0±1	0
				3	2	22	22.0±1	0
				6	0	21.01	22.0±1	0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
3MHz	19965	1711.5	QPSK	1	0	22.96	22.0±1	0
				1	8	22.30	22.0±1	0
				1	14	22.45	22.0±1	0
				8	0	21.18	22.0±1	1
				8	4	21.14	22.0±1	1
				8	9	21.48	22.0±1	1
				15	0	21.54	22.0±1	1
			16QAM	1	0	22.48	22.0±1	0
				1	8	22.58	22.0±1	0
				1	14	22.84	22.0±1	0
				8	0	21.37	21.0±1	0
				8	4	21.45	21.0±1	0
				8	9	21.5	21.0±1	0
				15	0	21.34	21.0±1	0
	20175	1732.5	QPSK	1	0	22.82	22.0±1	0
				1	8	22.88	22.0±1	0
				1	14	22.83	22.0±1	0
				8	0	21.87	22.0±1	0
				8	4	21.87	22.0±1	0
				8	9	21.89	22.0±1	0
				15	0	21.83	22.0±1	0
			16QAM	1	0	22.12	22.0±1	0
				1	8	22.16	22.0±1	0
				1	14	22.14	22.0±1	0
				8	0	20.94	21.0±1	1
				8	4	20.95	21.0±1	1
				8	9	20.95	21.0±1	1
				15	0	20.87	21.0±1	1
	20385	1753.5	QPSK	1	0	22.77	22.0±1	0
				1	8	22.79	22.0±1	0
				1	14	22.76	22.0±1	0
				8	0	21.92	22.0±1	0
				8	4	21.91	22.0±1	0
				8	9	21.9	22.0±1	0
				15	0	21.89	22.0±1	0
			16QAM	1	0	21.84	22.0±1	0
				1	8	21.84	22.0±1	0
				1	14	21.79	22.0±1	0
				8	0	20.94	21.0±1	1
				8	4	20.96	21.0±1	1
				8	9	20.94	21.0±1	1
				15	0	20.87	21.0±1	1

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	19975	1712.5	QPSK	1	0	22.99	22.0±1	0
				1	49	22.88	22.0±1	0
				1	99	22.88	22.0±1	0
				12	0	21.91	21.0±1	1
				12	24	21.85	21.0±1	1
				12	49	22	21.0±1	1
				25	0	21.93	21.0±1	1
			16QAM	1	0	22.17	22.0±1	0
				1	49	21.94	22.0±1	0
				1	99	22.06	22.0±1	0
				12	0	20.93	21.0±1	1
				12	24	20.92	21.0±1	1
				12	49	21.11	21.0±1	1
				25	0	20.92	21.0±1	1
	20175	1732.5	QPSK	1	0	22.86	22.0±1	0
				1	49	22.89	22.0±1	0
				1	99	22.87	22.0±1	0
				12	0	21.91	21.0±1	1
				12	24	21.89	21.0±1	1
				12	49	21.92	21.0±1	1
				25	0	21.87	21.0±1	1
			16QAM	1	0	22.34	22.0±1	0
				1	49	22.36	22.0±1	0
				1	99	22.33	22.0±1	0
				12	0	21.06	21.0±1	1
				12	24	21.03	21.0±1	1
				12	49	21.06	21.0±1	1
				25	0	20.94	21.0±1	1
	20375	1752.5	QPSK	1	0	22.95	22.0±1	0
				1	49	22.93	22.0±1	0
				1	99	22.88	22.0±1	0
				12	0	21.96	21.0±1	1
				12	24	21.94	21.0±1	1
				12	49	21.95	21.0±1	1
			16QAM	25	0	21.89	21.0±1	1
				1	0	22.03	22.0±1	0
				1	49	21.98	22.0±1	0
				1	99	21.94	22.0±1	0
				12	0	21.03	21.0±1	1
				12	24	21.01	21.0±1	1
				12	49	20.99	21.0±1	1
				25	0	20.86	21.0±1	1

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	20000	1715	QPSK	1	0	22.75	22.0±1	0
				1	49	22.47	22.0±1	0
				1	99	22.56	22.0±1	0
				25	0	22.31	22.0±1	0
				25	24	22.41	22.0±1	0
				25	49	22.64	22.0±1	0
				50	0	22.57	22.0±1	0
			16QAM	1	0	22.59	22.0±1	0
				1	49	22.94	22.0±1	0
				1	99	22.21	22.0±1	0
				25	0	21.53	21.0±1	1
				25	24	21.41	21.0±1	1
				25	49	21.31	21.0±1	1
				50	0	21.41	21.0±1	0
	20175	1732.5	QPSK	1	0	22.89	22.0±1	0
				1	49	22.87	22.0±1	0
				1	99	22.99	22.0±1	0
				25	0	21.86	22.0±1	0
				25	24	21.88	22.0±1	0
				25	49	21.92	22.0±1	0
				50	0	21.89	22.0±1	0
			16QAM	1	0	22.19	22.0±1	0
				1	49	22.15	22.0±1	0
				1	99	22.25	22.0±1	0
				25	0	20.9	21.0±1	1
				25	24	20.91	21.0±1	1
				25	49	20.96	21.0±1	1
				50	0	20.92	21.0±1	1
	20350	1750	QPSK	1	0	22.84	22.0±1	0
				1	49	22.84	22.0±1	0
				1	99	22.56	22.0±1	0
				25	0	21.9	22.0±1	0
				25	24	21.92	22.0±1	0
				25	49	21.87	22.0±1	0
			16QAM	50	0	21.88	22.0±1	0
				1	0	21.69	22.0±1	0
				1	49	21.8	22.0±1	0
				1	99	21.57	22.0±1	0
				25	0	20.96	21.0±1	1
				25	24	20.99	21.0±1	1
				25	49	20.95	21.0±1	1
				50	0	20.91	21.0±1	1

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
15MHz	20025	1717.5	QPSK	1	0	22.85	22.0±1	0
				1	49	22.97	22.0±1	0
				1	99	22.97	22.0±1	0
				36	0	21.92	22.0±1	0
				36	24	22.01	22.0±1	0
				36	49	22.03	22.0±1	0
				75	0	22.07	22.0±1	0
			16QAM	1	0	21.55	22.0±1	0
				1	49	21.9	22.0±1	0
				1	99	21.89	22.0±1	0
				36	0	20.84	21.0±1	1
				36	24	21.02	21.0±1	1
				36	49	21.04	21.0±1	1
				75	0	21.06	21.0±1	1
	20175	1732.5	QPSK	1	0	22.92	22.0±1	0
				1	49	22.96	22.0±1	0
				1	99	22.95	22.0±1	0
				36	0	21.96	22.0±1	0
				36	24	21.99	22.0±1	0
				36	49	22.05	22.0±1	0
				75	0	22.02	22.0±1	0
			16QAM	1	0	22.22	22.0±1	0
				1	49	22.24	22.0±1	0
				1	99	22.26	22.0±1	0
				36	0	21	21.0±1	1
				36	24	21.01	21.0±1	1
				36	49	21.06	21.0±1	1
				75	0	21.01	21.0±1	1
	20325	1747.5	QPSK	1	0	22.94	22.0±1	0
				1	49	22.75	22.0±1	0
				1	99	22.78	22.0±1	0
				36	0	21.73	22.0±1	0
				36	24	21.75	22.0±1	0
				36	49	21.81	22.0±1	0
				75	0	21.72	22.0±1	0
			16QAM	1	0	22.1	22.0±1	0
				1	49	22	22.0±1	0
				1	99	22.09	22.0±1	0
				36	0	20.69	21.0±1	1
				36	24	20.76	21.0±1	1
				36	49	20.79	21.0±1	1
				75	0	20.75	21.0±1	1

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
20MHz	20050	1720	QPSK	1	0	22.77	22.0±1	0
				1	49	22.87	22.0±1	0
				1	99	22.93	22.0±1	0
				50	0	22.01	22.0±1	0
				50	24	21.97	22.0±1	0
				50	49	22.02	22.0±1	0
				100	0	22.02	22.0±1	0
			16QAM	1	0	22.11	22.0±1	0
				1	49	22.39	22.0±1	0
				1	99	22.55	22.0±1	0
				50	0	21.05	21.0±1	1
				50	24	21.01	21.0±1	1
				50	49	21.06	21.0±1	1
				100	0	21.06	21.0±1	1
	20175	1732.5	QPSK	1	0	22.9	22.0±1	0
				1	49	22.88	22.0±1	0
				1	99	22.54	22.0±1	0
				50	0	22.39	22.0±1	0
				50	24	22.54	22.0±1	0
				50	49	22.21	22.0±1	0
				100	0	21.94	22.0±1	0
			16QAM	1	0	22.32	22.0±1	0
				1	49	22.26	22.0±1	0
				1	99	21.98	22.0±1	0
				50	0	20.94	21.0±1	1
				50	24	20.95	21.0±1	1
				50	49	21.04	21.0±1	1
				100	0	20.96	21.0±1	1
	20300	1745	QPSK	1	0	22.04	22.0±1	0
				1	49	22.59	22.0±1	0
				1	99	22.69	22.0±1	0
				50	0	21.88	22.0±1	0
				50	24	21.64	22.0±1	0
				50	49	21.75	22.0±1	0
				100	0	21.79	22.0±1	0
			16QAM	1	0	22.35	22.0±1	0
				1	49	21.91	22.0±1	0
				1	99	22.06	22.0±1	0
				50	0	20.84	21.0±1	1
				50	24	20.62	21.0±1	1
				50	49	20.73	21.0±1	1
				100	0	20.82	21.0±1	1

LTE Band 7:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	20775	2502.5	QPSK	1	0	23.41	23.0±1	0
				1	49	23.58	23.0±1	0
				1	99	23.72	23.0±1	0
				12	0	22.46	22.0±1	1
				12	24	22.45	22.0±1	1
				12	49	22.53	22.0±1	1
				25	0	22.45	22.0±1	1
			16QAM	1	0	22.8	22.0±1	1
				1	49	22.87	22.0±1	1
				1	99	22.9	22.0±1	1
				12	0	21.61	21.0±1	2
				12	24	21.62	21.0±1	2
				12	49	21.65	21.0±1	2
				25	0	21.51	21.0±1	2
	21100	2535	QPSK	1	0	23.62	23.0±1	0
				1	49	23.62	23.0±1	0
				1	99	23.63	23.0±1	0
				12	0	22.69	22.0±1	1
				12	24	22.67	22.0±1	1
				12	49	22.66	22.0±1	1
				25	0	22.61	22.0±1	1
			16QAM	1	0	22.66	22.0±1	1
				1	49	22.68	22.0±1	1
				1	99	22.64	22.0±1	1
				12	0	21.81	21.0±1	2
				12	24	21.77	21.0±1	2
				12	49	21.77	21.0±1	2
				25	0	21.64	21.0±1	2
	21425	2567.5	QPSK	1	0	22.91	23.0±1	0
				1	49	23.04	23.0±1	0
				1	99	23.45	23.0±1	0
				12	0	21.41	22.0±1	1
				12	24	21.74	22.0±1	1
				12	49	22.24	22.0±1	1
				25	0	21.81	22.0±1	1
			16QAM	1	0	21.7	22.0±1	1
				1	49	21.9	22.0±1	1
				1	99	22.3	22.0±1	1
				12	0	20.43	21.0±1	2
				12	24	20.79	21.0±1	2
				12	49	21.28	21.0±1	2
				25	0	20.81	21.0±1	2

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	20800	2505	QPSK	1	0	23.72	23.0±1	0
				1	49	22.58	23.0±1	0
				1	99	22.35	23.0±1	0
				25	0	22.38	22.0±1	1
				25	24	22.85	22.0±1	1
				25	49	22.48	22.0±1	1
				50	0	22.61	22.0±1	1
			16QAM	1	0	22.31	22.0±1	1
				1	49	22.14	22.0±1	1
				1	99	22.51	22.0±1	1
				25	0	22.31	22.0±1	1
				25	24	22.61	22.0±1	1
				25	49	22.14	22.0±1	1
				50	0	22.54	22.0±1	1
	21100	2535	QPSK	1	0	23.1	23.0±1	0
				1	49	23.67	23.0±1	0
				1	99	23.69	23.0±1	0
				25	0	22.33	22.0±1	1
				25	24	22.65	22.0±1	1
				25	49	22.65	22.0±1	1
				50	0	22.7	22.0±1	1
			16QAM	1	0	22.2	22.0±1	1
				1	49	22.97	22.0±1	1
				1	99	22.9	22.0±1	1
				25	0	21.25	22.0±1	1
				25	24	21.75	22.0±1	1
				25	49	21.74	22.0±1	1
				50	0	21.79	22.0±1	1
	21400	2565	QPSK	1	0	21.12	22.0±1	1
				1	49	21.79	22.0±1	1
				1	99	22.92	22.0±1	1
				25	0	21.24	22.0±1	1
				25	24	21.68	22.0±1	1
				25	49	21.51	22.0±1	1
			16QAM	50	0	21.85	22.0±1	1
				1	0	21.01	22.0±1	1
				1	49	21.72	22.0±1	1
				1	99	21.87	22.0±1	1
				25	0	21.46	22.0±1	1
				25	24	21.87	22.0±1	1
				25	49	21.62	22.0±1	1
				50	0	21.95	22.0±1	1

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
15MHz	20825	2507.5	QPSK	1	0	23.73	23.0±1	0
				1	49	23.13	23.0±1	0
				1	99	23.77	23.0±1	0
				36	0	22.95	22.0±1	1
				36	24	22.91	22.0±1	1
				36	49	22.83	22.0±1	1
				75	0	22.85	22.0±1	1
			16QAM	1	0	22.37	22.0±1	1
				1	49	22.58	22.0±1	1
				1	99	22.72	22.0±1	1
				36	0	21.78	21.0±1	2
				36	24	21.9	21.0±1	2
				36	49	22	21.0±1	2
				75	0	21.88	21.0±1	2
	21100	2535	QPSK	1	0	22.71	23.0±1	0
				1	49	23.69	23.0±1	0
				1	99	23.79	23.0±1	0
				36	0	21.97	22.0±1	1
				36	24	22.77	22.0±1	1
				36	49	22.82	22.0±1	1
				75	0	22.82	22.0±1	1
			16QAM	1	0	21.84	22.0±1	1
				1	49	22.97	22.0±1	1
				1	99	22.84	22.0±1	1
				36	0	21.99	21.0±1	2
				36	24	21.77	21.0±1	2
				36	49	21.81	21.0±1	2
				75	0	21.83	21.0±1	2
	21375	2562.5	QPSK	1	0	22.7	23.0±1	0
				1	49	22.12	23.0±1	0
				1	99	23.11	23.0±1	0
				36	0	21.13	22.0±1	1
				36	24	21.15	22.0±1	1
				36	49	21.03	22.0±1	1
			16QAM	75	0	21.49	22.0±1	1
				1	0	21.8	22.0±1	1
				1	49	21.45	22.0±1	1
				1	99	22.21	22.0±1	1
				36	0	20.23	21.0±1	2
				36	24	20.25	21.0±1	2
				36	49	20.07	21.0±1	2
				75	0	20.64	21.0±1	2

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
20MHz	20850	2510	QPSK	1	0	23.73	23.0±1	0
				1	49	23.92	23.0±1	0
				1	99	23.05	23.0±1	0
				50	0	22.75	22.0±1	1
				50	24	22.85	22.0±1	1
				50	49	22.95	22.0±1	1
				100	0	22.85	22.0±1	1
			16QAM	1	0	22.05	22.0±1	0
				1	49	22.26	22.0±1	0
				1	99	22.64	22.0±1	0
				50	0	21.69	21.0±1	1
				50	24	21.79	21.0±1	1
				50	49	21.9	21.0±1	1
				100	0	21.82	21.0±1	1
	21100	2535	QPSK	1	0	22.49	23.0±1	0
				1	49	23.71	23.0±1	0
				1	99	23.81	23.0±1	0
				50	0	21.71	22.0±1	1
				50	24	22.69	22.0±1	1
				50	49	22.67	22.0±1	1
				100	0	22.68	22.0±1	1
			16QAM	1	0	21.74	22.0±1	1
				1	49	22.98	22.0±1	1
				1	99	22.78	22.0±1	1
				50	0	20.7	21.0±1	2
				50	24	21.68	21.0±1	2
				50	49	21.72	21.0±1	2
				100	0	21.73	21.0±1	2
	21350	2560	QPSK	1	0	22.75	23.0±1	1
				1	49	22.85	23.0±1	1
				1	99	22.97	23.0±1	1
				50	0	21.66	22.0±1	2
				50	24	21	22.0±1	2
				50	49	21.56	22.0±1	2
				100	0	21.58	22.0±1	2
			16QAM	1	0	21.93	22.0±1	1
				1	49	21.23	22.0±1	1
				1	99	22.22	22.0±1	1
				50	0	20.79	21.0±1	2
				50	24	20.14	21.0±1	2
				50	49	20.64	21.0±1	2
				100	0	20.75	21.0±1	2

Radiated Power**EIRP****LTE Band 4**

Frequency	Receiver Reading	Turn table Angle	RX Antenna		Substituted			Absolute Level	Part 27	
			Height	Polar	SG Level	Cable	Antenna Gain		Limit	Margin
(MHz)	(dBμV)	Degree	(m)	(H/V)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dB)
LTE Band 4 Channel 19957 – 1.4MHz – QPSK										
1710.70	76.35	96	1.7	H	2.24	0.30	9.40	11.34	30	-18.66
1710.70	84.39	98	1.9	V	10.86	0.30	9.40	19.96	30	-10.04
LTE Band 4 Channel 20175 – 1.4MHz – QPSK										
1732.50	76.85	284	1.9	H	2.74	0.30	9.40	11.84	30	-18.16
1732.50	84.47	242	2.0	V	10.94	0.30	9.40	20.04	30	-9.96
LTE Band 4 Channel 20393 – 1.4MHz – QPSK										
1754.30	77.24	357	2.1	H	3.13	0.30	9.40	12.23	30	-17.77
1754.30	84.37	16	1.8	V	10.84	0.30	9.40	19.94	30	-10.06
LTE Band 4 Channel 19957 – 1.4MHz – 16QAM										
1710.70	78.56	338	1.6	H	4.45	0.30	9.40	13.55	30	-16.45
1710.70	84.18	145	1.5	V	10.65	0.30	9.40	19.75	30	-10.25
LTE Band 4 Channel 20175 – 1.4MHz – 16QAM										
1732.50	77.42	54	1.1	H	3.31	0.30	9.40	12.41	30	-17.59
1732.50	84.88	97	2.0	V	11.35	0.30	9.40	20.45	30	-9.55
LTE Band 4 Channel 20393 – 1.4MHz – 16QAM										
1754.30	77.38	200	2.0	H	3.27	0.30	9.40	12.37	30	-17.63
1754.30	84.71	71	2.1	V	11.18	0.30	9.40	20.28	30	-9.72
LTE Band 4 Channel 19965 – 3MHz – QPSK										
1710.70	76.90	157	1.7	H	2.79	0.30	9.40	11.89	30	-18.11
1710.70	84.35	2	1.3	V	10.82	0.30	9.40	19.92	30	-10.08
LTE Band 4 Channel 20175 – 3MHz – QPSK										
1732.50	76.45	273	1.7	H	2.34	0.30	9.40	11.44	30	-18.56
1732.50	84.70	113	1.6	V	11.17	0.30	9.40	20.27	30	-9.73
LTE Band 4 Channel 20385 – 3MHz – QPSK										
1754.30	77.64	131	1.0	H	3.53	0.30	9.40	12.63	30	-17.37
1754.30	84.20	74	2.4	V	10.67	0.30	9.40	19.77	30	-10.23
LTE Band 4 Channel 19965 – 3MHz – 16QAM										
1710.70	78.41	165	1.1	H	4.30	0.30	9.40	13.40	30	-16.60
1710.70	84.43	255	2.1	V	10.90	0.30	9.40	20.00	30	-10.00
LTE Band 4 Channel 20175 – 3MHz – 16QAM										
1732.50	79.62	48	1.3	H	5.51	0.30	9.40	14.61	30	-15.39
1732.50	84.16	172	1.0	V	10.63	0.30	9.40	19.73	30	-10.27
LTE Band 4 Channel 20385 – 3MHz – 16QAM										
1754.30	79.90	1	1.5	H	5.79	0.30	9.40	14.89	30	-15.11
1754.30	84.07	285	1.4	V	10.54	0.30	9.40	19.64	30	-10.36
LTE Band 4 Channel 19975 – 5MHz – QPSK										
1710.70	78.16	169	2.4	H	4.05	0.30	9.40	13.15	30	-16.85
1710.70	84.49	241	2.2	V	10.96	0.30	9.40	20.06	30	-9.94
LTE Band 4 Channel 20175 – 5MHz – QPSK										

1732.50	76.36	164	1.2	H	2.25	0.30	9.40	11.35	30	-18.65
1732.50	84.11	220	2.0	V	10.58	0.30	9.40	19.68	30	-10.32
LTE Band 4 Channel 20375 – 5MHz – QPSK										
1754.30	76.61	322	2.1	H	2.50	0.30	9.40	11.60	30	-18.40
1754.30	84.56	325	1.9	V	11.03	0.30	9.40	20.13	30	-9.87
LTE Band 4 Channel 19975 – 5MHz – 16QAM										
1710.70	79.14	221	2.4	H	5.03	0.30	9.40	14.13	30	-15.87
1710.70	84.49	313	2.3	V	10.96	0.30	9.40	20.06	30	-9.94
LTE Band 4 Channel 20175 – 5MHz – 16QAM										
1732.50	76.94	71	1.8	H	2.83	0.30	9.40	11.93	30	-18.07
1732.50	84.27	165	1.0	V	10.74	0.30	9.40	19.84	30	-10.16
LTE Band 4 Channel 20375 – 5MHz – 16QAM										
1754.30	79.96	335	2.1	H	5.85	0.30	9.40	14.95	30	-15.05
1754.30	84.02	264	1.5	V	10.49	0.30	9.40	19.59	30	-10.41
LTE Band 4 Channel 20000 – 10MHz – QPSK										
1710.70	76.95	169	1.4	H	2.84	0.30	9.40	11.94	30	-18.06
1710.70	84.62	340	1.9	V	11.09	0.30	9.40	20.19	30	-9.81
LTE Band 4 Channel 20175 – 10MHz – QPSK										
1732.50	76.76	228	1.4	H	2.65	0.30	9.40	11.75	30	-18.25
1732.50	84.76	100	1.1	V	11.23	0.30	9.40	20.33	30	-9.67
LTE Band 4 Channel 20350 – 10MHz – QPSK										
1754.30	77.27	279	1.6	H	3.16	0.30	9.40	12.26	30	-17.74
1754.30	84.85	85	1.6	V	11.32	0.30	9.40	20.42	30	-9.58
LTE Band 4 Channel 20000 – 10MHz – 16QAM										
1710.70	78.34	259	2.5	H	4.23	0.30	9.40	13.33	30	-16.67
1710.70	84.35	156	2.3	V	10.82	0.30	9.40	19.92	30	-10.08
LTE Band 4 Channel 20175 – 10MHz – 16QAM										
1732.50	78.64	345	2.1	H	4.53	0.30	9.40	13.63	30	-16.37
1732.50	84.03	147	2.3	V	10.50	0.30	9.40	19.60	30	-10.40
LTE Band 4 Channel 20350 – 10MHz – 16QAM										
1754.30	79.97	300	1.6	H	5.86	0.30	9.40	14.96	30	-15.04
1754.30	84.59	275	2.0	V	11.06	0.30	9.40	20.16	30	-9.84
LTE Band 4 Channel 20025 – 15MHz – QPSK										
1710.70	76.68	265	2.4	H	2.57	0.30	9.40	11.67	30	-18.33
1710.70	84.59	29	2.3	V	11.06	0.30	9.40	20.16	30	-9.84
LTE Band 4 Channel 20175 – 15MHz – QPSK										
1732.50	78.84	280	2.0	H	4.73	0.30	9.40	13.83	30	-16.17
1732.50	84.78	126	1.7	V	11.25	0.30	9.40	20.35	30	-9.65
LTE Band 4 Channel 20325 – 15MHz – QPSK										
1754.30	76.94	9	2.3	H	2.83	0.30	9.40	11.93	30	-18.07
1754.30	84.47	333	1.3	V	10.94	0.30	9.40	20.04	30	-9.96
LTE Band 4 Channel 20025 – 15MHz – 16QAM										
1710.70	76.54	98	2.3	H	2.43	0.30	9.40	11.53	30	-18.47
1710.70	84.12	81	1.8	V	10.59	0.30	9.40	19.69	30	-10.31
LTE Band 4 Channel 20175 – 15MHz – 16QAM										
1732.50	79.09	358	1.4	H	4.98	0.30	9.40	14.08	30	-15.92
1732.50	84.44	8	1.6	V	10.91	0.30	9.40	20.01	30	-9.99
LTE Band 4 Channel 20325 – 15MHz – 16QAM										

1754.30	79.69	327	1.3	H	5.58	0.30	9.40	14.68	30	-15.32
1754.30	84.12	181	1.3	V	10.59	0.30	9.40	19.69	30	-10.31
LTE Band 4 Channel 20050 – 20MHz – QPSK										
1710.70	78.94	170	1.3	H	4.83	0.30	9.40	13.93	30	-16.07
1710.70	84.04	234	1.7	V	10.51	0.30	9.40	19.61	30	-10.39
LTE Band 4 Channel 20175 – 20MHz – QPSK										
1732.50	77.65	298	1.1	H	3.54	0.30	9.40	12.64	30	-17.36
1732.50	84.63	332	1.4	V	11.10	0.30	9.40	20.20	30	-9.80
LTE Band 4 Channel 20300 – 20MHz – QPSK										
1754.30	77.88	340	1.2	H	3.77	0.30	9.40	12.87	30	-17.13
1754.30	84.86	210	1.4	V	11.33	0.30	9.40	20.43	30	-9.57
LTE Band 4 Channel 20050 – 20MHz – 16QAM										
1710.70	76.05	88	1.6	H	1.94	0.30	9.40	11.04	30	-18.96
1710.70	84.56	16	2.5	V	11.03	0.30	9.40	20.13	30	-9.87
LTE Band 4 Channel 20175 – 20MHz – 16QAM										
1732.50	79.88	280	1.7	H	5.77	0.30	9.40	14.87	30	-15.13
1732.50	84.26	138	1.3	V	10.73	0.30	9.40	19.83	30	-10.17
LTE Band 4 Channel 20300 – 20MHz – 16QAM										
1754.30	77.34	177	2.2	H	3.23	0.30	9.40	12.33	30	-17.67
1754.30	84.99	135	2.2	V	11.46	0.30	9.40	20.56	30	-9.44

LTE Band 7

Frequency	Receiver Reading	Turn table Angle	RX Antenna		Substituted			Absolute Level	Part 27	
			Height	Polar	SG Level	Cable	Antenna Gain		Limit	Margin
(MHz)	(dBμV)	Degree	(m)	(H/V)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dB)
LTE Band 7 Channel 20775 – 5MHz – QPSK										
2502.50	78.80	267	2.4	H	4.80	0.43	10.60	14.97	30	-15.03
2502.50	81.35	26	1.3	V	11.07	0.43	10.60	21.24	30	-8.76
LTE Band 7 Channel 21100 – 5MHz – QPSK										
2535.00	79.74	186	1.9	H	5.74	0.43	10.60	15.91	30	-14.09
2535.00	81.60	113	1.2	V	11.32	0.43	10.60	21.49	30	-8.51
LTE Band 7 Channel 21425 – 5MHz – QPSK										
2567.50	76.56	285	1.0	H	2.45	0.43	10.60	12.62	30	-17.38
2567.50	81.52	131	1.2	V	11.33	0.43	10.60	21.50	30	-8.50
LTE Band 7 Channel 20775 – 5MHz – 16QAM										
2502.50	79.35	254	1.1	H	5.35	0.43	10.60	15.52	30	-14.48
2502.50	81.50	347	2.5	V	11.22	0.43	10.60	21.39	30	-8.61
LTE Band 7 Channel 21100 – 5MHz – 16QAM										
2535.00	76.47	273	1.6	H	2.47	0.43	10.60	12.64	30	-17.36
2535.00	81.68	29	2.4	V	11.40	0.43	10.60	21.57	30	-8.43
LTE Band 7 Channel 21425 – 5MHz – 16QAM										
2567.50	79.99	152	2.5	H	5.88	0.43	10.60	16.05	30	-13.95
2567.50	81.18	295	1.6	V	10.99	0.43	10.60	21.16	30	-8.84
LTE Band 7 Channel 20800 – 10MHz – QPSK										
2502.50	77.42	82	2.3	H	3.42	0.43	10.60	13.59	30	-16.41
2502.50	81.65	229	1.1	V	11.37	0.43	10.60	21.54	30	-8.46
LTE Band 7 Channel 21100 – 10MHz – QPSK										
2535.00	78.87	208	1.4	H	4.87	0.43	10.60	15.04	30	-14.96
2535.00	81.18	122	1.3	V	10.90	0.43	10.60	21.07	30	-8.93
LTE Band 7 Channel 21400 – 10MHz – QPSK										
2567.50	79.42	112	2.1	H	5.31	0.43	10.60	15.48	30	-14.52
2567.50	81.42	222	2.5	V	11.23	0.43	10.60	21.40	30	-8.60
LTE Band 7 Channel 20800 – 10MHz – 16QAM										
2502.50	76.44	326	2.2	H	2.44	0.43	10.60	12.61	30	-17.39
2502.50	81.57	303	1.3	V	11.29	0.43	10.60	21.46	30	-8.54
LTE Band 7 Channel 21100 – 10MHz – 16QAM										
2535.00	78.20	205	2.0	H	4.20	0.43	10.60	14.37	30	-15.63
2535.00	81.02	299	2.2	V	10.74	0.43	10.60	20.91	30	-9.09
LTE Band 7 Channel 21400 – 10MHz – 16QAM										
2567.50	77.91	84	1.1	H	3.80	0.43	10.60	13.97	30	-16.03
2567.50	81.24	153	2.2	V	11.05	0.43	10.60	21.22	30	-8.78
LTE Band 7 Channel 20825 – 15MHz – QPSK										
2502.50	78.69	124	2.0	H	4.69	0.43	10.60	14.86	30	-15.14
2502.50	81.47	201	1.7	V	11.19	0.43	10.60	21.36	30	-8.64
LTE Band 7 Channel 21100 – 15MHz – QPSK										
2535.00	78.22	34	2.1	H	4.22	0.43	10.60	14.39	30	-15.61
2535.00	81.09	186	2.5	V	10.81	0.43	10.60	20.98	30	-9.02

LTE Band 7 Channel 21375 – 15MHz – QPSK										
2567.50	78.81	28	2.2	H	4.70	0.43	10.60	14.87	30	-15.13
2567.50	81.03	158	1.1	V	10.84	0.43	10.60	21.01	30	-8.99
LTE Band 7 Channel 20825 – 15MHz – 16QAM										
2502.50	79.12	41	1.7	H	5.12	0.43	10.60	15.29	30	-14.71
2502.50	81.28	284	2.2	V	11.00	0.43	10.60	21.17	30	-8.83
LTE Band 7 Channel 21100 – 15MHz – 16QAM										
2535.00	76.49	253	2.4	H	2.49	0.43	10.60	12.66	30	-17.34
2535.00	81.92	95	1.3	V	11.64	0.43	10.60	21.81	30	-8.19
LTE Band 7 Channel 21375 – 15MHz – 16QAM										
2567.50	77.73	291	1.5	H	3.62	0.43	10.60	13.79	30	-16.21
2567.50	81.76	132	2.3	V	11.57	0.43	10.60	21.74	30	-8.26
LTE Band 7 Channel 20850 – 20MHz – QPSK										
2502.50	78.86	341	1.7	H	4.86	0.43	10.60	15.03	30	-14.97
2502.50	81.56	76	2.3	V	11.28	0.43	10.60	21.45	30	-8.55
LTE Band 7 Channel 21100 – 20MHz – QPSK										
2535.00	77.84	176	1.5	H	3.84	0.43	10.60	14.01	30	-15.99
2535.00	81.41	47	2.3	V	11.13	0.43	10.60	21.30	30	-8.70
LTE Band 7 Channel 21350 – 20MHz – QPSK										
2567.50	77.88	266	1.1	H	3.77	0.43	10.60	13.94	30	-16.06
2567.50	81.75	82	1.6	V	11.56	0.43	10.60	21.73	30	-8.27
LTE Band 7 Channel 20850 – 20MHz – 16QAM										
2502.50	78.67	85	2.2	H	4.67	0.43	10.60	14.84	30	-15.16
2502.50	81.85	160	2.2	V	11.57	0.43	10.60	21.74	30	-8.26
LTE Band 7 Channel 21100 – 20MHz – 16QAM										
2535.00	78.88	325	1.8	H	4.88	0.43	10.60	15.05	30	-14.95
2535.00	81.44	332	1.4	V	11.16	0.43	10.60	21.33	30	-8.67
LTE Band 7 Channel 21350 – 20MHz – 16QAM										
2567.50	77.45	104	1.3	H	3.34	0.43	10.60	13.51	30	-16.49
2567.50	81.95	247	2.3	V	11.76	0.43	10.60	21.93	30	-8.07

8 Peak-to-Average Ratio

Test Requirement:	27.50(d)
Test Method:	N/A
Test Mode:	Transmitting


8.1 EUT Operation

Operating Environment :

Temperature:	22.5 °C
Humidity:	52.3% RH
Atmospheric Pressure:	101.2kPa

8.2 Test Procedure

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. Set EUT to transmit at maximum output power.
3. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
4. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer. Record the maximum PAPR level associated with a probability of 0.1%.



8.3 Test Result

PASS

LTE Band

Please refer to the Appendix Band 4/7 LTE Peak to Average Ratio.

9 BANDWIDTH

Test Requirement: FCC Part 2.1049, 27.53(a)

Test Method: TIA/EIA-603-D:2010

Test Mode: Transmitting

9.1 EUT Operation

Operating Environment :

Temperature: 22.5 °C


Humidity: 52.3% RH

Atmospheric Pressure: 101.2kPa

9.2 Test Procedure

The RF output of the transmitter was connected to the wireless test set and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 3 kHz (Cellular /PCS) and the 26 dB & 99%bandwidth was recorded.



9.3 Test Result

LTE Band 4 (Part 27):

BW(MHz)	Channel	Frequency (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1.4	19957	1710.7	QPSK	1.15	1.33
			16QAM	1.15	1.33
1.4	20175	1732.5	QPSK	1.15	1.33
			16QAM	1.16	1.33
1.4	20393	1754.3	QPSK	1.16	1.33
			16QAM	1.15	1.34
3	19965	1711.5	QPSK	2.72	2.96
			16QAM	2.72	2.95
3	20175	1732.5	QPSK	2.73	2.96
			16QAM	2.72	2.96
3	20385	1753.5	QPSK	2.73	2.96
			16QAM	2.72	2.97
5	19975	1712.5	QPSK	4.5	4.84
			16QAM	4.5	4.82
5	20175	1732.5	QPSK	4.5	4.85
			16QAM	4.49	4.85
5	20375	1752.5	QPSK	4.49	4.85
			16QAM	4.5	4.85
10	2000	1715	QPSK	8.93	9.41
			16QAM	8.92	9.38
10	20175	1732.5	QPSK	8.91	9.37
			16QAM	8.91	9.33
10	20350	1750	QPSK	8.92	9.36
			16QAM	8.92	9.38
15	20025	1717.5	QPSK	13.39	13.96
			16QAM	13.38	13.94
15	20175	1732.5	QPSK	13.37	13.89
			16QAM	13.36	13.93


15	20325	1747.5	QPSK	13.38	13.96
			16QAM	13.38	13.92
20	20050	1720	QPSK	17.85	18.43
			16QAM	17.84	18.45
20	20175	1732.5	QPSK	17.82	18.43
			16QAM	17.82	18.42
20	20300	1745	QPSK	17.83	18.44
			16QAM	17.84	18.49


LTE Band 7 (Part 27):

BW(MHz)	Channel	Frequency (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
5	20775	2502.5	QPSK	4.51	5.55
			16QAM	4.5	4.96
5	21100	2535	QPSK	4.5	4.83
			16QAM	4.5	4.83
5	21425	2567.5	QPSK	4.49	4.83
			16QAM	4.5	4.85
10	20850	2510	QPSK	8.94	12.19
			16QAM	8.93	9.73
10	21100	2535	QPSK	8.92	9.35
			16QAM	8.92	9.33
10	21400	2565	QPSK	8.93	9.38
			16QAM	8.92	9.38
15	20800	2505	QPSK	13.42	21.89
			16QAM	13.39	18.55
15	21100	2535	QPSK	13.38	13.9
			16QAM	13.37	13.89
15	21375	2562.5	QPSK	13.39	13.93
			16QAM	13.39	13.91
20	20825	2507.5	QPSK	17.84	21.03
			16QAM	17.82	18.72

20	21100	2535	QPSK	17.82	18.41
			16QAM	17.82	18.39
20	21350	2560	QPSK	17.87	18.51
			16QAM	17.87	18.53

Test Plots LTE Band 4 (Part 27)







LTE band 4 - Low CH QPSK-3




LTE band 4 - Low CH 16QAM-3




LTE band 4 - Middle CH QPSK-3




LTE band 4 - Middle CH 16QAM-3



LTE band 4 - High CH QPSK-3




LTE band 4 - High CH 16QAM-3



LTE band 4 - Low CH QPSK-5




LTE band 4 - Low CH 16QAM-5



LTE band 4 - Middle CH QPSK-5




LTE band 4 - Middle CH 16QAM-5




LTE band 4 - High CH QPSK-5




LTE band 4 - High CH 16QAM-5








LTE Band 7 (Part 27)





LTE band 7 - Low CH QPSK-10




LTE band 7 - Low CH 16QAM-10




LTE band 7 - Middle CH QPSK-10



LTE band 7 - Middle CH 16QAM-10




LTE band 7 - High CH QPSK-10




LTE band 7 - High CH 16QAM-10







LTE band 7 - Low CH QPSK-20




LTE band 7 - Low CH 16QAM-20




LTE band 7 - Middle CH QPSK-20



LTE band 7 - Middle CH 16QAM-20



LTE band 7 - High CH QPSK-20



LTE band 7 - High CH 16QAM-20

10 SPURIOUS EMISSIONS AT ANTENNA TERMINALS

Test Requirement:	FCC Part 2.1051, 27.53(h)
Test Method:	TIA/EIA-603-D:2010
Test Mode:	Transmitting


10.1 EUT Operation

Operating Environment :

Temperature:	23.5 °C
Humidity:	52.1 % RH
Atmospheric Pressure:	101.3kPa

10.2 Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonics.



10.3 Test Result

PASS

LTE Band

Please refer to the Appendix Band 4/7 LTE Transmitter Spurious Emissions.

11 SPURIOUS RADIATED EMISSIONS


Test Requirement:	FCC Part 2.1053, 27.53(h), 27.53(m)
Test Method:	TIA/EIA-603-D:2010
Test Mode:	Transmitting

11.1 EUT Operation


Operating Environment :	
Temperature:	23.5 °C
Humidity:	52.1 % RH
Atmospheric Pressure:	101.2kPa

11.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site. The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



11.3 Spectrum Analyzer Setup

30MHz ~ 1GHz

Sweep Speed Auto
Detector PK
Resolution Bandwidth..... 100kHz
Video Bandwidth..... 300kHz

Above 1GHz

Sweep Speed Auto
Detector PK
Resolution Bandwidth..... 1MHz
Video Bandwidth..... 3MHz
Detector Ave.
Resolution Bandwidth..... 1MHz
Video Bandwidth..... 10Hz

11.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from 30MHz up to the tenth harmonic of the highest fundamental frequency.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.
7. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg (\text{TXpwr in Watts}/0.001)$ – the absolute level
Spurious attenuation limit in dB = $43 + 10 \lg (\text{power out in Watts})$
Spurious attenuation limit in dB = $55 + 10 \lg (\text{power out in Watts})$ for the band 7.
8. Repeat above procedures until the measurements for all frequencies are completed.

11.5 Summary of Test Results

Remark: Test performed from 30MHz to 10th harmonics with low/middle/high channels, only the worst data were recorded.

LTE Band 4 (Part 27)

Frequency	Receiver Reading	Turn table Angle	RX Antenna		Substituted			Absolute Level	Result	
			Height	Polar	SG Level	Cable	Antenna Gain		Limit	Margin
(MHz)	(dBμV)	Degree	(m)	(H/V)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dB)
LTE BAND 4 Channel 19957										
199.55	38.52	226	1.5	H	-71.99	0.15	0.00	-72.14	-13.00	-59.14
199.55	30.06	218	1.5	V	-77.53	0.15	0.00	-77.68	-13.00	-64.68
3421.40	65.95	84	1.4	H	-47.10	2.34	12.40	-37.04	-13.00	-24.04
3421.40	59.98	13	2.0	V	-51.17	2.34	12.40	-41.11	-13.00	-28.11
5132.10	53.58	6	1.1	H	-55.83	2.79	12.70	-45.92	-13.00	-32.92
5132.10	44.73	49	1.5	V	-64.04	2.79	12.70	-54.13	-13.00	-41.13
LTE BAND 4 Channel 20175										
199.55	38.89	172	1.9	H	-71.62	0.15	0.00	-71.77	-13.00	-58.77
199.55	29.61	206	1.6	V	-77.98	0.15	0.00	-78.13	-13.00	-65.13
3465.00	58.61	188	1.2	H	-54.44	2.37	12.50	-44.31	-13.00	-31.31
3465.00	51.98	167	2.2	V	-59.17	2.37	12.50	-49.04	-13.00	-36.04
5197.50	45.60	52	1.7	H	-63.81	2.79	12.70	-53.90	-13.00	-40.90
5197.50	37.42	79	1.1	V	-71.35	2.79	12.70	-61.44	-13.00	-48.44
LTE BAND 4 Channel 20393										
199.55	38.69	87	1.3	H	-71.82	0.15	0.00	-71.97	-13.00	-58.97
199.55	30.26	343	2.0	V	-77.33	0.15	0.00	-77.48	-13.00	-64.48
3508.60	51.02	199	1.7	H	-61.62	2.37	12.50	-51.49	-13.00	-38.49
3508.60	44.63	40	1.1	V	-66.10	2.37	12.50	-55.97	-13.00	-42.97
5262.90	38.53	92	2.0	H	-71.05	2.81	12.80	-61.06	-13.00	-48.06
5262.90	29.68	81	1.0	V	-79.12	2.81	12.80	-69.13	-13.00	-56.13

LTE Band 7 (Part 27)

Frequency	Receiver Reading	Turn table Angle	RX Antenna		Substituted			Absolute Level	Result	
			Height	Polar	SG Level	Cable	Antenna Gain		Limit	Margin
(MHz)	(dBμV)	Degree	(m)	(H/V)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dB)
LTE BAND 7 Channel 20775										
199.55	37.17	118	1.1	H	-73.34	0.15	0.00	-73.49	-25.00	-48.49
199.55	29.82	68	1.5	V	-77.77	0.15	0.00	-77.92	-25.00	-52.92
5005.00	65.95	34	1.5	H	-43.29	2.79	12.70	-33.38	-25.00	-8.38
5005.00	59.98	217	2.1	V	-48.79	2.79	12.70	-38.88	-25.00	-13.88
7507.50	53.58	60	1.8	H	-52.96	3.12	11.50	-44.58	-25.00	-19.58
7507.50	44.73	289	1.8	V	-60.70	3.12	11.50	-52.32	-25.00	-27.32
LTE BAND 7 Channel 21100										
199.55	36.33	188	1.2	H	-74.18	0.15	0.00	-74.33	-25.00	-49.33
199.55	30.74	283	1.4	V	-76.85	0.15	0.00	-77.00	-25.00	-52.00
5070.00	59.36	245	1.8	H	-49.88	2.37	12.50	-39.75	-25.00	-14.75
5070.00	52.24	138	1.5	V	-56.53	2.37	12.50	-46.40	-25.00	-21.40
7605.00	47.11	63	1.3	H	-59.43	3.12	11.50	-51.05	-25.00	-26.05
7605.00	37.02	143	1.8	V	-68.41	3.12	11.50	-60.03	-25.00	-35.03
LTE BAND 7 Channel 21425										
199.55	36.60	304	1.1	H	-73.91	0.15	0.00	-74.06	-25.00	-49.06
199.55	31.50	53	1.5	V	-76.09	0.15	0.00	-76.24	-25.00	-51.24
5135.00	52.58	331	1.2	H	-56.83	2.37	12.50	-46.70	-25.00	-21.70
5135.00	45.20	117	2.1	V	-63.57	2.37	12.50	-53.44	-25.00	-28.44
7702.50	40.68	146	1.1	H	-64.55	3.12	11.50	-56.17	-25.00	-31.17
7702.50	29.23	110	2.2	V	-75.66	3.12	11.50	-67.28	-25.00	-42.28

Note: 1) Absolute Level = SG Level - Cable loss + Antenna Gain

2) Margin = Limit- Absolute Level

12 Band Edge Measurement

Test Requirement:	FCC Part 2.1051, 27.53(h), 27.53(m)
Test Method:	TIA/EIA-603-D:2010
Test Mode:	Transmitting

12.1 EUT Operation

Operating Environment :

Temperature:	23.5 °C
Humidity:	52.3 % RH
Atmospheric Pressure:	101.3kPa


12.2 Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

According to FCC Part 27.53(h), *General protection levels*. Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10} (P)$ dB.

According to FCC Part 27.53(m), For BRS and EBS stations, the power of any emissions outside the licensee's frequency bands of operation shall be attenuated below the transmitter power (P) measured in watts in accordance with the standards. For digital base stations, the attenuation shall be not less than $55 + 10 \log (P)$ dB for the band 7.

The center of the spectrum analyzer was set to block edge frequency



12.3 Test Result

PASS

LTE Band

Please refer to the Appendix Band 4/7 LTE Band Edge.

13 FREQUENCY STABILITY

Test Requirement:	FCC Part 2.1055, 27.5(h),27.54
Test Method:	TIA/EIA-603-D:2010
Test Mode:	Transmitting

13.1 EUT Operation

Operating Environment :


Temperature:	22.9 °C
Humidity:	52.0 % RH
Atmospheric Pressure:	101.3kPa

13.2 Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: For hand carried, battery powered equipment; reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.



13.3 Test Result

LTE Band 4 (Part 27)

Test Frequency:1732.5MHz QPSK 1.4MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	-89	-0.0514	2.5
40		-95	-0.0548	2.5
30		-90	-0.0519	2.5
20		-88	-0.0509	2.5
10		-87	-0.0502	2.5
0		-79	-0.0456	2.5
-10		-84	-0.0485	2.5
-20		-86	-0.0496	2.5
-30		-81	-0.0468	2.5
20	3.3	-93	-0.0537	2.5
20	4.2	-83	-0.0479	2.5

Test Frequency:1732.5MHz 16QAM 1.4MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	17	0.0098	2.5
40		15	0.0087	2.5
30		17	0.0098	2.5
20		21	0.0121	2.5
10		17	0.0098	2.5
0		24	0.0139	2.5
-10		15	0.0087	2.5
-20		24	0.0139	2.5
-30		13	0.0075	2.5
20	3.3	15	0.0087	2.5
20	4.2	18	0.0104	2.5

LTE Band 4 (Part 27)

Test Frequency:1732.5MHz QPSK 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	-99	-0.0571	2.5
40		-99	-0.0571	2.5
30		-92	-0.0531	2.5
20		-93	-0.0539	2.5
10		-89	-0.0514	2.5
0		-100	-0.0577	2.5
-10		-101	-0.0583	2.5
-20		-98	-0.0566	2.5
-30		-85	-0.0491	2.5
20	3.3	-102	-0.0589	2.5
20	4.2	-94	-0.0543	2.5

Test Frequency:1732.5MHz 16QAM 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	13	0.0075	2.5
40		18	0.0104	2.5
30		8	0.0046	2.5
20		12	0.0068	2.5
10		19	0.0110	2.5
0		12	0.0069	2.5
-10		4	0.0023	2.5
-20		5	0.0029	2.5
-30		20	0.0115	2.5
20	3.3	7	0.0040	2.5
20	4.2	20	0.0115	2.5

LTE Band 4 (Part 27)

Test Frequency:1732.5MHz QPSK 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	-15	-0.0087	2.5
40		-12	-0.0069	2.5
30		-16	-0.0092	2.5
20		-20	-0.0116	2.5
10		-26	-0.0150	2.5
0		-23	-0.0133	2.5
-10		-23	-0.0133	2.5
-20		-14	-0.0081	2.5
-30		-22	-0.0127	2.5
20	3.3	-22	-0.0127	2.5
20	4.2	-24	-0.0139	2.5

Test Frequency:1732.5MHz 16QAM 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	21	0.0121	2.5
40		16	0.0092	2.5
30		18	0.0104	2.5
20		20	0.0118	2.5
10		14	0.0081	2.5
0		23	0.0133	2.5
-10		29	0.0167	2.5
-20		16	0.0092	2.5
-30		16	0.0092	2.5
20	3.3	23	0.0133	2.5
20	4.2	20	0.0115	2.5

LTE Band 4 (Part 27)

Test Frequency:1732.5MHz QPSK 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	3	0.0017	2.5
40		3	0.0017	2.5
30		15	0.0087	2.5
20		7	0.0042	2.5
10		4	0.0023	2.5
0		8	0.0046	2.5
-10		9	0.0052	2.5
-20		0	0.0000	2.5
-30		15	0.0087	2.5
20	3.3	0	0.0000	2.5
20	4.2	12	0.0069	2.5

Test Frequency:1732.5MHz 16QAM 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	4	0.0023	2.5
40		4	0.0023	2.5
30		1	0.0006	2.5
20		8	0.0049	2.5
10		3	0.0017	2.5
0		10	0.0058	2.5
-10		4	0.0023	2.5
-20		2	0.0012	2.5
-30		12	0.0069	2.5
20	3.3	5	0.0029	2.5
20	4.2	10	0.0058	2.5

LTE Band 4 (Part 27)

Test Frequency:1732.5MHz QPSK 15MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	3	0.0017	2.5
40		5	0.0029	2.5
30		10	0.0058	2.5
20		5	0.0029	2.5
10		-1	-0.0006	2.5
0		10	0.0058	2.5
-10		10	0.0058	2.5
-20		-2	-0.0012	2.5
-30		8	0.0046	2.5
20	3.3	3	0.0017	2.5
20	4.2	2	0.0012	2.5

Test Frequency:1732.5MHz 16QAM 15MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	1	0.0006	2.5
40		15	0.0087	2.5
30		10	0.0058	2.5
20		8	0.0044	2.5
10		9	0.0052	2.5
0		4	0.0023	2.5
-10		3	0.0017	2.5
-20		16	0.0092	2.5
-30		14	0.0081	2.5
20	3.3	6	0.0035	2.5
20	4.2	4	0.0023	2.5

LTE Band 4 (Part 27)

Test Frequency:1732.5MHz QPSK 20MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	5	0.0029	2.5
40		1	0.0006	2.5
30		16	0.0092	2.5
20		9	0.0052	2.5
10		4	0.0023	2.5
0		17	0.0098	2.5
-10		0	0.0000	2.5
-20		18	0.0104	2.5
-30		14	0.0081	2.5
20	3.3	6	0.0035	2.5
20	4.2	5	0.0029	2.5

Test Frequency:1732.5MHz 16QAM 20MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	14	0.0081	2.5
40		7	0.0040	2.5
30		11	0.0063	2.5
20		9	0.0052	2.5
10		4	0.0023	2.5
0		11	0.0063	2.5
-10		14	0.0081	2.5
-20		12	0.0069	2.5
-30		6	0.0035	2.5
20	3.3	2	0.0012	2.5
20	4.2	6	0.0035	2.5

LTE Band 7 (Part 27)

Test Frequency:2535MHz QPSK 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	5	0.0020	2.5
40		-6	-0.0024	2.5
30		7	0.0028	2.5
20		1	0.0005	2.5
10		0	0.0000	2.5
0		-7	-0.0028	2.5
-10		7	0.0028	2.5
-20		0	0.0000	2.5
-30		-1	-0.0004	2.5
20	3.3	6	0.0024	2.5
20	4.2	7	0.0028	2.5

Test Frequency:2535MHz 16QAM 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	23	0.0091	2.5
40		10	0.0039	2.5
30		7	0.0028	2.5
20		15	0.0058	2.5
10		16	0.0063	2.5
0		19	0.0075	2.5
-10		9	0.0036	2.5
-20		15	0.0059	2.5
-30		22	0.0087	2.5
20	3.3	8	0.0032	2.5
20	4.2	12	0.0047	2.5

LTE Band 7 (Part 27)

Test Frequency:2535MHz QPSK 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	-20	-0.0079	2.5
40		-33	-0.0130	2.5
30		-26	-0.0103	2.5
20		-28	-0.0112	2.5
10		-30	-0.0118	2.5
0		-34	-0.0134	2.5
-10		-23	-0.0091	2.5
-20		-20	-0.0079	2.5
-30		-31	-0.0122	2.5
20	3.3	-25	-0.0099	2.5
20	4.2	-22	-0.0087	2.5

Test Frequency:2535MHz 16QAM 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	-22	-0.0087	2.5
40		-11	-0.0043	2.5
30		-8	-0.0032	2.5
20		-13	-0.0052	2.5
10		-21	-0.0083	2.5
0		-15	-0.0059	2.5
-10		-7	-0.0028	2.5
-20		-18	-0.0071	2.5
-30		-18	-0.0071	2.5
20	3.3	-14	-0.0055	2.5
20	4.2	-16	-0.0063	2.5

LTE Band 7 (Part 27)

Test Frequency:2535MHz QPSK 15MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	2	0.0008	2.5
40		11	0.0043	2.5
30		15	0.0059	2.5
20		8	0.0031	2.5
10		4	0.0016	2.5
0		4	0.0016	2.5
-10		7	0.0028	2.5
-20		9	0.0036	2.5
-30		12	0.0047	2.5
20	3.3	13	0.0051	2.5
20	4.2	-1	-0.0004	2.5

Test Frequency:2535MHz 16QAM 15MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	12	0.0047	2.5
40		18	0.0071	2.5
30		13	0.0051	2.5
20		10	0.0040	2.5
10		9	0.0036	2.5
0		7	0.0028	2.5
-10		9	0.0036	2.5
-20		4	0.0016	2.5
-30		9	0.0036	2.5
20	3.3	17	0.0067	2.5
20	4.2	11	0.0043	2.5

LTE Band 7 (Part 27)

Test Frequency:2535MHz QPSK 20MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	-8	-0.0032	2.5
40		-6	-0.0024	2.5
30		-14	-0.0055	2.5
20		-11	-0.0043	2.5
10		-14	-0.0055	2.5
0		-2	-0.0008	2.5
-10		-14	-0.0055	2.5
-20		-12	-0.0047	2.5
-30		-11	-0.0043	2.5
20	3.3	-12	-0.0047	2.5
20	4.2	-11	-0.0043	2.5

Test Frequency:2535MHz 16QAM 20MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	13	0.0051	2.5
40		0	0.0000	2.5
30		5	0.0020	2.5
20		8	0.0032	2.5
10		5	0.0020	2.5
0		3	0.0012	2.5
-10		9	0.0036	2.5
-20		5	0.0020	2.5
-30		3	0.0012	2.5
20	3.3	0	0.0000	2.5
20	4.2	3	0.0012	2.5

14 RF Exposure

Remark: refer to SAR test report: WTS16S0550257E

===== End of Report =====