

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	LinearFlux Headphones
Model Name	HyperSonic
Series Model	HyperSonic, HyperSonic GAME, HyperSonic GAMER, HyperSonic GAME PRO, HyperSonic GAME MAX, HyperSonic PRO, HyperSonic EVO, HyperSonic 360, HyperSonic BOOM, HyperSonic GO, HyperSonic V2, HyperSonic V3, 4897053631079, 4897053631352, 4897053631369, 4897053631376, 4897053631383, 4897053631390, 4897053631406, 4897053631413, 4897053631420
FCC ID	2ATO6-HYPERSONNC

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

$P_t = 1.254\text{dBm} = 1.33\text{mW}$

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation $\text{SAR} = (1.33\text{mW} / 5\text{mm}) \cdot [\sqrt{2.480\text{GHz}}] = 0.42 < 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

4. CONCLUSION

The SAR evaluation is not required.