

FCC RF EXPOSURE REPORT


FCC ID: KA2AP3712A1

Project No. : 2004H006
Equipment : 20km Long Range 802.11ac Wireless Bridge
Brand Name : D-Link Corporation
Test Model : DAP-3712
Series Model : N/A
Applicant : D-Link Corporation
Address : 17595 Mt. Herrmann, Fountain Valley, California United State 92708
Manufacturer : D-Link Corporation
Address : No.289, SinHu 3rd Rd.,Neihi District Taiper City 114, Taiwan, R.O.C
Date of Receipt : May 18, 2020
Date of Test : May 18, 2020 ~ Jul. 01, 2020
Issued Date : Jul. 20, 2020
Report Version : R00
Test Sample : Engineering Sample No.: SH2020051844, SH2020021842-1
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091
FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.



Prepared by : Krain Wu



Approved by : Ryan Wang



Certificate # 5123. 03

Add: No. 29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210, China

TEL: +86-021-61765666

Web: www.newbtl.com

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue	Jul. 20, 2020

1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

For 5GHz:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	PCB	N/A	21
2	N/A	N/A	PCB	N/A	21

Note:

- (1) The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and receivers (2T2R), all transmit signals are completely uncorrelated, then, Direction gain = GANT, that is Directional gain=21.

For UNII-1:

The antenna were fixed point to point,so the power and PSD limit not need to be reduced.

For UNII-3:

The output power limit is 30-21.00+6=15.00, the power spectral density limit is 30-21.00+6=15.00.

2. TEST RESULTS

For 5GHz UNII-1:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
21	125.89250	12	15.8489	0.39690	1	Complies

For 5GHz UNII-3:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
21	125.89250	12	15.8489	0.39690	1	Complies

Note: The calculated distance is 20 cm.
Output power including tune up tolerance.

End of Test Report