



ANT Manufacturers: ANWEI communication Equipment Co.,Ltd

Address: 2nd Floor, East Block, Building 5, Yifenghua Innovation Industrial Park,
Huaning Road, Dalang Street, Longhua District, Shenzhen City, Guangdong Province


Antenna specifications

客户 Customer	Youmi	规格型号 Specs	PG2311GBA
安威料号 Part Number	G6 4G-MAIN-AW G6 4G-DIV-AW G6 4G-2.4GWIFI/GPS/5GWIFI-AW G6 5G-NFC/FM-AW	频 段 Frequency Band	GSMB8/B2/B3/B5 WCDMA:B1/B2/B4/B8/B5/B6 LTE:1/2/3/4/5/7/8/12/13/17/18/19/20/2 5/26/28/66/71/34/38/39/40/41 BT&2.5G WIFI:2400~2483.5MHZ 5G WIFI:5100~5800MHZ
颜色 Color	black	版 本 Edition	REV:A0
销售 Salesperson	Mr.Xie	设 计 Design	WUXI
结 构 Structure	QIN YUN LIN		
日 期 Date	2023.12.5		
客户确认 Customer confirmation:			
携手共进 共创未来 Join hands to create the future			

1. Product specifications

The report mainly provides parameter testing of PG2311GBA antenna performance. The PG2311GBA antenna is a 4G antenna. (As shown below)

MAIN ANT




DIV ANT

1	2	3	4	5	6																																																								
A	<p>丝印白色亮光字码/正面压黑色覆盖膜</p> <p>背面无胶区域</p>					A																																																							
B						B																																																							
C	<p>半对半材料</p> <p>技术要求:</p> <ol style="list-style-type: none"> 1、绿色为外形轮廓,白色填充部位为电气走线覆铜; 2、基材材质为聚酰亚胺或聚酯薄膜; 3、图示为正面,反面背胶,此FPC背胶3M3001SE(9471LE); 4、打*为必测尺寸及重点尺寸,铜箔线路所有尺寸公差不超过±0.05,模具冲出外型尺寸公差不超过±0.1,未注尺寸以图形为准; 5、基材25 μm,铜箔18 μm,镀镍1.5~5.0μm;镀金0.025~0.075 μm;走线面除焊盘外其它区域正面黑色覆盖膜; 6、可靠性测试:盐水喷雾试验48H\槿皮摩擦测试(100个循环)\耐寒性测试(50个循环)\恒温恒湿试验\冷热冲击试验(12个循环)\附着力测试\金手指引脚处挠折性测试; 7、出现下列问题均视为不合格:起泡分层\露铜\折皱、折痕\边缘毛边\字符不清; 8、包装应防潮、防震、表面干净,完好无破损。 					C																																																							
D	<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th colspan="4">第三视角</th> <th rowspan="2">项目名称</th> <th rowspan="2">G6 5G</th> <th colspan="2">日 期</th> </tr> <tr> <th>0°</th> <th>10°</th> <th>30°</th> <th>50°</th> <th>设 计</th> <th colspan="2">2023-11-16</th> </tr> </thead> <tbody> <tr> <td>10°</td> <td>±0.05</td> <td>○ 0.03</td> <td></td> <td>产品名称</td> <td>DIV天线</td> <td>MD</td> <td>QYL</td> </tr> <tr> <td>30°</td> <td>±0.10</td> <td>○ 0.03</td> <td></td> <td>产品料号</td> <td>AW006-G6 4G-023-A0</td> <td>RF</td> <td>WX</td> </tr> <tr> <td>50°</td> <td>±0.15</td> <td>○ 0.02</td> <td></td> <td>材 质</td> <td>FPC</td> <td colspan="2">批 准</td> </tr> <tr> <td>角度</td> <td>±1°</td> <td>○ 0.05</td> <td></td> <td>单 位</td> <td>mm</td> <td>比例</td> <td> FIT</td> </tr> <tr> <td colspan="4">第1页,共1页</td> <td></td> <td></td> <td>版 本</td> <td>A1</td> </tr> </tbody> </table>					第三视角				项目名称	G6 5G	日 期		0°	10°	30°	50°	设 计	2023-11-16		10°	±0.05	○ 0.03		产品名称	DIV天线	MD	QYL	30°	±0.10	○ 0.03		产品料号	AW006-G6 4G-023-A0	RF	WX	50°	±0.15	○ 0.02		材 质	FPC	批 准		角度	±1°	○ 0.05		单 位	mm	比例	FIT	第1页,共1页						版 本	A1	D
第三视角				项目名称	G6 5G	日 期																																																							
0°	10°	30°	50°			设 计	2023-11-16																																																						
10°	±0.05	○ 0.03		产品名称	DIV天线	MD	QYL																																																						
30°	±0.10	○ 0.03		产品料号	AW006-G6 4G-023-A0	RF	WX																																																						
50°	±0.15	○ 0.02		材 质	FPC	批 准																																																							
角度	±1°	○ 0.05		单 位	mm	比例	FIT																																																						
第1页,共1页						版 本	A1																																																						
	1	2	3	4	5	6																																																							

	1	2	3	4	5	6																																						
A	丝印白色亮光字码/正面压黑色覆盖膜																																											
B																																												
C	半对半材料 技术要求: 1. 绿色为外形轮廓,白色填充部位为电气走线覆铜; 2. 基材材质为聚酰亚胺或聚酯薄膜; 3. 图示为正面,反面背胶,此FPC背胶3M300LSE(9471LE); 4. 打*为必测尺寸及重点尺寸,铜箔线路所有尺寸公差不超过±0.05, 模具冲出外型尺寸公差不超过±0.1,未注尺寸以图形为准; 5. 基材25 μm, 铜箔1.5~5.0μm; 镍金0.025~0.075 μm; 走线面除焊盘外其它区域正面黑色覆盖膜; 6. 可靠性测试: 盐水喷雾试验48H\橡皮摩擦测试(100个循环)\耐醇性测试(50个循环)\ 恒温恒湿试验\冷热冲击试验(12个循环)\附着力测试\金手指引脚处拉折性测试; 7. 出现下列问题均视为不合格: 起泡分层\露铜\折皱、折痕\边缘毛边\字符不清; 8. 包装应防湿、防潮、表面干净,完好无破损。																																											
D	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="4" style="text-align: center;">深圳市安威无线科技有限公司</th> </tr> <tr> <th colspan="2" style="text-align: center;">第三视角</th> <th style="text-align: center;">项目名称</th> <th style="text-align: center;">日期</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">Φ</td> <td style="text-align: center;">□</td> <td style="text-align: center;">G6 5G</td> <td style="text-align: center;">2023-11-16</td> </tr> <tr> <td colspan="2" style="text-align: center;">设计</td> <td></td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">产品名称</td> <td style="text-align: center;">2.4GWIFI/GPS/5GWIFI天线</td> <td style="text-align: center;">MD QYL</td> </tr> <tr> <td colspan="2" style="text-align: center;">产品料号</td> <td style="text-align: center;">AW006-G6 4G-022-A0</td> <td style="text-align: center;">RF WX</td> </tr> <tr> <td colspan="2" style="text-align: center;">角度</td> <td style="text-align: center;">0°~90°</td> <td style="text-align: center;">0.02</td> </tr> <tr> <td colspan="2" style="text-align: center;">单位</td> <td style="text-align: center;">mm</td> <td style="text-align: center;">比例 FIT 版本 A1</td> </tr> <tr> <td colspan="6" style="text-align: center;">第1页,共1页</td> </tr> </tbody> </table>						深圳市安威无线科技有限公司				第三视角		项目名称	日期	Φ	□	G6 5G	2023-11-16	设计				产品名称		2.4GWIFI/GPS/5GWIFI天线	MD QYL	产品料号		AW006-G6 4G-022-A0	RF WX	角度		0°~90°	0.02	单位		mm	比例 FIT 版本 A1	第1页,共1页					
深圳市安威无线科技有限公司																																												
第三视角		项目名称	日期																																									
Φ	□	G6 5G	2023-11-16																																									
设计																																												
产品名称		2.4GWIFI/GPS/5GWIFI天线	MD QYL																																									
产品料号		AW006-G6 4G-022-A0	RF WX																																									
角度		0°~90°	0.02																																									
单位		mm	比例 FIT 版本 A1																																									
第1页,共1页																																												
E	1	2	3	4	5	6																																						

NFC+FM ANT



2. Electrical performance

(1.) Specifications and standards

The working frequency band of antenna is 699~960MHZ, 1710~2700MHZ, and resonates in this frequency band

Antenna structure: FPC

3. Parameter testing

(1.) Test settings

The sequential connections of the VSWR test device are:

E5071B Network Analyzer → 50 ohm coaxial cable → 110mm long copper tube → Test Fixture

Handling of test fixtures:

Use a hard cable to lead out the SMA-J connector from the 50 ohm test point of the antenna on the mobile phone PCB, connect it to a copper tube covered with a choke, and then connect it to other devices in turn.

4. Settings for active testing

The active test device connections in sequence are:

Agilent8960 → 50 ohm coaxial cable → Satimo SG16 test system → Mobile phone to be tested

(1.) test site

AW microwave anechoic chamber: The test frequency range is 400MHz-6GHz, the quiet zone range is 40cm circumference, and the reflectivity is less than -90 dB.

(2.) Test Results

The maximum radiated power and maximum receiving sensitivity reflect the maximum power radiation value and best receiving performance of the antenna in the entire radiation space. TRP and TIS reflect the average radiated power and average receiving sensitivity of the antenna, that is, they reflect the overall receiving performance of the antenna.

The following are the mobile phone antenna active test results:

主天线暗室数据

GSM 850	128	24.67		W 1	LOW	18.75			
	190	24.76			medium	18.16			
	251	25.03	-102.3		high	18.55	-102.2		
GSM 900	1	24.79		W 2	LOW	16.68			
	62	24.55			medium	17.14			
	124	25.02	-100.41		high	17.63	-103.0		
DCS 1800	512	24.01		W 4	LOW	17.5			
	698	24.12			medium	17.29			
	885	24.1	-102		high	18.12	-103.3		
PCS 1900	512	24.63		W 5	LOW	15.01			
	661	25.19			medium	15.18			
	810	25.12	-100		high	15.15	-101		
				W 6	LOW	15.36			
					medium	15.58			
					high	15.62	-102.2		
				W 8	LOW	15.08			
					medium	15.44			
					high	15.95	-101.2		



	Channel	TRP (dBm)	TIS (dBm)						Channel	TRP (dBm)	TIS (dBm)
FDD B1	LOW	18.72		FDD B17	LOW	15.5		FDD B13	LOW		
	medium	18.11			medium	15.12			medium	15.04	-88.0
	high	18.41	-89.2		high	15.38	-88.2		high		
FDD B2	LOW	18.65		FDD B18	LOW	15.24		FDD B66	LOW	17.13	
	medium	18.98			medium	15.09			medium	17.11	
	high	18.19	-90.4		high	15.35	-90.24		high	17.21	-90.3
FDD B3	LOW	18.04		FDD B19	LOW	15.25		FDD B71	LOW	14.42	
	medium	17.84			medium	15.12			medium	14.67	
	high	17.7	-90.4		high	15.14	-90		high	14.1	-90.12
FDD B4	LOW	18.42		FDD B20	LOW	15.49		TDD B34	LOW	17.8	
	medium	17.55			medium	15.44			medium	18.61	
	high	18.41	-90.2		high	15.01	-90		high	17.7	-89.2
FDD B5	LOW	16.12		FDD B25	LOW	17.95		TDD B38	LOW	17.53	
	medium	16.06			medium	17.21			medium	17.85	
	high	16.62	-89.6		high	17.72	-89		high	16.06	-88
FDD B7	LOW	18.29		FDD B26	LOW	15.03		TDD B39	LOW	17.11	
	medium	18.37			medium	15.3			medium	17.54	
	high	18.71	-90.4		high	15.27	-89		high	17.58	-88
FDD B8	LOW	16.17		FDD B28A	LOW	15.6		TDD B40	LOW	18.5	
	medium	16.32			medium	15.47			medium	18.54	
	high	16.39	-88.3		high	15.76	-89		high	18.29	-89.2
FDD B12	LOW	15.14		FDD B28B	LOW	15.04		TDD B41	LOW		
	medium	15.72			medium	15.12			medium	17.05	-87.1
	high	15.12	-88.1		high	15.27	-89		high		



Main antenna:



工作频段(Working frequency band): 699~960MHZ, 1710~2700MHZ



2G	2/3/5/8
3G	1/2/4/5/6/8 CDMA:BC0/BC10/BC1
4G	B1/2/3/4/5/7/8/12/13/17/18/19/20/25/26/28/66/71/34/38/39/40/41
BT/WIFI	2.4G+5G
GPS	1575.42MHz


频段 Band	Gain 增益 (dBi)
LTE:B12/17/28 NR:N28	-4.55
LTE:B13	-3.69
LTE:B71	-5.03
CDMA:BC0/BC10 GSM850,WCDMA-B5/6,LTE-B5/18/19/20/26	-4.02
GSM900,WCDMA-B8,LTE-B8	-3.85
DCS1800,WCDMA-B4 ,LTE-B3/4/66	1.2
PCS1900,WCDMA-B2,LTE-B39/25/2	1.15
CDMA:BC1 WCDMA-B1,LTE-B1/B34	0.68
LTE-B7/B38/B41	0.47
LTE-B40	1.46
GPS	1.5
2.4G WIFI/BT	1.1
5G WIFI	0.55
NFC	0.98
FM	1.02











**GPS/WIFI/BT:**

工作频段(**Working frequency band**): 1560~1580MHZ, 2400~2500MHZ, 5180~8525MHZ





Join Hands To Create The Future