

## RF EXPOSURE EVALUATION

#### 1. PRODUCT INFORMATION

<u>   1100001   111 011   111</u>	
Product Description	Smart Body Fat Scale
Model Name	FG2109LB
Series Model	FI2109LB, FG2109LB-A, FI2109LB-A, FG2209LB, FI2209LB
FCC ID	2AP3Q-FG2109LB

## 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR.

Where f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

### 3. CALCULATION

**BR&EDR**:

P<sub>t</sub>=-0.096dBm=0.98mW

The value of the Maximum output power P<sub>t</sub> is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation SAR= $(0.98\text{mW} / 5\text{mm}).[\sqrt{2.402\text{GHz}}]=0.304<3.0$  for 1-g SAR and  $\leq$  7.5 for 10-g extremity SAR.

# 4. CONCLUSION

The SAR evaluation is not required.