

## RF Exposure Requirements

---

Product Description: Bluetooth headset

Model No.: WMSOUNDPOD,LS-i2,LS-i3,LS-i4,LS-i5,LS-i6,LS-i7,LS-i8,LS-i9,LS -i10

FCC ID: 2AG5CLSSOUND

According to the KDB 447498 D01 v06 section 4.3.1, for 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$\left[ \frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

-  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

- Power and distance are rounded to the nearest mW and mm before calculation

- The result is rounded to one decimal place for comparison

### Calculation Result:

Tx frequency range: 2402 MHz

Min. test separation distance: 5 mm

Maximum Conducted Output Power: 1.17 dBm (1.309 mW)

Tune-Up output power: 4 dBm (2.5 mW)

RF channel transmit frequency: 2402 MHz

Result: 0.77

Limit: 3.0

Tx frequency range: 2442 MHz

Min. test separation distance: 5 mm

Maximum Conducted Output Power: 1.53 dBm (1.422 mW)

Tune-Up output power: 4 dBm (2.5 mW)

RF channel transmit frequency: 2442 MHz

Result: 0.78

Limit: 3.0

Tx frequency range: 2480 MHz

Min. test separation distance: 5 mm

Maximum Conducted Output Power: -1.09 dBm (0.778 mW)

Tune-Up output power: 4 dBm (2.5 mW)

RF channel transmit frequency: 2480 MHz

Result: 0.79

Limit: 3.0

The exclusion threshold is  $0.31 < 3$ , so the transmitter complies with the RF exposure requirements and the SAR is not required.