

SAR Test exclusion documentation according to FCC KDB 447498

Report identification number: 1-5821/23-01-12-A Exclusion (FCC)

contains the module with the following certification numbers	
FCC ID	2AXDT-RFM015

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:



Alexander Hnatovskiy
Lab Manager
Radio Communications & EMC



Michael Dorongovski
Lab Manager
Radio Communications & EMC

EUT technologies:

Technologies:	Max. measured cond. AVG Power	Antenna gain	Rated power for RF exposure
Proprietary 10.6 MHz	-5.2 dBm (0.30 mW)	< 0 dBi	-5.2 dBm (0.30 mW)
BT LE 2450 MHz ²⁾	2.8 dBm (1.91 mW)	< 0 dBi	3.0 dBm (2.0 mW)

Note: Measured max taken from cetecom advanced GmbH 1-5821/23-01-26 and customer declarations

Collocation overview:

Active scenario: Technology	1	2	3	4
Proprietary 10.6 MHz	x		x	
BT LE 2450 MHz	x	x		

SAR test exclusion according to KDB447498 (General RF Exposure Guidance v06)

Equation from Chapter 4.3.1: Standalone SAR test exclusion considerations page 11 and ff and tables in Annex C.

(c) (2) Standalone SAR test exclusion below 100 MHz < 50mm

$$0.5 \times (\text{Threshold}_{100\text{MHz}}) \times (1 + \log(100/f))$$

where

Threshold_{1-g;10-g} is 3 for 1-g; 7.5 for 10-g

f is the RF channel transmit frequency

Threshold_{100MHz,50mm} is Threshold_{1-g;10-g} × d / f^{0.5}; with f = 100MHz and d=50mm

The table below gives the calculated maximal power that could be used for source based time averaged conducted power, adjusted for tune up tolerance. If this is below the calculated value SAR testing is excluded.

frequency [MHz]	Threshold _{1-g;10-g}	Threshold _{100MHz,50mm}	Powerlimit [mW]	P _{max-declared}		Exclusion
				[dBm]	[mW]	
10.60	3	474.34	468.34	-5.20	0.30	yes

Equation from Chapter 4.3.1: Standalone SAR test exclusion considerations page 11 and ff.

(1) Standalone SAR test exclusion for 100 MHz to 6 GHz at test separation distances $\leq 50\text{mm}$

$$(\text{Threshold}_{1\text{-g};10\text{-g}}) \times d_{\text{separation}} / f^{0.5}$$

where

Threshold_{1-g;10-g} is 3 for 1-g; 7.5 for 10-g

$d_{\text{separation}}$ is the min. test separation distance; 5mm is used if the distance is less

f is the RF channel transmit frequency

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

frequency [MHz]	$d_{\text{separation}}$ [mm]	Threshold _{1-g}	Powerlimit [mW]	P _{max-declared}		Exclusion
				[dBm]	[mW]	
2450.00	5	3	9.58	3.00	2.00	yes

Collocation:

Overview:

Technology , [MHz]	NFC, 10.6 MHz	BT, 2450
Exemption based on	SAR , 5mm distance	
Limit ERP [mW]:	468.34	9.58
Result ERP [mW]:	0.30	2
Limit-Exhaustion [%]	0.1	20.9
Collocated percentage [%]	20.9	
Verdict:	PASS	