

FCC SAR EVALUATION REPORT

**In accordance with the requirements of
FCC 47 CFR Part 2(2.1093), ANSI/IEEE C95.1-1992 and
IEEE Std 1528-2013**

Product Name : Mobile Phone

Trademark : ulefone

Model Name : GQ3276

Family Model : Note 10P, Note 10, Note 10T, Note 10E, Note
10S, Note 10X, Note 10 Pro, Note 10 Lite,
Note 10 Plus

Report No. : STR220328001008E

FCC ID : 2AOWK-3276

Prepared for

Shenzhen Gotron Electronic CO.,LTD.
7B01, Building A, Block 1, Anhongji Tianyao Plaza, Longhua
District, Shenzhen City, Guangdong Province China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street,
Bao'an District, Shenzhen 518126 P.R.China.
Tel.: 400-800-6106, 0755-2320 0050, 0755-2320 0090
Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name : Shenzhen Gotron Electronic CO.,LTD.
Address : 7B01, Building A, Block 1, Anhongji Tianyao Plaza, Longhua District,
Shenzhen City, Guangdong Province China
Manufacturer's Name : Shenzhen Gotron Electronic CO.,LTD.
Address : 7B01, Building A, Block 1, Anhongji Tianyao Plaza, Longhua District,
Shenzhen City, Guangdong Province China

Product description

Product name : Mobile Phone
Trademark : ulefone
Model Name : GQ3276
Family Model : Note 10P, Note 10, Note 10T, Note 10E, Note 10S, Note 10X,
Note 10 Pro, Note 10 Lite, Note 10 Plus
FCC 47 CFR Part 2(2.1093)

Standards : ANSI/IEEE C95.1-1992;IEEE Std 1528-2013
Published RF exposure KDB procedures

This device described above has been tested by Shenzhen NTEK. In accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 and KDB 865664 D01. Testing has shown that this device is capable of compliance with localized specific absorption rate (SAR) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992. The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK, this document may be altered or revised by Shenzhen NTEK, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests : Mar. 31, 2022 ~ Apr. 18, 2022

Date of Issue : Apr. 27, 2022

Test Result : **Pass**

Prepared By : Jacob . chen
(Test Engineer) (Jacob Chen)

Approved By : Alex
(Lab Manager) (Alex Li)

※ ※ Revision History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	Apr. 27, 2022	Jacob Chen

TABLE OF CONTENTS

1. General Information	6
1.1. RF exposure limits	6
1.2. Statement of Compliance.....	7
1.3. EUT Description	7
1.4. Test specification(s)	9
1.5. Ambient Condition	9
2. SAR Measurement System	10
2.1. SATIMO SAR Measurement Set-up Diagram	10
2.2. Robot	11
2.3. E-Field Probe	12
2.3.1. E-Field Probe Calibration.....	12
2.4. SAM phantoms	13
2.4.1. Technical Data	14
2.5. Device Holder	15
2.6. Test Equipment List	16
3. SAR Measurement Procedures	18
3.1. Power Reference.....	18
3.2. Area scan & Zoom scan	18
3.3. Description of interpolation/extrapolation scheme	20
3.4. Volumetric Scan	20
3.5. Power Drift	20
4. System Verification Procedure.....	21
4.1. Tissue Verification.....	21
4.1.1. Tissue Dielectric Parameter Check Results	22
4.2. System Verification Procedure	23
4.2.1. System Verification Results	24
5. SAR Measurement variability and uncertainty	25
5.1. SAR measurement variability	25
5.2. SAR measurement uncertainty.....	25
6. RF Exposure Positions	26
6.1. Ear and handset reference point.....	26
6.2. Definition of the cheek position	26
6.3. Definition of the tilt position.....	28
6.4. Body Worn Accessory	28
6.5. Wireless Router Devices.....	29
7. RF Output Power	30
7.1. GSM Conducted Power	30
7.2. WCDMA Conducted Power.....	31
7.3. LTE Conducted Power.....	32

7.4. WLAN & Bluetooth Output Power	44
7.4.1. Output Power Results Of WLAN	44
7.4.2. Output Power Results Of Bluetooth	45
8. Antenna Location.....	46
9. Stand-alone SAR test exclusion	47
10. SAR Results	47
10.1. SAR measurement results	47
10.1.1. SAR measurement Result of GSM850.....	47
10.1.2. SAR measurement Result of GSM1900.....	48
10.1.3. SAR measurement Result of WCDMA Band 2.....	49
10.1.4. SAR measurement Result of WCDMA Band 4.....	50
10.1.5. SAR measurement Result of WCDMA Band 5.....	51
10.1.6. SAR measurement Result of LTE Band 2	52
10.1.7. SAR measurement Result of LTE Band 4	54
10.1.8. SAR measurement Result of LTE Band 5	56
10.1.9. SAR measurement Result of LTE Band 7	57
10.1.10. SAR measurement Result of LTE Band 12	60
10.1.11. SAR measurement Result of LTE Band 17	62
10.1.12. SAR measurement Result of WLAN 2.4G.....	64
10.1.13. SAR measurement Result of WLAN 5.2G.....	64
10.1.14. SAR measurement Result of WLAN 5.8G.....	65
10.2. SAR Summation Scenario	66
11. Appendix A. Photo documentation.....	68
12. Appendix B. System Check Plots	68
13. Appendix C. Plots of High SAR Measurement	85
14. Appendix D. Calibration Certificate.....	142

1. General Information

1.1. RF exposure limits

(A).Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE
HEAD AND TRUNK LIMIT
1.6 W/kg
APPLIED TO THIS EUT

1.2. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for GQ3276 are as follows.

RF Exposure Conditions		Equipment Class -Highest Reported SAR (W/kg)			
		PCE	DTS	NII	DSS
1-g Head		0.447	0.538	0.242	N/A
1-g Body-Worn (Separation distance of 10mm)		1.103	0.194	0.131	N/A
1-g Hotspot (Separation distance of 10mm)		1.103	0.194	0.131	N/A
Max Simultaneous Tx	Head	0.985	0.985	0.689	0.712
	Body-Worn	1.297	1.297	1.234	1.235
	Hotspot	1.297	1.297	1.234	1.235

Note: The Max Simultaneous Tx is calculated based on the same configuration and test position. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 & KDB 865664 D01.

1.3. EUT Description

Device Information	
Product Name	Mobile Phone
Trade Name	ulefone
Model Name	GQ3276
Family Model	Note 10P,Note 10,Note 10T,Note 10E,Note 10S,Note 10X,Note 10 Pro, Note 10 Lite, Note 10 Plus
FCC ID	2AOWK-3276
Device Phase	Identical Prototype
Exposure Category	General population / Uncontrolled environment
Antenna	PIFA Antenna
Battery Information	DC 3.85V, 5500mAh, 21.17Wh
Hard Ware Version	S658_V1.0
Soft Ware Version	Note 10P_SH2_EEA_V01
Device Operating Configurations	
Supporting Mode(s)	GSM 850/1900, WCDMA Band 2/4/5, LTE Band 2/4/5/7/12/17, WLAN 2.4G/5G, Bluetooth
Test Modulation	GSM(GMSK/8PSK), WCDMA(QPSK), LTE(QPSK/16QAM), WLAN(DSSS/OFDM), Bluetooth(GFSK, $\pi/4$ -DQPSK, 8DPSK),

Device Class	B		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM 850	824-849	869-894
	GSM 1900	1850-1910	1930-1990
	WCDMA Band 2	1850-1910	1930-1990
	WCDMA Band 4	1710-1755	2110-2155
	WCDMA Band 5	824-849	869-894
	LTE Band 2	1850-1910	1930-1990
	LTE Band 4	1710-1755	2110-2155
	LTE Band 5	824-849	869-894
	LTE Band 7	2500-2570	2620-2690
	LTE Band 12	699-716	729-746
	LTE Band 17	704-716	734-746
	WLAN 2.4G	2412-2462	
	WLAN 5.2G	5180-5240	
	WLAN 5.8G	5745-5825	
	Bluetooth	2402-2480	
GPRS Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
EDGE Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
Power Class	4, tested with power level 5(GSM 850)		
	1, tested with power level 0(GSM 1900)		
	3, tested with power control "all 1"(WCDMA Band 2)		
	3, tested with power control "all 1"(WCDMA Band 4)		
	3, tested with power control "all 1"(WCDMA Band 5)		
	3, tested with power control all Max.(LTE Band 2)		
	3, tested with power control all Max.(LTE Band 4)		
	3, tested with power control all Max.(LTE Band 5)		
	3, tested with power control all Max.(LTE Band 7)		
	3, tested with power control all Max.(LTE Band 12)		
	3, tested with power control all Max.(LTE Band 17)		

1.4. Test specification(s)


FCC 47 CFR Part 2(2.1093)
ANSI/IEEE C95.1-1992
IEEE Std 1528-2013
KDB 865664 D01 SAR measurement 100 MHz to 6 GHz
KDB 865664 D02 RF Exposure Reporting
KDB 447498 D01 General RF Exposure Guidance
KDB 248227 D01 802.11 Wi-Fi SAR
KDB 941225 D01 3G SAR Procedures
KDB 941225 D05 SAR for LTE Devices
KDB 941225 D06 Hotspot SAR
KDB 648474 D04 Handset SAR

1.5. Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

2. SAR Measurement System

2.1. SATIMO SAR Measurement Set-up Diagram



These measurements were performed with the automated near-field scanning system OPENSAR from SATIMO. The system is based on a high precision robot (working range: 901 mm), which positions the probes with a positional repeatability of better than ± 0.03 mm. The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation.

The first step of the field measurement is the evaluation of the voltages induced on the probe by the device under test. Probe diode detectors are nonlinear. Below the diode compression point, the output voltage is proportional to the square of the applied E-field; above the diode compression point, it is linear to the applied E-field. The compression point depends on the diode, and a calibration procedure is necessary for each sensor of the probe.

The Keithley multimeter reads the voltage of each sensor and send these three values to the PC. The corresponding E field value is calculated using the probe calibration factors, which are stored in the working directory. This evaluation includes linearization of the diode characteristics. The field calculation is done separately for each sensor. Each component of the E field is displayed on the "Dipole Area Scan Interface" and the total E field is displayed on the "3D Interface"

2.2. Robot

The SATIMO SAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA) from KUKA is used. The KUKA robot series have many features that are important for our application:



- High precision (repeatability ± 0.03 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

2.3. E-Field Probe

This E-field detection probe is composed of three orthogonal dipoles linked to special Schottky diodes with low detection thresholds. The probe allows the measurement of electric fields in liquids such as the one defined in the IEEE and CENELEC standards.

For the measurements the Specific Dosimetric E-Field Probe SN 08/16 EPGO287 with following specifications is used



- Dynamic range: 0.01-100 W/kg
 - Tip Diameter : 2.5 mm
 - Distance between probe tip and sensor center: 1 mm
 - Distance between sensor center and the inner phantom surface: 2 mm (repeatability better than ± 1 mm).
 - Probe linearity: ± 0.08 dB
 - Axial isotropy: ± 0.01 dB
 - Hemispherical Isotropy: ± 0.01 dB
 - Calibration range: 650MHz to 5900MHz for head & body simulating liquid.
 - Lower detection limit: 8mW/kg
- Angle between probe axis (evaluation axis) and surface normal line: less than 30° .

2.3.1. E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (Norm X, Norm Y, and Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe are tested. The calibration data can be referred to appendix D of this report.

2.4. SAM phantoms


Photo of SAM phantom SN 16/15 SAM119



The SAM phantom is used to measure the SAR relative to people exposed to electro-magnetic field radiated by mobile phones.

2.4.1. Technical Data

Serial Number	Shell thickness	Filling volume	Dimensions	Positionner Material	Permittivity	Loss Tangent
SN 16/15 SAM119	2 mm $\pm$ 0.2 mm	27 liters	Length:1000 mm Width:500 mm Height:200 mm	Gelcoat with fiberglass	3.4	0.02




Serial Number	Left Head(mm)		Right Head(mm)		Flat Part(mm)	
SN 16/15 SAM119	2	2.02	2	2.08	1	2.09
	3	2.05	3	2.06	2	2.06
	4	2.07	4	2.07	3	2.08
	5	2.08	5	2.08	4	2.10
	6	2.05	6	2.07	5	2.10
	7	2.05	7	2.05	6	2.07
	8	2.07	8	2.06	7	2.07
	9	2.08	9	2.06	-	-

The test, based on ultrasonic system, allows measuring the thickness with an accuracy of 10 μ m.

2.5. Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1 degree.



Serial Number	Holder Material	Permittivity	Loss Tangent
SN 16/15 MSH100	Delrin	3.7	0.005

2.6. Test Equipment List

This table gives a complete overview of the SAR measurement equipment.

Devices used during the test described are marked ☒

	Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
					Last Cal.	Due Date
☒	MVG	E FIELD PROBE	SSE2	SN 08/16 EPGO287	Feb. 01, 2022	Jan. 01, 2023
☒	MVG	750 MHz Dipole	SID750	SN 03/15 DIP 0G750-355	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	835 MHz Dipole	SID835	SN 03/15 DIP 0G835-347	Mar. 01, 2021	Feb. 28, 2024
☐	MVG	900 MHz Dipole	SID900	SN 03/15 DIP 0G900-348	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	1800 MHz Dipole	SID1800	SN 03/15 DIP 1G800-349	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	1900 MHz Dipole	SID1900	SN 03/15 DIP 1G900-350	Mar. 01, 2021	Feb. 28, 2024
☐	MVG	2000 MHz Dipole	SID2000	SN 03/15 DIP 2G000-351	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	2450 MHz Dipole	SID2450	SN 03/15 DIP 2G450-352	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	2600 MHz Dipole	SID2600	SN 03/15 DIP 2G600-356	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	5000 MHz Dipole	SWG5500	SN 13/14 WGA 33	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	Liquid measurement Kit	SCLMP	SN 21/15 OCPG 72	NCR	NCR
☒	MVG	Power Amplifier	N.A	AMPLISAR_28/14_003	NCR	NCR
☒	KEITHLEY	Millivoltmeter	2000	4072790	NCR	NCR
☒	R&S	Universal radio communication tester	CMU200	117858	Jul. 01, 2021	Jun. 30, 2022
☒	R&S	Wideband radio communication tester	CMW500	103917	Jul. 01, 2021	Jun. 30, 2022
☒	HP	Network Analyzer	8753D	3410J01136	Jul. 01, 2021	Jun. 30, 2022
☒	Agilent	PSG Analog Signal Generator	E8257D	MY51110112	Jul. 01, 2021	Jun. 30, 2022

☒	Agilent	Power meter	E4419B	MY45102538	Jul. 01, 2021	Jun. 30, 2022
☒	Agilent	Power sensor	E9301A	MY41495644	Jul. 01, 2021	Jun. 30, 2022
☒	Agilent	Power sensor	E9301A	US39212148	Jul. 01, 2021	Jun. 30, 2022
☒	MCLI/USA	Directional Coupler	CB11-20	0D2L51502	Jul. 17, 2020	Jul. 16, 2023

3. SAR Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/Bluetooth power measurement, use engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power in each supported wireless interface and frequency band.
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/Bluetooth output power.

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix A demonstrates.
- (c) Set scan area, grid size and other setting on the OPENSAR software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band.
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

3.1. Power Reference

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

3.2. Area scan & Zoom scan

The area scan is a 2D scan to find the hot spot location on the DUT. The zoom scan is a 3D scan above the hot spot to calculate the 1g and 10g SAR value.

Measurement of the SAR distribution with a grid of 8 to 16 mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8 * 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that will not be within the zoom scan of other peaks; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR compliance limit (e.g., 1 W/kg for 1,6 W/kg 1 g limit, or 1,26 W/kg for 2 W/kg, 10 g limit).

Area scan & Zoom scan scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the *reported* SAR from the *area scan based 1-g SAR estimation* procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

3.3. Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is used to determine this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

3.4. Volumetric Scan

The volumetric scan consists to a full 3D scan over a specific area. This 3D scan is useful for multi Tx SAR measurement. Indeed, it is possible with OpenSAR to add, point by point, several volumetric scan to calculate the SAR value of the combined measurement as it is defined in the standard IEEE1528 and IEC62209.

3.5. Power Drift

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In OpenSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in V/m. If the power drifts more than $\pm 5\%$, the SAR will be retested.

4. System Verification Procedure

4.1. Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% of weight)	Head Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	34.40	34.40	34.40	55.36	55.36	57.87	57.87	57.87	65.53	65.53
NaCl	0.79	0.79	0.79	0.35	0.35	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	64.81	64.81	64.81	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	30.45	30.45	19.97	19.97	19.97	24.24	24.24
DGBE	0.00	0.00	0.00	13.84	13.84	22.00	22.00	22.00	10.23	10.23

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid depth from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm.

Photo of Liquid depth for Head Position	Photo of Liquid depth for Body Position
	

4.1.1. Tissue Dielectric Parameter Check Results

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.


Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Liquid Temp.	Test Date
		$\epsilon_r (\pm 5\%)$	σ (S/m) ($\pm 5\%$)	ϵ_r	σ (S/m)		
Head 750	750	41.96 (39.86~44.06)	0.89 (0.85~0.93)	40.96	0.90	21.5 °C	Apr. 14, 2022
Head 850	835	41.50 (39.43~43.58)	0.90 (0.86~0.95)	42.16	0.92	21.7 °C	Apr. 18, 2022
Head 1800	1800	40.00 (38.00~42.00)	1.40 (1.33~1.47)	38.68	1.38	21.5 °C	Apr. 13, 2022
Head 1900	1900	40.00 (38.00~42.00)	1.40 (1.33~1.47)	38.17	1.46	21.3 °C	Apr. 15, 2022
Head 2450	2450	39.20 (37.24~41.16)	1.80 (1.71~1.89)	38.61	1.81	21.1 °C	Mar. 31, 2022
Head 2600	2600	39.01 (37.06~40.96)	1.96 (1.86~2.06)	38.35	2.00	21.3 °C	Apr. 12, 2022
Head 5200	5200	36.00 (34.20~37.80)	4.66 (4.43~4.89)	36.42	4.76	21.3 °C	Apr. 11, 2022
Head 5800	5800	35.30 (33.54~37.07)	5.27 (5.01~5.53)	35.33	5.38	21.9 °C	Apr. 08, 2022

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

4.2. System Verification Procedure

The system verification is performed for verifying the accuracy of the complete measurement system and performance of the software. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 100mW (below 5GHz) or 100mW (above 5GHz). To adjust this power a power meter is used. The power sensor is connected to the cable before the system verification to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system verification to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

The system verification is shown as below picture:



4.2.1. System Verification Results

Comparing to the original SAR value provided by SATIMO, the verification data should be within its specification of $\pm 10\%$. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance verification can meet the variation criterion and the plots can be referred to Appendix B of this report.

System Verification	Target SAR (1W) ($\pm 10\%$)		Measured SAR (Normalized to 1W)		Liquid Temp.	Test Date
	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)		
750MHz	8.53 (7.68~9.38)	5.56 (5.01~6.11)	8.67	5.33	21.5 °C	Apr. 14, 2022
835MHz	9.84 (8.86~10.82)	6.22 (5.60~6.84)	9.70	6.26	21.7 °C	Apr. 18, 2022
1800MHz	37.96 (34.17~41.75)	19.81 (17.83~21.79)	37.77	21.35	21.5 °C	Apr. 13, 2022
1900MHz	40.37 (36.34~44.40)	20.48 (18.44~22.52)	41.15	21.61	21.3 °C	Apr. 15, 2022
2450MHz	53.69 (48.33~59.05)	23.94 (21.55~26.33)	51.15	23.36	21.1 °C	Mar. 31, 2022
2600MHz	55.83 (50.25~61.41)	24.19 (21.78~26.60)	60.40	23.36	21.3 °C	Apr. 12, 2022
5200MHz	162.34 (146.11~178.57)	55.42 (49.88~60.96)	162.36	50.79	21.3 °C	Apr. 11, 2022
5800MHz	178.89 (161.01~196.77)	59.32 (53.39~65.25)	184.68	56.92	21.9 °C	Apr. 08, 2022

5. SAR Measurement variability and uncertainty

5.1. SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

5.2. SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

6. RF Exposure Positions

6.1. Ear and handset reference point

Figure 6.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M”, the left ear reference point (ERP) is marked “LE”, and the right ERP is marked “RE”.



Fig 6.1.1 Front, back, and side views of SAM phantom

6.2. Definition of the cheek position

1. Define two imaginary lines on the handset, the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 6.2.1 and Figure 6.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 6.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 6.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
2. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
3. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP
4. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
5. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.

6. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 6.2.3. The actual rotation angles should be documented in the test report.




Fig 6.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 6.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 6.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

6.3. Definition of the tilt position

1. While maintaining the orientation of the handset, retract the handset parallel to the reference plane far enough away from the phantom to enable a rotation of the device by 15 degree.
2. Rotate the Handset around the horizontal line by 15 degree (see Figure 6.3.1).
3. While maintaining the orientation of the handset, move the handset towards the phantom on a line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, e.g., the antenna with the back of the phantom head, the angle of the handset shall be reduced. In this case, the tilt position is obtained if any part of the handset is in contact with the pinna as well as a second part of the handset is in contact with the phantom, e.g., the antenna with the back of the head.




Figure 6.3.1 – Tilt position of the wireless device on the left side of SAM

6.4. Body Worn Accessory

1. Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6.4.1). Per KDB 648474 D04, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $< 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a handset attached to the handset.
2. Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest

spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Figure 6.4.1 – Test positions for body-worn devices

6.5. Wireless Router Devices

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WLAN simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WLAN transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WLAN transmitter according to FCC KDB Publication 447498 D01 publication procedures. The “Portable Hotspot” feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

7. RF Output Power

7.1. GSM Conducted Power

Band GSM850	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	128	189	251	Tune-up	128	189	251
Frequency (MHz)	(dBm)	824.2	836.4	848.8	(dBm)	824.2	836.4	848.8
GSM (GMSK)	33.00	32.62	32.43	32.52	23.97	23.59	23.40	23.49
GPRS(GMSK,1 Tx slot)	33.00	32.63	32.42	32.53	23.97	23.60	23.39	23.50
GPRS(GMSK,2 Tx slot)	31.00	30.51	30.30	30.42	24.98	24.49	24.28	24.40
GPRS(GMSK,3 Tx slot)	29.00	28.50	28.30	28.37	24.74	24.24	24.04	24.11
GPRS(GMSK,4 Tx slot)	26.50	26.28	26.12	26.15	23.49	23.27	23.11	23.14
EGPRS(8PSK,1 Tx slot)	25.50	25.28	24.64	24.40	16.47	16.25	15.61	15.37
EGPRS(8PSK,2 Tx slot)	24.50	24.16	24.46	24.08	18.48	18.14	18.44	18.06
EGPRS(8PSK,3 Tx slot)	22.00	21.79	21.95	21.35	17.74	17.53	17.69	17.09
EGPRS(8PSK,4 Tx slot)	19.50	18.98	19.08	18.32	16.49	15.97	16.07	15.31
Band GSM1900	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	512	661	810	Tune-up	512	661	810
Frequency (MHz)	(dBm)	1850.2	1880.0	1909.8	(dBm)	1850.2	1880.0	1909.8
GSM (GMSK)	29.50	29.12	29.00	28.77	20.47	20.09	19.97	19.74
GPRS(GMSK,1 Tx slot)	29.50	29.10	28.98	28.77	20.47	20.07	19.95	19.74
GPRS(GMSK,2 Tx slot)	27.50	27.05	26.62	26.16	21.48	21.03	20.60	20.14
GPRS(GMSK,3 Tx slot)	25.50	25.49	25.02	24.56	21.24	21.23	20.76	20.30
GPRS(GMSK,4 Tx slot)	23.50	23.38	22.93	22.45	20.49	20.37	19.92	19.44
EGPRS(8PSK,1 Tx slot)	25.50	24.59	25.02	24.83	16.47	15.56	15.99	15.80
EGPRS(8PSK,2 Tx slot)	23.50	23.03	23.03	22.94	17.48	17.01	17.01	16.92
EGPRS(8PSK,3 Tx slot)	21.50	21.00	21.33	20.99	17.24	16.74	17.07	16.73
EGPRS(8PSK,4 Tx slot)	19.00	18.83	18.76	18.78	15.99	15.82	15.75	15.77

Note: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.
The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 TS) - 9.03 dB

Frame-averaged power = Maximum burst averaged power (2 TS) - 6.02 dB

Frame-averaged power = Maximum burst averaged power (3 TS) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 TS) - 3.01 dB

7.2. WCDMA Conducted Power

Band	WCDMA Band 2			
Tx Channel	Tune-up	9262	9400	9538
Frequency (MHz)		1852.4	1880	1907.6
RMC 12.2Kbps	22.50	22.23	22.01	22.02
HSDPA Subtest-1	22.50	22.02	21.39	21.39
HSDPA Subtest-2	22.00	21.71	21.16	21.18
HSDPA Subtest-3	21.50	21.38	20.83	20.93
HSDPA Subtest-4	21.50	21.31	20.70	20.82
HSUPA Subtest-1	22.00	21.95	21.37	21.28
HSUPA Subtest-2	22.00	21.91	21.38	21.39
HSUPA Subtest-3	22.00	21.65	21.03	21.08
HSUPA Subtest-4	22.00	21.90	21.36	21.42
HSUPA Subtest-5	22.00	21.54	21.28	20.97
Band	WCDMA Band 4			
Tx Channel	Tune-up	1312	1413	1513
Frequency (MHz)		1712.4	1732.6	1752.6
RMC12.2K	22.50	22.38	22.28	22.36
HSDPA Sub 1	22.50	22.26	21.86	22.12
HSDPA Sub 2	22.00	21.89	21.57	21.90
HSDPA Sub 3	22.00	21.57	21.35	21.40
HSDPA Sub 4	21.50	21.42	21.25	21.19
HSUPA Sub 1	22.50	22.03	21.91	21.93
HSUPA Sub 2	22.50	22.19	21.94	22.12
HSUPA Sub 3	22.00	21.85	21.48	21.76
HSUPA Sub 4	22.50	22.11	21.90	22.17
HSUPA Sub 5	22.00	21.75	21.68	21.91
Band	WCDMA Band 5			
Tx Channel	Tune-up	4132	4182	4233
Frequency (MHz)		826.4	836.4	846.6
RMC12.2K	22.00	21.80	21.89	21.84
HSDPA Sub 1	24.00	23.87	23.74	23.63
HSDPA Sub 2	23.50	23.44	23.48	23.43
HSDPA Sub 3	23.50	23.02	22.98	22.77
HSDPA Sub 4	23.00	22.86	22.93	22.81
HSUPA Sub 1	24.00	23.58	23.55	23.42
HSUPA Sub 2	24.00	23.74	23.70	23.57
HSUPA Sub 3	23.50	23.23	23.23	22.86

HSUPA Sub 4	24.00	23.74	23.70	23.56
HSUPA Sub 5	23.50	23.40	23.33	23.25

7.3. LTE Conducted Power

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18607/1850.7	18900/1880	19193/1909.3
LTE Band 2	1.4MHz	QPSK	1	0	22.50	22.11	22.20	22.16
			1	2	22.50	22.06	22.10	22.10
			1	5	22.50	22.00	22.08	22.15
			3	0	22.50	22.14	21.99	22.02
			3	1	22.50	22.06	22.01	22.04
			3	2	22.50	22.11	22.04	22.05
			6	0	21.50	21.02	21.00	21.00
		16QAM	1	0	22.50	22.12	21.15	21.34
			1	2	22.50	22.08	21.03	21.29
			1	5	22.50	22.17	21.12	21.21
			3	0	21.50	21.32	21.10	21.42
			3	1	21.50	21.29	21.04	21.44
			3	2	21.50	21.32	21.09	21.44
			6	0	20.50	20.27	20.09	20.19
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18615/1851.5	18900/1880	19185/1908.5
LTE Band 2	3MHz	QPSK	1	0	22.50	21.99	22.20	22.13
			1	7	22.50	22.01	22.12	22.19
			1	14	22.50	22.00	22.14	22.13
			8	0	21.50	21.05	21.04	20.93
			8	4	21.50	21.09	20.99	20.89
			8	7	21.50	21.07	21.03	20.94
			15	0	21.50	21.06	20.99	21.04
		16QAM	1	0	22.50	22.21	21.09	21.32
			1	7	22.50	22.24	21.11	21.31
			1	14	22.50	22.22	21.10	21.35
			8	0	20.50	20.13	20.13	20.04
			8	4	20.50	20.07	20.18	20.00
			8	7	20.50	20.07	20.24	20.04

			15	0	20.50	20.28	20.03	20.04
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18625/1852.5	18900/1880	19175/1907.5
LTE Band 2	5MHz	QPSK	1	0	22.50	21.85	22.07	21.73
			1	12	22.50	21.89	22.08	21.79
			1	24	22.50	21.87	22.08	21.88
			12	0	21.50	21.09	20.96	20.91
			12	6	21.50	21.11	21.01	20.87
			12	11	21.50	21.07	21.01	21.00
			25	0	21.50	21.01	20.99	20.90
		16QAM	1	0	21.50	21.38	21.26	20.96
			1	12	21.50	21.36	21.16	20.94
			1	24	21.50	21.27	21.19	20.95
			12	0	20.50	20.18	19.95	20.04
			12	6	20.50	20.11	19.88	20.00
			12	11	20.50	20.05	20.00	20.03
			25	0	20.50	20.23	20.15	20.00
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18650/1855	18900/1880	19150/1905
LTE Band 2	10MHz	QPSK	1	0	22.50	22.01	21.97	22.20
			1	24	22.50	22.06	22.00	22.19
			1	49	22.50	21.91	22.04	22.29
			25	0	21.50	21.14	21.12	20.89
			25	12	21.50	21.03	20.94	20.91
			25	24	21.50	21.03	21.01	20.99
			50	0	21.50	20.97	21.01	20.99
		16QAM	1	0	22.50	22.28	21.10	20.99
			1	24	22.50	22.26	21.08	21.00
			1	49	22.50	22.23	21.12	21.08
			25	0	20.50	20.09	20.19	20.01
			25	12	20.50	20.13	20.11	20.03
			25	24	20.50	20.09	20.24	20.03
			50	0	20.50	20.12	20.19	20.07
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB	RB		18675/1857.5	18900/1880	19125/1902.5

			Size	Offset				
LTE Band 2	15MHz	QPSK	1	0	22.50	22.08	22.20	21.93
			1	37	22.50	22.02	22.18	21.81
			1	74	22.50	21.96	22.13	21.85
			36	0	21.50	20.96	21.06	20.88
			36	18	21.50	21.06	20.94	20.98
			36	37	21.50	21.02	20.93	20.92
			75	0	21.50	21.08	21.05	20.87
		16QAM	1	0	22.50	22.35	21.13	21.75
			1	37	22.50	22.17	21.08	21.69
			1	74	22.50	22.20	21.10	21.70
			36	0	20.50	20.14	20.36	20.07
			36	18	20.50	20.11	20.26	20.02
			36	37	20.50	20.11	20.29	19.98
			75	0	20.50	20.16	20.18	20.09
Band	Band Width	RB Size 1	RB Offset			Channel/Frequency(MHz)		
			0	22.50		18700/1860	18900/1880	19100/1900
LTE Band 2	20MHz	QPSK				22.20	22.04	22.16
			1	49	22.50	22.12	21.96	22.16
			1	99	22.50	22.08	22.20	22.16
			50	0	21.50	21.08	20.97	21.04
			50	24	21.50	20.97	21.04	21.01
			50	49	21.50	21.05	21.07	20.97
			100	0	21.50	21.02	21.02	21.07
		16QAM	1	0	21.50	20.91	20.71	21.01
			1	49	21.50	20.69	20.77	20.94
			1	99	21.50	20.75	20.84	20.98
			50	0	20.50	20.28	20.12	20.18
			50	24	20.50	20.14	20.12	20.05
			50	49	20.50	20.16	20.14	20.03
			100	0	20.50	20.11	20.12	20.09

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		19957/1710.7	20175/1732.5	20393/1754.3
LTE Band 4	1.4MHz	QPSK	1	0	23.00	22.53	22.09	22.62
			1	2	23.00	22.62	22.13	22.56
			1	5	23.00	22.57	22.17	22.55
			3	0	23.00	22.49	22.16	22.47

			3	1	23.00	22.56	22.18	22.41
			3	2	23.00	22.52	22.15	22.34
			6	0	21.50	21.45	21.12	21.31
		16QAM	1	0	23.00	22.63	21.93	21.97
			1	2	23.00	22.56	21.99	21.91
			1	5	23.00	22.64	21.93	22.01
			3	0	22.00	21.75	21.36	21.83
			3	1	22.00	21.81	21.32	21.74
			3	2	22.00	21.74	21.36	21.68
			6	0	21.00	20.65	20.21	20.54
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		19965/1711.5	20175/1732.5	20385/1753.5
LTE Band 4	3MHz	QPSK	1	0	23.00	22.43	22.16	22.62
			1	7	23.00	22.47	22.11	22.61
			1	14	23.00	22.42	22.16	22.55
			8	0	22.00	21.55	21.15	21.31
			8	4	22.00	21.51	21.20	21.33
			8	7	22.00	21.41	21.16	21.27
			15	0	22.00	21.59	21.16	21.33
		16QAM	1	0	23.00	22.75	21.93	21.87
			1	7	23.00	22.79	22.01	21.98
			1	14	23.00	22.67	21.95	22.00
			8	0	21.00	20.54	20.43	20.48
			8	4	21.00	20.50	20.57	20.45
			8	7	21.00	20.40	20.52	20.40
			15	0	21.00	20.61	20.39	20.48
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		19975/1712.5	20175/1732.5	20375/1752.5
LTE Band 4	5MHz	QPSK	1	0	23.00	22.36	22.20	22.24
			1	12	23.00	22.23	22.24	22.22
			1	24	23.00	22.24	22.23	22.18
			12	0	22.00	21.50	21.20	21.30
			12	6	22.00	21.38	21.09	21.36
			12	11	22.00	21.38	21.08	21.32
			25	0	21.50	21.37	21.09	21.27
		16QAM	1	0	22.00	21.75	20.82	21.54

			1	12	22.00	21.65	20.83	21.52
			1	24	22.00	21.69	20.88	21.52
			12	0	21.00	20.52	20.09	20.45
			12	6	21.00	20.42	20.23	20.48
			12	11	21.00	20.35	20.14	20.47
			25	0	20.50	20.47	20.37	20.44
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20000/1715	20175/1732.5	20350/1750
LTE Band 4	10MHz	QPSK	1	0	23.00	22.52	22.15	22.61
			1	24	23.00	22.29	22.19	22.71
			1	49	23.00	22.28	22.22	22.64
			25	0	21.50	21.31	21.14	21.38
			25	12	21.50	21.32	21.22	21.36
			25	24	21.50	21.30	21.15	21.31
			50	0	21.50	21.47	21.18	21.39
		16QAM	1	0	23.00	22.68	21.32	21.65
			1	24	23.00	22.62	21.28	21.71
			1	49	23.00	22.59	21.30	21.65
			25	0	21.00	20.43	20.29	20.51
			25	12	21.00	20.42	20.37	20.46
			25	24	21.00	20.43	20.39	20.52
			50	0	21.00	20.48	20.36	20.53
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20025/1717.5	20175/1732.5	20325/1747.5
LTE Band 4	15MHz	QPSK	1	0	23.00	22.54	22.27	22.15
			1	37	23.00	22.28	22.16	22.29
			1	74	23.00	22.23	22.26	22.19
			36	0	21.50	21.29	21.10	21.40
			36	18	21.50	21.38	21.19	21.40
			36	37	21.50	21.24	21.12	21.24
			75	0	21.50	21.44	21.15	21.41
		16QAM	1	0	23.00	22.75	21.35	22.05
			1	37	23.00	22.59	21.31	22.18
			1	74	23.00	22.55	21.35	22.13
			36	0	20.50	20.44	20.41	20.42
			36	18	20.50	20.41	20.49	20.44

			36	37	20.50	20.32	20.47	20.45
			75	0	21.00	20.52	20.33	20.58
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20050/1720	20175/1732.5	20300/1745
LTE Band 4	20MHz	QPSK	1	0	23.00	22.68	22.16	22.12
			1	49	23.00	22.40	22.09	22.21
			1	99	23.00	22.42	22.18	22.35
			50	0	21.50	21.30	21.25	21.24
			50	24	21.50	21.25	21.10	21.38
			50	49	21.50	21.17	21.12	21.32
			100	0	21.50	21.27	21.19	21.39
		16QAM	1	0	22.00	21.21	21.54	21.44
			1	49	22.00	21.01	21.33	21.59
			1	99	22.00	21.00	21.51	21.66
			50	0	21.00	20.52	20.41	20.30
			50	24	21.00	20.53	20.36	20.45
			50	49	21.00	20.47	20.30	20.42
			100	0	20.50	20.44	20.26	20.43

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20407/824.7	20525/836.5	20643/848.3
LTE Band 5	1.4MHz	QPSK	1	0	24.00	23.85	23.58	23.61
			1	2	24.00	23.80	23.70	23.68
			1	5	24.00	23.50	23.66	23.70
			3	0	24.00	23.71	23.53	23.36
			3	1	24.00	23.68	23.57	23.46
			3	2	24.00	23.72	23.50	23.47
			6	0	23.00	22.76	22.59	22.48
		16QAM	1	0	24.00	23.59	22.70	22.33
			1	2	24.00	23.63	22.63	22.47
			1	5	24.00	23.61	22.61	22.44
			3	0	23.00	22.89	22.63	22.21
			3	1	23.00	22.86	22.67	22.41
			3	2	23.00	22.89	22.65	22.43
			6	0	22.00	21.76	21.82	21.55
Band	Band	Modulation	RB		Tune-up	Channel/Frequency(MHz)		

	Width		Configuration		(dBm)			
			RB Size	RB Offset		20415/825.5	20525/836.5	20635/847.5
LTE Band 5	3MHz	QPSK	1	0	24.00	23.52	23.58	23.68
			1	7	24.00	23.49	23.69	23.64
			1	14	24.00	23.55	23.73	23.71
			8	0	23.00	22.74	22.71	22.34
			8	4	23.00	22.67	22.65	22.37
			8	7	23.00	22.68	22.61	22.48
			15	0	23.00	22.73	22.64	22.33
		16QAM	1	0	24.00	23.58	22.74	22.43
			1	7	24.00	23.57	22.63	22.40
			1	14	24.00	23.60	22.68	22.63
			8	0	22.00	21.59	21.58	21.51
			8	4	22.00	21.53	21.73	21.49
			8	7	22.00	21.65	21.69	21.58
			15	0	22.00	21.73	21.56	21.50
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20425/826.5	20525/836.5	20625/846.5
LTE Band 5	5MHz	QPSK	1	0	24.00	23.48	23.57	23.35
			1	12	24.00	23.44	23.55	23.39
			1	24	24.00	23.61	23.53	23.38
			12	0	23.00	22.67	22.60	22.37
			12	6	23.00	22.62	22.56	22.26
			12	11	23.00	22.65	22.54	22.25
			25	0	23.00	22.63	22.58	22.30
		16QAM	1	0	23.00	22.72	22.64	22.85
			1	12	23.00	22.75	22.57	22.78
			1	24	23.00	22.71	22.51	22.84
			12	0	21.50	21.49	21.34	21.39
			12	6	21.50	21.43	21.46	21.36
			12	11	21.50	21.43	21.46	21.27
			25	0	22.00	21.57	21.58	21.43
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20450/829	20525/836.5	20600/844
LTE	10MHz	QPSK	1	0	24.00	23.58	23.62	23.62

Band 5			1	24	24.00	23.65	23.49	23.51
			1	49	24.00	23.44	23.44	23.57
			25	0	23.00	22.63	22.67	22.40
			25	12	23.00	22.62	22.56	22.46
			25	24	23.00	22.68	22.48	22.27
			50	0	23.00	22.56	22.56	22.44
		16QAM	1	0	23.50	23.46	23.22	22.66
			1	24	23.50	23.42	23.11	22.64
			1	49	23.50	23.34	22.96	22.55
			25	0	22.00	21.51	21.56	21.40
			25	12	22.00	21.55	21.58	21.44
			25	24	22.00	21.70	21.45	21.43
			50	0	22.00	21.57	21.61	21.45

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20775/2502.5	21100/2535	21425/2567.5
LTE Band 7	5MHz	QPSK	1	0	23.50	22.35	22.49	22.83
			1	12	23.50	22.38	22.51	22.87
			1	24	23.50	22.42	22.54	22.89
			12	0	22.00	21.51	21.63	21.84
			12	6	22.00	21.41	21.70	21.88
			12	11	22.00	21.49	21.61	21.78
			25	0	22.00	21.47	21.58	21.87
		16QAM	1	0	22.00	21.60	21.81	21.91
			1	12	22.00	21.57	21.76	21.76
			1	24	22.00	21.60	21.84	21.95
			12	0	21.00	20.39	20.71	20.76
			12	6	21.00	20.31	20.74	20.80
			12	11	21.00	20.35	20.71	20.73
			25	0	21.50	20.50	20.68	21.04
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20800/2505	21100/2535	21400/2565
LTE Band 7	10MHz	QPSK	1	0	23.50	22.28	22.66	22.95
			1	24	23.50	22.34	22.79	23.05
			1	49	23.50	22.32	22.77	23.19
			25	0	22.00	21.42	21.58	21.79

			25	12	22.00	21.50	21.74	21.81
			25	24	22.00	21.46	21.73	21.83
			50	0	22.00	21.39	21.66	21.81
		16QAM	1	0	23.00	22.52	21.65	21.83
			1	24	23.00	22.52	21.72	21.87
			1	49	23.00	22.64	21.83	21.93
			25	0	21.00	20.40	20.74	20.88
			25	12	21.00	20.39	20.75	20.90
			25	24	21.00	20.47	20.82	20.92
			50	0	21.00	20.47	20.85	20.90
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20825/2507.5	21100/2535	21375/2562.5
LTE Band 7	15MHz	QPSK	1	0	23.50	22.36	22.69	22.67
			1	37	23.50	22.37	22.72	22.80
			1	74	23.50	22.40	22.81	22.87
			36	0	22.00	21.46	21.67	21.74
			36	18	22.00	21.38	21.65	21.76
			36	37	22.00	21.44	21.67	21.77
			75	0	22.00	21.40	21.63	21.76
		16QAM	1	0	23.00	22.63	21.64	22.53
			1	37	23.00	22.70	21.72	22.61
			1	74	23.00	22.72	21.75	22.73
			36	0	21.00	20.53	20.81	20.80
			36	18	21.00	20.60	20.82	20.82
			36	37	21.00	20.66	20.83	20.97
			75	0	21.00	20.62	20.78	20.87
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20850/2510	21100/2535	21350/2560
LTE Band 7	20MHz	QPSK	1	0	23.50	22.35	22.48	22.67
			1	49	23.50	22.33	22.51	22.73
			1	99	23.50	22.51	22.68	22.96
			50	0	22.00	21.38	21.67	21.72
			50	24	22.00	21.56	21.77	21.77
			50	49	22.00	21.52	21.64	21.84
			100	0	22.00	21.41	21.60	21.70
			1	0	22.50	21.72	21.98	21.76
		16QAM	1	0	22.50	21.72	21.98	21.76

			1	49	22.50	21.66	22.00	21.74
			1	99	22.50	21.78	22.08	21.97
			50	0	21.00	20.68	20.75	20.85
			50	24	21.00	20.63	20.77	20.90
			50	49	21.00	20.72	20.75	21.00
			100	0	21.00	20.62	20.71	20.94

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23017/699.7	23095/707.5	23173/715.3
LTE Band 12	1.4MHz	QPSK	1	0	24.50	22.11	24.09	23.43
			1	2	24.50	23.01	24.03	23.54
			1	5	24.50	22.87	24.06	23.47
			3	0	24.00	23.07	23.88	23.46
			3	1	24.00	23.07	23.93	23.49
			3	2	24.00	23.15	23.89	23.40
			6	0	23.50	22.16	23.11	22.18
		16QAM	1	0	23.50	22.73	22.70	23.45
			1	2	23.50	22.75	22.83	23.22
			1	5	23.50	22.67	22.87	23.30
			3	0	23.00	22.16	22.91	22.61
			3	1	23.00	22.18	22.87	22.41
			3	2	23.00	22.18	22.89	22.37
			6	0	22.50	21.06	22.06	21.80

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23025/700.5	23095/707.5	23165/714.5
LTE Band 12	3MHz	QPSK	1	0	24.50	22.10	24.14	23.51
			1	7	24.50	23.10	24.10	23.52
			1	14	24.50	23.66	24.07	23.42
			8	0	23.50	22.10	22.71	22.41
			8	4	23.50	22.08	22.88	22.36
			8	7	23.50	22.54	23.05	22.17
			15	0	23.00	22.14	22.97	22.38
		16QAM	1	0	24.00	22.90	23.60	22.39
			1	7	24.00	22.97	23.84	22.38
			1	14	24.00	23.24	23.86	22.25
			8	0	22.00	21.06	21.77	21.78

			8	4	22.00	20.89	21.87	21.81
			8	7	22.00	21.53	21.88	21.78
			15	0	22.50	21.19	22.05	21.75
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23035/701.5	23095/707.5	23155/713.5
LTE Band 12	5MHz	QPSK	1	0	24.50	22.93	23.76	23.45
			1	12	24.50	23.47	23.78	23.35
			1	24	24.50	23.60	23.73	23.30
			12	0	23.50	21.99	22.81	22.54
			12	6	23.50	22.39	23.08	22.34
			12	11	23.50	22.32	22.99	22.32
			25	0	23.50	22.35	23.01	22.37
		16QAM	1	0	23.50	22.10	22.89	23.09
			1	12	23.50	22.50	23.08	22.91
			1	24	23.50	22.68	22.83	22.72
			12	0	22.00	20.92	21.70	21.53
			12	6	22.00	21.42	21.80	21.80
			12	11	22.00	21.35	21.87	21.74
			25	0	22.50	21.63	22.09	21.97
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23060/704	23095/707.5	23130/711
LTE Band 12	10MHz	QPSK	1	0	24.50	23.07	23.61	24.04
			1	24	24.50	23.76	23.81	23.96
			1	49	24.50	23.97	23.57	23.69
			25	0	23.50	22.49	22.77	23.01
			25	12	23.50	22.62	23.00	22.63
			25	24	23.50	22.69	22.69	22.39
			50	0	23.50	22.59	23.08	22.68
		16QAM	1	0	24.00	22.94	23.02	23.27
			1	24	24.00	23.47	23.56	23.26
			1	49	24.00	23.87	23.24	22.85
			25	0	22.50	21.63	21.92	22.06
			25	12	22.50	21.64	22.04	21.90
			25	24	22.50	21.87	21.95	21.88
			50	0	22.50	21.68	22.03	21.86

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23755/706.5	23790/710	23825/713.5
LTE Band 17	5MHz	QPSK	1	0	24.50	23.62	23.64	23.54
			1	12	24.50	23.76	23.69	23.50
			1	24	24.50	23.75	23.44	23.49
			12	0	23.00	22.66	22.92	22.47
			12	6	23.00	22.63	22.66	22.39
			12	11	23.00	22.96	22.55	22.31
			25	0	23.00	22.71	22.70	22.34
		16QAM	1	0	23.50	22.31	23.07	22.63
			1	12	23.50	22.47	22.87	22.49
			1	24	23.50	22.61	22.71	22.34
			12	0	22.50	21.74	22.03	21.50
			12	6	22.50	21.77	21.87	21.64
			12	11	22.50	21.85	21.54	21.65
			25	0	22.00	21.92	21.87	21.77
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23780/709	23790/710	23800/711
LTE Band 17	10MHz	QPSK	1	0	24.50	23.77	23.94	24.03
			1	24	24.50	23.87	23.80	23.96
			1	49	24.50	23.58	23.48	23.63
			25	0	23.50	22.64	22.92	22.99
			25	12	23.50	23.08	22.69	22.68
			25	24	23.50	22.61	22.54	22.47
			50	0	23.00	22.98	22.64	22.73
		16QAM	1	0	24.00	23.42	23.43	23.21
			1	24	24.00	23.84	23.42	23.22
			1	49	24.00	23.26	23.21	22.92
			25	0	22.50	21.91	21.98	22.06
			25	12	22.50	22.00	21.94	21.92
			25	24	22.50	21.69	21.67	21.79
			50	0	22.50	22.01	21.99	21.86

7.4. WLAN & Bluetooth Output Power

7.4.1. Output Power Results Of WLAN

Mode	Channel	Frequency (MHz)	Tune-up	Output Power (dBm)
802.11b	1	2412	14.00	13.55
	6	2437	14.00	13.60
	11	2462	14.00	13.77
802.11g	1	2412	12.50	12.13
	6	2437	12.50	11.48
	11	2462	12.50	11.64
802.11n HT20	1	2412	13.00	12.52
	6	2437	13.00	11.73
	11	2462	13.00	11.99
802.11n HT40	3	2422	12.00	11.22
	6	2437	12.00	11.62
	9	2452	12.00	11.11

NOTE: Power measurement results of WLAN 2.4G.

Mode	Channel	Frequency (MHz)	Tune-up	Output Power (dBm)
802.11a	36	5180	10.00	9.33
	40	5200	10.00	9.52
	48	5240	10.00	9.59
802.11n HT20	36	5180	9.50	9.05
	40	5200	9.50	8.89
	48	5240	9.50	8.95
802.11n HT40	38	5190	7.50	7.36
	46	5230	7.50	7.46
802.11ac VHT20	36	5180	8.00	7.90
	40	5200	8.00	7.76
	48	5240	8.00	7.79
802.11ac VHT40	38	5190	8.00	7.58
	46	5230	8.00	7.40
802.11ac VHT80	42	5210	7.50	7.28

NOTE: Power measurement results of WLAN 5.2G.

Mode	Channel	Frequency (MHz)	Tune-up	Output Power (dBm)
------	---------	-----------------	---------	--------------------

802.11a	149	5745	10.50	9.42
	157	5785	10.50	10.02
	165	5825	10.50	9.95
802.11n HT20	149	5745	9.50	8.70
	157	5785	9.50	9.45
	165	5825	9.50	9.03
802.11n HT40	151	5755	10.00	9.50
	159	5795	10.00	8.32
802.11ac VHT20	149	5745	9.50	8.67
	157	5785	9.50	9.49
	165	5825	9.50	9.07
802.11ac VHT40	151	5755	8.50	7.45
	159	5795	8.50	8.27
802.11ac VHT80	155	5775	8.00	7.93

NOTE: Power measurement results of WLAN 5.8G.

7.4.2. Output Power Results Of Bluetooth

BR+EDR	Output Power (dBm)				
	Channel	Tune-up	Data Rates		
			1M	2M	3M
	0CH	8.000	6.088	7.423	7.587
	39CH	7.500	5.705	6.781	7.048
	78CH	8.000	6.349	7.463	7.810

BLE	Channel	Tune-up	Output Power (dBm)	
			1M	2M
	0CH	4.000	3.537	3.837
	19CH	4.000	3.248	3.503
	39CH	5.000	4.129	4.380

8. Antenna Location

Right Side

164mm

134mm

175mm

Front Side

Top Side

50mm

75mm

LTE Div ANT

GSM / WCDMA / LTE Main ANT

Bottom Side

Front View

Left Side

Note: Since the confidentiality request of EUT, the antenna location example diagram see as above.

Distance of the Antenna to the EUT surface/edge						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main ANT	≤ 25mm	≤ 25mm	≤ 25mm	≤ 25mm	> 25mm	≤ 25mm
WLAN & Bluetooth	≤ 25mm	≤ 25mm	> 25mm	≤ 25mm	≤ 25mm	>25mm
Positions for SAR tests						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main ANT	Yes	Yes	Yes	Yes	NO	Yes
WLAN & Bluetooth	Yes	Yes	NO	Yes	Yes	NO

9. Stand-alone SAR test exclusion

Refer to FCC KDB 447498D01, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	P _{max} (dBm)	P _{max} (mW)	Distance (mm)	f (GHz)	Calculation Result	SAR Exclusion threshold	SAR test exclusion
Bluetooth	8.00	6.31	5	2.480	1.99	3.00	Yes

NOTE: Standalone SAR test exclusion for Bluetooth.

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}/x] \text{ W/kg}$ for test separation distances $\leq 50\text{mm}$, where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Position	P _{max} (dBm)	P _{max} (mW)	Distance (mm)	f (GHz)	x	Estimated SAR (W/Kg)
Bluetooth	Head	8.00	6.31	5	2.48	7.5	0.265
Bluetooth	Body	8.00	6.31	10	2.48	7.5	0.132
Bluetooth	Hotspot	8.00	6.31	10	2.48	7.5	0.132

NOTE: Estimated SAR calculation for Bluetooth

10. SAR Results

10.1. SAR measurement results

10.1.1. SAR measurement Result of GSM850

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Left Cheek	189/836.4	GPRS(GMSK 2TS)	0.218	0.163	0.64	30.30	31.00	0.256	2022/4/18
Left Tilt 15	189/836.4	GPRS(GMSK 2TS)	0.115	0.085	3.73	30.30	31.00	0.135	2022/4/18

Degree									
Right Cheek	189/836.4	GPRS(GMSK 2TS)	0.206	0.146	-1.81	30.30	31.00	0.242	2022/4/18
Right Tilt 15 Degree	189/836.4	GPRS(GMSK 2TS)	0.103	0.077	2.17	30.30	31.00	0.121	2022/4/18

NOTE: Head SAR test results of GSM850.

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	189/836.4	GPRS(GMSK 2TS)	0.198	0.144	3.90	30.30	31.00	0.233	2022/4/18
Back Side	189/836.4	GPRS(GMSK 2TS)	0.297	0.222	-0.94	30.30	31.00	0.349	2022/4/18

NOTE: Body-Worn SAR test results of GSM850

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	189/836.4	GPRS(GMSK 2TS)	0.198	0.144	3.90	30.30	31.00	0.233	2022/4/18
Back Side	189/836.4	GPRS(GMSK 2TS)	0.297	0.222	-0.94	30.30	31.00	0.349	2022/4/18
Left Side	189/836.4	GPRS(GMSK 2TS)	0.069	0.050	-1.85	30.30	31.00	0.081	2022/4/18
Right Side	189/836.4	GPRS(GMSK 2TS)	0.138	0.099	-1.21	30.30	31.00	0.162	2022/4/18
Bottom Side	189/836.4	GPRS(GMSK 2TS)	0.187	0.134	3.70	30.30	31.00	0.220	2022/4/18

NOTE: Hotspot SAR test results of GSM850

10.1.2. SAR measurement Result of GSM1900

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Left Cheek	661/1880	GPRS(GMSK 2TS)	0.196	0.115	3.10	26.62	27.50	0.240	2022/4/15
Left Tilt 15 Degree	661/1880	GPRS(GMSK 2TS)	0.114	0.067	1.03	26.62	27.50	0.140	2022/4/15
Right Cheek	661/1880	GPRS(GMSK 2TS)	0.186	0.108	-2.36	26.62	27.50	0.228	2022/4/15
Right Tilt 15 Degree	661/1880	GPRS(GMSK 2TS)	0.097	0.054	-1.35	26.62	27.50	0.119	2022/4/15

NOTE: Head SAR test results of GSM1900

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	661/1880	GPRS(GMSK 2TS)	0.216	0.115	1.75	26.62	27.50	0.265	2022/4/15
Back Side	661/1880	GPRS(GMSK 2TS)	0.318	0.176	-0.80	26.62	27.50	0.389	2022/4/15

NOTE: Body-Worn SAR test results of GSM1900

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	661/1880	GPRS(GMSK 2TS)	0.216	0.115	1.75	26.62	27.50	0.265	2022/4/15
Back Side	661/1880	GPRS(GMSK 2TS)	0.318	0.176	-0.80	26.62	27.50	0.389	2022/4/15
Left Side	661/1880	GPRS(GMSK 2TS)	0.076	0.042	-3.89	26.62	27.50	0.093	2022/4/15
Right Side	661/1880	GPRS(GMSK 2TS)	0.142	0.076	3.44	26.62	27.50	0.174	2022/4/15
Bottom Side	661/1880	GPRS(GMSK 2TS)	0.193	0.107	-0.75	26.62	27.50	0.236	2022/4/15

NOTE: Hotspot SAR test results of GSM1900

10.1.3. SAR measurement Result of WCDMA Band 2

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Left Cheek	9400/1880	RMC12.2K	0.319	0.191	-3.99	22.01	22.50	0.357	2022/4/15
Left Tilt 15 Degree	9400/1880	RMC12.2K	0.164	0.093	-2.40	22.01	22.50	0.184	2022/4/15
Right Cheek	9400/1880	RMC12.2K	0.291	0.167	-1.09	22.01	22.50	0.326	2022/4/15
Right Tilt 15 Degree	9400/1880	RMC12.2K	0.156	0.093	-0.64	22.01	22.50	0.175	2022/4/15

NOTE: Head SAR test results of WCDMA Band 2

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g	Date
			1g	10g					

								(W/Kg)	
Front Side	9400/1880	RMC12.2K	0.372	0.189	-2.98	22.01	22.50	0.416	2022/4/15
Back Side	9400/1880	RMC12.2K	0.601	0.321	-0.85	22.01	22.50	0.673	2022/4/15

NOTE: Body-Worn SAR test results of WCDMA Band 2

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	9400/1880	RMC12.2K	0.372	0.189	-2.98	22.01	22.50	0.416	2022/4/15
Back Side	9400/1880	RMC12.2K	0.601	0.321	-0.85	22.01	22.50	0.673	2022/4/15
Left Side	9400/1880	RMC12.2K	0.145	0.077	-1.60	22.01	22.50	0.162	2022/4/15
Right Side	9400/1880	RMC12.2K	0.262	0.136	3.45	22.01	22.50	0.293	2022/4/15
Bottom Side	9400/1880	RMC12.2K	0.347	0.185	-2.47	22.01	22.50	0.388	2022/4/15

NOTE: Hotspot SAR test results of WCDMA Band 2

10.1.4. SAR measurement Result of WCDMA Band 4

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Left Cheek	1413/1732.6	RMC12.2K	0.249	0.160	-4.01	22.28	22.50	0.262	2022/4/13
Left Tilt 15 Degree	1413/1732.6	RMC12.2K	0.125	0.079	3.35	22.28	22.50	0.131	2022/4/13
Right Cheek	1413/1732.6	RMC12.2K	0.236	0.149	-1.15	22.28	22.50	0.248	2022/4/13
Right Tilt 15 Degree	1413/1732.6	RMC12.2K	0.126	0.077	-2.32	22.28	22.50	0.133	2022/4/13

NOTE: Head SAR test results of WCDMA Band 4

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	1413/1732.6	RMC12.2K	0.408	0.238	-1.08	22.28	22.50	0.429	2022/4/13
Back Side	1413/1732.6	RMC12.2K	0.637	0.383	-0.70	22.28	22.50	0.670	2022/4/13

NOTE: Body-Worn SAR test results of WCDMA Band 4

Test Position	Test channel	Test Mode	SAR Value (W/kg)	Power Drift	Conducted power	Tune-up power	Scaled SAR	Date
---------------	--------------	-----------	------------------	-------------	-----------------	---------------	------------	------

of Hotspot with 10mm	/Freq.		1g	10g	(±5%)	(dBm)	(dBm)	1g (W/Kg)	
Front Side	1413/1732.6	RMC12.2K	0.408	0.238	-1.08	22.28	22.50	0.429	2022/4/13
Back Side	1413/1732.6	RMC12.2K	0.637	0.383	-0.70	22.28	22.50	0.670	2022/4/13
Left Side	1413/1732.6	RMC12.2K	0.152	0.089	-0.87	22.28	22.50	0.160	2022/4/13
Right Side	1413/1732.6	RMC12.2K	0.292	0.170	-3.02	22.28	22.50	0.307	2022/4/13
Bottom Side	1413/1732.6	RMC12.2K	0.374	0.214	-1.99	22.28	22.50	0.393	2022/4/13

NOTE: Hotspot SAR test results of WCDMA Band 4

10.1.5. SAR measurement Result of WCDMA Band 5

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Left Cheek	4182/836.4	HSDPA Sub 1	0.267	0.203	1.25	23.74	24.00	0.283	2022/4/18
Left Tilt 15 Degree	4182/836.4	HSDPA Sub 1	0.157	0.118	3.92	23.74	24.00	0.167	2022/4/18
Right Cheek	4182/836.4	HSDPA Sub 1	0.249	0.187	3.77	23.74	24.00	0.264	2022/4/18
Right Tilt 15 Degree	4182/836.4	HSDPA Sub 1	0.120	0.088	-0.50	23.74	24.00	0.127	2022/4/18

NOTE: Head SAR test results of WCDMA Band 5

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	4182/836.4	HSDPA Sub 1	0.240	0.182	3.05	23.74	24.00	0.255	2022/4/18
Back Side	4182/836.4	HSDPA Sub 1	0.363	0.276	-0.01	23.74	24.00	0.385	2022/4/18

NOTE: Body-Worn SAR test results of WCDMA Band 5

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	4182/836.4	HSDPA	0.240	0.182	3.05	23.74	24.00	0.255	2022/4/18

		Sub 1							
Back Side	4182/836.4	HSDPA Sub 1	0.363	0.276	-0.01	23.74	24.00	0.385	2022/4/18
Left Side	4182/836.4	HSDPA Sub 1	0.092	0.067	-1.76	23.74	24.00	0.098	2022/4/18
Right Side	4182/836.4	HSDPA Sub 1	0.176	0.128	-0.15	23.74	24.00	0.187	2022/4/18
Bottom Side	4182/836.4	HSDPA Sub 1	0.215	0.163	0.54	23.74	24.00	0.228	2022/4/18

NOTE: Hotspot SAR test results of WCDMA Band 5

10.1.6. SAR measurement Result of LTE Band 2

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
1RB									
Left Cheek	18900/1880	20M QPSK(1,99)	0.308	0.185	-1.56	22.20	22.50	0.330	2022/4/15
Left Tilt 15 Degree	18900/1880	20M QPSK(1,99)	0.177	0.101	0.28	22.20	22.50	0.190	2022/4/15
Right Cheek	18900/1880	20M QPSK(1,99)	0.274	0.158	-1.25	22.20	22.50	0.294	2022/4/15
Right Tilt 15 Degree	18900/1880	20M QPSK(1,99)	0.138	0.082	-3.31	22.20	22.50	0.148	2022/4/15
50%RB									
Left Cheek	18900/1880	20M QPSK(50,0)	0.184	0.108	3.15	20.97	21.50	0.208	2022/4/15
Left Tilt 15 Degree	18900/1880	20M QPSK(50,0)	0.093	0.055	-1.14	20.97	21.50	0.105	2022/4/15
Right Cheek	18900/1880	20M QPSK(50,0)	0.141	0.091	2.30	20.97	21.50	0.159	2022/4/15
Right Tilt 15 Degree	18900/1880	20M QPSK(50,0)	0.076	0.045	-0.12	20.97	21.50	0.086	2022/4/15

NOTE: Head SAR test results of LTE Band 2

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
1RB									
Front Side	18900/1880	20M QPSK(1,99)	0.372	0.199	1.26	22.20	22.50	0.399	2022/4/15
Back Side	18900/1880	20M QPSK(1,99)	0.576	0.314	-0.99	22.20	22.50	0.617	2022/4/15
50%RB									
Front Side	18900/1880	20M QPSK(50,0)	0.197	0.117	3.14	20.97	21.50	0.223	2022/4/15
Back Side	18900/1880	20M QPSK(50,0)	0.305	0.170	-3.49	20.97	21.50	0.345	2022/4/15

NOTE: Body-Worn SAR test results of LTE Band 2

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
1RB									
Front Side	18900/1880	20M QPSK(1,99)	0.372	0.199	1.26	22.20	22.50	0.399	2022/4/15
Back Side	18900/1880	20M QPSK(1,99)	0.576	0.314	-0.99	22.20	22.50	0.617	2022/4/15
Left Side	18900/1880	20M QPSK(1,99)	0.133	0.070	-3.97	22.20	22.50	0.143	2022/4/15
Right Side	18900/1880	20M QPSK(1,99)	0.267	0.146	-3.03	22.20	22.50	0.286	2022/4/15
Bottom Side	18900/1880	20M QPSK(1,99)	0.319	0.167	3.80	22.20	22.50	0.342	2022/4/15
50%RB									
Front Side	18900/1880	20M QPSK(50,0)	0.197	0.117	3.14	20.97	21.50	0.223	2022/4/15
Back Side	18900/1880	20M QPSK(50,0)	0.305	0.170	-3.49	20.97	21.50	0.345	2022/4/15
Left Side	18900/1880	20M QPSK(50,0)	0.078	0.037	-3.46	20.97	21.50	0.088	2022/4/15

Right Side	18900/1880	20M QPSK(50,0)	0.149	0.087	-2.29	20.97	21.50	0.168	2022/4/15
Bottom Side	18900/1880	20M QPSK(50,0)	0.176	0.089	-1.50	20.97	21.50	0.199	2022/4/15

NOTE: Hotspot SAR test results of LTE Band 2

10.1.7. SAR measurement Result of LTE Band 4

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
1RB									
Left Cheek	20175/1732.5	20M QPSK(1,0)	0.250	0.159	0.25	22.16	23.00	0.303	2022/4/13
Left Tilt 15 Degree	20175/1732.5	20M QPSK(1,0)	0.146	0.088	-0.78	22.16	23.00	0.177	2022/4/13
Right Cheek	20175/1732.5	20M QPSK(1,0)	0.227	0.140	-1.83	22.16	23.00	0.275	2022/4/13
Right Tilt 15 Degree	20175/1732.5	20M QPSK(1,0)	0.103	0.066	-0.06	22.16	23.00	0.125	2022/4/13
50%RB									
Left Cheek	20175/1732.5	20M QPSK(50,24)	0.136	0.092	4.90	21.10	21.50	0.149	2022/4/13
Left Tilt 15 Degree	20175/1732.5	20M QPSK(50,24)	0.080	0.047	-0.31	21.10	21.50	0.088	2022/4/13
Right Cheek	20175/1732.5	20M QPSK(50,24)	0.133	0.083	-3.96	21.10	21.50	0.146	2022/4/13
Right Tilt 15 Degree	20175/1732.5	20M QPSK(50,24)	0.061	0.038	-0.59	21.10	21.50	0.067	2022/4/13

NOTE: Head SAR test results of LTE Band 4

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					

1RB									
Front Side	20175/1732.5	20M QPSK(1,0)	0.378	0.225	-0.74	22.16	23.00	0.459	2022/4/13
Back Side	20175/1732.5	20M QPSK(1,0)	0.618	0.372	-0.88	22.16	23.00	0.750	2022/4/13
50%RB									
Front Side	20175/1732.5	20M QPSK(50,24)	0.195	0.121	1.62	21.10	21.50	0.214	2022/4/13
Back Side	20175/1732.5	20M QPSK(50,24)	0.325	0.196	3.18	21.10	21.50	0.356	2022/4/13

NOTE: Body-Worn SAR test results of LTE Band 4

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
1RB									
Front Side	20175/1732.5	20M QPSK(1,0)	0.378	0.225	-0.74	22.16	23.00	0.459	2022/4/13
Back Side	20175/1732.5	20M QPSK(1,0)	0.618	0.372	-0.88	22.16	23.00	0.750	2022/4/13
Left Side	20175/1732.5	20M QPSK(1,0)	0.147	0.087	-0.12	22.16	23.00	0.178	2022/4/13
Right Side	20175/1732.5	20M QPSK(1,0)	0.284	0.164	-0.84	22.16	23.00	0.345	2022/4/13
Bottom Side	20175/1732.5	20M QPSK(1,0)	0.352	0.203	-0.93	22.16	23.00	0.427	2022/4/13
50%RB									
Front Side	20175/1732.5	20M QPSK(50,24)	0.195	0.121	1.62	21.10	21.50	0.214	2022/4/13
Back Side	20175/1732.5	20M QPSK(50,24)	0.325	0.196	3.18	21.10	21.50	0.356	2022/4/13
Left Side	20175/1732.5	20M QPSK(50,24)	0.082	0.045	3.05	21.10	21.50	0.090	2022/4/13
Right Side	20175/1732.5	20M QPSK(50,24)	0.160	0.092	-1.77	21.10	21.50	0.175	2022/4/13
Bottom	20175/1732.5	20M	0.198	0.121	-2.83	21.10	21.50	0.217	2022/4/13

Side		QPSK(50,24)							
------	--	-------------	--	--	--	--	--	--	--

NOTE: Hotspot SAR test results of LTE Band 4

10.1.8. SAR measurement Result of LTE Band 5

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
1RB									
Left Cheek	20525/836.5	10M QPSK(1,24)	0.226	0.171	0.98	23.49	24.00	0.254	2022/4/18
Left Tilt 15 Degree	20525/836.5	10M QPSK(1,24)	0.116	0.086	2.97	23.49	24.00	0.130	2022/4/18
Right Cheek	20525/836.5	10M QPSK(1,24)	0.196	0.148	3.88	23.49	24.00	0.220	2022/4/18
Right Tilt 15 Degree	20525/836.5	10M QPSK(1,24)	0.092	0.066	1.01	23.49	24.00	0.103	2022/4/18
50%RB									
Left Cheek	20525/836.5	10M QPSK(25,24)	0.129	0.092	2.97	22.48	23.00	0.145	2022/4/18
Left Tilt 15 Degree	20525/836.5	10M QPSK(25,24)	0.061	0.047	-3.29	22.48	23.00	0.069	2022/4/18
Right Cheek	20525/836.5	10M QPSK(25,24)	0.107	0.074	-2.86	22.48	23.00	0.121	2022/4/18
Right Tilt 15 Degree	20525/836.5	10M QPSK(25,24)	0.047	0.035	-0.22	22.48	23.00	0.053	2022/4/18

NOTE: Head SAR test results of LTE Band 5

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
1RB									
Front Side	20525/836.5	10M QPSK(1,24)	0.192	0.139	2.91	23.49	24.00	0.216	2022/4/18
Back Side	20525/836.5	10M	0.309	0.236	0.14	23.49	24.00	0.348	2022/4/18

		QPSK(1,24)							
50%RB									
Front Side	20525/836.5	10M QPSK(25,24)	0.105	0.075	1.50	22.48	23.00	0.118	2022/4/18
Back Side	20525/836.5	10M QPSK(25,24)	0.161	0.129	-1.43	22.48	23.00	0.181	2022/4/18

NOTE: Body-Worn SAR test results of LTE Band 5

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
1RB									
Front Side	20525/836.5	10M QPSK(1,24)	0.192	0.139	2.91	23.49	24.00	0.216	2022/4/18
Back Side	20525/836.5	10M QPSK(1,24)	0.309	0.236	0.14	23.49	24.00	0.348	2022/4/18
Left Side	20525/836.5	10M QPSK(1,24)	0.076	0.057	2.41	23.49	24.00	0.085	2022/4/18
Right Side	20525/836.5	10M QPSK(1,24)	0.138	0.101	1.35	23.49	24.00	0.155	2022/4/18
Bottom Side	20525/836.5	10M QPSK(1,24)	0.176	0.132	-1.34	23.49	24.00	0.198	2022/4/18
50%RB									
Front Side	20525/836.5	10M QPSK(25,24)	0.105	0.075	1.50	22.48	23.00	0.118	2022/4/18
Back Side	20525/836.5	10M QPSK(25,24)	0.161	0.129	-1.43	22.48	23.00	0.181	2022/4/18
Left Side	20525/836.5	10M QPSK(25,24)	0.038	0.032	0.44	22.48	23.00	0.043	2022/4/18
Right Side	20525/836.5	10M QPSK(25,24)	0.074	0.058	-0.34	22.48	23.00	0.083	2022/4/18
Bottom Side	20525/836.5	10M QPSK(25,24)	0.089	0.077	-1.45	22.48	23.00	0.100	2022/4/18

NOTE: Hotspot SAR test results of LTE Band 5

10.1.9. SAR measurement Result of LTE Band 7

Test	Test	Test Mode	SAR Value	Power	Conducted	Tune-up	Scaled	Date
------	------	-----------	-----------	-------	-----------	---------	--------	------

Position of Head	channel /Freq.		(W/kg)		Drift (±5%)	power (dBm)	power (dBm)	SAR 1g (W/Kg)	
			1g	10g					
1RB									
Left Cheek	21100/2535	20M QPSK(1,99)	0.370	0.204	-3.16	22.68	23.50	0.447	2022/4/12
Left Tilt 15 Degree	21100/2535	20M QPSK(1,99)	0.219	0.120	-3.51	22.68	23.50	0.265	2022/4/12
Right Cheek	21100/2535	20M QPSK(1,99)	0.348	0.190	2.65	22.68	23.50	0.420	2022/4/12
Right Tilt 15 Degree	21100/2535	20M QPSK(1,99)	0.164	0.087	1.84	22.68	23.50	0.198	2022/4/12
50%RB									
Left Cheek	21100/2535	20M QPSK(50,49)	0.190	0.108	3.28	21.64	22.00	0.206	2022/4/12
Left Tilt 15 Degree	21100/2535	20M QPSK(50,49)	0.116	0.061	0.45	21.64	22.00	0.126	2022/4/12
Right Cheek	21100/2535	20M QPSK(50,49)	0.175	0.099	-2.40	21.64	22.00	0.190	2022/4/12
Right Tilt 15 Degree	21100/2535	20M QPSK(50,49)	0.098	0.049	0.40	21.64	22.00	0.106	2022/4/12

NOTE: Head SAR test results of LTE Band 7

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
1RB									
Front Side	21100/2535	20M QPSK(1,99)	0.504	0.227	2.53	22.68	23.50	0.609	2022/4/12
Back Side	21100/2535	20M QPSK(1,99)	0.826	0.387	-1.20	22.68	23.50	0.998	2022/4/12
Back Side	20850/2510	20M QPSK(1,99)	0.775	0.365	-0.36	22.51	23.50	0.973	2022/4/12

Back Side	21350/2560	20M QPSK(1,99)	0.974	0.446	-0.72	22.96	23.50	1.103	2022/4/12
Back Side Repeated	21350/2560	20M QPSK(1,99)	0.970	0.443	1.25	22.96	23.50	1.098	2022/4/12
50%RB									
Front Side	21100/2535	20M QPSK(50,49)	0.260	0.120	-3.90	21.64	22.00	0.282	2022/4/12
Back Side	21100/2535	20M QPSK(50,49)	0.453	0.196	-1.70	21.64	22.00	0.492	2022/4/12
100%RB									
Back Side	21100/2535	20M QPSK(100,0)	0.430	0.188	1.25	21.60	22.00	0.471	2022/4/12

NOTE: Body-Worn SAR test results of LTE Band 7

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
1RB									
Front Side	21100/2535	20M QPSK(1,99)	0.504	0.227	2.53	22.68	23.50	0.609	2022/4/12
Back Side	21100/2535	20M QPSK(1,99)	0.826	0.387	-1.20	22.68	23.50	0.998	2022/4/12
Left Side	21100/2535	20M QPSK(1,99)	0.198	0.089	-1.23	22.68	23.50	0.239	2022/4/12
Right Side	21100/2535	20M QPSK(1,99)	0.361	0.161	0.13	22.68	23.50	0.436	2022/4/12
Bottom Side	21100/2535	20M QPSK(1,99)	0.462	0.214	-3.87	22.68	23.50	0.558	2022/4/12
Back Side	20850/2510	20M QPSK(1,99)	0.775	0.365	-0.36	22.51	23.50	0.973	2022/4/12
Back Side	21350/2560	20M QPSK(1,99)	0.974	0.446	-0.72	22.96	23.50	1.103	2022/4/12
Back Side Repeated	21350/2560	20M QPSK(1,99)	0.970	0.443	1.25	22.96	23.50	1.098	2022/4/12

50%RB									
Front Side	21100/2535	20M QPSK(50,49)	0.260	0.120	-3.90	21.64	22.00	0.282	2022/4/12
Back Side	21100/2535	20M QPSK(50,49)	0.453	0.196	-1.70	21.64	22.00	0.492	2022/4/12
Left Side	21100/2535	20M QPSK(50,49)	0.104	0.051	-0.95	21.64	22.00	0.113	2022/4/12
Right Side	21100/2535	20M QPSK(50,49)	0.200	0.084	3.00	21.64	22.00	0.217	2022/4/12
Bottom Side	21100/2535	20M QPSK(50,49)	0.250	0.122	-1.44	21.64	22.00	0.272	2022/4/12
100%RB									
Back Side	21100/2535	20M QPSK(100,0)	0.430	0.188	1.25	21.60	22.00	0.471	2022/4/12

NOTE: Hotspot SAR test results of LTE Band 7

10.1.10. SAR measurement Result of LTE Band 12

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
1RB									
Left Cheek	23095/707.5	10M QPSK(1,0)	0.159	0.131	3.39	23.61	24.50	0.195	2022/4/14
Left Tilt 15 Degree	23095/707.5	10M QPSK(1,0)	0.085	0.070	-2.93	23.61	24.50	0.104	2022/4/14
Right Cheek	23095/707.5	10M QPSK(1,0)	0.147	0.120	3.49	23.61	24.50	0.180	2022/4/14
Right Tilt 15 Degree	23095/707.5	10M QPSK(1,0)	0.078	0.061	-2.54	23.61	24.50	0.096	2022/4/14
50%RB									
Left Cheek	23095/707.5	10M QPSK(25,0)	0.094	0.067	1.31	22.77	23.50	0.111	2022/4/14
Left Tilt 15 Degree	23095/707.5	10M QPSK(25,0)	0.045	0.042	0.55	22.77	23.50	0.053	2022/4/14
Right Cheek	23095/707.5	10M QPSK(25,0)	0.075	0.071	0.00	22.77	23.50	0.089	2022/4/14

Right Tilt 15 Degree	23095/707.5	10M QPSK(25,0)	0.046	0.036	0.36	22.77	23.50	0.054	2022/4/14
----------------------------	-------------	-------------------	-------	-------	------	-------	-------	-------	-----------

NOTE: Head SAR test results of LTE Band 12

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
1RB									
Front Side	23095/707.5	10M QPSK(1,0)	0.210	0.162	-0.64	23.61	24.50	0.258	2022/4/14
Back Side	23095/707.5	10M QPSK(1,0)	0.310	0.247	0.85	23.61	24.50	0.381	2022/4/14
50%RB									
Front Side	23095/707.5	10M QPSK(25,0)	0.110	0.088	-4.85	22.77	23.50	0.130	2022/4/14
Back Side	23095/707.5	10M QPSK(25,0)	0.169	0.128	4.93	22.77	23.50	0.200	2022/4/14

NOTE: Body-Worn SAR test results of LTE Band 12

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
1RB									
Front Side	23095/707.5	10M QPSK(1,0)	0.210	0.162	-0.64	23.61	24.50	0.258	2022/4/14
Back Side	23095/707.5	10M QPSK(1,0)	0.310	0.247	0.85	23.61	24.50	0.381	2022/4/14
Left Side	23095/707.5	10M QPSK(1,0)	0.074	0.056	1.84	23.61	24.50	0.091	2022/4/14
Right Side	23095/707.5	10M QPSK(1,0)	0.146	0.113	-0.41	23.61	24.50	0.179	2022/4/14
Bottom Side	23095/707.5	10M QPSK(1,0)	0.176	0.136	2.55	23.61	24.50	0.216	2022/4/14
50%RB									
Front Side	23095/707.5	10M QPSK(25,0)	0.110	0.088	-4.85	22.77	23.50	0.130	2022/4/14

Back Side	23095/707.5	10M QPSK(25,0)	0.169	0.128	4.93	22.77	23.50	0.200	2022/4/14
Left Side	23095/707.5	10M QPSK(25,0)	0.041	0.031	2.12	22.77	23.50	0.049	2022/4/14
Right Side	23095/707.5	10M QPSK(25,0)	0.087	0.058	1.87	22.77	23.50	0.103	2022/4/14
Bottom Side	23095/707.5	10M QPSK(25,0)	0.088	0.078	-2.49	22.77	23.50	0.104	2022/4/14

NOTE: Hotspot SAR test results of LTE Band 12

10.1.11. SAR measurement Result of LTE Band 17

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
1RB									
Left Cheek	23790/710	10M QPSK(1,0)	0.185	0.150	3.49	23.94	24.50	0.210	2022/4/14
Left Tilt 15 Degree	23790/710	10M QPSK(1,0)	0.109	0.088	-3.65	23.94	24.50	0.124	2022/4/14
Right Cheek	23790/710	10M QPSK(1,0)	0.172	0.138	3.33	23.94	24.50	0.196	2022/4/14
Right Tilt 15 Degree	23790/710	10M QPSK(1,0)	0.089	0.072	-2.17	23.94	24.50	0.101	2022/4/14
50%RB									
Left Cheek	23790/710	10M QPSK(25,12)	0.103	0.075	3.49	22.69	23.50	0.124	2022/4/14
Left Tilt 15 Degree	23790/710	10M QPSK(25,12)	0.058	0.052	0.82	22.69	23.50	0.070	2022/4/14
Right Cheek	23790/710	10M QPSK(25,12)	0.094	0.080	4.72	22.69	23.50	0.113	2022/4/14
Right Tilt 15 Degree	23790/710	10M QPSK(25,12)	0.048	0.038	3.51	22.69	23.50	0.058	2022/4/14

NOTE: Head SAR test results of LTE Band17

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
1RB									
Front Side	23790/710	10M QPSK(1,0)	0.222	0.175	2.28	23.94	24.50	0.253	2022/4/14
Back Side	23790/710	10M QPSK(1,0)	0.350	0.276	2.26	23.94	24.50	0.398	2022/4/14
50%RB									
Front Side	23790/710	10M QPSK(25,12)	0.129	0.089	2.92	22.69	23.50	0.155	2022/4/14
Back Side	23790/710	10M QPSK(25,12)	0.204	0.156	-4.89	22.69	23.50	0.246	2022/4/14

NOTE: Body-Worn SAR test results of LTE Band 17

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
1RB									
Front Side	23790/710	10M QPSK(1,0)	0.222	0.175	2.28	23.94	24.50	0.253	2022/4/14
Back Side	23790/710	10M QPSK(1,0)	0.350	0.276	2.26	23.94	24.50	0.398	2022/4/14
Left Side	23790/710	10M QPSK(1,0)	0.090	0.071	-0.29	23.94	24.50	0.102	2022/4/14
Right Side	23790/710	10M QPSK(1,0)	0.172	0.134	-1.49	23.94	24.50	0.196	2022/4/14
Bottom Side	23790/710	10M QPSK(1,0)	0.215	0.168	-1.88	23.94	24.50	0.245	2022/4/14
50%RB									
Front Side	23790/710	10M QPSK(25,12)	0.129	0.089	2.92	22.69	23.50	0.155	2022/4/14
Back Side	23790/710	10M QPSK(25,12)	0.204	0.156	-4.89	22.69	23.50	0.246	2022/4/14
Left Side	23790/710	10M QPSK(25,12)	0.052	0.039	-2.98	22.69	23.50	0.063	2022/4/14
Right	23790/710	10M	0.100	0.075	0.47	22.69	23.50	0.121	2022/4/14

Side		QPSK(25,12)							
Bottom Side	23790/710	10M QPSK(25,12)	0.129	0.099	-2.05	22.69	23.50	0.155	2022/4/14

NOTE: Hotspot SAR test results of LTE Band 17

10.1.12. SAR measurement Result of WLAN 2.4G

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Left Cheek	6/2437	802.11b	0.491	0.253	-0.35	13.60	14.00	0.538	2022/3/31
Left Tilt 15 Degree	6/2437	802.11b	0.290	0.146	-0.64	13.60	14.00	0.318	2022/3/31
Right Cheek	6/2437	802.11b	0.421	0.215	-2.41	13.60	14.00	0.462	2022/3/31
Right Tilt 15 Degree	6/2437	802.11b	0.215	0.110	-1.44	13.60	14.00	0.236	2022/3/31

NOTE: Head SAR test results of WLAN 2.4G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	6/2437	802.11b	0.132	0.069	-1.51	13.60	14.00	0.145	2022/3/31
Back Side	6/2437	802.11b	0.177	0.097	-0.75	13.60	14.00	0.194	2022/3/31

NOTE: Body-Worn SAR test results of WLAN 2.4G

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	6/2437	802.11b	0.132	0.069	-1.51	13.60	14.00	0.145	2022/3/31
Back Side	6/2437	802.11b	0.177	0.097	-0.75	13.60	14.00	0.194	2022/3/31
Right Side	6/2437	802.11b	0.066	0.036	0.46	13.60	14.00	0.072	2022/3/31
Top Side	6/2437	802.11b	0.090	0.049	1.18	13.60	14.00	0.099	2022/3/31

NOTE: Hotspot SAR test results of WLAN 2.4G

10.1.13. SAR measurement Result of WLAN 5.2G

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g	Date
			1g	10g					

								(W/Kg)	
Left Cheek	40/5200	802.11a	0.217	0.089	-1.69	9.52	10.00	0.242	2022/4/11
Left Tilt 15 Degree	40/5200	802.11a	0.115	0.046	1.32	9.52	10.00	0.128	2022/4/11
Right Cheek	40/5200	802.11a	0.191	0.077	3.14	9.52	10.00	0.213	2022/4/11
Right Tilt 15 Degree	40/5200	802.11a	0.097	0.039	2.91	9.52	10.00	0.108	2022/4/11

NOTE: Head SAR test results of WLAN 5.2G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	40/5200	802.11a	0.072	0.038	-3.76	9.52	10.00	0.080	2022/4/11
Back Side	40/5200	802.11a	0.117	0.063	-3.16	9.52	10.00	0.131	2022/4/11

NOTE: Body-Worn SAR test results of WLAN 5.2G

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	40/5200	802.11a	0.072	0.038	-3.76	9.52	10.00	0.080	2022/4/11
Back Side	40/5200	802.11a	0.117	0.063	-3.16	9.52	10.00	0.131	2022/4/11
Right Side	40/5200	802.11a	0.050	0.027	0.93	9.52	10.00	0.056	2022/4/11
Top Side	40/5200	802.11a	0.059	0.030	3.80	9.52	10.00	0.066	2022/4/11

NOTE: Hotspot SAR test results of WLAN 5.2G

10.1.14. SAR measurement Result of WLAN 5.8G

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Left Cheek	157/5785	802.11a	0.136	0.068	-2.92	10.02	10.50	0.152	2022/4/08
Left Tilt 15 Degree	157/5785	802.11a	0.076	0.037	-1.10	10.02	10.50	0.085	2022/4/08
Right Cheek	157/5785	802.11a	0.118	0.059	-2.96	10.02	10.50	0.132	2022/4/08
Right Tilt 15 Degree	157/5785	802.11a	0.058	0.028	-0.87	10.02	10.50	0.065	2022/4/08

NOTE: Head SAR test results of WLAN 5.8G

Test	Test	Test Mode	SAR Value	Power	Conducted	Tune-up	Scaled	Date
------	------	-----------	-----------	-------	-----------	---------	--------	------

Position of Body-Worn with 10mm	channel /Freq.		(W/kg)		Drift (±5%)	power (dBm)	power (dBm)	SAR 1g (W/Kg)	
			1g	10g					
Front Side	157/5785	802.11a	0.054	0.037	0.10	10.02	10.50	0.060	2022/4/08
Back Side	157/5785	802.11a	0.065	0.046	-3.87	10.02	10.50	0.073	2022/4/08

NOTE: Body-Worn SAR test results of WLAN 5.8G

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date
			1g	10g					
Front Side	157/5785	802.11a	0.054	0.037	0.10	10.02	10.50	0.060	2022/4/08
Back Side	157/5785	802.11a	0.065	0.046	-3.87	10.02	10.50	0.073	2022/4/08
Right Side	157/5785	802.11a	0.030	0.021	3.27	10.02	10.50	0.034	2022/4/08
Top Side	157/5785	802.11a	0.045	0.031	0.46	10.02	10.50	0.050	2022/4/08

NOTE: Hotspot SAR test results of WLAN 5.8G

10.2. SAR Summation Scenario

Per KDB 447498 D01, simultaneous transmission SAR is compliant if,

- Scalar SAR summation $< 1.6\text{W/kg}$.
- $\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan. If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	DTS			
Head	Left Cheek	0.447	0.538	0.985	N/A	N/A
	Left Tilt 15 Degree	0.265	0.318	0.583	N/A	N/A
	Right Cheek	0.420	0.462	0.882	N/A	N/A
	Right Tilt 15 Degree	0.198	0.236	0.434	N/A	N/A
Body-Worn	Front Side	0.609	0.145	0.754	N/A	N/A
	Back Side	1.103	0.194	1.297	N/A	N/A
Hotspot	Front Side	0.609	0.145	0.754	N/A	N/A
	Back Side	1.103	0.194	1.297	N/A	N/A
	Left Side	0.239	N/A	0.239	N/A	N/A
	Right Side	0.436	0.072	0.508	N/A	N/A

	Top Side	N/A	0.099	0.099	N/A	N/A
	Bottom Side	0.558	N/A	0.558	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WWAN and DTS.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	NII			
Head	Left Cheek	0.447	0.242	0.689	N/A	N/A
	Left Tilt 15 Degree	0.265	0.128	0.393	N/A	N/A
	Right Cheek	0.420	0.213	0.633	N/A	N/A
	Right Tilt 15 Degree	0.198	0.108	0.306	N/A	N/A
Body-Worn	Front Side	0.609	0.080	0.689	N/A	N/A
	Back Side	1.103	0.131	1.234	N/A	N/A
Hotspot	Front Side	0.609	0.080	0.689	N/A	N/A
	Back Side	1.103	0.131	1.234	N/A	N/A
	Left Side	0.239	N/A	0.239	N/A	N/A
	Right Side	0.436	0.056	0.492	N/A	N/A
	Top Side	N/A	0.066	0.066	N/A	N/A
	Bottom Side	0.558	N/A	0.558	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WWAN and NII.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	DSS			
Head	Left Cheek	0.447	0.265	0.712	N/A	N/A
	Left Tilt 15 Degree	0.265	0.265	0.530	N/A	N/A
	Right Cheek	0.420	0.265	0.685	N/A	N/A
	Right Tilt 15 Degree	0.198	0.265	0.463	N/A	N/A
Body-Worn	Front Side	0.609	0.132	0.741	N/A	N/A
	Back Side	1.103	0.132	1.235	N/A	N/A
Hotspot	Front Side	0.609	0.132	0.741	N/A	N/A
	Back Side	1.103	0.132	1.235	N/A	N/A
	Left Side	0.239	N/A	0.239	N/A	N/A

	Right Side	0.436	0.132	0.568	N/A	N/A
	Top Side	N/A	0.132	0.132	N/A	N/A
	Bottom Side	0.558	N/A	0.558	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WWAN and DSS.

11. Appendix A. Photo documentation

Refer to appendix Test Setup photo---SAR

12. Appendix B. System Check Plots

Table of contents
MEASUREMENT 1 System Performance Check - 750MHz
MEASUREMENT 2 System Performance Check - 835MHz
MEASUREMENT 3 System Performance Check - 1800MHz
MEASUREMENT 4 System Performance Check - 1900MHz
MEASUREMENT 5 System Performance Check - 2450MHz
MEASUREMENT 6 System Performance Check - 2600MHz
MEASUREMENT 7 System Performance Check - 5200MHz
MEASUREMENT 8 System Performance Check - 5800MHz

MEASUREMENT 1

Date of measurement: 14/4/2022


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW750</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	750.000000
Relative permittivity (real part)	40.959338
Relative permittivity (imaginary part)	21.708176
Conductivity (S/m)	0.904507
Variation (%)	2.730000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=3.00

SAR Peak: 1.30 W/kg

SAR 10g (W/Kg)	0.533332
SAR 1g (W/Kg)	0.867321



MEASUREMENT 2

Date of measurement: 18/4/2022


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW835</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	42.164312
Relative permittivity (imaginary part)	19.898390
Conductivity (S/m)	0.923064
Variation (%)	-2.720000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 1.23 W/kg

SAR 10g (W/Kg)	0.626333
SAR 1g (W/Kg)	0.970172



MEASUREMENT 3


Date of measurement: 13/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1800.000000
Relative permittivity (real part)	38.675753
Relative permittivity (imaginary part)	13.800614
Conductivity (S/m)	1.380061
Variation (%)	2.980000



Maximum location: X=5.00, Y=3.00

SAR Peak: 7.59 W/kg

SAR 10g (W/Kg)	2.135307
SAR 1g (W/Kg)	3.777066



MEASUREMENT 4

Date of measurement: 15/4/2022


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative permittivity (real part)	38.167668
Relative permittivity (imaginary part)	13.877784
Conductivity (S/m)	1.464877
Variation (%)	2.220000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=3.00

SAR Peak: 6.57 W/kg

SAR 10g (W/Kg)	2.161347
SAR 1g (W/Kg)	4.115221



MEASUREMENT 5


Date of measurement: 31/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2450</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	2450.000000
Relative permittivity (real part)	38.612082
Relative permittivity (imaginary part)	13.282752
Conductivity (S/m)	1.807930
Variation (%)	1.290000



Maximum location: X=-1.00, Y=1.00

SAR Peak: 8.94 W/kg

SAR 10g (W/Kg)	2.336106
SAR 1g (W/Kg)	5.115340



MEASUREMENT 6

Date of measurement: 12/4/2022


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2600</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative permittivity (real part)	38.345468
Relative permittivity (imaginary part)	13.864885
Conductivity (S/m)	2.002706
Variation (%)	0.250000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=1.00

SAR Peak: 10.67 W/kg

SAR 10g (W/Kg)	2.336037
SAR 1g (W/Kg)	6.040199



MEASUREMENT 7

Date of measurement: 11/4/2022


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW5200</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	5200.000000
Relative permittivity (real part)	36.418778
Relative permittivity (imaginary part)	16.466482
Conductivity (S/m)	4.756984
Variation (%)	2.800000

SURFACE SAR



VOLUME SAR




Maximum location: X=0.00, Y=6.00


SAR Peak: 49.61 W/kg

SAR 10g (W/Kg)	5.079162
SAR 1g (W/Kg)	16.236032


Z (m m)	0.00	2.00	4.00	6.00	8.00	10.0	12.0	14.0	16.0	18.0	20.0	22.0
SAR (W/ Kg)	46.6 91	27.5 91	14.0 77	7.05 94	3.59 91	1.78 43	0.89 50	0.46 37	0.24 02	0.13 08	0.06 27	0.04 97



3D screen shot



Hot spot position



MEASUREMENT 8

Date of measurement: 8/4/2022


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW5800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results

Frequency (MHz)	5800.000000
Relative permittivity (real part)	35.329615
Relative permittivity (imaginary part)	16.686822
Conductivity (S/m)	5.376865
Variation (%)	-0.500000



SURFACE SAR



Maximum location: X=0.00, Y=6.00

SAR Peak: 51.30 W/kg

SAR 10g (W/Kg)	5.692228
SAR 1g (W/Kg)	18.468190



13. Appendix C. Plots of High SAR Measurement

Table of contents
MEASUREMENT 1 GSM 850 Head
MEASUREMENT 2 GSM 850 Body
MEASUREMENT 3 GSM 1900 Head
MEASUREMENT 4 GSM 1900 Body
MEASUREMENT 5 WCDMA Band 2 Head
MEASUREMENT 6 WCDMA Band 2 Body
MEASUREMENT 7 WCDMA Band 4 Head
MEASUREMENT 8 WCDMA Band 4 Body
MEASUREMENT 9 WCDMA Band 5 Head
MEASUREMENT 10 WCDMA Band 5 Body
MEASUREMENT 11 WLAN 5.2G Head
MEASUREMENT 12 WLAN 5.8G Head
MEASUREMENT 13 WLAN 5.2G Body
MEASUREMENT 14 WLAN 5.8G Body
MEASUREMENT 15 WLAN 2.4G Head
MEASUREMENT 16 WLAN 2.4G Body
MEASUREMENT 17 LTE Band 2 Head
MEASUREMENT 18 LTE Band 2 Body
MEASUREMENT 19 LTE Band 4 Head
MEASUREMENT 20 LTE Band 4 Body
MEASUREMENT 21 LTE Band 5 Head
MEASUREMENT 22 LTE Band 5 Body
MEASUREMENT 23 LTE Band 7 Head
MEASUREMENT 24 LTE Band 7 Body
MEASUREMENT 25 LTE Band 12 Head
MEASUREMENT 26 LTE Band 12 Body
MEASUREMENT 27 LTE Band 17 Head
MEASUREMENT 28 LTE Band 17 Body

MEASUREMENT 1

Date of measurement: 18/4/2022


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 4.0)</u>

B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	42.079971
Relative permittivity (imaginary part)	19.924231
Conductivity (S/m)	0.925813
Variation (%)	0.640000



SURFACE SAR



Maximum location: X=-53.00, Y=-25.00

SAR Peak: 0.28 W/kg

SAR 10g (W/Kg)	0.163249
SAR 1g (W/Kg)	0.218140



MEASUREMENT 2


Date of measurement: 18/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 4.0)</u>

B. SAR Measurement Results



Frequency (MHz)	836.400000
Relative permittivity (real part)	42.079971
Relative permittivity (imaginary part)	19.924231
Conductivity (S/m)	0.925813
Variation (%)	-0.940000



Maximum location: X=-5.00, Y=38.00

SAR Peak: 0.38 W/kg

SAR 10g (W/Kg)	0.221651
SAR 1g (W/Kg)	0.297037



MEASUREMENT 3


Date of measurement: 15/4/2022

A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>GSM1900</u>
Channels	<u>Middle</u>
Signal	<u>TDMA (Crest factor: 4.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.254066
Relative permittivity (imaginary part)	13.895584
Conductivity (S/m)	1.451317
Variation (%)	3.100000



Maximum location: X=-51.00, Y=-52.00

SAR Peak: 0.30 W/kg

SAR 10g (W/Kg)	0.115106
SAR 1g (W/Kg)	0.195792



MEASUREMENT 4


Date of measurement: 15/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 4.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.254066
Relative permittivity (imaginary part)	13.895584
Conductivity (S/m)	1.451317
Variation (%)	-0.800000



Maximum location: X=-23.00, Y=-8.00

SAR Peak: 0.49 W/kg

SAR 10g (W/Kg)	0.175503
SAR 1g (W/Kg)	0.317556



MEASUREMENT 5


Date of measurement: 15/4/2022

A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>Band2 WCDMA1900</u>
Channels	<u>Middle</u>
Signal	<u>WCDMA (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.254066
Relative permittivity (imaginary part)	13.895584
Conductivity (S/m)	1.451317
Variation (%)	-3.990000



Maximum location: X=-51.00, Y=-52.00

SAR Peak: 0.47 W/kg

SAR 10g (W/Kg)	0.191190
SAR 1g (W/Kg)	0.318502



MEASUREMENT 6


Date of measurement: 15/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.254066
Relative permittivity (imaginary part)	13.895584
Conductivity (S/m)	1.451317
Variation (%)	-0.850000



Maximum location: X=22.00, Y=3.00

SAR Peak: 0.96 W/kg

SAR 10g (W/Kg)	0.320507
SAR 1g (W/Kg)	0.600853



MEASUREMENT 7

Date of measurement: 13/4/2022


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>Band4 WCDMA1700</u>
Channels	<u>Middle</u>
Signal	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1732.600000
Relative permittivity (real part)	39.135452
Relative permittivity (imaginary part)	13.752914
Conductivity (S/m)	1.323336
Variation (%)	-4.010000

SURFACE SAR





VOLUME SAR



Maximum location: X=-51.00, Y=-53.00

SAR Peak: 0.36 W/kg

SAR 10g (W/Kg)	0.159663
SAR 1g (W/Kg)	0.248547



MEASUREMENT 8


Date of measurement: 13/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band4 WCDMA1700</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1732.600000
Relative permittivity (real part)	39.135452
Relative permittivity (imaginary part)	13.752914
Conductivity (S/m)	1.323336
Variation (%)	-0.700000



Maximum location: X=-26.00, Y=-3.00

SAR Peak: 0.99 W/kg

SAR 10g (W/Kg)	0.382951
SAR 1g (W/Kg)	0.636686



MEASUREMENT 9


Date of measurement: 18/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band5 WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	836.400000
Relative permittivity (real part)	42.079971
Relative permittivity (imaginary part)	19.924231
Conductivity (S/m)	0.925813
Variation (%)	1.250000



Maximum location: X=-51.00, Y=-24.00

SAR Peak: 0.33 W/kg

SAR 10g (W/Kg)	0.203201
SAR 1g (W/Kg)	0.266787



MEASUREMENT 10


Date of measurement: 18/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band5 WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	836.400000
Relative permittivity (real part)	42.079971
Relative permittivity (imaginary part)	19.924231
Conductivity (S/m)	0.925813
Variation (%)	-0.010000



Maximum location: X=-5.00, Y=40.00

SAR Peak: 0.45 W/kg

SAR 10g (W/Kg)	0.275782
SAR 1g (W/Kg)	0.362676



MEASUREMENT 11

Date of measurement: 11/4/2022


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11a (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	5200.000000
Relative permittivity (real part)	36.418777
Relative permittivity (imaginary part)	16.466482
Conductivity (S/m)	4.756984
Variation (%)	-1.690000

SURFACE SAR





VOLUME SAR



Maximum location: X=-16.00, Y=25.00

SAR Peak: 0.59 W/kg

SAR 10g (W/Kg)	0.089202
SAR 1g (W/Kg)	0.217245



MEASUREMENT 12


Date of measurement: 8/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11a (Crest factor: 1.0)</u>

B. SAR Measurement Results

Frequency (MHz)	5785.000000
Relative permittivity (real part)	35.405567
Relative permittivity (imaginary part)	16.562380
Conductivity (S/m)	5.322965
Variation (%)	-2.920000




Maximum location: X=-16.00, Y=24.00


SAR Peak: 0.35 W/kg

SAR 10g (W/Kg)	0.068321
SAR 1g (W/Kg)	0.135678


Z (m m)	0.00	2.00	4.00	6.00	8.00	10.0	12.0	14.0	16.0	18.0	20.0	22.0
SAR (W/ Kg)	0.22 89	0.14 58	0.09 34	0.05 75	0.04 81	0.04 13	0.04 23	0.04 01	0.04 14	0.04 18	0.04 61	0.04 00



3D screen shot



Hot spot position



MEASUREMENT 13


Date of measurement: 11/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11a (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	5200.000000
Relative permittivity (real part)	36.418777
Relative permittivity (imaginary part)	16.466482
Conductivity (S/m)	4.756984
Variation (%)	-3.160000



Maximum location: X=-9.00, Y=28.00

SAR Peak: 0.30 W/kg

SAR 10g (W/Kg)	0.063273
SAR 1g (W/Kg)	0.116527



MEASUREMENT 14


Date of measurement: 8/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11a (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	5785.000000
Relative permittivity (real part)	35.405567
Relative permittivity (imaginary part)	16.562380
Conductivity (S/m)	5.322965
Variation (%)	-3.870000



Maximum location: X=-9.00, Y=17.00

SAR Peak: 0.15 W/kg

SAR 10g (W/Kg)	0.045834
SAR 1g (W/Kg)	0.065115



MEASUREMENT 15

Date of measurement: 31/3/2022


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11b (Crest factor: 1.0)</u>

B. SAR Measurement Results

Frequency (MHz)	2437.000000
Relative permittivity (real part)	38.664181
Relative permittivity (imaginary part)	13.201252
Conductivity (S/m)	1.787303
Variation (%)	-0.350000



SURFACE SAR



Maximum location: X=-12.00, Y=23.00

SAR Peak: 0.87 W/kg

SAR 10g (W/Kg)	0.253125
SAR 1g (W/Kg)	0.490961



MEASUREMENT 16


Date of measurement: 31/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11b (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	2437.000000
Relative permittivity (real part)	38.664181
Relative permittivity (imaginary part)	13.201252
Conductivity (S/m)	1.787303
Variation (%)	-0.750000



Maximum location: X=-28.00, Y=-11.00

SAR Peak: 0.32 W/kg

SAR 10g (W/Kg)	0.097443
SAR 1g (W/Kg)	0.177419



MEASUREMENT 17


Date of measurement: 15/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.254066
Relative permittivity (imaginary part)	13.895584
Conductivity (S/m)	1.451317
Variation (%)	-1.560000



Maximum location: X=-51.00, Y=-52.00

SAR Peak: 0.45 W/kg

SAR 10g (W/Kg)	0.185167
SAR 1g (W/Kg)	0.308463



MEASUREMENT 18


Date of measurement: 15/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.254066
Relative permittivity (imaginary part)	13.895584
Conductivity (S/m)	1.451317
Variation (%)	-0.990000



Maximum location: X=5.00, Y=-9.00

SAR Peak: 0.90 W/kg

SAR 10g (W/Kg)	0.313807
SAR 1g (W/Kg)	0.575946



MEASUREMENT 19


Date of measurement: 13/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1732.500000
Relative permittivity (real part)	39.143353
Relative permittivity (imaginary part)	13.737764
Conductivity (S/m)	1.322260
Variation (%)	0.250000



Maximum location: X=-52.00, Y=-53.00

SAR Peak: 0.36 W/kg

SAR 10g (W/Kg)	0.159090
SAR 1g (W/Kg)	0.249816



MEASUREMENT 20


Date of measurement: 13/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1732.500000
Relative permittivity (real part)	39.143353
Relative permittivity (imaginary part)	13.737764
Conductivity (S/m)	1.322260
Variation (%)	-0.880000



Maximum location: X=-25.00, Y=-11.00

SAR Peak: 0.96 W/kg

SAR 10g (W/Kg)	0.371948
SAR 1g (W/Kg)	0.617581



MEASUREMENT 21

Date of measurement: 18/4/2022


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 5</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.500000
Relative permittivity (real part)	42.082561
Relative permittivity (imaginary part)	19.922890
Conductivity (S/m)	0.925861
Variation (%)	0.980000

SURFACE SAR





VOLUME SAR



Maximum location: X=-52.00, Y=-25.00

SAR Peak: 0.28 W/kg

SAR 10g (W/Kg)	0.171090
SAR 1g (W/Kg)	0.225700



MEASUREMENT 22


Date of measurement: 18/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 5</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	836.500000
Relative permittivity (real part)	42.082561
Relative permittivity (imaginary part)	19.922890
Conductivity (S/m)	0.925861
Variation (%)	0.140000



Maximum location: X=1.00, Y=45.00

SAR Peak: 0.38 W/kg

SAR 10g (W/Kg)	0.235826
SAR 1g (W/Kg)	0.309321



MEASUREMENT 23

Date of measurement: 12/4/2022


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 7</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2535.000000
Relative permittivity (real part)	38.680767
Relative permittivity (imaginary part)	13.732785
Conductivity (S/m)	1.934034
Variation (%)	-3.160000

SURFACE SAR





VOLUME SAR



Maximum location: X=-47.00, Y=-49.00

SAR Peak: 0.58 W/kg

SAR 10g (W/Kg)	0.204030
SAR 1g (W/Kg)	0.370211



MEASUREMENT 24


Date of measurement: 12/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 7</u>
<u>Channels</u>	<u>High</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	2560.000000
Relative permittivity (real part)	38.528267
Relative permittivity (imaginary part)	13.800485
Conductivity (S/m)	1.962736
Variation (%)	-0.720000



Maximum location: X=19.00, Y=-12.00

SAR Peak: 1.76 W/kg

SAR 10g (W/Kg)	0.445805
SAR 1g (W/Kg)	0.973748



MEASUREMENT 25


Date of measurement: 14/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 12</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	707.500000
Relative permittivity (real part)	41.501987
Relative permittivity (imaginary part)	22.019926
Conductivity (S/m)	0.865505
Variation (%)	3.390000



Maximum location: X=-52.00, Y=-32.00

SAR Peak: 0.18 W/kg

SAR 10g (W/Kg)	0.131477
SAR 1g (W/Kg)	0.159064



MEASUREMENT 26


Date of measurement: 14/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 12</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	707.500000
Relative permittivity (real part)	41.501987
Relative permittivity (imaginary part)	22.019926
Conductivity (S/m)	0.865505
Variation (%)	0.850000



Maximum location: X=-8.00, Y=35.00

SAR Peak: 0.37 W/kg

SAR 10g (W/Kg)	0.247332
SAR 1g (W/Kg)	0.309871



MEASUREMENT 27


Date of measurement: 14/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 17</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	710.000000
Relative permittivity (real part)	41.486637
Relative permittivity (imaginary part)	21.960377
Conductivity (S/m)	0.866215
Variation (%)	3.490000



Maximum location: X=-52.00, Y=-33.00

SAR Peak: 0.22 W/kg

SAR 10g (W/Kg)	0.149881
SAR 1g (W/Kg)	0.184927



MEASUREMENT 28


Date of measurement: 14/4/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 17</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	710.000000
Relative permittivity (real part)	41.486637
Relative permittivity (imaginary part)	21.960377
Conductivity (S/m)	0.866215
Variation (%)	2.260000



Maximum location: X=1.00, Y=29.00

SAR Peak: 0.43 W/kg

SAR 10g (W/Kg)	0.275602
SAR 1g (W/Kg)	0.349628



14. Appendix D. Calibration Certificate

Table of contents
E Field Probe - SN 08/16 EPGO287
750 MHz Dipole - SN 03/15 DIP 0G750-355
835 MHz Dipole - SN 03/15 DIP 0G835-347
1800 MHz Dipole - SN 03/15 DIP 1G800-349
1900 MHz Dipole - SN 03/15 DIP 1G900-350
2450 MHz Dipole - SN 03/15 DIP 2G450-352
2600 MHz Dipole - SN 03/15 DIP 2G600-356
5000-6000 MHz Dipole - SN 13/14 WGA 33
Extended Calibration Certificate



COMOSAR E-Field Probe Calibration Report

Ref : ACR.60.1.21.MVGB.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA
MVG COMOSAR DOSIMETRIC E-FIELD PROBE
SERIAL NO.: SN 08/16 EPG0287

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon
29280 PLOUZANE - FRANCE

Calibration date: 02/01/2022



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr

Summary:

This document presents the method and results from an accredited COMOSAR E-Field Probe calibration performed at MVG, using the CALIPROBE test bench, for use with a MVG COMOSAR system only. The test results covered by accreditation are traceable to the International System of Units (SI).



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

	Name	Function	Date	Signature
Prepared by :	Jérôme Luc	Technical Manager	2/1/2022	<i>JS</i>
Checked by :	Jérôme Luc	Technical Manager	2/1/2022	<i>JS</i>
Approved by :	Yann Toutain	Laboratory Director	2/1/2022	<i>Yann Toutain</i>

2022.02.0
1 10:07:13
+01'00'

	Customer Name
Distribution :	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

Issue	Name	Date	Modifications
A	Jérôme Luc	2/1/2022	Initial release



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

TABLE OF CONTENTS

1	Device Under Test	4
2	Product Description	4
2.1	General Information	4
3	Measurement Method	4
3.1	Linearity	4
3.2	Sensitivity	5
3.3	Lower Detection Limit	5
3.4	Isotropy	5
3.1	Boundary Effect	5
4	Measurement Uncertainty	6
5	Calibration Measurement Results	6
5.1	Sensitivity in air	6
5.2	Linearity	7
5.3	Sensitivity in liquid	8
5.4	Isotropy	9
6	List of Equipment	10



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

1 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Manufacturer	MVG
Model	SSE2
Serial Number	SN 08/16 EPGO287
Product Condition (new / used)	Used
Frequency Range of Probe	0.15 GHz-6GHz
Resistance of Three Dipoles at Connector	Dipole 1: R1=0.211 MΩ Dipole 2: R2=0.199 MΩ Dipole 3: R3=0.199 MΩ

2 PRODUCT DESCRIPTION

2.1 GENERAL INFORMATION

MVG's COMOSAR E field Probes are built in accordance to the IEEE 1528, FCC KDB865664 D01, CENELEC EN62209 and CEI/IEC 62209 standards.



Figure 1 – MVG COMOSAR Dosimetric E field Dipole

Probe Length	330 mm
Length of Individual Dipoles	2 mm
Maximum external diameter	8 mm
Probe Tip External Diameter	2.5 mm
Distance between dipoles / probe extremity	1 mm

3 MEASUREMENT METHOD

The IEEE 1528, FCC KDB865664 D01, CENELEC EN62209 and CEI/IEC 62209 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their affect. All calibrations / measurements performed meet the fore mentioned standards.

3.1 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range 0.01W/kg to 100W/kg.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

3.2 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and tissue simulating liquid) using waveguides as outlined in the standards.

3.3 LOWER DETECTION LIMIT

The lower detection limit was assessed using the same measurement set up as used for the linearity measurement. The required lower detection limit is 10 mW/kg.

3.4 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 to 360 degrees in 15-degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

3.1 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

The boundary effect uncertainty can be estimated according to the following uncertainty approximation formula based on linear and exponential extrapolations between the surface and $d_{be} + d_{step}$ along lines that are approximately normal to the surface:

$$SAR_{uncertainty} [\%] = \Delta SAR_{be} \frac{(d_{be} + d_{step})^2}{2d_{step}} \frac{(e^{-d_{be}/\delta})}{\delta/2} \quad \text{for } (d_{be} + d_{step}) < 10 \text{ mm}$$

where

$SAR_{uncertainty}$	is the uncertainty in percent of the probe boundary effect
d_{be}	is the distance between the surface and the closest <i>zoom-scan</i> measurement point, in millimetre
Δ_{step}	is the separation distance between the first and second measurement points that are closest to the phantom surface, in millimetre, assuming the boundary effect at the second location is negligible
δ	is the minimum penetration depth in millimetres of the head tissue-equivalent liquids defined in this standard, i.e., $\delta \approx 14 \text{ mm}$ at 3 GHz;
ΔSAR_{be}	in percent of SAR is the deviation between the measured SAR value, at the distance d_{be} from the boundary, and the analytical SAR value.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

The measured worst case boundary effect SARuncertainty[%] for scanning distances larger than 4mm is 1.0% Limit ,2%).

4 MEASUREMENT UNCERTAINTY

The guidelines outlined in the IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty associated with an E-field probe calibration using the waveguide technique. All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

Uncertainty analysis of the probe calibration in waveguide					
ERROR SOURCES	Uncertainty value (%)	Probability Distribution	Divisor	ci	Standard Uncertainty (%)
Expanded uncertainty 95 % confidence level k = 2					14 %

5 CALIBRATION MEASUREMENT RESULTS

Calibration Parameters	
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

5.1 SENSITIVITY IN AIR

Normx dipole 1 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normy dipole 2 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normz dipole 3 ($\mu\text{V}/(\text{V}/\text{m})^2$)
0.72	0.66	0.77

DCP dipole 1 (mV)	DCP dipole 2 (mV)	DCP dipole 3 (mV)
107	110	110

Calibration curves $e_i=f(V)$ ($i=1,2,3$) allow to obtain E-field value using the formula:


$$E = \sqrt{E_1^2 + E_2^2 + E_3^2}$$



COMOSAR E-FIELD PROBE CALIBRATION REPORT


Ref: ACR.60.1.21.MVGB.A

Calibration curves



5.2 LINEARITY

Linearity



Linearity: $\pm 1.90\%$ ($\pm 0.08\text{dB}$)



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

5.3 SENSITIVITY IN LIQUID

Liquid	Frequency (MHz +/- 100MHz)	ConvF
HL750	750	1.49
HL850	835	1.50
HL900	900	1.61
HL1800	1800	1.73
HL1900	1900	1.91
HL2000	2000	1.97
HL2300	2300	1.92
HL2450	2450	1.98
HL2600	2600	1.87
HL3300	3300	1.79
HL3500	3500	1.85
HL3700	3700	1.79
HL3900	3900	2.07
HL4200	4200	2.21
HL4600	4600	2.25
HL4900	4900	2.05
HL5200	5200	1.80
HL5400	5400	2.05
HL5600	5600	2.16
HL5800	5800	2.07

LOWER DETECTION LIMIT: 8mW/kg