

Test Report No.: FCC2023-0029-H

RF Test Report

EUT : Bluetooth keyboard

MODEL : BAIPTHK109

BRAND NAME : N/A

APPLICANT : Digital Gadgets LLC

CLASSIFICATION OF TEST : N/A

CVC Testing Technology Co., Ltd.



Test Report No.: FCC2023-0029-H Page 2 of 8

Applicant		Name: Digital Gadgets LLC Address: 183 Locust Ave #427, West Long Branch, NJ					
Manufacturer	Name: Digital Gadgets LLC Address: 183 Locust Ave #427, West Long Branch, NJ Name: Bluetooth keyboard Model/Type: BAIPTHK109 Brand: N/A						
Equipment Under Test							
		Serial NO.: N/A Sample NO.: 3-1					
Date of Receipt. 2023.06.01				f Testing	2023.06.01~2023.06.09		
	Test Specificati	on		Test Result			
FCC Part 2 (Section KDB 447498 DO		,			PASS		
	The equipment under test was found to comply with the						
		requireme	ents of the	standards	s applied.		
Evaluation of Tes	t Result				Seal of CVC Issue Date: 2023.00		
Tested by:		Reviewe	d by:		Approved by:		
Xu Zhanfei		Linyonghai		nì	Charlinan		
X u Z hen	Fei Signature	Nan	Liu YongH	l ai Signature	Chen HuaWen Name Signature		
Name							

This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.



Test Report No.: FCC2023-0029-H Page 3 of 8

TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1. GERTIFICATION	
2. RF EXPOSURE LIMIT	б
3. CLASSIFICATION	7
4. ANTENNA GAIN	7
5. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER	7



Test Report No.: FCC2023-0029-H Page 4 of 8

RELEASE CONTROL RECORD

ISSUE NO.	SUE NO. REASON FOR CHANGE	
FCC2023-0029-H	Original release	2023.06.12



Test Report No.: FCC2023-0029-H Page 5 of 8

1. GERTIFICATION

PRODUCT	Bluetooth keyboard			
BRAND	N/A			
MODEL	BAIPTHK109			
FCC ID	X2K-BAIPTHK109			
POWER SUPPLY	 DC 5V from USB host unit DC 3.7V from Li-ion battery 			
MODULATIONTECHNOLOGY	GFKS			
MODULATION TYPE	GKSK for BT-LE			
OPERATING FREQUENCY	2402MHz ~ 2480MHz for BT-LE (1Mbps)			
NUMBER OF CHANNEL	BT-LE GFSK (1Mbps): 40			
PEAK OUTPUT POWER	-0.26dBm (Maximum)			
ANTENNA TYPE (Remark 4)	PCB Antenna, with 1.5dBi gain			
HARDWARE VERSION:	V3.0			
SOFTWARE VERSION:	V3.0			
I/O PORTS	Refer to user's manual			
CABLE SUPPLIED	Micro USB Cable, 0.5m, non-detachable, unshielded			

Remark:

- 1. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- 2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
- 3. Please refer to the EUT photo document for detailed product photo. (Report NO.: FCC2023-0029-E)
- 4. Please refer to the antenna report.
- 5. Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, CVC is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.



Test Report No.: FCC2023-0029-H Page 6 of 8

2. RF EXPOSURE LIMIT

According to Part2.1093, Evaluation of compliance with the exposure limits in \S 1.1310 of this chapter, and preparation of an EA if the limits are exceeded, is necessary for portable devices having single RF sources with more than an available maximum time-averaged power of 1 mW, more than the ERP listed in Table 1 to \S 1.1307(b)(3)(i)(C), or more than the Pth in the following formula, whichever is greater. The following formula shall only be used in conjunction with portable devices not exempt by \S 1.1307(b)(3)(i)(C) at distances from 0.5 centimeters to 20 centimeters and frequencies from 0.3 GHz to 6 GHz.P is given as:

$$P_{\rm th} \; ({\rm mW}) = \begin{cases} ERP_{\rm 20 \; cm} (d/20 \; {\rm cm})^x & d \leq 20 \; {\rm cm} \\ \\ ERP_{\rm 20 \; cm} & 20 \; {\rm cm} < d \leq 40 \; {\rm cm} \end{cases}$$

Where:

$$x = -\log_{10}\left(\frac{60}{ERP_{20}\,\mathrm{cm}\sqrt{f}}\right)$$

and f is in GHz;

and

$$P_{\rm th} \ ({\rm mW}) = ERP_{\rm 20 \ cm} \ ({\rm mW}) = \begin{cases} 2040f & 0.3 \ {\rm GHz} \le f < 1.5 \ {\rm GHz} \\ \\ 3060 & 1.5 \ {\rm GHz} \le f \le 6 \ {\rm GHz} \end{cases}$$



Test Report No.: FCC2023-0029-H Page 7 of 8

3. CLASSIFICATION

The antenna of this product, under normal use condition, is within 20 centimeters of the body of the user So, this device is classified as **Portable Device**.

4. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type
BT-LE	1.5	PCB Antenna

This is provided by the manufacturer. The laboratory is not responsible for technical data provided by the customer.

5. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER

The measured Conducted Average Power

Mode	requency (MHz)		Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)	
BT-LE	2402 ~ 2480	1	+-1	0	2	

The tuned Conducted Average Power (declared by client)

Technology	Maximum conducted power (dBm)	Maximum Antenna Gain (dBi)	EIRP (dBm)	ERP (dBm)	ERP (mW)	Part1.1307b Threshold (mW)	Verify
BT-LE	-0.26	1.5	1.24	-0.91	0.81	1	PASS



Test Report No.: FCC2023-0029-H Page 8 of 8

Important

- (1) The test report is valid without the official stamp of CVC;
- (2) Any part photocopies of the test report are forbidden without the written permission from CVC;
- (3) The test report is invalid without the signatures of Approval and Reviewer;
- (4) The test report is invalid if altered;
- (5) Objections to the test report must be submitted to CVC within 15 days.
- (6) Generally, commission test is responsible for the tested samples only.
- (7) As for the test result "-" or "N" means "not applicable", "/" means "not test", "P" means "pass" and "F" means "fail"

The test data and test results given in this test report should only be used for purposes of scientific research, teaching and internal quality control when the CMA symbol is not presented.

Laboratory: CVC Testing Technology Co., Ltd.

Address: No.3, TiantaiyiRoad, KaitaiAvenue, ScienceCity, Guangzhou, China

Post Code: 510663 Tel: 020-32293888

FAX: 020-32293889 E-mail: office@cvc.org.cn