



#### FCC RF EXPOSURE REPORT

For

**Forward Phased Array Radar** 

**MODEL NUMBER: RD241608RFV2** 

REPORT NUMBER: 4791309052-5-4

**ISSUE DATE: August 9, 2024** 

FCC ID: SS3-RD241608RF2

Prepared for

SZ DJI TECHNOLOGY CO.,LTD.

Lobby of T2, DJI Sky City, No. 53 Xianyuan Road, Xili Community, Xili Street,

Nanshan District, Shenzhen

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

> Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com



REPORT NO.: 4791309052-5-4 Page 2 of 8

**Revision History** 

Rev.Issue DateRevisionsRevised ByV0August 9, 2024Initial Issue



## **TABLE OF CONTENTS**

1.	ATTESTATION OF TEST RESULTS	4
2.	TEST METHODOLOGY	. 5
3.	FACILITIES AND ACCREDITATION	5
4.	DESCRIPTION OF EUT	6
5.	REQUIREMENT	7



REPORT NO.: 4791309052-5-4 Page 4 of 8

#### 1. ATTESTATION OF TEST RESULTS

**Applicant Information** 

Company Name: SZ DJI TECHNOLOGY CO.,LTD.

Address: Lobby of T2, DJI Sky City, No. 53 Xianyuan Road, Xili

Community, Xili Street, Nanshan District, Shenzhen

**Manufacturer Information** 

Company Name: SZ DJI TECHNOLOGY CO.,LTD.

Address: Lobby of T2, DJI Sky City, No. 53 Xianyuan Road, Xili

Community, Xili Street, Nanshan District, Shenzhen

**EUT Information** 

Operations Manager

EUT Name: Forward Phased Array Radar

Model: RD241608RFV2

Brand Name: DJI
Sample Status: normal
Sample ID: 7201002-2
Sample Received Date: May 10, 2024

Date of Tested: May 10, 2024 ~ July 10, 2024

APPLICABLE STANDARDS			
STANDARD	TEST RESULTS		
FCC 47CFR§2.1091	PASS		
KDB-447498 D01 V06	PASS		

Prepared By:

Checked By:

Lamry Huang

Fanny Huang

Engineer Project Associate

Approved By:

Herhand

Stephen Guo

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

This report shall not be reproduced except in full, without the written approval of UL Verification Services

(Guangzhou) Co., Ltd, Song Shan Lake Branch.

#### 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 and KDB 447498 D01 General RF Exposure Guidance v06.

Page 5 of 8


#### 3. FACILITIES AND ACCREDITATION

	A2LA (Certificate No.: 4102.01)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	has been assessed and proved to be in compliance with A2LA.
	FCC (FCC Designation No.: CN1187)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	Has been recognized to perform compliance testing on equipment subject
	to the Commission's Declaration of Conformity (DoC) and Certification rules
	ISED (Company No.: 21320)
	, , ,
Accreditation	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
Certificate	has been registered and fully described in a report filed with ISED.
Certificate	The Company Number is 21320 and the test lab Conformity Assessment
	Body Identifier (CABID) is CN0046.
	VCCI (Registration No.: G-20192, C-20153, T-20155 and R-20202)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	has been assessed and proved to be in compliance with VCCI, the
	Membership No. is 3793.
	· ·
	Facility Name:
	Chamber D, the VCCI registration No. is G-20192 and R-20202
	Shielding Room B, the VCCI registration No. is C-20153 and T-20155

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.





# 4. DESCRIPTION OF EUT

EUT Name	Forward Phased Array Radar
Model	RD241608RFV2

Frequency Range:	24.05 ~ 24.25 GHz
Channel Number:	1
Type of Modulation:	FMCW
Antenna Type:	Antenna for Forward Radar: Linear Antenna Antenna for Upward Radar: Linear Antenna
Antenna Gain:	Antenna gain for Forward Radar: 10 dBi Antenna gain for Upward Radar: 10 dBi
Normal Test Voltage:	DC 52.22 V

REPORT NO.: 4791309052-5-4 Page 7 of 8

#### 5. REQUIREMENT

#### **LIMIT AND CALCULATION METHOD**

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with. Limits for General Population/Uncontrolled Exposure

#### RF EXPOSURE LIMIT

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time  E ²,  H ² or S (Minutes)
0.3 1.34	614	1.63	(100)*	30
1.34 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 300	27.5	0.073	0.2	30
300 1500			f/1500	30
1500 100,000			1.0	30

### **CALCULATION METHOD**

S=PG/4πR<sup>2</sup>

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna



REPORT NO.: 4791309052-5-4

Page 8 of 8

#### **CALCULATED RESULTS**

Radio Frequency Radiation Exposure Evaluation

(Worst case)			
Operating	Max. EIRP	Power density	Limit
Mode	(dBm)	(mW/ cm <sup>2</sup> )	Liiik
Forward Radar FMCW	2.90	0.00039	1

(Worst case)			
Operating Mode	Max. EIRP	Power density	Limit
	(dBm)	(mW/ cm <sup>2</sup> )	Liiiit
Upward Radar FMCW	4.97	0.00062	1

#### Note:

- 1. The calculated distance is 20 cm.
- 2. The power comes from operation description.

Forward Radar: Max. EIRP = 107.67 dBuV/m in 1m = (107.67-104.77) dBm=2.90 dBm Upward Radar: Max. EIRP = 109.74 dBuV/m in 1m = (109.74-104.77) dBm=4.97 dBm

3. The manufacturer declared that the EUT can support Forward Radar and Upward Radar simultaneous emission.

Forward Radar + Upward Radar =  $0.00039 + 0.00062 = 0.00101 \text{ (mW/cm}^2\text{)}$ 

Therefor the maximum calculations of above situations are less than the "1" limit.

**END OF REPORT**