## HANDS-FREE MODE TEST SETUP

#### Ear-Microphone Jack

Portable transmitting devices which have an Ear-Microphone jack must be evaluated for RF exposure in a body-worn configuration. The testing is performed with the use of a torso phantom filled with muscle equivalent tissue. The EUT is positioned with the keypad facing away from the phantom, and the Ear-Microphone wire attached to the phone jack, simulating the device placed in a shirt pocket or attached to a body holster. The SAR tests are then performed in both the antenna in and antenna out positions using the low, middle, and high channels to investigate the worst case SAR value (see figure 11). Body-worn configurations that have not been SAR tested may result in operating conditions that could exceed FCC RF exposure limits, therefore, users are cautioned to use tested and/or approved accessories.

### Shirt Pocket Configuration

The shirt pocket configuration is used for devices designed to be body-worn, and small enough to be placed inside a shirt pocket. To simulate the worstcase configuration, the EUT is placed in a torso position on the phantom with the keypad facing away from the phantom, and the Ear-Microphone wire connected to the phone to simulate hands-free operation in a shirt-pocket configuration (see figure 12).

#### **Body Holster Configuration**

The body holster configuration is used for body-worn devices which have a body holster accessory. Typically, a holster or carrying case is provided or available as an accessory item for supporting headset and body-worn operations. SAR may vary depending on the body separation distance provided by the type of holster and batteries supplied for a phone. In most cases, the antenna may become closer to the user's body than next to the head. The design of the holster permits the phone to be positioned only with the keypad facing away from the phantom. Proper usage of the holster restricts the antenna to a specified distance away from the surface of the body. For this test the EUT is placed into the holster and the holster is positioned against the torso of the phantom in a normal operating position. The Ear-Microphone wire is then connected to the phone to simulate hands-free operation in a body holster configuration. (see figure 13)

#### **Other Configurations**

If other operating configurations are possible (i.e.: pants pocket, car adapter kit, etc), it will be indicated to users in the instruction manual about untested conditions and the possibility of exceeding FCC exposure limits for such use or the use of third-party accessories. If there is a high potential for exceeding limits in certain unintended configurations, a warning statement will be included in the manual, warning the user to avoid such operating conditions.

© 1999 PCTEST Lab

SAMSUNG Dual-Mode Cellular Phone (AMPS/CDMA) FCC ID: A3LSCH850 (Tx 824-849 MHz)



Figure 11. Ear-Microphone Jack



Figure 12. Shirt Pocket Configuration



Figure 13. Body Holster Configuration

## **TEST DATA SUMMARY**

		Ambient TEMPERATURE (°C)	23.0		
		Relative HUMIDITY (%)	47.0		
		Atmospheric PRESSURE (kPa)	100.0		
Mixture Type:	Muscle	_			
Dielectric Constant:	56.2				
Conductivity:	0.95 S/m	_			
Closest Distance (between E-Probe & Phone Antenna):2.0 cm					

# Measurement Results (Hands-Free Mode)

FREQUENCY		Modulation	POWER	Test	Antenna	SAR
MHz	Ch.		(dBm)	Configuration	Position	(W/kg)
836.49	383	AMPS	25.5	Holster	IN	1.11
836.49	383	AMPS	25.5	Holster	OUT	1.33
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak (Muscle) Uncontrolled Exposure/General Population			1.6 W/kg (mW/g)			

NOTES:

- 1. All modes of operation were investigated and the worst-case are reported.
- 2. Battery condition is fully charged for all readings.

Randy Ortanez President & Chief Engineer

PCTEST SEAL

© 1999 PCTEST Lab

#### SAMSUNG Dual-Mode Cellular Phone (AMPS/CDMA) FCC ID: A3LSCH850 (Tx 824-849 MHz)