

FCC EMC Test Report

Report No.: JYTSZ-R01-2300603
Applicant: Hangzhou Roombanker Technology Co., Ltd.
Address of Applicant: A#801 Wantong center, Hangzhou, China

Equipment Under Test (EUT)

Product Name: Wall Switch
Model No.: RBAD-WS1-915, RBAD-WSx-915: (X: 0~9 or X: A~Z), RBAD-WSx-915(YY)/ZZZ: (X: 0~9 or X: A~Z), (Y: 0~9 or Y: A~Z)/(Z: 0~9 or Z: A~Z)
Trade Mark: Roombanker
FCC ID: 2AUXBRBAD-WS1915
Applicable Standards: FCC CFR Title 47 Part 15B
Date of Sample Receipt: 23 Nov., 2023
Date of Test: 24 Nov., 2023 to 08 Jan., 2024
Date of report Issued: 09 Jan., 2024
Test Result: PASS

Project by:**Date:**

09 Jan., 2024

Reviewed by:**Date:**

09 Jan., 2024

Approved by:**Date:**

09 Jan., 2024

Manager

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

1 Version

Version No.	Date	Description
00	09 Jan., 2024	Original

2 Contents

Page

Cover Page	1
1 Version	2
2 Contents.....	3
3 General Information.....	4
3.1 Client Information	4
3.2 General Description of E.U.T.	4
3.3 Test Mode	4
3.4 Description of Test Auxiliary Equipment	5
3.5 Description of Cable Used.....	5
3.6 Measurement Uncertainty	5
3.7 Additions to, Deviations, or Exclusions from the Method	5
3.8 Laboratory Facility	5
3.9 Laboratory Location.....	6
3.10 Test Instruments List.....	6
4 Measurement Setup and Procedure	7
4.1 Test Setup	7
4.2 Test Procedure	9
5 Test Results.....	10
5.1 Summary	10
5.1.1 Clause and data summary	10
5.1.2 Test Limit.....	10
5.2 Conducted Emission	11
5.3 Radiated Emission	13

3 General Information

3.1 Client Information

Applicant:	Hangzhou Roombanker Technology Co., Ltd.
Address:	A#801 Wantong center, Hangzhou, China
Manufacturer/ Factory:	Zhejiang dusun electron co., ltd
Address:	No.640 Feng Qing St, DeQing Zhejiang China

3.2 General Description of E.U.T.

Product Name:	Wall Switch
Model No.:	RBAD-WS1-915, RBAD-WSx-915: (X: 0~9 or X: A~Z), RBAD-WSx-915(YY)/ZZZ: (X: 0~9 or X: A~Z), (Y: 0~9 or Y: A~Z)/(Z: 0~9 or Z: A~Z)
Power Supply:	AC 110V / AC 230V, $\pm 10\%$ 50/60Hz
Remark:	Model No.: RBAD-WS1-915, RBAD-WSx-915, (X:0~9 or X:A~Z), RBAD-WSx-915(YY)/ZZZ:(X:0~9 or X:A~Z), (Y:0~9 or Y:A~Z)/(Z:0~9 or Z:A~Z) were identical inside, the electrical circuit design, layout, components used and internal wiring, with only difference being model name.
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

3.3 Test Mode

Operating Mode	Detail Description
Working mode	Keep the EUT in Working mode
The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

3.4 Description of Test Auxiliary Equipment

Manufacturer	Description	Model	S/N	FCC ID/DoC
/	/	/	/	/

3.5 Description of Cable Used

Cable Type	Description	Length	From	To
/	/	/	/	/

3.6 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
Conducted Emission for LISN (9kHz ~ 150kHz)	3.57 dB
Conducted Emission for LISN (150kHz ~ 30MHz)	3.14 dB
Radiated Emission (30MHz ~ 200MHz) (3m SAC)	4.6 dB
Radiated Emission (200MHz ~ 1000MHz) (3m SAC)	5.8 dB
Radiated Emission (1GHz ~ 6GHz) (3m SAC)	4.5 dB
Radiated Emission (6GHz ~ 18GHz) (3m SAC)	4.7 dB

Note: All the measurement uncertainty value were shown with a coverage $k=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

3.7 Additions to, Deviations, or Exclusions from the Method

No

3.8 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L15527**

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

3.9 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info-JYTee@lets.com, Website: <http://jyt.lets.com>

3.10 Test Instruments List


Radiated Emission(3m SAC):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	ETS	9m*6m*6m	WXJ001-1	04-14-2021	04-13-2024
BiConiLog Antenna	Schwarzbeck	VULB9163	WXJ002	02-09-2023	02-08-2024
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ002-2	02-09-2023	02-08-2024
Pre-amplifier (30MHz ~ 1GHz)	Schwarzbeck	BBV9743B	WXJ001-2	01-10-2023	01-09-2024
Pre-amplifier (1GHz ~ 18GHz)	SKET	LNPA_0118G-50	WXJ001-3	01-10-2023	01-09-2024
EMI Test Receiver	Rohde & Schwarz	ESRP7	WXJ003-1	01-11-2023	01-10-2024
Spectrum Analyzer	Rohde & Schwarz	FSP 30	WXJ004	01-10-2023	01-09-2024
Coaxial Cable (30MHz ~ 1GHz)	JYTSZ	JYT3M-1G-NN-8M	WXG001-4	01-18-2023	01-17-2024
Coaxial Cable (1GHz ~ 18GHz)	JYTSZ	JYT3M-18G-NN-8M	WXG001-5	01-18-2023	01-17-2024
Band Reject Filter Group	Tonscend	JS0806-F	WXJ089	N/A	
Test Software	Tonscend	TS+	Version: 3.0.0.1		

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESR3	WXJ003-2	07-05-2023	07-04-2024
LISN	Schwarzbeck	NSLK 8127	QCJ001-13	01-10-2023	01-09-2024
LISN	Rohde & Schwarz	ESH3-Z5	WXJ005-1	01-11-2023	01-10-2024
LISN Coaxial Cable (9kHz ~ 30MHz)	JYTSZ	JYTCE-1G-NN-2M	WXG003-1	01-18-2023	01-17-2024
RF Switch	TOP PRECISION	RSU0301	WXG003	N/A	
Test Software	AUDIX	E3	Version: 6.110919b		

4 Measurement Setup and Procedure

4.1 Test Setup


1) Conducted emission measurement:




Note: The detailed descriptions please refer to Figure 8 of ANSI C63.4:2014.

2) Radiated emission measurement:

Below 1GHz (3m SAC)






4.2 Test Procedure

Test method	Test step
Conducted emission	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4 on conducted measurement.
Radiated emission	For below 1GHz: 1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m. 2. EUT works in each mode of operation that needs to be tested, and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data. For above 1GHz: 1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m. 2. EUT works in each mode of operation that needs to be tested, and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.

5.2 Conducted Emission

Product name:	Wall Switch	Product model:	RBAD-WS1-915
Test by:	Asher	Test mode:	Working mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz		




	Freq	Read Level	LISN Factor	Aux2 Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.170	22.90	0.20	10.50	0.01	33.61	54.94	-21.33	Average
2	0.170	41.92	0.20	10.50	0.01	52.63	64.94	-12.31	QP
3	0.361	23.27	0.20	10.50	0.02	33.99	48.69	-14.70	Average
4	0.406	39.81	0.20	10.50	0.04	50.55	57.73	-7.18	QP
5	0.928	40.17	0.20	10.50	0.04	50.91	56.00	-5.09	QP
6	1.135	25.66	0.20	10.50	0.08	36.44	46.00	-9.56	Average
7	3.740	30.57	0.20	10.50	0.08	41.35	56.00	-14.65	QP
8	3.881	22.97	0.20	10.50	0.08	33.75	46.00	-12.25	Average
9	5.993	27.77	0.20	10.50	0.09	38.56	60.00	-21.44	QP
10	13.197	21.76	0.20	10.50	0.11	32.57	50.00	-17.43	Average
11	15.970	27.70	0.22	10.50	0.16	38.58	60.00	-21.42	QP
12	18.426	20.89	0.27	10.50	0.15	31.81	50.00	-18.19	Average

Remark:

1. Level = Read level + LISN Factor + Cable Loss.

Product name:	Wall Switch	Product model:	RBAD-WS1-915
Test by:	Asher	Test mode:	Working mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz		



	Freq	Read Level	LISN Factor	Aux2 Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.174	22.84	0.20	10.50	0.01	33.55	54.77	-21.22	Average
2	0.174	41.61	0.20	10.50	0.01	52.32	64.77	-12.45	QP
3	0.518	24.31	0.20	10.50	0.03	35.04	46.00	-10.96	Average
4	0.567	40.14	0.20	10.50	0.02	50.86	56.00	-5.14	QP
5	0.923	39.93	0.20	10.50	0.04	50.67	56.00	-5.33	QP
6	1.197	26.92	0.23	10.50	0.09	37.74	46.00	-8.26	Average
7	3.840	25.26	0.30	10.50	0.08	36.14	46.00	-9.86	Average
8	3.943	29.66	0.30	10.50	0.08	40.54	56.00	-15.46	QP
9	10.397	22.84	0.40	10.50	0.12	33.86	50.00	-16.14	Average
10	10.733	27.67	0.40	10.50	0.12	38.69	60.00	-21.31	QP
11	13.267	27.26	0.40	10.50	0.11	38.27	60.00	-21.73	QP
12	13.408	21.81	0.40	10.50	0.11	32.82	50.00	-17.18	Average


Remark:

1. Level = Read level + LISN Factor + Cable Loss.

5.3 Radiated Emission

Below 1GHz:

Product Name:	Wall Switch	Product Model:	RBAD-WS1-915
Test By:	Kiran	Test mode:	Working mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		



Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	39.7975	50.16	-13.73	36.43	40.00	3.57	PK	Vertical
2	44.1627	52.24	-12.97	39.27	40.00	0.73	PK	Vertical
3	62.0116	45.30	-14.48	30.82	40.00	9.18	PK	Vertical
4	112.066	47.19	-15.20	31.99	43.50	11.51	PK	Vertical
5	203.978	43.93	-15.18	28.75	43.50	14.75	PK	Vertical
6	779.071	34.11	-3.86	30.25	46.00	15.75	PK	Vertical


Final Data List

NO.	Freq. [MHz]	QP Reading [dBμV/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Angle [°]	Verdict
1	44.0614	48.58	-12.97	35.61	40.00	4.39	175.7	PASS

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Wall Switch	Product Model:	RBAD-WS1-915
Test By:	Kiran	Test mode:	Working mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



Suspected Data List


NO.	Freq. [MHz]	Reading[dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	44.3082	34.06	-12.95	21.11	40.00	18.89	PK	Horizontal
2	112.017	36.94	-15.19	21.75	43.50	21.75	PK	Horizontal
3	201.213	43.13	-15.26	27.87	43.50	15.63	PK	Horizontal
4	289.730	38.35	-13.00	25.35	46.00	20.65	PK	Horizontal
5	551.789	33.82	-8.22	25.60	46.00	20.40	PK	Horizontal
6	813.508	31.31	-3.35	27.96	46.00	18.04	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Above 1GHz:

Product Name:	Wall Switch	Product Model:	RBAD-WS1-915
Test By:	Kiran	Test mode:	Working mode
Test Frequency:	1000 MHz ~ 6000 MHz	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1584.44	49.94	26.60	-23.34	50.00	23.40	AV	Vertical
2	1588.82	71.71	48.36	-23.35	70.00	21.64	PK	Vertical
3	4027.25	61.95	48.30	-13.65	74.00	25.70	PK	Vertical
4	4039.75	49.39	35.88	-13.51	54.00	18.12	AV	Vertical
5	5586.82	59.44	54.43	-5.01	74.00	19.57	PK	Vertical
6	5602.45	48.11	43.26	-4.85	54.00	10.74	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Wall Switch	Product Model:	RBAD-WS1-915
Test By:	Kiran	Test mode:	Working mode
Test Frequency:	1000 MHz ~ 6000 MHz	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2848.98	50.43	32.80	-17.63	50.00	17.20	AV	Horizontal
2	2854.60	60.96	43.37	-17.59	70.00	26.63	PK	Horizontal
3	4787.34	49.94	38.76	-11.18	54.00	15.24	AV	Horizontal
4	4787.34	61.21	50.03	-11.18	74.00	23.97	PK	Horizontal
5	5620.57	48.07	43.05	-5.02	54.00	10.95	AV	Horizontal
6	5628.07	58.84	53.75	-5.09	74.00	20.25	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

-----End of report-----