5.2 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

5.2.1 Applicable Standard

According to RSS-102 Clause 2.5.2

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

Report No.: CR221259082-00A

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

Calculated Data:

Mode	Frequency (MHz)	Antenna Gain	Conducted output power including Tune-up Tolerance	EIRP		Exemption limits (mW)
		(dBi)	(dBm)	(dBm)	(mW)	
Wi-Fi	2412-2462	2.9	18	20.9	123.03	2684
BLE	2402-2480	2.9	5.5	8.4	6.92	2676
BDR/EDR	2402-2480	2.9	6	8.9	7.76	2676
WLAN 5.2G	5180-5240	0.7	17	17.7	58.88	4525
WLAN 5.3G	5260-5320	1.9	18	19.9	97.72	4573
WLAN 5.6G	5500-5580 5660-5720	3	19	22	158.49	4714
WLAN 5.8G	5745-5825	2.8	19	21.8	151.36	4909

Note:

The Maximum Conducted Power including Tune-up Tolerance was declared by manufacturer.

The Bluetooth, WLAN 2.4G, 5G can't transmission simutenuously.

So the device is compliance exemption from Routine Evaluation Limits –RF exposure Evaluation.

Result: Compliance

===== END OF REPORT =====