

MRT Technology (Taiwan) Co., Ltd Phone: +886-3-3288388 Web: www.mrt-cert.com

Report No.: 2105TW0001-U2 Report Version: V1.0 Issue Date: 2021-07-09

MEASUREMENT REPORT

FCC PART 15 Subpart C WLAN 802.11b/g/n

FCC ID: 2ALGLX2000-MP

CASSIA NETWORKS INC **Applicant:**

Application Type: Certification

Product: X2000/ATX2000 Main PCBA

Model No.: X2000-MP

Brand Name: CASSIA

FCC Classification: Digital Transmission System (DTS)

FCC Rule Part(s): Part15 Subpart C (Section 15.247)

ANSI C63.10-2013 Test Procedure(s):

Received Date: 2020.12.23

Test Date:

2021.01.20 ~ 2021.06.15

Tested By

Reviewed By

Approved By

: kevin ker (Kevin Ker) Paddy Chen (Paddy Chen)



(Chenz Ker)

Testing Laboratory

The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.



Revision History

Report No.	Version	Description	Issue Date	Note
2105TW0001-U2	1.0	Initial Report	2021-07-09	Valid

Note: This report reused the test data from another authorized device (FCC ID: 2ALGLX2000, Original Grant Date: April 08, 2021). And add some spot check verified data according to KDB 484596 D01v01 and the difference between the FCC IDs.



CONTENTS

1. INTRODUCTION 6 1.1. Scope 6 1.2. MRT Test Location 6 2. PRODUCT INFORMATION 7 2.1. Feature of Equipment under Test 7 2.2. Product Specification Subjective to this Report 8 2.3. Working Frequencies for this report 8 2.4. Description of Available Antennas 9 2.5. Test Mode 10 2.6. Configuration of Test System 11 2.7. Test System Details 11 2.8. Description of Test Software 11 2.9. Applied Standards 12 2.10. Duty Cycle 12 2.11. Test Configuration 13 2.12. EMI Suppression Device(s)/Modifications 13 2.13. Labeling Requirements 13 3.1 DESCRIPTION of TEST 14 3.1. Evaluation Procedure 14 3.2. AC Line Conducted Emissions 15 4. ANTENNA REQUIREMENTS 16 5. TEST EQUIPMENT CALIBRATION DATE 17 6. MEASUREMENT UNCERTAINTY 19 7. L Summary 20 7.1. Summary 20 7.2. 6dB Bandwidth Meas	Des	scriptio	n	Page
1.1. Scope 6 1.2. MRT Test Location 6 2. PRODUCT INFORMATION 7 2.1. Feature of Equipment under Test 7 2.2. Product Specification Subjective to this Report 8 2.3. Working Frequencies for this report 8 2.4. Description of Available Antennas 9 2.5. Test Mode 10 2.6. Configuration of Test System 11 2.7. Test System Details 11 2.8. Description of Test Software 11 2.9. Applied Standards 12 2.10. Duty Cycle 12 2.11. Test Configuration 13 2.12. EMI Suppression Device(s)/Modifications 13 2.13. Labeling Requirements 13 3. DESCRIPTION of TEST 14 3.1. Evaluation Procedure 14 3.2. AC Line Conducted Emissions 15 4. ANTENNA REQUIREMENTS 16 5. TEST EQUIPMENT CALIBRATION DATE 17	1.	INTR	ODUCTION	6
1.2. MRT Test Location 6 2. PRODUCT INFORMATION 7 2.1. Feature of Equipment under Test 7 2.2. Product Specification Subjective to this Report 8 2.3. Working Frequencies for this report 8 2.4. Description of Available Antennas 9 2.5. Test Mode 10 2.6. Configuration of Test System 11 2.7. Test System Details 11 2.8. Description of Test System 11 2.6. Configuration of Test Software 11 2.8. Description of Test Software 11 2.9. Applied Standards 12 2.10. Duty Cycle 12 2.11. Test Configuration 13 2.12. EMI Suppression Device(s)/Modifications 13 2.13. Labeling Requirements 13 3.1 Evaluation Procedure 14 3.1. Evaluation Procedure 14 3.2. AC Line Conducted Emissions 15 4. ANTENNA REQUIREMENTS 16		1.1.	Scope	6
2. PRODUCT INFORMATION 7 2.1. Feature of Equipment under Test 7 2.2. Product Specification Subjective to this Report 8 2.3. Working Frequencies for this report 8 2.4. Description of Available Antennas 9 2.5. Test Mode 10 2.6. Configuration of Test System 11 2.7. Test System Details 11 2.8. Description of Test System 11 2.8. Description of Test System 11 2.8. Description of Test Software 12 2.10. Duty Cycle 12 2.11. Test Configuration 13 2.12. EMI Suppression Device(s)/Modifications 13 2.13. Labeling Requirements 13 3.1 Evaluation Procedure 14 3.2. AC Line Conducted Emissions 15 4. ANTENNA REQUIREMENTS 16 5. TEST EQUIPMENT CALIBRATION DATE 17 6. MEASUREMENT UNCERTAINTY 19 7.1. Summary 20		1.2.	MRT Test Location	6
2.1. Feature of Equipment under Test 7 2.2. Product Specification Subjective to this Report 8 2.3. Working Frequencies for this report. 8 2.4. Description of Available Antennas. 9 2.5. Test Mode 10 2.6. Configuration of Test System 11 2.7. Test System Details 11 2.8. Description of Test Software 11 2.7. Test System Details 11 2.8. Description of Test Software 11 2.8. Description of Test Software 12 2.10. Duty Cycle 12 2.11. Test Configuration 13 2.12. EMI Suppression Device(s)/Modifications 13 2.13. Labeling Requirements 13 3.1 Evaluation Procedure 14 3.1. Evaluation Procedure 14 3.2. AC Line Conducted Emissions 15 4. ANTENNA REQUIREMENTS 16 5. TEST EQUIPMENT CALIBRATION DATE 17 6. MEASUREMENT UNCERTAINTY	2.	PRO	DUCT INFORMATION	7
2.2. Product Specification Subjective to this Report 8 2.3. Working Frequencies for this report 8 2.4. Description of Available Antennas 9 2.5. Test Mode 10 2.6. Configuration of Test System 11 2.7. Test System Details 11 2.7. Test System Details 11 2.8. Description of Test Software 11 2.9. Applied Standards 12 2.10. Duty Cycle 12 2.11. Test Configuration 13 2.12. EMI Suppression Device(s)/Modifications 13 2.13. Labeling Requirements 13 3.1 Evaluation Procedure 14 3.1. Evaluation Procedure 14 3.2. AC Line Conducted Emissions 15 4. ANTENNA REQUIREMENTS 16 5. TEST EQUIPMENT CALIBRATION DATE 17 6. MEASUREMENT UNCERTAINTY 19 7. TEST RESULT 20 7.1. Summary 20 7.2. <td></td> <td>2.1.</td> <td>Feature of Equipment under Test</td> <td>7</td>		2.1.	Feature of Equipment under Test	7
2.3. Working Frequencies for this report. 8 2.4. Description of Available Antennas. 9 2.5. Test Mode 10 2.6. Configuration of Test System 11 2.7. Test System Details 11 2.7. Test System Details 11 2.7. Test System Details 11 2.8. Description of Test Software 11 2.9. Applied Standards 12 2.10. Duty Cycle 12 2.11. Test Configuration 13 2.12. EMI Suppression Device(s)/Modifications 13 2.13. Labeling Requirements 13 3.1 Evaluation Procedure 14 3.1. Evaluation Procedure 14 3.2. AC Line Conducted Emissions 15 4. ANTENNA REQUIREMENTS 16 5. TEST EQUIPMENT CALIBRATION DATE 17 6. MEASUREMENT UNCERTAINTY 19 7. TEST RESULT 20 7.1. Summary. 20 7.2. 6dB Bandwidt		2.2.	Product Specification Subjective to this Report	8
2.4. Description of Available Antennas. 9 2.5. Test Mode 10 2.6. Configuration of Test System 11 2.7. Test System Details 11 2.7. Test System Details 11 2.7. Test System Details 11 2.8. Description of Test Software 11 2.9. Applied Standards 12 2.10. Duty Cycle 12 2.11. Test Configuration 13 2.12. EMI Suppression Device(s)/Modifications 13 2.13. Labeling Requirements 13 3.1 Evaluation Procedure 14 3.1. Evaluation Procedure 14 3.2. AC Line Conducted Emissions 15 4. ANTENNA REQUIREMENTS 16 5. TEST EQUIPMENT CALIBRATION DATE 17 6. MEASUREMENT UNCERTAINTY 19 7. TEST RESULT 20 7.1. Summary 20 7.2. 6dB Bandwidth Measurement 21		2.3.	Working Frequencies for this report	8
2.5. Test Mode 10 2.6. Configuration of Test System 11 2.7. Test System Details 11 2.7. Test System Details 11 2.8. Description of Test Software 11 2.9. Applied Standards 12 2.10. Duty Cycle 12 2.11. Test Configuration 13 2.12. EMI Suppression Device(s)/Modifications 13 2.13. Labeling Requirements 13 2.14. Evaluation Procedure 14 3.1. Evaluation Procedure 14 3.2. AC Line Conducted Emissions 14 3.3. Radiated Emissions 15 4. ANTENNA REQUIREMENTS 16 5. TEST EQUIPMENT CALIBRATION DATE 17 6. MEASUREMENT UNCERTAINTY 19 7. TEST RESULT 20 7.1. Summary 20 7.2. 6dB Bandwidth Measurement 21		2.4.	Description of Available Antennas	9
2.6. Configuration of Test System 11 2.7. Test System Details 11 2.8. Description of Test Software 11 2.8. Description of Test Software 11 2.9. Applied Standards 12 2.10. Duty Cycle 12 2.11. Test Configuration 13 2.12. EMI Suppression Device(s)/Modifications 13 2.13. Labeling Requirements 13 2.14. Evaluation Procedure 14 3.1. Evaluation Procedure 14 3.2. AC Line Conducted Emissions 14 3.3. Radiated Emissions 15 4. ANTENNA REQUIREMENTS 16 5. TEST EQUIPMENT CALIBRATION DATE 17 6. MEASUREMENT UNCERTAINTY 19 7. TEST RESULT 20 7.1. Summary 20 7.2. 6dB Bandwidth Measurement 21		2.5.	Test Mode	10
2.7. Test System Details 11 2.8. Description of Test Software 11 2.9. Applied Standards 12 2.10. Duty Cycle 12 2.11. Test Configuration 13 2.12. EMI Suppression Device(s)/Modifications 13 2.13. Labeling Requirements 13 2.14. EVALUATION of TEST 14 3.1. Evaluation Procedure 14 3.2. AC Line Conducted Emissions 14 3.3. Radiated Emissions 15 4. ANTENNA REQUIREMENTS 16 5. TEST EQUIPMENT CALIBRATION DATE 17 6. MEASUREMENT UNCERTAINTY 19 7. TEST RESULT 20 7.1. Summary 20 7.2. 6dB Bandwidth Measurement 21		2.6.	Configuration of Test System	11
2.8. Description of Test Software. 11 2.9. Applied Standards 12 2.10. Duty Cycle. 12 2.11. Test Configuration 13 2.12. EMI Suppression Device(s)/Modifications. 13 2.13. Labeling Requirements. 13 3. DESCRIPTION of TEST. 14 3.1. Evaluation Procedure 14 3.2. AC Line Conducted Emissions 15 4. ANTENNA REQUIREMENTS. 16 5. TEST EQUIPMENT CALIBRATION DATE. 17 6. MEASUREMENT UNCERTAINTY 19 7. TEST RESULT 20 7.1. Summary. 20 7.2. 6dB Bandwidth Measurement. 21		2.7.	Test System Details	11
2.9. Applied Standards 12 2.10. Duty Cycle 12 2.11. Test Configuration 13 2.12. EMI Suppression Device(s)/Modifications 13 2.13. Labeling Requirements 13 3. DESCRIPTION of TEST 14 3.1. Evaluation Procedure 14 3.2. AC Line Conducted Emissions 15 4. ANTENNA REQUIREMENTS 16 5. TEST EQUIPMENT CALIBRATION DATE 17 6. MEASUREMENT UNCERTAINTY 19 7. TEST RESULT 20 7.1. Summary 20 7.2. 6dB Bandwidth Measurement 21		2.8.	Description of Test Software	11
2.10. Duty Cycle		2.9.	Applied Standards	12
2.11. Test Configuration 13 2.12. EMI Suppression Device(s)/Modifications 13 2.13. Labeling Requirements 13 3. DESCRIPTION of TEST 14 3.1. Evaluation Procedure 14 3.2. AC Line Conducted Emissions 14 3.3. Radiated Emissions 15 4. ANTENNA REQUIREMENTS 16 5. TEST EQUIPMENT CALIBRATION DATE 17 6. MEASUREMENT UNCERTAINTY 19 7. TEST RESULT 20 7.1. Summary 20 7.2. 6dB Bandwidth Measurement 21		2.10.	Duty Cycle	12
2.12. EMI Suppression Device(s)/Modifications. 13 2.13. Labeling Requirements. 13 3. DESCRIPTION of TEST. 14 3.1. Evaluation Procedure 14 3.2. AC Line Conducted Emissions 14 3.3. Radiated Emissions 15 4. ANTENNA REQUIREMENTS. 16 5. TEST EQUIPMENT CALIBRATION DATE. 17 6. MEASUREMENT UNCERTAINTY 19 7. TEST RESULT 20 7.1. Summary. 20 7.2. 6dB Bandwidth Measurement. 21		2.11.	Test Configuration	13
2.13. Labeling Requirements. 13 3. DESCRIPTION of TEST. 14 3.1. Evaluation Procedure 14 3.2. AC Line Conducted Emissions 14 3.3. Radiated Emissions 15 4. ANTENNA REQUIREMENTS. 16 5. TEST EQUIPMENT CALIBRATION DATE. 17 6. MEASUREMENT UNCERTAINTY 19 7. TEST RESULT 20 7.1. Summary. 20 7.2. 6dB Bandwidth Measurement. 21		2.12.	EMI Suppression Device(s)/Modifications	13
3. DESCRIPTION of TEST		2.13.	Labeling Requirements	13
3.1. Evaluation Procedure 14 3.2. AC Line Conducted Emissions 14 3.3. Radiated Emissions 15 4. ANTENNA REQUIREMENTS 16 5. TEST EQUIPMENT CALIBRATION DATE 17 6. MEASUREMENT UNCERTAINTY 19 7. TEST RESULT 20 7.1. Summary 20 7.2. 6dB Bandwidth Measurement 21	3.	DESC	RIPTION of TEST	14
3.2. AC Line Conducted Emissions 14 3.3. Radiated Emissions 15 4. ANTENNA REQUIREMENTS 16 5. TEST EQUIPMENT CALIBRATION DATE 17 6. MEASUREMENT UNCERTAINTY 19 7. TEST RESULT 20 7.1. Summary 20 7.2. 6dB Bandwidth Measurement 21		3.1.	Evaluation Procedure	14
3.3. Radiated Emissions		3.2.	AC Line Conducted Emissions	14
 ANTENNA REQUIREMENTS		3.3.	Radiated Emissions	15
 5. TEST EQUIPMENT CALIBRATION DATE	4.	ANTE	INNA REQUIREMENTS	16
6. MEASUREMENT UNCERTAINTY 19 7. TEST RESULT 20 7.1. Summary 20 7.2. 6dB Bandwidth Measurement 21	5.	TEST	EQUIPMENT CALIBRATION DATE	17
7. TEST RESULT 20 7.1. Summary 20 7.2. 6dB Bandwidth Measurement 21	6.	MEAS	SUREMENT UNCERTAINTY	19
7.1. Summary	7.	TEST	RESULT	20
7.1. Summary 20 7.2. 6dB Bandwidth Measurement 21		71	Summary	20
		7.1.	6dB Bandwidth Moasuromont	20
7.2.1 Test limit 21		721		21
7.2.7. Test Procedure used 21		722	Test Procedure used	21 21
7.2.3 Test Setting 21		722	Test Setting	21
7.2.4 Test Setup 21		724	Test Setun	···· 21
7.2.5. Test Result 22		7.2.5	Test Result	21
7.3. Output Power Measurement		7.3.	Output Power Measurement	26



Арр	Appendix C - Internal Photograph145				
Арр	Appendix B - External Photograph144				
Арр	Appendix A - Test Setup Photograph143				
8.	CONC	LUSION14	42		
	7.8.3.	Test Result14	10		
	7.8.2.	Test Setup	39		
	7.8.1.	Test Limit	39		
	7.8.	AC Conducted Emissions Measurement 13	39		
	7.7.5.	Test Result	79		
	7.7.4.	Test Setup	78		
	7.7.3.	Test Setting	77		
	7.7.2.	Test Procedure Used	77		
	7.7.1.	Test Limit	76		
	7.7.	Radiated Restricted Band Edge Measurement	76		
	7.6.5.	Test Result	47		
	7.6.4.	Test Setup	46		
	7.6.3.	Test Setting	14		
	7.6.2.	Test Procedure Used	 14		
	7.6.1.	Test Limit	14		
	7.6	Radiated Spurious Emission Measurement	44		
	7.5.5	Test Result	37		
	7.5.4	Test Setup	36		
	7.5.3	Test Setting	35		
	7.5.2	Test Procedure Used	35		
	751	Test Limit	35		
	7.5	Conducted Band Edge and Out-of-Band Emissions	35		
	745	Test Result	ر ۲1		
	7 <u>4</u> <u>4</u>	Test Setun	-9 30		
	743	Test Setting	29		
	742	Test Procedure Used	-9 29		
	7.4.1	Test Limit	20		
	7.4.	Power Spectral Density Measurement	-' 29		
	735	Test Result	-0 27		
	7.3.4	Test Setup	26		
	733	Test Setting	26		
	732	Test Procedure Lised	26		
	731	Test Limit	26		



General Information

Applicant	CASSIA NETWORKS INC		
Applicant Address	1840 Majestic Way San Jose, CA 95132,USA		
Manufacturer	CASSIA NETWORKS INC		
Manufacturer Address 1840 Majestic Way San Jose, CA 95132,USA			
Test Site	MRT Technology (Taiwan) Co., Ltd		
Test Site Address	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)		
MRT FCC Registration No.	291082		
FCC Rule Part(s) Part 15.247			
Test Device Serial No.	N/A Droduction Pre-Production Dengineering		

Test Facility / Accreditations

- 1. MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Firm.
- 2. MRT facility is an IC registered (MRT Reg. No. 21723) test laboratory with the site description on file at Industry Canada.
- MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC (Designation Number: TW3261), Industry Taiwan, EU and TELEC Rules.



1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada and Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).





2. PRODUCT INFORMATION

2.1. Feature of Equipment under Test

Product Name X2000/ATX2000 Main PCBA		
Model No.	X2000-MP	
Chip 0 Bluetooth Version	v5.0 (Single Mode)	
Chip 1 Bluetooth Version V5.0 (Single Mode)		
Wi-Fi Specification	802.11a/b/g/n/ac	
Working Voltage 12Vdc 2.0A or 57Vdc 350mA (PoE)		
D a sea a sel se		

Remark:

1. PoE adapter was selected by MRT for all testing, due to DC adapter and PoE adapter not selling with product.

2. For new device (X2000-MP), it's a PCBA, same as the internal PCBA of original device (X2000). The difference is shown in the table 1 as below.

	Table 1					
Diff	Original (X2000)	New (X2000-MP)	Remark			
1		Without Enclosure,	Remove enclosure and do not change			
I		only PCBA	PCBA design.			
2	With three internal BLE antennas	Without Internal BLE antenna	Remove BLE internal antennas, but reserve the antenna connect, the function of these internal antenna ports will be closed by software.			
3	Without Omni Antenna	Add Omni antennas for BLE and Wi-Fi 2.4G and 5G	Add some omni antennas for BLE and Wi-Fi, but the Power setting and power will not be greater than the original device under directional antennas.			



Frequency Range	802.11b/g/n-HT20: 2412 ~ 2462MHz	
Channel Number	802.11b/g/n-HT20: 11	
Type of Modulation	802.11b: DSSS	
	802.11g/n: OFDM	
Data Rate	802.11b: 1/2/5.5/11Mbps	
	802.11g: 6/9/12/18/24/36/48/54Mbps	
	802.11n: up to 72.2Mbps	

2.2. Product Specification Subjective to this Report

Note: For other features of this EUT, test report will be issued separately.

2.3. Working Frequencies for this report

802.11b/g/n-HT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz		



2.4. Description of Available Antennas

Antenna	Model No.	Manufacturer	Frequency Band	T _X	Ant Gain		
Туре			(MHz)	Paths	(dBi)		
BLE (Externa	BLE (External Antenna)						
Directional	DF24-30V14F				14.0		
Directional	DB24-40V14A				14.0		
Directional	DB24-120VH14A				14.0		
Directional	DB24-65V12A				12.0		
Directional	DF24-60V12M				12.0		
Directional	DB24-90V11A				11.0		
Directional	DF24-90V11M	5 LIIVITED			11.0		
Directional	DF24-110V10F		2402 ~ 2480 potong logy Co., td.	1	10.0		
Directional	DB24-120V10A				10.0		
Directional	DB24-120VH09A				9.0		
Directional	TDJ-2400BKC14	Kenbotong Technology Co.,			14.0		
Directional	TDJ-2400BFE				14.0		
Directional	KBT120VP13-24RT0				13.0		
Directional	TDJ-2400BKCH70	Liu.			11.0		
Directional	SPDG16T2	SuperPass			12.2		
Birootional	01 00 1012	Company Inc.			12.2		
Directional	OSCAR18	Siretta Ltd			10.0		
Directional	iANT214-2400				8.5		
Directional	iANT214-2400D	Extronics Ltd.			8.0		
Directional	iANT221				7.5		
Wi-Fi (Interna	al Antenna)						
			2412 ~ 2462	1	3.70		
PCB	N2420DTS	Airgain	5150 ~ 5725	1	6.60		
			5725 ~ 5850	1	7.30		



Wi-Fi & BLE (External Antenna)					
	iANT213-2400	Extronics Ltd.	2402 ~ 2480	1	6.0
Omni			2412 ~ 2462	1	6.0
			5150 ~ 5850	1	6.0
			2402 ~ 2480	1	6.0
Omni	iANT216M	Extronics Ltd.	2412 ~ 2462	1	6.0
			5150 ~ 5850	1	6.0
	iANT212	Extronics Ltd.	2402 ~ 2480	1	2.0
Omni			2412 ~ 2462	1	2.0
			5150 ~ 5850	1	2.0
Omni			2402 ~ 2480	1	5.0
		PCTEL, Inc.	2412 ~ 2462	1	5.0
	-1P		5150 ~ 5850	1	7.0

Note 1: Bluetooth and Wi-Fi 2.4G or Wi-Fi 5G can transmit simultaneously, but it can not transmit simultaneously between the Bluetooth chips.

Note 2: Only the directional antenna (DF24-30V14F) was selected for all test, the same power setting with the different BLE external antennas.

Note 3: The omni antenna (iANT216M) was selected for Wi-Fi 2.4G & BLE test, omni antenna (MHODB24490507NM-IP) was selected for Wi-Fi 5G test, the same power setting with the different external omni antennas.

Note 3: All messages as above are declared by manufacturer.

2.5. Test Mode

Test Mode	Mode 1: Transmit by 802.11b (1Mbps)
	Mode 2: Transmit by 802.11g (6Mbps)
	Mode 3: Transmit by 802.11n-HT20 (MCS0)



2.6. Configuration of Test System

The measurement procedures and appropriate EUT setup described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) was used in the measurement.



2.7. Test System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product		Manufacturer	Model No.	
1 PoE Adapter		N/A	N/A	
2	Notebook	DELL	Vostro 3300	

2.8. Description of Test Software

The test utility software used during testing was "SecureCRT".

Note: Final power setting please refer to operational description.



2.9. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.247
- KDB 558074 D01v05r02
- ANSI C63.10-2013

2.10. Duty Cycle

2.4GHz WLAN (DTS) operation is possible in 20MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Test Mode	Duty Cycle		
802.11b	98.79%		
802.11g	93.34%		
802.11n-HT20	92.71%		
Duty Cycle (T = Tra	nsmission Duration)		
802.11b (T=8.595ms)	802.11g (T=1.429ms)		
Report Spectram Adapter - Sweet Sal Marker 3 & 3.70000 ms Sector Marker Processor Sector Marker Processor Sector Marker Atter: 22 dB Sector Marker Avg Type: Log-Pwr Trice Processor Marker Marker Ref Offset 13.5 dB (0.500 500 500 500 500 500 500 500 500 50	Rec Offset 3actions Adulger - Sardt 3a Strice INT Aug Type Log-Part Track 2 J - Sardt 3a Marker 3 L - Sardt 3a		
Δ 4 1 1 2.27 (0) Properties 4 7 1 12.23 ms 17.46 dBm 100	Ad 1 0		



002.111-1120 (1=1.000113)
Keynglet Spectrum Analyzer - Swegt SA Ref (SG) ≪ SENSE.INT ALIGN AUTO (6443236 PM/Ab 24, 2621 Marker Marker 3 A 1.44027 ms PN0: Fast → Trig: Free Run Froint.cvm Froint.cvm Atten: 22 dB Community
Ref Offset 13.6 dB 10 dBdW Ref 25.00 dBm 0.32 dB 00 db ware 11 of those at a consistence in 47/63/4 d a di u passida da ta di
son the additional sector of the sector of t
150 50 50 50 50 50 50 50 50 50
460 W K K K K K K K K K K K K K K K K K K
Center 2.412000000 GHz Span 0 Hz Res BW 8 MHz #VBW 50 MHz Sweep 5.867 ms (2001 pts) Of
1 Δ2 1 1 (Δ) 1,335 m (Δ) 2,27 dB 2 F 1 4 1921 ms 15,81 dBm Δ Δ 1 1 (Δ) 1,440 ms (Δ) 0,32 dB 4 F 1 1 (Δ) 1,440 ms (Δ) 0,32 dB 5 F 1 1 1,521 ms 15,81 dBm 5 F
7 8 9 9 10 10

2.11. Test Configuration

The device was tested per the guidance of ANSI C63.10-2013. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.12. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.13. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.



3. DESCRIPTION of TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance was used in the measurement.

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, $50\Omega/50$ uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst-case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.



3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable. For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.



4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

The antenna of the device uses a unique connector (i-PEX connector).

Conclusion:

The unit complies with the requirement of §15.203.



5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Two-Line V-Network	DVC	ENV216	MRTTWA00019	1 year	2021/03/26
	Kao			1 year	2022/3/23
Two-Line V-Network	R&S	ENV216	MRTTWA00020	1 year	2021/04/24
				1 year	2022/4/28
EMI Test Receiver	R&S	ESR3	MRTTWA00045	1 year	2021/5/26
				1 year	2022/5/25
Temperature/Humidity Meter	TFA	35.1078.10.IT	MRTTWA00033	1 year	2021/8/28

Radiated Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00001	1 year	2021/10/5
Acitya Loop Antonna				1 year	2021/04/27
Active Loop Antenna	SCHWARZBECK	LINTE 1218D		1 year	2022/5/6
Preadband Harnantanna				1 year	2021/4/24
	SCHWARZBECK	DDHA 9120D		1 year	2022/4/21
Proithand Hornantanna				1 year	2021/4/24
	SCHWARZBECK	DDNA 9170	WRTTWA00004	1 year	2022/4/28
Proodbond Proomplifier	SCHWARZBECK	BBV 9718	MRTTWA00005	1 year	2021/4/24
Broadband Preampliner				1 year	2022/4/21
Proodbond Amplifier	SCHWARZBECK	BBV 9721	MRTTWA00006	1 year	2021/4/24
				1 year	2022/4/26
Signal Analyzar	R&S	FSV40	MRTTWA00007	1 year	2021/3/24
Signal Analyzei				1 year	2022/3/23
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2021/3/25
				1 year	2022/3/24
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2021/10/14
Antonno Cablo		SF106	MRTTWE00010	1 year	2021/6/16
	HUBERSUHNER			1 year	2022/6/15
Temperature/Humidity Meter	TFA	35.1078.10.IT	MRTTWA00032	1 year	2021/8/28





Conducted Test Equipment

Instrument	Manufacturer	Туре No.	Asset No.	Cali. Interval	Cali. Due Date
X-Series USB Peak and	KEVOLOUT			1 year	2022/4/21
Average Power Sensor	RETSIGNT	020217A		1 year	2022/4/21
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2021/10/14
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2021/7/14
Attenuetor	WTI	218FS-20	MRTTWE00026	1 year	2021/05/30
Attenuator				1 year	2022/05/30
Attenuator	WTI	04050.40	MRTTWE00027	1 year	2021/05/30
		21053-10		1 year	2022/05/30
Attenuator	WTI		MRTTWE00028	1 year	2021/05/30
		21053-00		1 year	2022/05/30
Temperature & Humidity		TTH-B3UP		1 year	2021/6/10
Chamber				1 year	2022/6/9
Temperature/Humidity Meter	TFA	35.1078.10.IT	MRTTWA00033	1 year	2021/8/28

Software	Version	Function
e3	V 9	EMI Test Software
EMI	V 3	EMI Test Software



6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

AC Conducted Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):
150kHz~30MHz: 2.53dB
Radiated Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):
9kHz ~ 1GHz: 4.25dB
1GHz ~ 40GHz: 4.45dB
Conducted Power
Measuring Uncertainty for a Level of Confidence of 95% $(U=2Uc(y))$: ± 0.84dB
Conducted Spurious Emission
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): ± 2.65 dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 3.3%
Temp. / Humidity
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): ±0.82°C/ ±3%



7. TEST RESULT

7.1. Summary

FCC	Test	Test	Test	Test	Reference
Section(s)	Description	Limit	Condition	Result	
15.247(a)(2)	6dB Bandwidth	≥ 500kHz		Pass	Section 7.2
15.247(b)(3)	Output Power	≤ 30dBm		Pass	Section 7.3
15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Conducted	Pass	Section 7.4
15.247(d)	Band Edge / Out-of-Band Emissions	≥ 30dBc (Average)		Pass	Section 7.5
15.205 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	Radiated	Pass	Section 7.6 & 7.7
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	Line Conducted	N/A	Section 7.8

Notes:

- Determining compliance is based on the test results met the regulation limits or requirements declared by clients, and the test results don't take into account the value of measurement uncertainty.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- Output power test was verified over all data rates of each mode (data refers to operational description), and then choose the maximum power output (low data rate) for the final test of each channel.
- 4) For radiated emission tests, the test results shown in the following sections represent the worst-case emissions.



7.2. 6dB Bandwidth Measurement

7.2.1.Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.

7.2.2.Test Procedure used

ANSI C63.10 - 2013 - Section 11.8

7.2.3.Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB

bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth

measurement was not influenced by any intermediate power nulls in the fundamental emission.

- 2. Set RBW = 100 kHz
- 3. VBW \geq 3 × RBW
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep = auto couple
- 7. Allow the trace was allowed to stabilize

7.2.4.Test Setup

Spectrum Analyzer





7.2.5.Test Result

Product	X2000/ATX2000 Main PCBA	Temperature	23 ~ 25°C
Test Engineer	Eric Lin	Relative Humidity	46 ~ 54%
Test Site	SR2	Test Date	2021/02/24

Test Mode	Data Rate /	Channel No.	Frequency	6dB Bandwidth	Limit	Result
	MCS		(MHz)	(MHz)	(MHz)	
802.11b	1Mbps	01	2412	8.10	≥ 0.5	Pass
802.11b	1Mbps	06	2437	8.10	≥ 0.5	Pass
802.11b	1Mbps	11	2462	8.57	≥ 0.5	Pass
802.11g	6Mbps	01	2412	16.32	≥ 0.5	Pass
802.11g	6Mbps	06	2437	16.32	≥ 0.5	Pass
802.11g	6Mbps	11	2462	16.06	≥ 0.5	Pass
802.11n-HT20	MCS0	01	2412	17.31	≥ 0.5	Pass
802.11n-HT20	MCS0	06	2437	17.05	≥ 0.5	Pass
802.11n-HT20	MCS0	11	2462	16.91	≥ 0.5	Pass















7.3. Output Power Measurement

7.3.1.Test Limit

The maximum output power shall be less 1 Watt (30dBm).

The conducted output power limit specified in paragraph FCC Part 15.247(b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs FCC Part 15.247(b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

7.3.2.Test Procedure Used

ANSI C63.10 - 2013 - Section 11.9.2.3.2

7.3.3.Test Setting

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

7.3.4.Test Setup





7.3.5.Test Result

Product	X2000/ATX2000 Main PCBA	Temperature	22 ~ 25°C
Test Engineer	Kevin Ker	Relative Humidity	46 ~ 56%
Test Site	SR2	Test Date	2021/02/08

Test Mode	Data Rate/	Channel No.	Freq.	Average	Limit	Result
	MCS		(MHz)	Power (dBm)	(dBm)	
PCB Antenna						
802.11b	1Mbps	01	2412	24.05	≤ 30.00	Pass
802.11b	1Mbps	06	2437	24.23	≤ 30.00	Pass
802.11b	1Mbps	11	2462	24.27	≤ 30.00	Pass
802.11g	6Mbps	01	2412	23.05	≤ 30.00	Pass
802.11g	6Mbps	02	2417	24.24	≤ 30.00	Pass
802.11g	6Mbps	06	2437	24.22	≤ 30.00	Pass
802.11g	6Mbps	09	2452	23.09	≤ 30.00	Pass
802.11g	6Mbps	11	2462	24.26	≤ 30.00	Pass
802.11n-HT20	MCS0	01	2412	24.26	≤ 30.00	Pass
802.11n-HT20	MCS0	02	2417	24.05	≤ 30.00	Pass
802.11n-HT20	MCS0	06	2437	24.23	≤ 30.00	Pass
802.11n-HT20	MCS0	10	2457	24.27	≤ 30.00	Pass
802.11n-HT20	MCS0	11	2462	23.05	≤ 30.00	Pass



Product	X2000/ATX2000 Main PCBA	Temperature	22 ~ 25°C	
Test Engineer	Kevin Ker	Relative Humidity	46 ~ 56%	
Test Site	SR2	Test Date	2021/06/08	

Test Mode	Data Rate/	Channel No.	Freq.	Average	Limit	Result	
	MCS		(MHz)	Power (dBm)	(dBm)		
Omni Antenna							
802.11b	1Mbps	01	2412	14.43	≤ 30.00	Pass	
802.11b	1Mbps	06	2437	14.56	≤ 30.00	Pass	
802.11b	1Mbps	11	2462	14.76	≤ 30.00	Pass	
802.11g	6Mbps	01	2412	13.53	≤ 30.00	Pass	
802.11g	6Mbps	06	2437	13.93	≤ 30.00	Pass	
802.11g	6Mbps	11	2462	12.59	≤ 30.00	Pass	
802.11n-HT20	MCS0	01	2412	13.01	≤ 30.00	Pass	
802.11n-HT20	MCS0	06	2437	13.48	≤ 30.00	Pass	
802.11n-HT20	MCS0	11	2462	13.57	≤ 30.00	Pass	



7.4. Power Spectral Density Measurement

7.4.1.Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

The same method of determining the conducted output power shall be used to determine the power

spectral density.

7.4.2.Test Procedure Used

ANSI C63.10 - 2013 - Section 11.10.5

7.4.3.Test Setting

- 1. Measure the duty cycle (x) of the transmitter output signal.
- 2. Set instrument center frequency to DTS channel center frequency.
- 3. Set span to at least 1.5 times the OBW.
- 4. RBW = 10 kHz.
- 5. VBW = 30 kHz.
- 6. Detector = RMS.
- 7. Ensure that the number of measurement points in the sweep $\ge 2 \times \text{span/RBW}$.
- 8. Sweep time = auto couple.
- 9. Don't use sweep triggering. Allow sweep to "free run".
- 10. Employ trace averaging (RMS) mode over a minimum of 100 traces.
- 11. Use the peak marker function to determine the maximum amplitude level.
- 12. Add 10 log (1/x), where x is the duty cycle measured in step (a, to the measured PSD to compute the average PSD during the actual transmission time. If measured value exceeds requirement specified by regulatory agency, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).



7.4.4.Test Setup

Spectrum Analyzer





7.4.5.Test Result

Product	X2000/ATX2000 Main PCBA	Temperature	23 ~ 25°C	
Test Engineer	Kevin Ker	Relative Humidity	46 ~ 54%	
Test Site	SR2	Test Date	2021/02/24	

Test	Data Rate/	Channel	Frequency	AVG PSD	Duty Cycle	10*log	Total PSD	Limit	Result
Mode	MCS	No.	(MHz)	(dBm/ 10kHz)	(%)	(1/x)	(dBm/ 10kHz)	(dBm / 3kHz)	
11b	1Mbps	01	2412	-11.71	98.79	0.05	-11.66	≤ 8.0	Pass
11b	1Mbps	06	2437	-11.32	98.79	0.05	-11.27	≤ 8.0	Pass
11b	1Mbps	11	2462	-11.07	98.79	0.05	-11.02	≤ 8.0	Pass
11g	6Mbps	01	2412	-11.93	93.34	0.30	-11.63	≤ 8.0	Pass
11g	6Mbps	06	2437	-11.51	93.34	0.30	-11.21	≤ 8.0	Pass
11g	6Mbps	11	2462	-11.46	93.34	0.30	-11.16	≤ 8.0	Pass
11n-HT20	MCS0	01	2412	-13.51	92.71	0.33	-13.18	≤ 8.0	Pass
11n-HT20	MCS0	06	2437	-13.47	92.71	0.33	-13.14	≤ 8.0	Pass
11n-HT20	MCS0	11	2462	-13.13	92.71	0.33	-12.80	≤ 8.0	Pass

Note:

EUT duty cycle ≥ 98%, Total AVGPSD = AVG PSD

EUT duty cycle ≤ 98%, Total AVGPSD = AVG PSD+ 10*log (1/Duty Cycle).



















7.5. Conducted Band Edge and Out-of-Band Emissions

7.5.1.Test Limit

The limit for out-of-band spurious emissions at the band edge is 30dB below the fundamental

emission level, as determined from the in-band power measurement of the DTS channel performed

in a 100 kHz bandwidth per the PSD procedure.

7.5.2.Test Procedure Used

ANSI C63.10 - 2013 - Section 11.11

7.5.3.Test Setting

Reference level measurement

- 1. Set instrument center frequency to DTS channel center frequency
- 2. Set the span to \geq 1.5 times the DTS bandwidth
- 3. Set the RBW = 100 kHz
- 4. Set the VBW \geq 3 x RBW
- 5. Detector = peak
- 6. Sweep time = auto couple
- 7. Trace mode = max hold
- 8. Allow trace to fully stabilize

Emission level measurement

- 1. Set the center frequency and span to encompass frequency range to be measured
- 2. RBW = 100KHz
- 3. VBW = 300KHz
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep time = auto couple
- 7. The trace was allowed to stabilize



7.5.4.Test Setup

Spectrum Analyzer




7.5.5.Test Result

Product	X2000/ATX2000 Main PCBA	Temperature	23 ~ 25°C
Test Engineer	Kevin Ker	Relative Humidity 46 ~ 54%	
Test Site	SR2	Test Date	2021/02/24

Test Mode	Data Rate	Channel No.	Frequency	Limit	Result
	/ MCS		(MHz)	(dBc)	
802.11b	1Mbps	01	2412	≤ 30	Pass
802.11b	1Mbps	06	2437	≤ 30	Pass
802.11b	1Mbps	11	2462	≤ 30	Pass
802.11g	6Mbps	01	2412	≤ 30	Pass
802.11g	6Mbps	06	2437	≤ 30	Pass
802.11g	6Mbps	11	2462	≤ 30	Pass
802.11n-HT20	MCS0	01	2412	≤ 30	Pass
802.11n-HT20	MCS0	06	2437	≤ 30	Pass
802.11n-HT20	MCS0	11	2462	≤ 30	Pass



























7.6. Radiated Spurious Emission Measurement

7.6.1.Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title

47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209						
Frequency	Field Strength	Measured Distance				
[MHz]	[Uv/m]	[Meters]				
0.009 - 0.490	2400/F (kHz)	300				
0.490 – 1.705	24000/F (kHz)	30				
1.705 – 30	30	30				
30 – 88	100	3				
88 – 216	150	3				
216 – 960	200	3				
Above 960	500	3				

7.6.2.Test Procedure Used

ANSI C63.10 - 2013 - Section 11.11 & 11.12

ANSI C63.10 - 2013 - Section 6.3 (General Requirements)

ANSI C63.10 - 2013 - Section 6.4 (Standard test method below 30MHz)

ANSI C63.10 - 2013 - Section 6.5 (Standard test method above 30MHz to 1GHz)

ANSI C63.10 - 2013 - Section 6.6 (Standard test method above 1GHz)

7.6.3.Test Setting

Table 1 – RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000MHz	1MHz



Quasi-Peak Measurements below 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as specified in Table 1
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

Peak Measurements above 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW; If the EUT is configured to transmit with duty cycle \ge 98%, set VBW = 10 Hz.
- If the EUT duty cycle is < 98%, set VBW \geq 1/T. T is the minimum transmission duration.
- 4. Detector = Peak
- 5. Sweep time = auto
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize



7.6.4.Test Setup

Below 1GHz Test Setup:





7.6.5.Test Result

Data for PCB Antenna

EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	20.9°C/36.3%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at Channel 2412MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		4068.500	41.63	1.11	42.73	-31.27	74.00	Peak
2		5097.000	41.64	3.85	45.49	-28.51	74.00	Peak
3	*	11132.000	32.79	17.96	50.75	-23.25	74.00	Peak

Note:

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)- Preamplifier(dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	20.9°C/36.3%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at Channel 2412MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		4825.000	42.76	3.33	46.09	-27.91	74.00	Peak
2		7460.000	36.05	11.60	47.65	-26.35	74.00	Peak
3	*	10800.500	33.09	17.50	50.58	-23.42	74.00	Peak

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)- Preamplifier(dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	20.9°C/36.3%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at Channel 2437MHz	Test Voltage	120V/60Hz



No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1		4357.500	41.14	2.07	43.21	-30.79	74.00	Peak
2		4723.000	42.04	3.09	45.13	-28.87	74.00	Peak
3	*	8046.500	36.46	12.52	48.98	-25.02	74.00	Peak

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)- Preamplifier(dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	20.9°C/36.3%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at Channel 2437MHz	Test Voltage	120V/60Hz



Na		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		3652.000	43.54	-0.32	43.22	-30.78	74.00	Peak
2		4876.000	44.56	3.45	48.01	-25.99	74.00	Peak
3	*	8097.500	35.98	12.52	48.49	-25.51	74.00	Peak

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)- Preamplifier(dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	20.9°C/36.3%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at Channel 2462MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		4774.000	41.75	3.21	44.96	-29.04	74.00	Peak
2		7468.500	35.68	11.63	47.31	-26.69	74.00	Peak
3	*	11081.000	32.21	17.89	50.10	-23.90	74.00	Peak

1. " *", means this data is the worst emission level.

2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)- Preamplifier(dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	20.9°C/36.3%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at Channel 2462MHz	Test Voltage	120V/60Hz



No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1		3694.500	44.28	-0.17	44.11	-29.89	74.00	Peak
2	*	4927.000	46.36	3.57	49.94	-24.06	74.00	Peak
3		8140.000	35.25	12.51	47.76	-26.24	74.00	Peak

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)- Preamplifier(dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	20.9°C/36.3%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11g at Channel 2412MHz	Test Voltage	120V/60Hz



No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1		4799.500	40.97	3.27	44.24	-29.76	74.00	Peak
2		8344.000	35.17	12.48	47.65	-26.35	74.00	Peak
3	*	10843.000	32.26	17.56	49.81	-24.19	74.00	Peak

1. " *", means this data is the worst emission level.

2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)- Preamplifier(dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	20.9°C/36.3%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11g at Channel 2412MHz	Test Voltage	120V/60Hz



Na		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		4825.000	41.76	3.33	45.09	-28.91	74.00	Peak
2		7715.000	36.08	12.07	48.15	-25.85	74.00	Peak
3	*	10962.000	33.07	17.73	50.80	-23.20	74.00	Peak

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)- Preamplifier(dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	20.9°C/36.3%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11g at Channel 2437MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INU		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		4791.000	40.68	3.25	43.93	-30.07	74.00	Peak
2		7409.000	35.38	11.46	46.84	-27.16	74.00	Peak
3	*	11098.000	31.51	17.91	49.42	-24.58	74.00	Peak

1. " *", means this data is the worst emission level.

2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)- Preamplifier(dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	20.9°C/36.3%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11g at Channel 2437MHz	Test Voltage	120V/60Hz



No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1		3652.000	43.75	-0.32	43.43	-30.57	74.00	Peak
2		4876.000	42.81	3.45	46.27	-27.73	74.00	Peak
3	*	10877.000	32.49	17.61	50.09	-23.91	74.00	Peak

1. " *", means this data is the worst emission level.

2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	22.2°C/35.9%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11g at Channel 2462MHz	Test Voltage	120V/60Hz



No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1		4068.500	40.89	1.11	42.00	-32.00	74.00	Peak
2		4867.500	40.35	3.43	43.78	-30.22	74.00	Peak
3	*	7460.000	36.70	11.60	48.31	-25.69	74.00	Peak

1. " *", means this data is the worst emission level.

2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)- Preamplifier(dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	22.2°C/35.9%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11g at Channel 2462MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
NO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		3694.500	43.90	-0.17	43.72	-30.28	74.00	Peak
2		4927.000	41.92	3.57	45.50	-28.50	74.00	Peak
3	*	9457.500	37.06	14.36	51.42	-22.58	74.00	Peak

1. " *", means this data is the worst emission level.

2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)- Preamplifier(dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	22.2°C/35.9%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11n-HT20 at Channel 2412MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		3890.000	41.68	0.50	42.18	-31.82	74.00	Peak
2		4935.500	39.48	3.60	43.08	-30.92	74.00	Peak
3	*	7570.500	36.89	11.83	48.72	-25.28	74.00	Peak

1. " *", means this data is the worst emission level.

2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)- Preamplifier(dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	22.2°C/35.9%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11n-HT20 at Channel 2412MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		3873.000	42.07	0.44	42.51	-31.49	74.00	Peak
2		4825.000	41.09	3.33	44.42	-29.58	74.00	Peak
3	*	8250.500	37.39	12.49	49.88	-24.12	74.00	Peak

1. " $^{\ast }$ ", means this data is the worst emission level.

2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)- Preamplifier(dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	22.2°C/35.9%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11n-HT20 at Channel 2437MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		4808.000	40.24	3.29	43.53	-30.47	74.00	Peak
2		7562.000	36.29	11.82	48.11	-25.89	74.00	Peak
3	*	10868.500	34.86	17.59	52.45	-21.55	74.00	Peak

1. " *", means this data is the worst emission level.

2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)- Preamplifier(dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	22.2°C/35.9%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11n-HT20 at Channel 2437MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		4876.000	41.39	3.45	44.84	-29.16	74.00	Peak
2		8106.000	36.13	12.51	48.65	-25.35	74.00	Peak
3	*	11047.000	34.61	17.84	52.45	-21.55	74.00	Peak

1. " *", means this data is the worst emission level.

2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)- Preamplifier(dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	22.2°C/35.9%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11n-HT20 at Channel 2462MHz	Test Voltage	120V/60Hz



No	Frequency		Reading	C.F	Measurement	Margin	Limit	Remark
NO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		5054.500	41.19	3.81	45.00	-29.00	74.00	Peak
2		7383.500	36.26	11.39	47.65	-26.35	74.00	Peak
3	*	10962.000	34.74	17.73	52.47	-21.53	74.00	Peak

1. " *", means this data is the worst emission level.

2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)- Preamplifier(dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	22.2°C/35.9%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11n-HT20 at Channel 2462MHz	Test Voltage	120V/60Hz



No	Frequency		Reading	C.F	Measurement	Margin	Limit	Remark
NO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		4918.500	41.87	3.55	45.43	-28.57	74.00	Peak
2		7383.500	36.80	11.39	48.19	-25.81	74.00	Peak
3	*	11081.000	33.89	17.89	51.78	-22.22	74.00	Peak

1. " *", means this data is the worst emission level.

2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)- Preamplifier(dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).



Data for Omni Antenna

Test Site	AC1	Test Engineer	Jay Chou				
Test Date	2021/06/09	Test Mode	802.11b				
Test Channel	01						
Remark:	1. Average measurement was no	ot performed if peak	level lower than average				
	limit.						
	2. Other frequency was 20dB below limit line within 1-18GHz, there is not show						
	in the report.						

Mark	Frequency	Reading	Factor	Measure	Limit	Margin	Detector	Polarization
	(MHz)	Level	(dB)	Level	(dBµV/m)	(dB)		
		(dBµV)		(dBµV/m)				
	8199.5	32.7	12.5	45.2	74.0	-28.8	Peak	Horizontal
	11778.0	28.1	18.1	46.2	74.0	-27.8	Peak	Horizontal
	15773.0	29.2	21.0	50.2	74.0	-23.8	Peak	Horizontal
	8284.5	32.7	12.5	45.2	74.0	-28.8	Peak	Vertical
	11395.5	26.9	18.3	45.2	74.0	-28.8	Peak	Vertical
	15824.0	28.9	20.9	49.8	74.0	-24.2	Peak	Vertical
Note: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)								
Factor	(dB) = Cable	Loss (dB) + /	Antenna Fa	actor (dB/m)	- Pre_Amplifier	[.] Gain (dE	3)	



Test Site	AC1	Test Engineer	Jay Chou				
Test Date	2021/06/09	Test Mode	802.11b				
Test Channel	06						
Remark:	1. Average measurement was no	ot performed if peak	level lower than average				
	limit.						
	2. Other frequency was 20dB below limit line within 1-18GHz, there is not show						
	in the report.						

Mark	Frequency	Reading	Factor	Measure	Limit	Margin	Detector	Polarization
	(MHz)	Level	(dB)	Level	(dBµV/m)	(dB)		
		(dBµV)		(dBµV/m)				
	8403.5	31.5	12.5	44.0	74.0	-30.0	Peak	Horizontal
	11812.0	25.2	18.1	43.3	74.0	-30.7	Peak	Horizontal
	15917.5	26.7	20.7	47.4	74.0	-26.6	Peak	Horizontal
	8403.5	32.7	12.5	45.2	74.0	-28.8	Peak	Vertical
	11888.5	27.8	18.0	45.8	74.0	-28.2	Peak	Vertical
	15543.5	27.9	21.4	49.3	74.0	-24.7	Peak	Vertical
Note: N	Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)							
Factor	(dB) = Cable	Loss (dB) + /	Antenna Fa	actor (dB/m)	- Pre_Amplifier	[.] Gain (dE	8)	



Test Site	AC1	Test Engineer	Jay Chou			
Test Date	2021/06/09	Test Mode	802.11b			
Test Channel	11					
Remark:	1. Average measurement was no	ot performed if peak	level lower than average			
	limit.					
	2. Other frequency was 20dB below limit line within 1-18GHz, there is not show					
	in the report.					

Mark	Frequency	Reading	Factor	Measure	Limit	Margin	Detector	Polarization
	(MHz)	Level	(dB)	Level	(dBµV/m)	(dB)		
		(dBµV)		(dBµV/m)				
	8284.5	32.5	12.5	45.0	74.0	-29.0	Peak	Horizontal
	11047.0	27.7	17.8	45.5	74.0	-28.5	Peak	Horizontal
	15467.0	28.0	21.5	49.5	74.0	-24.5	Peak	Horizontal
	8276.0	31.4	12.5	43.9	74.0	-30.1	Peak	Vertical
	11293.5	27.4	18.2	45.6	74.0	-28.4	Peak	Vertical
	15467.0	26.5	21.5	48.0	74.0	-26.0	Peak	Vertical
Note: N	Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)							
Factor	(dB) = Cable	Loss (dB) + /	Antenna Fa	actor (dB/m)	- Pre_Amplifier	Gain (dE	8)	



Test Site	AC1	Test Engineer	Jay Chou				
Test Date	2021/06/09	Test Mode	802.11g				
Test Channel	01						
Remark:	1. Average measurement was no	ot performed if peak	level lower than average				
	limit.						
	2. Other frequency was 20dB below limit line within 1-18GHz, there is not show						
	in the report.						

Mark	Frequency	Reading	Factor	Measure	Limit	Margin	Detector	Polarization
	(MHz)	Level	(dB)	Level	(dBµV/m)	(dB)		
		(dBµV)		(dBµV/m)				
	8293.0	32.7	12.5	45.2	74.0	-28.8	Peak	Horizontal
	12118.0	28.0	17.8	45.8	74.0	-28.2	Peak	Horizontal
	15747.5	28.1	21.0	49.1	74.0	-24.9	Peak	Horizontal
	8386.5	32.9	12.5	45.4	74.0	-28.6	Peak	Vertical
	12118.0	26.5	17.8	44.3	74.0	-29.7	Peak	Vertical
	15543.5	27.7	21.4	49.1	74.0	-24.9	Peak	Vertical
Note: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)								
Factor	(dB) = Cable	Loss (dB) + /	Antenna Fa	actor (dB/m)	- Pre_Amplifier	[.] Gain (dE	3)	



Test Site	AC1	Test Engineer	Jay Chou					
Test Date	2021/06/09	Test Mode	802.11g					
Test Channel	06							
Remark:	1. Average measurement was not performed if peak level lower than average							
	limit.							
	2. Other frequency was 20dB below limit line within 1-18GHz, there is not show							
	in the report.							

Mark	Frequency	Reading	Factor	Measure	Limit	Margin	Detector	Polarization
	(MHz)	Level	(dB)	Level	(dBµV/m)	(dB)		
		(dBµV)		(dBµV/m)				
	8344.0	32.5	12.5	45.0	74.0	-29.0	Peak	Horizontal
	11786.5	27.7	18.1	45.8	74.0	-28.2	Peak	Horizontal
	15739.0	28.9	21.0	49.9	74.0	-24.1	Peak	Horizontal
	8242.0	33.4	12.5	45.9	74.0	-28.1	Peak	Vertical
	11948.0	28.6	17.9	46.5	74.0	-27.5	Peak	Vertical
	15560.5	28.4	21.3	49.7	74.0	-24.3	Peak	Vertical
Note: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)								
Factor	(dB) = Cable	Loss (dB) + /	Antenna Fa	actor (dB/m)	- Pre_Amplifier	[.] Gain (dE	8)	



Test Site	AC1	Test Engineer	Jay Chou					
Test Date	2021/06/09	Test Mode	802.11g					
Test Channel	11							
Remark:	1. Average measurement was not performed if peak level lower than average							
	limit.							
	2. Other frequency was 20dB below limit line within 1-18GHz, there is not show							
	in the report.							

Mark	Frequency	Reading	Factor	Measure	Limit	Margin	Detector	Polarization
	(MHz)	Level	(dB)	Level	(dBµV/m)	(dB)		
		(dBµV)		(dBµV/m)				
	8284.5	32.6	12.5	45.1	74.0	-28.9	Peak	Horizontal
	11880.0	28.5	18.0	46.5	74.0	-27.5	Peak	Horizontal
	15543.5	27.6	21.4	49.0	74.0	-25.0	Peak	Horizontal
	8386.5	33.3	12.5	45.8	74.0	-28.2	Peak	Vertical
	11446.5	27.1	18.4	45.5	74.0	-28.5	Peak	Vertical
	15773.0	28.5	21.0	49.5	74.0	-24.5	Peak	Vertical
Note: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)								
Factor	(dB) = Cable	Loss (dB) + /	Antenna Fa	actor (dB/m)	- Pre_Amplifier	⁻ Gain (dE	3)	



Test Site	AC1	Test Engineer	Jay Chou					
Test Date	2021/06/09	Test Mode	802.11n-HT20					
Test Channel	01							
Remark:	1. Average measurement was not performed if peak level lower than average							
	limit.							
	2. Other frequency was 20dB below limit line within 1-18GHz, there is not show							
	in the report.							

Mark	Frequency	Reading	Factor	Measure	Limit	Margin	Detector	Polarization
	(MHz)	Level	(dB)	Level	(dBµV/m)	(dB)		
		(dBµV)		(dBµV/m)				
	8335.5	32.2	12.5	44.7	74.0	-29.3	Peak	Horizontal
	12458.0	28.5	17.9	46.4	74.0	-27.6	Peak	Horizontal
	15560.5	28.7	21.3	50.0	74.0	-24.0	Peak	Horizontal
	8284.5	32.4	12.5	44.9	74.0	-29.1	Peak	Vertical
	11659.0	27.5	18.3	45.8	74.0	-28.2	Peak	Vertical
	15739.0	28.1	21.0	49.1	74.0	-24.9	Peak	Vertical
Note: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)								
Factor	(dB) = Cable	Loss (dB) + /	Antenna Fa	actor (dB/m)	- Pre_Amplifier	[.] Gain (dE	3)	



Test Site	AC1	Test Engineer	Jay Chou					
Test Date	2021/06/09	Test Mode	802.11n-HT20					
Test Channel	06							
Remark:	1. Average measurement was not performed if peak level lower than average							
	limit.							
	2. Other frequency was 20dB below limit line within 1-18GHz, there is not show							
	in the report.							

Mark	Frequency	Reading	Factor	Measure	Limit	Margin	Detector	Polarization
	(MHz)	Level	(dB)	Level	(dBµV/m)	(dB)		
		(dBµV)		(dBµV/m)				
	8301.5	34.0	12.5	46.5	74.0	-27.5	Peak	Horizontal
	11931.0	28.5	17.9	46.4	74.0	-27.6	Peak	Horizontal
	15560.5	28.2	21.3	49.5	74.0	-24.5	Peak	Horizontal
	8335.5	45.2	12.5	57.7	74.0	-16.3	Peak	Vertical
	11642.0	28.2	18.3	46.5	74.0	-27.5	Peak	Vertical
	15577.5	29.0	21.3	50.3	74.0	-23.7	Peak	Vertical
Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)								
Factor	(dB) = Cable	Loss (dB) + /	Antenna Fa	actor (dB/m)	- Pre_Amplifier	Gain (dE	8)	


Test Site	AC1	Test Engineer	Jay Chou					
Test Date	2021/06/09	Test Mode	802.11n-HT20					
Test Channel	11							
Remark:	1. Average measurement was not performed if peak level lower than average							
	limit.							
	2. Other frequency was 20dB be	low limit line within 1	-18GHz, there is not show					
	in the report.							

Mark	Frequency	Reading	Factor	Measure	Limit	Margin	Detector	Polarization		
	(MHz)	Level	(dB)	Level	(dBµV/m)	(dB)				
		(dBµV)		(dBµV/m)						
	8284.5	33.7	12.5	46.2	74.0	-27.8	Peak	Horizontal		
	11659.0	27.7	18.3	46.0	74.0	-28.0	Peak	Horizontal		
	15450.0	27.8	21.5	49.3	74.0	-24.7	Peak	Horizontal		
	7392.0	36.9	11.4	48.3	74.0	-25.7	Peak	Vertical		
	11888.5	27.8	18.0	45.8	74.0	-28.2	Peak	Vertical		
	15764.5	28.7	21.0	49.7	74.0	-24.3	Peak	Vertical		
Note: N	Note: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)									
Factor	(dB) = Cable	Loss (dB) + /	Antenna Fa	actor (dB/m)	- Pre_Amplifier	[.] Gain (dE	3)			



The Worst Case of Radiated Emission below 1GHz:

EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-02
Factor	VULB 9162	Temp. / Humidity	21.3°C /55%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at channel 2412MHz	Test Voltage	120V/60Hz



Frequency (MHz)

No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		66.382	1.52	18.14	19.66	-20.34	40.00	QP
2		107.699	2.27	18.82	21.09	-22.41	43.50	QP
3		255.175	6.56	20.56	27.12	-18.88	46.00	QP
4		340.185	3.68	22.89	26.57	-19.43	46.00	QP
5		700.532	8.00	29.33	37.33	-8.67	46.00	QP
6	*	766.057	7.94	30.24	38.18	-7.82	46.00	QP

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.
- 5. The amplitude of Radiated emissions (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), is that proximity to ambient noise, which also are attenuated more than 20 dB below the permissible value. Therefore, the data is not presented in the report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-02
Factor	VULB 9162	Temp. / Humidity	21.3°C /55%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at channel 2412MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		54.643	-0.21	21.20	20.99	-19.01	40.00	QP
2		139.606	6.58	16.04	22.62	-20.88	43.50	QP
3		200.337	6.31	19.23	25.54	-17.96	43.50	QP
4		239.987	7.88	20.20	28.08	-17.92	46.00	QP
5		425.028	5.50	24.48	29.98	-16.02	46.00	QP
6	*	766.057	2.58	30.24	32.82	-13.18	46.00	QP

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.
- 5.The amplitude of Radiated emissions (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), is that proximity to ambient noise, which also are attenuated more than 20 dB below the permissible value. Therefore, the data is not presented in the report.



7.7. Radiated Restricted Band Edge Measurement

7.7.1.Test Limit

For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(2)
13.36 - 13.41			



All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209 Limits									
Frequency	Field Strength	Measured Distance							
[MHz]	[uV/m]	[Meters]							
0.009 - 0.490	2400/F (kHz)	300							
0.490 - 1.705	24000/F (kHz)	30							
1.705 - 30	30	30							
30 - 88	100	3							
88 - 216	150	3							
216 - 960	200	3							
Above 960	500	3							

7.7.2.Test Procedure Used

ANSI C63.10 - 2013 - Section 11.12

ANSI C63.10 - 2013 - Section 6.3 (General Requirements)

ANSI C63.10 - 2013 - Section 6.6 (Standard test method above 1GHz)

7.7.3.Test Setting

Peak Field Strength Measurements

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize



Average Measurements above 1GHz (Method VB)

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW; If the EUT is configured to transmit with duty cycle \ge 98%, set VBW = 10 Hz.

If the EUT duty cycle is < 98%, set VBW \geq 1/T. T is the minimum transmission duration.

- 4. Detector = Peak
- 5. Sweep time = auto
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

7.7.4.Test Setup





7.7.5.Test Result

DATA for PCB Antenna

EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at Channel 2412MHz	Test Voltage	120V/60Hz



No	Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1	2370.424	27.29	32.21	59.50	-14.50	74.00	Peak
2	2390.000	26.09	32.30	58.39	-15.61	74.00	Peak
3	* 2410.744	73.41	32.39	105.80	N/A	N/A	Peak

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at Channel 2412MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2390.000	14.56	32.30	46.86	-7.14	54.00	Average
2	*	2413.208	69.46	32.40	101.86	N/A	N/A	Average

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at Channel 2412MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INU		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2387.280	28.46	32.28	60.74	-13.26	74.00	Peak
2		2390.000	26.63	32.30	58.93	-15.07	74.00	Peak
3	*	2410.632	75.64	32.39	108.03	N/A	N/A	Peak

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at Channel 2412MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2390.000	14.98	32.30	47.28	-6.72	54.00	Average
2	*	2410.184	71.92	32.38	104.30	N/A	N/A	Average

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at Channel 2437MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2361.870	27.21	32.17	59.38	-14.62	74.00	Peak
2		2390.000	25.62	32.30	57.91	-16.09	74.00	Peak
3	*	2438.345	75.30	32.51	107.81	N/A	N/A	Peak
4		2483.500	26.04	32.71	58.75	-15.25	74.00	Peak
5		2492.400	26.65	32.75	59.39	-14.61	74.00	Peak

- 1. " $^{\ast }$ ", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at Channel 2437MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INU		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2390.000	14.35	32.30	46.65	-7.35	54.00	Average
2	*	2438.250	68.48	32.51	100.99	N/A	N/A	Average
3		2483.500	14.26	32.71	46.97	-7.03	54.00	Average

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at Channel 2437MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2362.535	29.04	32.18	61.21	-12.79	74.00	Peak
2		2390.000	26.21	32.30	58.51	-15.49	74.00	Peak
3	*	2435.685	75.34	32.50	107.84	N/A	N/A	Peak
4		2483.500	26.04	32.71	58.75	-15.25	74.00	Peak
5		2487.365	26.92	32.72	59.64	-14.36	74.00	Peak

- 1. " $^{\ast }$ ", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at Channel 2437MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INU		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2390.000	14.54	32.30	46.83	-7.17	54.00	Average
2	*	2436.065	72.36	32.50	104.85	N/A	N/A	Average
3		2483.500	14.39	32.71	47.10	-6.90	54.00	Average

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at Channel 2462MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1	*	2463.184	74.16	32.62	106.77	N/A	N/A	Peak
2		2483.500	26.04	32.71	58.74	-15.26	74.00	Peak
3		2485.216	26.91	32.71	59.62	-14.38	74.00	Peak

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at Channel 2462MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1	*	2461.216	70.25	32.61	102.85	N/A	N/A	Average
2		2483.500	13.80	32.71	46.51	-7.49	54.00	Average

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at Channel 2462MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1	*	2463.352	74.17	32.62	106.79	N/A	N/A	Peak
2		2483.500	27.34	32.71	60.05	-13.95	74.00	Peak
3		2483.704	27.74	32.71	60.45	-13.55	74.00	Peak

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11b at Channel 2462MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1	*	2463.232	70.98	32.62	103.60	N/A	N/A	Average
2		2483.500	15.47	32.71	48.18	-5.82	54.00	Average

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11g at Channel 2412MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2389.464	36.78	32.29	69.08	-4.92	74.00	Peak
2		2390.000	35.55	32.30	67.84	-6.16	74.00	Peak
3	*	2411.136	74.10	32.39	106.49	N/A	N/A	Peak

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11g at Channel 2412MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2390.000	18.34	32.30	50.63	-3.37	54.00	Average
2	*	2411.360	65.83	32.39	98.22	N/A	N/A	Average

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11g at Channel 2412MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2389.744	40.87	32.29	73.16	-0.84	74.00	Peak
2		2390.000	40.53	32.30	72.83	-1.17	74.00	Peak
3	*	2411.248	78.44	32.39	110.83	N/A	N/A	Peak

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11g at Channel 2412MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2390.000	21.42	32.30	53.72	-0.28	54.00	Average
2	*	2411.192	70.12	32.39	102.51	N/A	N/A	Average

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11g at Channel 2437MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2360.920	27.42	32.17	59.59	-14.41	74.00	Peak
2		2390.000	25.24	32.30	57.54	-16.46	74.00	Peak
3	*	2437.585	77.98	32.51	110.48	N/A	N/A	Peak
4		2483.500	25.81	32.71	58.52	-15.48	74.00	Peak
5		2498.290	27.14	32.77	59.92	-14.08	74.00	Peak

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11g at Channel 2437MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
NO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2390.000	15.10	32.30	47.40	-6.60	54.00	Average
2	*	2436.730	69.30	32.50	101.80	N/A	N/A	Average
3		2483.500	15.04	32.71	47.75	-6.25	54.00	Average

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11g at Channel 2437MHz	Test Voltage	120V/60Hz



Na		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2388.280	27.40	32.29	59.69	-14.31	74.00	Peak
2		2390.000	25.84	32.30	58.14	-15.86	74.00	Peak
3	*	2437.680	77.73	32.51	110.24	N/A	N/A	Peak
4		2483.500	26.60	32.71	59.31	-14.69	74.00	Peak
5		2491.070	27.59	32.74	60.33	-13.67	74.00	Peak

- 1. " $^{\ast }$ ", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11g at Channel 2437MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INU		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2390.000	15.91	32.30	48.20	-5.80	54.00	Average
2	*	2436.350	69.44	32.50	101.94	N/A	N/A	Average
3		2483.500	15.59	32.71	48.30	-5.70	54.00	Average

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11g at Channel 2462MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1	*	2461.168	77.07	32.61	109.68	N/A	N/A	Peak
2		2483.500	33.97	32.71	66.68	-7.32	74.00	Peak

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11g at Channel 2462MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1	*	2461.384	68.88	32.61	101.49	N/A	N/A	Average
2		2483.500	18.17	32.71	50.87	-3.13	54.00	Average
3		2483.752	18.32	32.71	51.03	-2.97	54.00	Average

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11g at Channel 2462MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1	*	2462.536	78.40	32.62	111.01	N/A	N/A	Peak
2		2483.500	37.13	32.71	69.84	-4.16	74.00	Peak
3		2483.752	37.64	32.71	70.35	-3.65	74.00	Peak

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11g at Channel 2462MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1	*	2461.288	70.00	32.61	102.61	N/A	N/A	Average
2		2483.500	19.91	32.71	52.61	-1.39	54.00	Average
3		2483.752	19.88	32.71	52.58	-1.42	54.00	Average

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11n-HT20 at Channel 2412MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2390.000	37.61	32.30	69.91	-4.09	74.00	Peak
2	*	2409.848	77.84	32.38	110.22	N/A	N/A	Peak

1. " *", means this data is the worst emission level.

2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11n-HT20 at Channel	Test Voltage	120V/60Hz



No		Frequency	Reading	C.⊢	Measurement	Margin	Limit	Remark
		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2390.000	20.26	32.47	52.73	-1.27	54.00	Average
2	*	2411.248	67.04	32.59	99.63	N/A	N/A	Average

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11n-HT20 at Channel 2412MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2390.000	41.27	32.30	73.57	-0.43	74.00	Peak
2	*	2410.296	79.56	32.39	111.94	N/A	N/A	Peak

1. " *", means this data is the worst emission level.

2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11n-HT20 at Channel 2412MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2390.000	20.46	32.30	52.76	-1.24	54.00	Average
2	*	2411.136	69.87	32.39	102.26	N/A	N/A	Average

1. " *", means this data is the worst emission level.

2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

4. The emission levels of other frequencies are very lower than the limit and not show in test report.





EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11n-HT20 at Channel 2437MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2370.230	27.46	32.21	59.67	-14.33	74.00	Peak
2		2390.000	25.70	32.30	58.00	-16.00	74.00	Peak
3	*	2438.345	75.95	32.51	108.46	N/A	N/A	Peak
4		2483.500	26.06	32.71	58.77	-15.23	74.00	Peak
5		2494.205	26.80	32.75	59.56	-14.44	74.00	Peak

- 1. " *", means this data is the worst emission level.
- 2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- 3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	X2000/ATX2000 Main PCBA	Date of Test	2021-03-01
Factor	BBHA 9120D	Temp. / Humidity	21.8°C/38.2%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay Chou
Test Mode	Transmit by 802.11n-HT20 at Channel 2437MHz	Test Voltage	120V/60Hz



No		Frequency	Reading	C.F	Measurement	Margin	Limit	Remark
INO		(MHz)	(dBuV)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(QP/PK/AV)
1		2390.000	15.18	32.30	47.48	-6.52	54.00	Average
2	*	2437.870	67.84	32.51	100.35	N/A	N/A	Average
3		2483.500	14.83	32.71	47.54	-6.46	54.00	Average

1. " *", means this data is the worst emission level.

2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).

3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

4. The emission levels of other frequencies are very lower than the limit and not show in test report.