

Measurement Report

Product: *Remote Control Transmitter*
Applicant: *SKYTECH II, INC.*
FCC ID: *K9LSP1001TH*
Model: *SP-1001TH (See Appendix II)*
Report No.: *MLT0504P15009*
Test Date: *May.09,2005*

Test By

Max Light Technology Co.,Ltd.

*Room 5, 8F, No.125, Section 3 Roosevelt Road,
Taipei, Taiwan., R.O.C.*

Tel: 886-2-363-2447 Fax: 886-2-363-2597

The test report consists of 35 pages in total. It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of our laboratory.



MAX LIGHT

MEASUREMENT REPORT

Page: 2/35

Table of Contents :

I. General	4.
II. Conducted Emissions Requirements	6.
III. Radiated Emissions Requirements	7.
IV. Transmitter Bandwidth Measurements	19.
V. Transmitter Duty Cycle Measurements	22.
VI. Verification of De-activation after 5 seconds	28.
Appendix I (EUT Test Setup)	32.
Appendix II (Model No. list)	33.
Appendix III (Chipset IC Photo)	34.



MAX LIGHT

MEASUREMENT REPORT

Page: 3/35

CERTIFICATION

We here by verify that :

The test data, data evaluation, test procedures and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4:2001. All test were conducted by *MLT (Max Light Technology Co.,Ltd) Room 5, 8F, No.125, Section 3 Roosevelt Road, Taipei, Taiwan, R.O.C* Also, we attest to the accuracy of each.

We further submit that the energy emitted by the sample EUT tested as described in the report is in compliance with radiated emission limit of FCC Rules Part 15 Subpart C Section 15.231.

EUT : Remote Control Transmitter

Applicant : SKYTECH II, INC.
9230 CONSERVATION WAY,
FORT WAYNE, IN 46809, U.S.A

Manufacturer : FEGO PRECISION INDUSTRIAL CO., LTD.
947 LIN SEN RD., WU-FENG
SHIANG TAICHUNG HSIEN R.O.C.

Model No : SP-1001TH (See Appendix II)

FCC ID : K9LSP1001TH

Prepared by:  Country Huang
Approved by:  Roger Chen



MAX LIGHT

MEASUREMENT REPORT

Page: 4/35

I. GENERAL

1.1 Introduction

The following measurement report is submitted on behalf of SKYTECH II, INC. In support of an Intentional Periodic Radiator certification in accordance with Part 2 Subpart J and Part 15 Subpart A And C of the Commission's and Regulations.

1.2 Description of EUT

EUT : Remote Control Transmitter

Applicant : SKYTECH II, INC.
9230 CONSERVATION WAY,
FORT WAYNE, IN 46809, U.S.A

Manufacturer : FEGO PRECISION INDUSTRIAL CO., LTD.
947 LIN SEN RD., WU-FENG
SHIANG TAICHUNG HSIEN R.O.C.

Model No : SP-1001TH

FCC ID : K9LSP1001TH

Power Type : Powered by Battery (AAA Size X2).


The EUTs(SP-1001TH) are remote transmitters and have the same circuit and PCB layout. The operation frequency is 303.87Mhz. Press the button on remote transmitter, can set the ON/OFF/MODE/SET/TIMER/Continuous Pilot button.

Note: The EUT's main DSP chip has two kind version ,the chip only difference is the IC print (See Appendix III)

1.3 Description of Support Equipment

The EUT itself forms a system. No support equipment is required for its normal operation.

1.4 Configuration of System Under Test



1.5 Test Procedure

All measurements contained in this report were performed according to the techniques described in Measurement procedure ANSI C63.4:2001 "Measurement of Intentional Radiators."

1.6 General Test Condition

The conditions under which the EUT operates were varied to determine their effect on the equipment's emission characteristics. The final configuration of the test system and the mode of operation used during these tests was chosen as that which produced the highest emission levels. However, only those conditions which the EUT was considered likely to encounter in normal use were investigated.



MAX LIGHT

MEASUREMENT REPORT

Page: 6/35

II. Conducted Emissions Requirements

The EUT operates solely by the battery. According to the rule of Section 15.207(c), the EUT exempt to the power line conducted test.



III. Radiated Emissions Requirements

3.1 General Configuration:

Prior to open-field testing, the EUT was placed in a shielded enclosure and scanned at a close distance to determine its emission characteristics. The physical arrangement of the EUT was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude, directivity, and frequency. The exact system configuration which produced the highest emissions was noted so it could be reproduced later during the open-field tests. This was done to ensure that the final measurements would demonstrate the worst-case interference potential of the EUT.

3.2 General Configuration:

Final radiation measurements were made on a three-meter, open-field test site. The EUT system was placed on a nonconductive turntable which is 0.8 meters height, top surface 1.0 x 1.5 meter. The spectrum was examined from 250 MHz to 2.5 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously & Measurements spectrum range from 30 MHz to 5 GHz is investigated.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.



MAX LIGHT

MEASUREMENT REPORT

Page: 8/35

A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

The field strength below 1 GHz was measured by EMCO Biconilog Antenna (mode 3142) at 3 Meter and the SCHWARZBECK Double Ridged Guide Antenna (model BBHA9120D&9170) was used in frequencies 1 – 40 GHz at a distance of 1 meter. All test results were extrapolated to equivalent signal at 3 meters utilizing an inverse linear distance extrapolation Factor (20dB/decade).

For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test.

The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The actual field intensity is referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

$$(1) \text{ Amplitude (dBuV/m)} = \text{FI(dBuV)} + \text{AF(dBuV)} + \text{CL(dBuV)} - \text{Gain(dB)}$$

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

P.S Amplitude is auto calculate in spectrum analyzer.

$$(2) \text{ Actual Amplitude (dBuV/m)} = \text{Amplitude (dBuV)} - \text{Duty(dB)} - \text{Dis(dB)}$$

The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:

(1) For fundamental frequency :

FUNDAMENTAL FREQUENCY (MHz), excluding restricted band frequencies of Table 2	FIELD STRENGTH OF FUNDAMENTAL microvolts/m at 3 metres, (watts, EIRP)(1)	FIELD STRENGTH OF UNWANTED EMISSIONS(1) microvolt/metre at 3 metres
40.66-40.70	See RSS-210 section 6.2.2(g).	
70-130	500 (75 nW)	50
130-174	500 to 1500*	50 to 150
174-260 (note 1)	1500 (0.68 uW)	150
260-470 (note 1)	1500 to 5,000*	150 to 500
Above 470	5,000 (7.5 uW)	500

Note : Use quasi-peak or averaging meter.

* Linear interpolation with frequency F in MHz:

For 130-174 MHz: FS (microvolts/m) = (22.73 x F) – 2454.55

For 260-470 MHz: FS (microvolts/m) = (16.67 x F) – 2833.33

nW = nanowatt (EIRP); uW = microwatt (EIRP);

(2) For spurious frequency :

Spurious emission limits = fundamental emission limit /10



MAX LIGHT

MEASUREMENT REPORT

Page: 10/35

3.3 Test Equipment List:

- A. HP 8591EM 9KHz-1.8GHz Spectrum Analyzer (S/N:73412A00230)
- B. HP 8447D Pre Amplifier (S/N:2944A08954)
- C. EMCO 3142 26MHz~2000MHz Biconilog Antenna (S/N:1184)
- D. R&S ESVP 20MHz~1300MHz Test Receiver (S/N:881121/01)
- E. Agilent E4407B 9KHz-26.5GHz Spectrum Analyzer (S/N:A872JS02291)
- F. HP 8449B 1GHZ~26.5GHZ PRE Amplifier (S/N:1982901A91)
- G. SCHWARZBECK BBHA 9120D 1GHz~18GHz Horn Antenna (S/N:141S3)
- H. SCHWARZBECK BBHA 9170 15GHz~40GHz Horn Antenna (S/N:192S5)

3.4 Test Configuration:



Front View of The Test Configuration



Rear View of The Test Configuration



MAX LIGHT

MEASUREMENT REPORT

Page: 13/35

3.5 Measurement Data Of Radiated Emissions:

3.5.1 Open Field Radiated Emissions (Horizontal/X-axis)

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarization, EUT orientation , etc. are recorded on the following

Applicant : SKYTECH II, INC.
Model No : SP-1001TH
EUT : Remote Control Transmitter
Test Date : 05/06/2005

Radiated Emissions (HORIZONTAL)								
Frequency (MHz)	Amplitude (dBuV/m)	Ant. (m)	Table (Degree)	Duty (dB)	Dist (dB)	Actual Amp (dBuV/m)	Limit (dBuV/m)	Margin (dB)
303.87	59.31	1.1	280	7.08	0	52.23	66.97	-14.74
607.50	35.28	1.3	220	7.08	0	28.20	46.97	-18.77
911.41	33.12	1.5	300	7.08	0	26.04	54.00	-27.96
1215.24	48.23	1.1	120	7.08	9.54	31.61	54.00	-22.39
1519.36	46.85	1	200	7.08	9.54	30.23	54.00	-23.77
1823.58	43.09	1	320	7.08	9.54	26.47	54.00	-27.53
2126.79	42.27	1	300	7.08	9.54	25.65	46.97	-21.32

- Notes* : 1.Margin= Amplitude - Limits
2.Distance of Measurement : 3 Meter (30-1000MHz)
3.Height of table for EUT placed: 0.8 Meter.
4.ANT= Antenna height.
5.Duty= Duty cycle correction factor.
6.Dis= Distance extrapolation factor.
7.Amplitude= Reading Amplitude – Amplifier gain+Cable loss
+Antenna factor
(Auto calculate in spectrum analyzer)
8.Actual Amp= Amplitude – Duty – Dis.
9. EUT Orthogonal Axes : X denotes Laid on Table ; Z denotes Side Stand ; Y denotes Vertical Stand.

3.5.2 Open Field Radiated Emissions (Vertical/X-axis)

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarization, EUT orientation , etc. are recorded on the following.

Applicant : SKYTECH II, INC.
 Model No : SP-1001TH
 EUT : Remote Control Transmitter
 Test Date : 05/06/2005

Radiated Emissions (VERTICAL)								
Frequency (MHz)	Amplitude (dBuV/m)	Ant. (m)	Table (Degree)	Duty (dB)	Dist (dB)	Actual Amp (dBuV/m)	Limit (dBuV/m)	Margin (dB)
303.87	62.42	1.6	300	7.08	0	55.34	66.97	-11.63
607.50	49.52	1.1	280	7.08	0	42.44	46.97	-4.53
911.41	31.07	1.3	320	7.08	0	23.99	54.00	-30.01
1215.24	50.62	1.4	270	7.08	9.54	34.00	54.00	-20.00
1519.36	49.35	1	150	7.08	9.54	32.73	54.00	-21.27
1823.58	47.58	1	190	7.08	9.54	30.96	54.00	-23.04
2126.79	46.83	1	240	7.08	9.54	30.21	46.97	-16.76

- Notes :
- 1.Margin= Amplitude - Limits
 - 2.Distance of Measurement : 3 Meter (30-1000MHz)
 - 3.Height of table for EUT placed: 0.8 Meter.
 - 4.ANT= Antenna height.
 - 5.Duty= Duty cycle correction factor.
 - 6.Dis= Distance extrapolation factor.
 - 7.Amplitude= Reading Amplitude - Amplifier gain+Cable loss
+Antenna factor
(Auto calculate in spectrum analyzer)
 - 8.Actual Amp= Amplitude - Duty - Dis.
 9. EUT Orthogonal Axes : X denotes Laid on Table ; Z denotes Side Stand ; Y denotes Vertical Stand.

3.5.3 Open Field Radiated Emissions (Horizontal/Y-axis)

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarization, EUT orientation , etc. are recorded on the following

Applicant : SKYTECH II, INC.
 Model No : SP-1001TH
 EUT : Remote Control Transmitter
 Test Date : 05/06/2005

Radiated Emissions (HORIZONTAL)								
Frequency (MHz)	Amplitude (dBuV/m)	Ant. (m)	Table (Degree)	Duty (dB)	Dist (dB)	Actual Amp (dBuV/m)	Limit (dBuV/m)	Margin (dB)
303.87	65.22	1.5	280	7.08	0	58.14	66.97	-8.83
607.62	44.68	1.2	360	7.08	0	37.60	46.97	-9.37
911.70	29.50	1.4	290	7.08	0	22.42	54.00	-31.58
1215.36	49.21	1	110	7.08	9.54	32.59	54.00	-21.41
1519.62	50.30	1	160	7.08	9.54	33.68	54.00	-20.32
1823.40	47.99	1	220	7.08	9.54	31.37	54.00	-22.63
2126.87	48.08	1	310	7.08	9.54	31.46	46.97	-15.51

- Notes :
- 1.Margin= Amplitude - Limits
 - 2.Distance of Measurement : 3 Meter (30-1000MHz)
 - 3.Height of table for EUT placed: 0.8 Meter.
 - 4.ANT= Antenna height.
 - 5.Duty= Duty cycle correction factor.
 - 6.Dis= Distance extrapolation factor.
 - 7.Amplitude= Reading Amplitude - Amplifier gain+Cable loss
+Antenna factor
(Auto calculate in spectrum analyzer)
 - 8.Actual Amp= Amplitude - Duty - Dis.
 9. EUT Orthogonal Axes : X denotes Laid on Table ; Z denotes Side Stand ; Y denotes Vertical Stand.

3.5.4 Open Field Radiated Emissions (Vertical/Y-axis)

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarization, EUT orientation , etc. are recorded on the following.

Applicant : SKYTECH II, INC.
 Model No : SP-1001TH
 EUT : Remote Control Transmitter
 Test Date : 05/06/2005

Radiated Emissions (VERTICAL)								
Frequency (MHz)	Amplitude (dBuV/m)	Ant. (m)	Table (Degree)	Duty (dB)	Dist (dB)	Actual Amp (dBuV/m)	Limit (dBuV/m)	Margin (dB)
303.87	58.44	1.3	200	7.08	0	51.36	66.97	-15.61
607.62	32.36	1.1	360	7.08	0	25.28	46.97	-21.69
911.70	28.48	1.4	340	7.08	0	21.40	54.00	-32.60
1215.36	51.16	1.6	280	7.08	9.54	34.54	54.00	-19.46
1519.62	48.92	1	270	7.08	9.54	32.30	54.00	-21.70
1823.40	49.88	1	310	7.08	9.54	33.26	54.00	-20.74
2126.87	49.97	1	280	7.08	9.54	33.35	46.97	-13.62

- Notes :
- 1.Margin= Amplitude - Limits
 - 2.Distance of Measurement : 3 Meter (30-1000MHz)
 - 3.Height of table for EUT placed: 0.8 Meter.
 - 4.ANT= Antenna height.
 - 5.Duty= Duty cycle correction factor.
 - 6.Dis= Distance extrapolation factor.
 - 7.Amplitude= Reading Amplitude - Amplifier gain+Cable loss
+Antenna factor
(Auto calculate in spectrum analyzer)
 - 8.Actual Amp= Amplitude - Duty - Dis.
 9. EUT Orthogonal Axes : X denotes Laid on Table ; Z denotes Side Stand ; Y denotes Vertical Stand.



MAX LIGHT

MEASUREMENT REPORT

Page: 17/35

3.5.5 Open Field Radiated Emissions (Horizontal/Z-axis)

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarization, EUT orientation , etc. are recorded on the following

Applicant : SKYTECH II, INC.
Model No : SP-1001TH
EUT : Remote Control Transmitter
Test Date : 05/06/2005

Radiated Emissions (HORIZONTAL)								
Frequency (MHz)	Amplitude (dBuV/m)	Ant. (m)	Table (Degree)	Duty (dB)	Dist (dB)	Actual Amp (dBuV/m)	Limit (dBuV/m)	Margin (dB)
303.87	64.64	1.1	270	7.08	0	57.56	66.97	-9.41
607.49	47.93	1.8	100	7.08	0	40.85	46.97	-6.12
911.83	30.61	1.6	190	7.08	0	23.53	54.00	-30.47
1215.19	49.98	1	280	7.08	9.54	33.36	54.00	-20.64
1519.38	47.80	1	340	7.08	9.54	31.18	54.00	-22.82
1823.65	48.06	1	290	7.08	9.54	31.44	54.00	-22.56
2126.78	45.88	1	210	7.08	9.54	29.26	46.97	-17.71

- Notes :
- 1.Margin= Amplitude - Limits
 - 2.Distance of Measurement : 3 Meter (30-1000MHz)
 - 3.Height of table for EUT placed: 0.8 Meter.
 - 4.ANT= Antenna height.
 - 5.Duty= Duty cycle correction factor.
 - 6.Dis= Distance extrapolation factor.
 - 7.Amplitude= Reading Amplitude - Amplifier gain+Cable loss
+Antenna factor
(Auto calculate in spectrum analyzer)
 - 8.Actual Amp= Amplitude - Duty - Dis.
 9. EUT Orthogonal Axes : X denotes Laid on Table ; Z denotes Side Stand ; Y denotes Vertical Stand.



MAX LIGHT

MEASUREMENT REPORT

Page: 18/35

3.5.6 Open Field Radiated Emissions (Vertical/Z-axis)

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarization, EUT orientation , etc. are recorded on the following.

Applicant : SKYTECH II, INC.
Model No : SP-1001TH
EUT : Remote Control Transmitter
Test Date : 05/06/2005

Radiated Emissions (VERTICAL)								
Frequency (MHz)	Amplitude (dBuV/m)	Ant. (m)	Table (Degree)	Duty (dB)	Dist (dB)	Actual Amp (dBuV/m)	Limit (dBuV/m)	Margin (dB)
303.87	59.29	1.2	350	7.08	0	52.21	66.97	-14.76
607.49	38.16	1.7	360	7.08	0	31.08	46.97	-15.89
911.83	29.47	1.5	240	7.08	0	22.39	54.00	-31.61
1215.19	50.92	1.4	290	7.08	9.54	34.30	54.00	-19.70
1519.38	51.26	1	200	7.08	9.54	34.64	54.00	-19.36
1823.65	48.04	1	260	7.08	9.54	31.42	54.00	-22.58
2126.78	47.77	1	210	7.08	9.54	31.15	46.97	-15.82

- Notes* :
- 1.Margin= Amplitude - Limits
 - 2.Distance of Measurement : 3 Meter (30-1000MHz)
 - 3.Height of table for EUT placed: 0.8 Meter.
 - 4.ANT= Antenna height.
 - 5.Duty= Duty cycle correction factor.
 - 6.Dis= Distance extrapolation factor.
 - 7.Amplitude= Reading Amplitude – Amplifier gain+Cable loss
+Antenna factor
(Auto calculate in spectrum analyzer)
 - 8.Actual Amp= Amplitude – Duty – Dis.
 9. EUT Orthogonal Axes : X denotes Laid on Table ; Z denotes Side Stand ; Y denotes Vertical Stand.


IV. Transmitter Bandwidth Measurement

4.1 Test Condition & Setup :

The transmitter bandwidth measurements were performed in a shielded enclosure. The EUT was placed on a wooded table which is 0.8 meters height and a near field probe was used at a distance about 20 cm for receiving. While testing, EUT was set to transmit continuously.

The resolution bandwidth of the spectrum analyzer was set to 10KHz. The detector function was set to peak and hold mode to clearly observe the components. The maximum permitted bandwidth at -20dB with respect to the reference level specified by the rule was 0.25 % of the center frequency of the EUT.

4.2 Test Instruments Configuration:





MAX LIGHT

MEASUREMENT REPORT

Page: 20/35

4.3 Test Equipment List:


- A. Tektronix FG504 0.1H~40MHz (S/N:43AS251)
- B. EMCO Near Field Probe (S/N:7901-291)
- C. HPE4407B 9KHz~26.8GHz Spectrum Analyzer (S/N: US39240419)
- D. Shielded Room (MLT-SR1)

4.4 Test Result:

Permitted Maximum Bandwidth	759.60KHz
Bandwidth Measurement	76.00KHz

4.5 Test Graphs:

See next page.



V. Transmitter Duty Cycle Measurement

5.1 Test Condition & Setup :

The transmitter bandwidth measurements were performed in a shielded enclosure. The EUT was placed on a wooded table which is 0.8 meters height and a near field probe was used at a distance about 20 cm for receiving. While testing, EUT was set to transmit continuously. Various key configurations were also investigated to find the maximum duty cycle.

The spectrum analyzer resolution bandwidth and video bandwidth were all set to 1 MHz to encompass all Significant spectral components during the test. The analyzer was operated in linear scale and zero span mode after tuning to the transmitter carrier frequency. A digital oscilloscope was connected to the aux video output of the spectrum analyzer for measuring pulse width. The pulse width was determined by the difference between the half voltage points on a pulse.


The duty cycle was determined by the following equation :

TO calculate the actual field intensity, the duty cycle correction factor in decibel is needed for later use and can be obtained from following conversion :

$$\text{Duty Cycle(\%)} = \frac{(\text{Total On Interval in a Complete Pulse Train})}{(\text{Length of a Complete Pulse Train})} \times 100\%$$

$$\text{Duty Cycle Correction Factor (dB)} = 20 \times \log_{10} (\text{Duty Cycle(\%)})$$

5.2 Test Instruments Configuration:





MAX LIGHT

MEASUREMENT REPORT

Page: 23/35

5.3 Test Equipment List:

- A. Tektronix FG504 0.1H~40MHz (S/N:43AS251)
- B. EMCO Near Field Probe (S/N:7901-291)
- C. HPE4407B 9KHz~26.8GHz Spectrum Analyzer (S/N: US39240419)
- D. Tektronix 2230 Digitizing Oscilloscope (S/N:A13F148F09)
- E. Shielded Room (MLT-SR1)


5.4 Test Result:

Pulse Train	Number of Pulse	T(ms)	Total Time (ms)
Long Pulse	19	0.9	17.10 msec
Short Pulse	13	0.375	4.875 msec


Total ON interval in a complete pulse train	21.97 msec
Length of a complete pulse train	49.68 msec
Duty Cycle (%)	44.22%
Duty Cycle Correction Factor (dB)	7.08

5.5 Test Graphs: *See next page.*


Length of A Complete Pulse Train




Long Pulse



Short Pulse



Long Pulse & Short Pulse (Number of Pulse)




VI. Verification of De-activation after 5 seconds

6.1 Test Condition & Setup :

Verification of the transmitter de-activation after 5 seconds was performed in a shielded enclosure. The EUT was placed on a wooded table which is 0.8 meters height and a near field probe was used at a distance about 20 cm for receiving.

The spectrum analyzer resolution bandwidth and video bandwidth were all set to 100KHZ to encompass all Significant spectral components during the test. The analyzer was operated in linear scale and zero span mode after tuning to the transmitter carrier frequency.

6.2 Test Instruments Configuration:



6.3 Test Equipment List:

- A. Tektronix FG504 0.1H~40MHz (S/N:43AS251)
- B. EMCO Near Field Probe (S/N:7901-291)
- C. E4407B 9KHz~26.8GHz Spectrum Analyzer (S/N: US39240419)
- D. Shielded Room (MLT-SR1)



MAX LIGHT

MEASUREMENT REPORT


Page: 29/35

6.4 Test Result:


Compliant Conditions (Section 15.231)	EUT Status	
Was the EUT manually operated ?	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
If yes, did the EUT employ a switch that would automatically deactivate the transmitter within not more than 5 seconds of being released ?	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
Was the EUT automatically activated ?	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
The devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No

Note: This device stops transmitting once the activation button is depressed.

Manually Operated




Automatically Operated



Appendix I- EUT Test SETUP

MEASUREMENT OF RADIATED EMISSION



Appendix II- Model No. List

Model	Key description
RCAF-1 , 1001THBE , CON1001TH , 1410TH-A , 1001TH-A	On , Off , Mode , Set
SR1001TH	Hi/On , Low/Off , Mode , Set
RCAF-3TH	H/L , off , Mode , Set
SP-1001TH	On/ Off , Mode, Set , Continuous Pilot
SP-1001H/LTH	ON H/L , OFF Continuous Pilot , MODE , SET
1410T/LCD-A , 1001T/LCD-A	On , Off , Timer , Set

Note: All the remote controller listed in above have the same circuit and PCB layout, the only difference is the number of the function key.

Appendix III- Chipset IC Photo (1)



Appendix III- Chipset IC Photo (2)

