

# FCC Test Report

Report No.: AGC00688211209FE02

FCC ID	:	2AMSUWBT171
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	Wireless Mouse
BRAND NAME	:	SANWA
MODEL NAME	:	GMAWBT171
APPLICANT	:	SANWA LIMITED
DATE OF ISSUE	:	Apr. 12, 2022
STANDARD(S)	:	FCC Part 15.247
<b>REPORT VERSION</b>	:	V1.0
<u>Attestation of (</u>	<u>alc</u>	bell compliance (Shenzhen) Co., Ltd

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



#### **REPORT REVISE RECORD**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Apr. 12, 2022	Valid	Initial Release



## TABLE OF CONTENTS

1. VERIFICATION OF COMPLIANCE	5
2. GENERAL INFORMATION	6
2.1. PRODUCT DESCRIPTION	6
2.2. TABLE OF CARRIER FREQUENCYS	7
2.3. RELATED SUBMITTAL(S)/GRANT(S)	
2.4. TEST METHODOLOGY	
2.5. SPECIAL ACCESSORIES	-
2.6. EQUIPMENT MODIFICATIONS	
2.7. ANTENNA REQUIREMENT	
3. MEASUREMENT UNCERTAINTY	9
4. DESCRIPTION OF TEST MODES	
5. SYSTEM TEST CONFIGURATION	11
5.1. CONFIGURATION OF TESTED SYSTEM	11
5.2. EQUIPMENT USED IN TESTED SYSTEM	11
5.3. SUMMARY OF TEST RESULTS	11
6. TEST FACILITY	
7. PEAK OUTPUT POWER	
7.1. MEASUREMENT PROCEDURE	
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
7.3. LIMITS AND MEASUREMENT RESULT	
8. BANDWIDTH	
8.1. MEASUREMENT PROCEDURE	
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
8.3. LIMITS AND MEASUREMENT RESULTS	
9. CONDUCTED SPURIOUS EMISSION	
9.1. MEASUREMENT PROCEDURE	
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
9.3. MEASUREMENT EQUIPMENT USED	
9.4. LIMITS AND MEASUREMENT RESULT	
10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY	



10.1. MEASUREMENT PROCEDURE	27
10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	27
10.3. MEASUREMENT EQUIPMENT USED	27
10.4. LIMITS AND MEASUREMENT RESULT	27
11. RADIATED EMISSION	29
11.1. MEASUREMENT PROCEDURE	29
11.2. TEST SETUP	30
11.3. LIMITS AND MEASUREMENT RESULT	31
11.4. TEST RESULT	31
12. LINE CONDUCTED EMISSION TEST	41
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST	41
12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	41
12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	42
12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	42
12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	43
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	45
APPENDIX B: PHOTOGRAPHS OF EUT	45



# **1. VERIFICATION OF COMPLIANCE**

SANWA LIMITED
Room 1005, 10/F., Tower 2, Silvercord, 30 Canton Road, Tsim Sha Tsui, Kowloon, Hong Kong, China
Dongguan ShangGui Electronics Co., Ltd.
Room 101, No.7, Yincheng 7nd Road, Xiabian Village, Chang'an Town, Dongguan City, GuangDong Province, China
Dongguan ShangGui Electronics Co., Ltd.
Room 101, No.7, Yincheng 7nd Road, Xiabian Village, Chang'an Town, Dongguan City, GuangDong Province, China
Wireless Mouse
SANWA
GMAWBT171
Mar. 21, 2022 to Apr. 12, 2022
No any deviation from the test method
Normal
Pass
AGCRT-US-BLE/RF

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC part 15.247.

Prepared By Kelly Cheng Apr. 12, 2022 (Project Engineer) **Reviewed By** Calvin Liu Apr. 12, 2022 (Reviewer) Approved By Max Zhang Apr. 12, 2022 (Authorized Officer)



# 2. GENERAL INFORMATION

### 2.1. PRODUCT DESCRIPTION

The EUT is designed as a "Wireless Mouse". It is designed by way of utilizing the GFSK technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	2.405 GHz to 2.470GHz
RF Output Power	-0.645dBm (Max)
Modulation	GFSK
Number of channels	66 Channels
Antenna Designation	PCB Antenna (Comply with requirements of the FCC part 15.203)
Antenna Gain	4.43dBi
Hardware Version	V1.0
Software Version	V1.0
Power Supply	DC 3.7V by battery or DC 5V by adapter



#### 2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency	Channel Number	Frequency	Channel Number	Frequency
	0	2405	22	2427	44	2449
	1	2406	23	2428	45	2450
	2	2407	24	2429	46	2451
	3	2408	25	2430	47	2452
	4	2409	26	2431	48	2453
	5	2410	27	2432	49	2454
	6	2411	28	2433	50	2455
	7	2412	29	2434	51	2456
	8	2413	30	2435	52	2457
	9	2414	31	2436	53	2458
	10	2415	32	2437	54	2459
2405~2470MHz	11	2416	33	2438	55	2460
	12	2417	34	2439	56	2461
	13	2418	35	2440	57	2462
	14	2419	36	2441	58	2463
	15	2420	37	2442	59	2464
	16	2421	38	2443	60	2465
	17	2422	39	2444	61	2466
	18	2423	40	2445	62	2467
	19	2424	41	2446	63	2468
	20	2425	42	2447	64	2469
	21	2426	43	2448	65	2470



#### 2.3. RELATED SUBMITTAL(S)/GRANT(S)

This submittal(s) (test report) is intended for FCC ID: 2AMSUWBT171 filing to comply with the FCC Part 15.247 requirements.

#### 2.4. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

#### **2.5. SPECIAL ACCESSORIES**

Refer to section 5.2.

#### 2.6. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

#### 2.7. ANTENNA REQUIREMENT

This intentional radiator is designed with a permanently attached antenna of an antenna to ensure that no antenna other than that furnished by the responsible party shall be used with the device. For more information of the antenna, please refer to the APPENDIX B: PHOTOGRAPHS OF EUT.



# **3. MEASUREMENT UNCERTAINTY**

The reported uncertainty of measurement y  $\pm U$ , where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 3.1 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 4.0 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.8 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_c = \pm 2 \%$
Uncertainty of Occupied Channel Bandwidth	U <sub>c</sub> = ±2 %



### **4. DESCRIPTION OF TEST MODES**

NO.	TEST MODE DESCRIPTION
1	Low channel TX
2	Middle channel TX
3	High channel TX

Note:

1. Only the result of the worst case was recorded in the report, if no other cases.

2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.

4. The EUT adjusts the frequency through the button.



# **5. SYSTEM TEST CONFIGURATION**

### **5.1. CONFIGURATION OF TESTED SYSTEM**

Radiated Emission Configure:

EUT

Conducted Emission Configure:

EUT	AE

#### **5.2. EQUIPMENT USED IN TESTED SYSTEM**

ltem	Equipment	Model No.	ID or Specification	Remark
1	Wireless Mouse	GMAWBT171	2AMSUWBT171	EUT
2	PC	Nbl-WAQ9R		AE
3	PC adapter	HW-200200CP1		AE

#### **5.3. SUMMARY OF TEST RESULTS**

FCC RULES	DESCRIPTION OF TEST	RESULT
15.247 (b)(3)	Peak Output Power	Compliant
15.247 (a)(2)	6 dB Bandwidth	Compliant
15.247 (d)	Conducted Spurious Emission	Compliant
15.247 (e)	Maximum Conducted Output Power Density	Compliant
15.209	Radiated Emission	Compliant
15.207	Conducted Emission	Compliant



# 6. TEST FACILITY

Test software

Test Site	Attestation of C	Attestation of Global Compliance (Shenzhen) Co., Ltd					
Location		1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China					
Designation Number	CN1259						
FCC Test Firm Registration Number	975832						
A2LA Cert. No.	5054.02						
Description	Attestation of C	Global Compliance (S	Shenzhen) Co., L	td is accredited t	by A2LA		
TEST EQUIPMENT OF	CONDUCTED E	MISSION TEST					
Equipment	Manufacturer Model S/N Cal. Date				Cal. Due		
TEST RECEIVER	R&S	ESPI	101206	May 15, 2021	May 14, 2022		
LISN	R&S	ESH2-Z5	100086	Jun. 09, 2021	Jun. 08, 2022		

ES-K1(Ver.V1.71)

N/A

N/A

N/A

#### TEST EQUIPMENT OF RADIATED EMISSION TEST

R&S

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due			
TEST RECEIVER	R&S	ESCI	10096	May 15, 2021	May 14, 2022			
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Nov. 17, 2021	Nov. 16, 2022			
2.4GHz Filter	EM Electronics	2400-2500MHz	N/A	Mar. 22, 2022	Mar. 21, 2024			
Attenuator	ZHINAN	E-002	N/A	Sep. 03, 2020	Sep. 02, 2022			
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Oct. 31, 2021	Oct. 30, 2023			
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	May 22, 2020	May 21, 2022			
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	Apr. 23, 2021	Apr. 22, 2022			
Broadband Preamplifier	ETS LINDGREN	3117PA	00225134	Sep. 03, 2020	Sep. 02, 2022			
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 08, 2020	Jan. 07, 2023			
Test software	Tonscend	JS32-RE (Ver.2.5)	N/A	N/A	N/A			



# 7. PEAK OUTPUT POWER


#### 7.1. MEASUREMENT PROCEDURE

For peak power test:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. RBW≥DTS bandwidth
- 3. VBW≥3\*RBW.
- 4. SPAN≥VBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.


#### 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) PEAK POWER TEST SETUP






#### 7.3. LIMITS AND MEASUREMENT RESULT

Test Data of Conducted Output Power							
Test Mode	Test Channel (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail			
	2405	-7.615	≪30	Pass			
GFSK	2430	-0.645	≪30	Pass			
	2470	-0.740	≤30	Pass			



#### **Test Graphs of Conducted Output Power**







# 8. BANDWIDTH

#### 8.1. MEASUREMENT PROCEDURE

6dB bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 kHz, VBW $\ge$ 3×RBW.
- 4. Set SPA Trace 1 Max hold, then View.

Occupied bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

# 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.


# 8.3. LIMITS AND MEASUREMENT RESULTS

Test Data of Occupied Bandwidth and DTS Bandwidth								
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (MHz)	-6dB Bandwidth (MHz)	Limits (MHz)	Pass or Fail			
	2405	1.038	0.673	≥0.5	Pass			
GFSK	2430	1.018	0.670	≥0.5	Pass			
	2470	1.027	0.681	≥0.5	Pass			





#### Test Graphs of Occupied Bandwidth









Test\_Graph\_LE1M\_ANT1\_2470\_1Mbps\_OBW

Test Graphs of DTS Bandwidth











# 9. CONDUCTED SPURIOUS EMISSION

#### 9.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

#### 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.

#### 9.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.

#### 9.4. LIMITS AND MEASUREMENT RESULT


LIMITS AND MEASUREMENT RESULT						
Applieghte Limite	Measurement Result					
Applicable Limits	Test Data	Criteria				
In any 100 kHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power.	At least -20dBc than the reference level	PASS				






Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands

















enter Freq 13.7500000	PHO: Fast	Trig: Free Run #Atten: 30 dB	Avg Type: Log-Pwr Avg[Hold>10/10	D0:38:30 PM Apr 07, 2022 TRACE TI 2 7.4 TYPE MONITOR	Frequency
dB/div Ref 20.00 dBm			Mk	r1 4.939 8 GHz -35.083 dBm	Auto Tun
g 					Center Fre 13.750000000 GH
u					Start Fre 2.50000000 GP
n1				-20.26 (8%)	Stop Fre 25.00000000 GH
0				lana la mana antonegation d	CF Ste 2.25000000 GF Auto Ma
	m//max	personal de la constante			Freq Offse 0 F
art 2.50 GHz tes BW 100 kHz	#VBW :	300 kHz	Sweep 2	Stop 25.00 GHz .152 s (30000 pts)	





#### Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands



# **10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY**

#### **10.1. MEASUREMENT PROCEDURE**

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set the SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the KDB 558074 item 8.4 was used in this testing.

#### **10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)**

Refer to Section 7.2.

#### **10.3. MEASUREMENT EQUIPMENT USED**

Refer to Section 6.


#### **10.4. LIMITS AND MEASUREMENT RESULT**

Test Data of Conducted Output Power Spectral Density							
Test Mode	Test Channel (MHz)	Power density (dBm/3kHz)	Limit (dBm/3kHz)	Pass or Fail			
	2405	-20.356	<b>≤8</b>	Pass			
GFSK	2430	-10.340	≪8	Pass			
	2470	-10.046	≪8	Pass			

#### Test Graphs of Conducted Output Power Spectral Density










# **11. RADIATED EMISSION**

#### **11.1. MEASUREMENT PROCEDURE**

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



#### 11.2. TEST SETUP





#### **11.3. LIMITS AND MEASUREMENT RESULT**

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

# 11.4. TEST RESULT


#### Radiated emission below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.



EUT	Wireless Mouse	Model Name	GMAWBT171				
Temperature	25° C	Relative Humidity	55%				
Pressure	960hPa	Test Voltage	Normal Voltage				
Test Mode	Mode 2	Antenna	Horizontal				

#### Radiated emission from 30MHz to 1000MHz




_								
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	34.85	26.94	10.70	40.00	13.06	100	207	Horizontal
2	38.73	26.54	10.73	40.00	13.46	100	224	Horizontal
3	66.86	32.41	9.76	40.00	7.59	100	200	Horizontal
4	99.84	25.52	11.30	43.50	17.98	100	289	Horizontal
5	265.71	33.27	15.04	46.00	12.73	100	73	Horizontal
6	315.18	32.93	15.09	46.00	13.07	100	207	Horizontal

#### **RESULT: PASS**



EUT	Wireless Mouse	Model Name	GMAWBT171
Temperature	25° C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Vertical



NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	34.85	31.55	10.70	40.00	8.45	100	266	Vertical
2	38.73	29.73	10.73	40.00	10.27	100	263	Vertical
3	50.37	29.15	11.64	40.00	10.85	100	214	Vertical
4	66.86	31.56	9.76	40.00	8.44	100	283	Vertical
5	125.06	23.75	13.81	43.50	19.75	100	77	Vertical
6	279.29	33.14	16.23	46.00	12.86	100	332	Vertical

# RESULT: PASS Note:

1. Factor=Antenna Factor + Cable loss, Margin=Limit-Level.

2. All test modes had been tested. The mode 2 is the worst case and recorded in the report.



#### Radiated emission above 1GHz

EUT	Wireless Mouse	Model Name	GMAWBT171
Temperature	25° C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

(dBµV/m) 74 54	(dB) -29.35 -17.94	Value Type peak AVG
54		· · · · · · · · · · · · · · · · · · ·
-	-17.94	AVG
74	-31.65	peak
54	-20.18	AVG
-		

EUT	Wireless Mouse	Model Name	GMAWBT171
Temperature	25° C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

(MHz)         (dBµV)         (dB)         (dBµV/m)         (dBµV/m)         (dB)           4810.000         46.27         0.08         46.35         74         -27.65           4810.000         35.99         0.08         36.07         54         -17.93           7215.000         42.53         2.21         44.74         74         -29.26           7215.000         31.68         2.21         33.89         54         -20.11	Value Type
4810.000         35.99         0.08         36.07         54         -17.93           7215.000         42.53         2.21         44.74         74         -29.26	
7215.000 42.53 2.21 44.74 74 -29.26	peak
	AVG
7215,000 31,68 2,21 33,89 54 -20,11	peak
	AVG
emark:	



EUT	Wireless Mouse	Model Name	GMAWBT171
Temperature	25° C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4860.000	46.55	0.14	46.69	74	-27.31	peak
4860.000	35.97	0.14	36.11	54	-17.89	AVG
7290.000	42.16	2.36	44.52	74	-29.48	peak
7290.000	32.12	2.36	34.48	54	-19.52	AVG
Remark:						
emark.						
actor = Anter	nna Factor + Cable	e Loss – Pre-	amplifier.			

EUT	Wireless Mouse	Model Name	GMAWBT171
Temperature	25° C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4860.000	46.25	0.14	46.39	74	-27.61	peak
4860.000	37.27	0.14	37.41	54	-16.59	AVG
7290.000	41.26	2.36	43.62	74	-30.38	peak
7290.000	32.69	2.36	35.05	54	-18.95	AVG
emark:						



EUT	Wireless Mouse	Model Name	GMAWBT171
Temperature	25° C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4940.000	45.97	0.22	46.19	74	-27.81	peak
4940.000	37.52	0.22	37.74	54	-16.26	AVG
7410.000	40.14	2.64	42.78	74	-31.22	peak
7410.000	30.55	2.64	33.19	54	-20.81	AVG
emark:						

EUT	Wireless Mouse	Model Name	GMAWBT171
Temperature	25° C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4940.000	45.87	0.22	46.09	74	-27.91	peak
4940.000	35.26	0.22	35.48	54	-18.52	AVG
7410.000	40.14	2.64	42.78	74	-31.22	peak
7410.000	30.55	2.64	33.19	54	-20.81	AVG
emark:						

#### **RESULT: PASS**

#### Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Margin=Level-Limit.

The "Factor" value can be calculated automatically by software of measurement system.




EUT	Wireless Mouse	Model Name	GMAWBT171
Temperature	25° C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

#### est result for band edge emission at restricted bands

Test Graph for Peak Measurement



Test Graph for Average Measurement



**RESULT: PASS** 

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd



#### Report No.: AGC00688211209FE02 Page 38 of 45

EUT	Wireless Mouse	Model Name	GMAWBT171
Temperature	25° C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement




#### **RESULT: PASS**




#### Report No.: AGC00688211209FE02 Page 39 of 45

EUT	Wireless Mouse	Model Name	GMAWBT171
Temperature	25° C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




# **RESULT: PASS**



EUT	Wireless Mouse	Model Name	GMAWBT171
Temperature	25° C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



#### **RESULT: PASS**

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



# **12. LINE CONDUCTED EMISSION TEST**


#### **12.1. LIMITS OF LINE CONDUCTED EMISSION TEST**

Frequency	Maximum RF Line Voltage				
Frequency	Q.P.( dBuV)	Average( dBuV)			
150kHz~500kHz	66-56	56-46			
500kHz~5MHz	56	46			
5MHz~30MHz	60	50			

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

#### 12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





# 12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

#### 12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.







#### MEASUREMENT RESULT: "agc\_fin"

2022/3/25 Frequen M		Transd dB	Limit dBµV	Margin dB	Detector	Line
0.1540 0.2300 0.2580 0.3060 8.5820 9.1500	00         40.10           00         34.40           00         28.20           00         27.70	6.9 6.4 6.2 6.0 6.8 6.8	66 62 60 60 60	13.7 22.3 27.1 31.9 32.3 32.4	QP QP	L1 L1 L1 L1 L1 L1

#### MEASUREMENT RESULT: "agc fin2"

2022/3/25 9:1 Frequency MHz	0 Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.150000 0.182000 0.782000 1.558000 3.118000 3.898000	36.10 30.20 24.30 24.10 23.50 24.90	6.9 6.7 5.4 6.1 6.5 6.5	56 54 46 46 46	19.9 24.2 21.7 21.9 22.5 21.1	AV AV AV AV	L1 L1 L1 L1 L1 L1

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd


 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd


 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com

 Web: http://www.agccert.com/









2022/3/25 9: Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line
0.154000	50.80	6.9	66	15.0	QP	N
0.186000	43.10	6.6	64	21.1	QP	N
0.214000	37.60	6.5	63	25.4	QP	N
0.258000	33.80	6.2	62	27.7	QP	N
0.318000	28.20	6.0	60	31.6	QP	N
8.542000	27.60	6.8	60	32.4	QP	N

#### MEASUREMENT RESULT: "agc fin2"

2022/3/25 Frequenc Mi		Transd dB	Limit dBµV	Margin dB	Detector	Line
0.1500	00 36.00	6.9	56	20.0	AV	N
0.1860	00 28.80	6.6	54	25.4	AV	N
0.7820	00 24.00	5.4	46	22.0	AV	Ν
1.5580	00 23.00	6.1	46	23.0	AV	N
3.1180	00 22.60	6.5	46	23.4	AV	N
3.8980	00 24.20	6.5	46	21.8	AV	Ν

#### **RESULT: PASS**

Note: All test modes had been pre-tested. The mode 2 is the worst case and recorded in the report.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com
 Web: http://www.agccert.com/



# **APPENDIX A: PHOTOGRAPHS OF TEST SETUP**

Refer to the Report No.: AGC00688211209AP01

# **APPENDIX B: PHOTOGRAPHS OF EUT**

Refer to the Report No.: AGC00688211209AP02

# ----END OF REPORT----



# Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.