

ANSI/IEEE Std. C95.1-2005

in accordance with the requirements of
FCC Report and Order: ET Docket 93-62



FCC TEST REPORT

For

Portable Computer

(Tested inside of Portable Computer, model P54G)

Trade Name: Qualcomm Atheros

Model: QCNFA364A

Issued to

**Qualcomm Atheros, Inc
1700 Technology Drive, san Jose, CA95110**

Issued by

Compliance Certification Services Inc.

**No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City 24891,
Taiwan. (R.O.C.)**

<http://www.ccsrf.com>

service@ccsrf.com

Issued Date: 2016/08/18



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	2016/07/20	Initial Issue	ALL	Andy Lin
01	2016/08/18	Revise module transmit configurations, Revise section 15.2.1 title describe and Wi-Fi 2.4GHz Aux value, Revise 2.4GHz SPLSR calculate result.	21,42,43	Andy Lin

Table of Contents

1	Certificate of Compliance (SAR Evaluation)	5
2	Description of Equipment Under Test	6
2.1	Summary of Highest SAR Values	7
3	Requirements for Compliance Testing Defined	8
3.1	Requirements for Compliance Testing Defined by the FCC	8
4	Dosimetric Assessment System	9
4.1	Measurement System Diagram	10
4.2	System Components	11
5	Evaluation Procedures	14
6	SAR Measurement Procedures	16
6.1	Normal SAR Test Procedure	16
7	Measurement Uncertainty	18
8	Device Under Test	19
8.1	Wireless Technologies	19
8.2	Maximum Tune-up Power	20
8.3	Simultaneous Transmission	21
9	Summary of SAR Test Exclusion Configurations	22
9.1	Standalone SAR Test Exclusion Calculations	22
9.1.1	SAR Exclusion Calculations for Wi-Fi Antenna < 50mm from the User	23
9.1.2	SAR Exclusion Calculations for Wi-Fi Antenna > 50mm from the User	24
9.1.3	SAR Required Test Configuration	25
10	Exposure Limit	26
11	Tissue Dielectric Properties	27
11.1	Test Liquid Confirmation	27
11.2	Typical Composition of Ingredients for Liquid Tissue Phantoms	28
11.3	Simulating Liquids Parameter Check Results	29
12	System Performance Check	30
12.1	System Performance Check Results	31
13	RF Output Power Measurement	32
13.1	Wi-Fi (2.4GHz Band)	33
13.2	Wi-Fi (5GHz Band)	34
13.3	Bluetooth	37
14	SAR Measurements Results	38
15	Simultaneous Transmission SAR Analysis	40
15.1	Estimated SAR for Simultaneous Transmission SAR Analysis	41

15.1.1	Estimated SAR for Bluetooth.....	41
15.2	Sum of the SAR for Simultaneous Transmission Analysis	42
15.2.1	Sum of the SAR for Wi-Fi & Wi-Fi(MIMO)	42
15.2.2	Sum of the SAR for Wi-Fi & Bluetooth	42
15.2.3	Sum of the 1g SAR for Body Exposure Condition	43
16	Equipment List & Calibration Status	44
17	Facilities	45
18	Reference	45
19	Attachments.....	46

1 Certificate of Compliance (SAR Evaluation)

Applicant Qualcomm Atheros, Inc
1700 Technology Drive, san Jose, CA95110

Equipment Under Test: Portable Computer
(Tested inside of Portable Computer, model P54G)

Trade Name: Qualcomm Atheros

Model Number: QCNFA364A

Date of Test: July 20, 2016

Device Category: PORTABLE DEVICES

Exposure Category: GENERAL POPULATION/UNCONTROLLED EXPOSURE

Applicable Standards	
FCC	● IEEE 1528 2013 ● KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04 ● KDB 447498 D01 General RF Exposure Guidance V06 ● KDB 616217 D04 SAR for laptop and tablets v01r02 ● KDB 248227 D01 SAR Measurement Guidance for 802.11 Transmitters v02r02
Limit	
1.6 W/kg	
Test Result	
Pass	


The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:

Tested by:



Scott Hsu
Section Manager
Compliance Certification Services Inc.



Andy Lin
SAR Engineer
Compliance Certification Services Inc.

2 Description of Equipment Under Test

Product	Portable Computer		
Trade Name	Qualcomm Atheros		
Model Number	QCNFA364		
RF Module	Qualcomm Atheros	Model:	QCNFA364
Test Software	QCARCT	Version	3.0.169.0
Transmitters	Wi-Fi & Bluetooth		
Modulation Technique	Bluetooth:GFSK for 1Mbps; $\pi/4$ -DQPSK for 2Mbps;8DPSK for 3Mbps		
	802.11a: Orthogonal Frequency Division Multiplexing (OFDM)		
	802.11b: Direct Sequence Spread Spectrum(DSSS)		
	802.11g: Orthogonal Frequency Division Multiplexing (OFDM)		
	802.11n: Orthogonal Frequency Division Multiplexing (OFDM)		
Antenna Specification	Ant 1	Brand name	ACON
		Parts Number	Main:APL6Y-700000 Aux:APL6Y-700000
		Type	PIFA
	Ant 2	Brand name	TE
		Parts Number	Main:1556694-2 Aux:1556694-2
		Type	PIFA
Rechargeable Li-polymer Battery–alternate	1.Brand : LG Model: PW23Y Rating: 7.6Vdc, 60Wh 2.Brand : SIMPLO Model: PW23Y Rating: 7.6Vdc, 60Wh Test is using battery No.1. There are same rating of battery, we chooses No.1 to perform the SAR testing.		

Remark:

1. The sample selected for test was prototype that representative to production product and was provided by manufacturer
2. This computer is only used for notebook mode, doesn't include tablet mode.

2.1 Summary of Highest SAR Values

Results for highest reported SAR values for each frequency band and mode

Technology/Band	Test configuration	Mode	Highest Reported 1g-SAR (W/kg)
Wi-Fi 2.4 GHz	Bottom	802.11b	1.050
Wi-Fi 5.3 GHz(U-NII 2A)	Bottom	802.11n HT40	1.079
Wi-Fi 5.5 GHz(U-NII 2C)	Bottom	802.11ac	1.200
Wi-Fi 5.8 GHz(U-NII 3)	Bottom	802.11n HT40	1.220

3 Requirements for Compliance Testing Defined


3.1 Requirements for Compliance Testing Defined by the FCC

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996 [1]. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 W/kg for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992 [6].

4 Dosimetric Assessment System

These measurements were performed with the automated near-field scanning system DASY4/DASY5 from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9 m) which positions the probes with a positional repeatability of better than ± 0.02 mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The SAR measurements were conducted with the dosimetric probe EX3DV4-SN: 3665 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure with accuracy of better than $\pm 10\%$. The spherical isotropy was evaluated with the procedure and found to be better than ± 0.25 dB. The phantom used was the SAM Twin Phantom as described in FCC supplement C, IEEE 1528 2013.

4.1 Measurement System Diagram




The DASY5 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 7 or Windows XP.
- DASY5 software version: 52.8.8.1222.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing validating the proper functioning of the system.

4.2 System Components

DASY4/DASY5 Measurement Server	
	The DASY4/DASY5 measurement server is based on a PC/104 CPU board with a 166MHz low-power Pentium, 32MB chip disk and 64MB RAM. The necessary circuits for communication with either the DAE3 electronic box as well as the 16-bit AD-converter system for optical detection and digital I/O interface are contained on the DASY4/DASY5 I/O-board, which is directly connected to the PC/104 bus of the CPU board. The measurement server performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.
	The PC-operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with two expansion slots which are reserved for future applications. Please note that the expansion slots do not have a standardized pinout and therefore only the expansion cards provided by SPEAG can be inserted. Expansion cards from any other supplier could seriously damage the measurement server. Calibration: No calibration required.
Data Acquisition Electronics (DAE)	
	The data acquisition electronics (DAE4) consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of the DAE4 box is 200MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

EX3DV4 Isotropic E-Field Probe for Dosimetric Measurements

	Construction: Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE) Calibration: Basic Broad Band Calibration in air: 10-3000 MHz. Conversion Factors (CF) for HSL 900 and HSL 1800 CF-Calibration for other liquids and frequencies upon request. Frequency: 10 MHz to > 6 GHz; Linearity: ± 0.2 dB (30 MHz to 3 GHz) Directivity: ± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in HSL (rotation normal to probe axis) Dynamic Range: 10 μW/g to > 100 mW/g; Linearity: ± 0.2 dB (noise: typically < 1 μW/g)
	Dimensions: Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Distance from probe tip to dipole centers: 1 mm Application: High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.

SAM Phantom (V4.0)

	Construction: The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 2013, CENELEC 50361 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot. Shell Thickness: 2 ± 0.2 mm Filling Volume: Approx. 25 liters Dimensions: Height: 810mm; Length: 1000mm; Width: 500mm
---	---


SAM Phantom (ELI4)

	Construction: Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with the latest draft of the standard IEC 62209 Part II and all known tissue simulating liquids. ELI4 has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is supported by software version DASY4/DASY5 and higher and is compatible with all SPEAG dosimetric probes and dipoles Shell Thickness: 2.0 ± 0.2 mm (sagging: <1%) Filling Volume: Approx. 25 liters Dimensions: Major ellipse axis: 600 mm Minor axis: 400 mm 500mm
---	---


Device Holder for SAM Twin Phantom

	Construction: In combination with the Twin SAM Phantom V4.0 or Twin SAM, the Mounting Device (made from POM) enables the rotation of the mounted transmitter in spherical coordinates, whereby the rotation point is the ear opening. The devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked at different phantom locations (left head, right head, and flat phantom).
---	---

System Validation Kits for SAM Phantom (V4.0)

	Construction: Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor. Frequency: 2450, 5300, 5600, 5800 MHz Return loss: > 20 dB at specified validation position Power capability: > 100 W (f < 1GHz); > 40 W (f > 1GHz) Dimensions: D2450V2: dipole length: 51.5 mm; overall height: 290 mm D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm
--	---

System Validation Kits for ELI4 phantom

	Construction: Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor. Frequency: 2450, 5300, 5600, 5800 MHz Return loss: > 20 dB at specified validation position Power capability: > 100 W (f < 1GHz); > 40 W (f > 1GHz) Dimensions: D2450V2: dipole length: 51.5 mm; overall height: 290 mm D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm
---	---

5 Evaluation Procedures

Data Evaluation

The DASY4/DASY5 post processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	$Norm_i, a_{i0}, a_{i1}, a_{i2}$
	- Conversion factor	$ConvF_i$
	- Diode compression point	dcp_i
Device parameters:	- Frequency	f
	- Crest factor	cf
Media parameters:	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with	V_i	= Compensated signal of channel i	(i = x, y, z)
	U_i	= Input signal of channel i	(i = x, y, z)
	cf	= Crest factor of exciting field	(DASY parameter)
	dcp_i	= Diode compression point	(DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:
$$E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

H-field probes:
$$H_i = \sqrt{V_i} \cdot \frac{a_{i10} + a_{i11}f + a_{i12}f^2}{f}$$

with	V_i	= Compensated signal of channel i	(i = x, y, z)
	$Norm_i$	= Sensor sensitivity of channel i	(i = x, y, z)

$\mu V/(V/m)^2$ for E0field Probes

$ConvF$	= Sensitivity enhancement in solution
a_{ij}	= Sensor sensitivity factors for H-field probes
f	= Carrier frequency (GHz)
E_i	= Electric field strength of channel i in V/m
H_i	= Magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with

SAR	= local specific absorption rate in W/kg
E_{tot}	= total field strength in V/m
σ	= conductivity in [mho/m] or [Siemens/m]
ρ	= equivalent tissue density in g/cm ³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{377} \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

with

P_{pwe}	= Equivalent power density of a plane wave in mW/cm ²
E_{tot}	= total electric field strength in V/m
H_{tot}	= total magnetic field strength in A/m

6 SAR Measurement Procedures

6.1 Normal SAR Test Procedure

- **Power Reference Measurement**

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

- **Area Scan**

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in DASY4/DASY5 software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the area scan's property sheet is brought-up, the grid resolution has to less than 15 mm by 15 mm at frequency ≤ 2 GHz; the grid resolution has to less than 12mm by 12 mm at frequency between 2GHz to 4GHz; grid resolution has to less than 10 mm by 10 mm at frequency between 4GHz to 6GHz.

According to KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

- Zoom Scan**

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default zoom scan measures points in accordance with the frequency can be divided into three parts. (1)The zoom scan volume was set to 5x5x7 points at frequency ≤ 2 GHz. (2) The zoom scan volume was set to 7x7x7 points at frequency between 2GHz to 4GHz (3) The zoom scan volume was set to 7x7x12 points at frequency between 4GHz to 6GHz. The measures points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more then one maximum, the number of Zoom Scans has to be enlarged accordingly.

According to KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm	3 – 4 GHz: ≤ 5 mm 4 – 6 GHz: ≤ 4 mm
Maximum zoom scan spatial resolution, normal to phantom surface	Uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$:between 1 st two points losest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Maximum zoom scan volume	x, y, z	≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm	

- Power Drift Measurement**

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have DASY4/DASY5 software stop the measurements if this limit is exceeded.

- Z-Scan**

The Z Scan job measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. A user can anchor the grid to the current probe location. As with any other grids, the local Z-axis of the anchor location establishes the Z-axis of the grid.

7 Measurement Uncertainty

According to KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz section 2.8.2, SAR measurement uncertainty analysis is required in SAR reports only when the highest measured SAR in a frequency band is ≥ 1.5 W/kg for 1-g SAR, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.

8 Device Under Test

8.1 Wireless Technologies

Wireless technologies	Tx Frequency Bands	Operating mode	Duty Cycle used for testing
Wi-Fi	2.4GHz Band	802.11b 802.11g 802.11n(HT20) 802.11n(HT40)	100%
	5GHz Band	802.11a 802.11n(HT20) 802.11n(HT40) 802.11ac(VHT20) 802.11ac(VHT40) 802.11ac(VHT80)	100%
Bluetooth	2.4GHz	2.1 4.1	N/A

8.2 Maximum Tune-up Power

Tolerance (dB): ± 1.5		RF Output Power (dBm)	
Band (GHz)	Mode	Target	Max. tune-up power
2.4	802.11b	19.0	20.5
	802.11g	18.0	19.5
	802.11n HT20	18.0	19.5
	802.11n HT40	17.0	18.5
Tolerance (dB): ± 2.0		RF Output Power (dBm)	
Band (GHz)	Mode	Target	Max. tune-up power
5.2 (UNII-1)	802.11a	13.0	15.0
	802.11n HT20	13.0	15.0
	802.11n HT40	13.0	15.0
	802.11ac VHT20	13.0	15.0
	802.11ac VHT40	13.0	15.0
	802.11ac VHT80	13.0	15.0
5.3 (UNII-2A)	802.11a	17.0	19.0
	802.11n HT20	17.0	19.0
	802.11n HT40	17.0	19.0
	802.11ac VHT20	17.0	19.0
	802.11ac VHT40	17.0	19.0
	802.11ac VHT80	12.0	14.0
5.5 (UNII-2C)	802.11a	16.0	18.0
	802.11n HT20	16.0	18.0
	802.11n HT40	16.0	18.0
	802.11ac VHT20	16.0	18.0
	802.11ac VHT40	16.0	18.0
	802.11ac VHT80	16.0	18.0
5.8 (UNII-3)	802.11a	17.0	19.0
	802.11n HT20	17.0	19.0
	802.11n HT40	17.0	19.0
	802.11ac VHT20	17.0	19.0
	802.11ac VHT40	17.0	19.0
	802.11ac VHT80	12.0	14.0
Bluetooth		7.0	

Note(s):

- For Bluetooth the Average power is included in manufacturing tolerance.

8.3 Simultaneous Transmission

RF Exposure Condition	Transmit Configurations
Wi-Fi	2.4GHz(Chain 0 + Chain 1) 2.4GHz(Chain 1) + Bluetooth (Chain 0) 5GHz(Chain 0 + Chain 1) 5GHz(Chain 1) + Bluetooth (Chain 0) Bluetooth (Chain 0)

Note(s):

1. The Chain 0 and Chain 1 can be used as transmitting or receiving antennas, and the Bluetooth used the Chain 0 antenna can be transmitting or receiving antenna.

9 Summary of SAR Test Exclusion Configurations

9.1 Standalone SAR Test Exclusion Calculations

Since the Dedicated Host Approach is applied, the standalone SAR test exclusion procedure in KDB 447498 section 4.3.1 is applied in conjunction with KDB 616217 section 4.3 to determine the minimum test separation distance:

1. According to KDB 447498 Section 4.1 5) if the antenna is at close proximity to user then the outer surface of the DUT should be treated as the radiating surface. The test separation distance is then determined by the smallest distance between the outer surface of the device and the user. For the purposes of this report close proximity has been defined as closer than 50 mm. For antennas <50 mm from the rear or edge the separation distance used for the estimated SAR calculations is 0 mm.
2. When the minimum test separation distance is < 5mm, a distance of 5mm is applied to determine SAR test exclusion.
3. When the separation distance from the antenna to an adjacent edge is > 5 mm, the actual antenna-to-edge separation distance is applied to determine SAR test exclusion.
4. If the antenna to DUT adjacent edge or bottom separation distance >50mm the actual antenna to user separation distance is used to determine SAR exclusion and estimated SAR value.

Refer to Appendix for the specific details on the antenna-to-antenna and antenna-to-edge distances used for test exclusion calculations.

9.1.1 SAR Exclusion Calculations for Wi-Fi Antenna < 50mm from the User

According to KDB 447498 v05 r02 in section 4.3.1, if the calculated **threshold value** is > 3 then SAR testing is required.

Antenna	Band	Frequency (MHz)	Output Power		Separation Distances(mm)					Calculated Threshold Value				
			dBm	mW	Bottom	Edge1	Edge2	Edge3	Edge4	Bottom	Edge1	Edge2	Edge3	Edge4
Wi-Fi Main	2.4GHz	2437	15.5	35	11.0					5.0				
	5.2GHz	5210	15.0	32	11.0					6.6				
	5.3GHz	5270	19.0	79	11.0					16.5				
	5.5GHz	5690	18.0	63	11.0					13.7				
	5.8GHz	5795	19.0	79	11.0					17.3				
	Bluetooth	2402	7.0	5	11.0					0.7				

Antenna	Band	Frequency (MHz)	Output Power		Separation Distances(mm)					Calculated Threshold Value				
			dBm	mW	Bottom	Edge1	Edge2	Edge3	Edge4	Bottom	Edge1	Edge2	Edge3	Edge4
Wi-Fi Aux	2.4GHz	2437	15.5	35	11.0					5.0				
	5.2GHz	5210	15.0	32	11.0					6.6				
	5.3GHz	5270	19.0	79	11.0					16.5				
	5.5GHz	5690	18.0	63	11.0					13.7				
	5.8GHz	5795	19.0	79	11.0					17.3				
	Bluetooth	2402	7.0	5	11.0					0.7				

9.1.2 SAR Exclusion Calculations for Wi-Fi Antenna > 50mm from the User

According to KDB 447498 v05 r02, if the calculated Power threshold is less than the output power then SAR testing is required.

Antenna	Band	Frequency (MHz)	Output Power		Separation Distances(mm)					Calculated Threshold Value				
			dBm	mW	Bottom	Edge1	Edge2	Edge3	Edge4	Bottom	Edge1	Edge2	Edge3	Edge4
Wi-Fi Main	2.4GHz	2437	15.5	35	11.0					<50mm				
	5.2GHz	5210	15.0	32	11.0					<50mm				
	5.3GHz	5270	19.0	79	11.0					<50mm				
	5.5GHz	5690	18.0	63	11.0					<50mm				
	5.8GHz	5795	19.0	79	11.0					<50mm				
	Bluetooth	2402	7.0	5	11.0					<50mm				

Antenna	Band	Frequency (MHz)	Output Power		Separation Distances(mm)					Calculated Threshold Value				
			dBm	mW	Bottom	Edge1	Edge2	Edge3	Edge4	Bottom	Edge1	Edge2	Edge3	Edge4
Wi-Fi Aux	2.4GHz	2437	15.5	35	11.0					<50mm				
	5.2GHz	5210	15.0	32	11.0					<50mm				
	5.3GHz	5270	19.0	79	11.0					<50mm				
	5.5GHz	5690	18.0	63	11.0					<50mm				
	5.8GHz	5795	19.0	79	11.0					<50mm				
	Bluetooth	2402	7.0	5	11.0					<50mm				

9.1.3 SAR Required Test Configuration For Wi-Fi and Bluetooth

Test Configurations	Bottom	Edge1	Edge2	Edge3	Edge4
Wi-Fi Main 2.4GHz	YES	No	No	No	No
Wi-Fi Main 5.2GHz	YES	No	No	No	No
Wi-Fi Main 5.3GHz	YES	No	No	No	No
Wi-Fi Main 5.5GHz	YES	No	No	No	No
Wi-Fi Main 5.8GHz	YES	No	No	No	No
Bluetooth	No	No	No	No	No

Note(s):

1. Yes = SAR is required.
2. No = SAR is not required.

10 Exposure Limit

(A). Limits for Occupational/Controlled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
0.4	8.0	2.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Population/Uncontrolled Environments:

are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Occupational/Controlled Environments:

are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE

GENERAL POPULATION/UNCONTROLLED EXPOSURE

PARTIAL BODY LIMIT

1.6 W/kg

11 Tissue Dielectric Properties

11.1 Test Liquid Confirmation

Simulating Liquids Parameter Check

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values

The relative permittivity and conductivity of the tissue material should be within $\pm 5\%$ of the values given in the table below. 5% may not be easily achieved at certain frequencies.

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in IEEE 1528 2013 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in IEEE 1528 2013 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in IEEE 1528 2013

Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5000	36.2	4.45	49.3	5.07
5100	36.1	4.55	49.1	5.18
5200	36.0	4.66	49.0	5.30
5300	35.9	4.76	48.9	5.42
5400	35.8	4.86	48.7	5.53
5500	35.6	4.96	48.6	5.65
5600	35.5	5.07	48.5	5.77
5700	35.4	5.17	48.3	5.88
5800	35.3	5.27	48.2	6.00

11.2 Typical Composition of Ingredients for Liquid Tissue Phantoms

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

alt: 99⁺% Pure Sodium Chloride

Sugar: 98⁺% Pure Sucrose

Water: De-ionized, 16 MΩ⁺ resistivity

HEC: Hydroxy thyl Cellulose

DGBE: 99⁺% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]

Triton X-100 (ultra-pure): Polyethylene glycol mono [4-(1, 1, 3, 3-tetramethylbutyl)phenyl]ether

Simulating Liquids for 5 GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	78
Mineral oil	11
Emulsifiers	9
Additives and Salt	2

11.3 Simulating Liquids Parameter Check Results

Date	Band	Freq(MHz)	Measured			Standard		Δ		Limit(%)
			e' (ϵ_r)	e''	σ	e' (ϵ_r)	σ	e' (ϵ_r)	σ	± 5
2016/7/20	Body 2450	2412	53.68	13.68	1.83	52.75	1.91	1.76%	-4.23%	± 5
		2437	53.63	13.90	1.88	52.72	1.94	1.72%	-2.87%	± 5
		2442	53.65	13.92	1.89	52.71	1.94	1.78%	-2.78%	± 5
		2450	53.67	13.97	1.90	52.70	1.95	1.83%	-2.47%	± 5
		2462	53.70	14.04	1.92	52.68	1.97	1.93%	-2.35%	± 5
		2472	53.72	14.05	1.93	52.67	1.98	1.98%	-2.60%	± 5
2016/7/20	Body 5000	5180	48.78	17.62	5.07	49.02	5.28	-0.49%	-3.90%	± 5
		5200	48.78	17.60	5.09	49.00	5.30	-0.44%	-4.05%	± 5
		5220	48.72	17.65	5.12	48.98	5.32	-0.54%	-3.88%	± 5
		5240	48.67	17.65	5.14	48.96	5.35	-0.60%	-3.92%	± 5
		5260	48.65	17.67	5.16	48.94	5.37	-0.60%	-3.87%	± 5
		5280	48.61	17.70	5.19	48.92	5.40	-0.63%	-3.78%	± 5
		5300	48.59	17.71	5.21	48.90	5.42	-0.63%	-3.78%	± 5
		5320	48.56	17.74	5.24	48.86	5.44	-0.62%	-3.67%	± 5
		5500	48.24	17.85	5.45	48.60	5.65	-0.74%	-3.48%	± 5
		5520	48.23	17.87	5.48	48.58	5.67	-0.71%	-3.42%	± 5
		5540	48.20	17.89	5.51	48.56	5.70	-0.75%	-3.37%	± 5
		5560	48.17	17.93	5.54	48.54	5.72	-0.76%	-3.21%	± 5
		5580	48.12	17.95	5.57	48.52	5.75	-0.83%	-3.15%	± 5
		5600	48.08	17.95	5.58	48.50	5.77	-0.87%	-3.21%	± 5
		5620	48.05	17.97	5.61	48.46	5.79	-0.85%	-3.12%	± 5
		5640	48.04	17.95	5.62	48.42	5.81	-0.78%	-3.25%	± 5
		5660	48.00	17.99	5.66	48.38	5.84	-0.79%	-3.09%	± 5
		5680	47.96	18.00	5.68	48.34	5.86	-0.79%	-3.01%	± 5
		5700	47.93	18.03	5.71	48.30	5.88	-0.78%	-2.91%	± 5
		5745	47.86	18.05	5.76	48.26	5.93	-0.82%	-2.93%	± 5
		5765	47.82	18.07	5.79	48.24	5.96	-0.86%	-2.86%	± 5
		5785	47.78	18.09	5.81	48.22	5.98	-0.91%	-2.82%	± 5
		5805	47.76	18.10	5.84	48.19	6.01	-0.89%	-2.81%	± 5
		5825	47.73	18.11	5.86	48.15	6.03	-0.87%	-2.82%	± 5

12 System Performance Check

The system performance check is performed prior to any usage of the system in order to guarantee reproducible results. The system performance check verifies that the system operates within its specifications. The system performance check results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

System Performance Check Measurement Conditions

- The measurements were performed in the flat section of the SAM twin phantom filled with Body simulating liquid of the following parameters.
- The DASY4/DASY5 system with an E-field probe EX3DV4 SN: 3665 was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 15 mm (below 1 GHz) and 10 mm (above 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 10mm was aligned with the dipole.
- Special 7x7x7 fine cube was chosen for cube integration ($dx=dy=5\text{ mm}$, $dz=5\text{ mm}$).
- Distance between probe sensors and phantom surface was set to 3.0 mm.
- The dipole input power (forward power) was $100\text{ mW}\pm 3\%$.
- The results are normalized to 1 W input power.

Reference SAR Values for System Performance Check

The reference SAR values can be obtained from the calibration certificate of system validation dipoles

System Dipole	Serial No.	Cal. Date	Freq. (MHz)	Target SAR Values (W/kg)		
				1g/10g	Head	Body
D2450V2	728	2016/5/24	2450	1g	50.5	50.3
				10g	23.7	23.7
D5GHzV2	1004	2015/11/20	5300	1g	86.1	80.2
				10g	24.5	22.2
D5GHzV2	1004	2015/11/20	5600	1g	86.1	83.9
				10g	24.5	23.2
D5GHzV2	1004	2015/11/20	5800	1g	80.8	79.9
				10g	22.9	22.1

12.1 System Performance Check Results

Date	System Dipole			Parameters	Target	Measured	Deviation[%]	Limited[%]
	Type	Serial No.	Liquid					
2016/7/20	D2450V2	728	Body	1g SAR:	50.3	49.0	-2.58	± 5
				10g SAR:	23.7	23.1	-2.53	± 5
2016/7/20	D5GHzV2 (5.3GHz)	1004	Body	1g SAR:	80.2	76.5	-4.61	± 5
				10g SAR:	22.2	21.7	-2.25	± 5
2016/7/20	D5GHzV2 (5.6GHz)	1004	Body	1g SAR:	83.9	80.2	-4.41	± 5
				10g SAR:	23.2	22.5	-3.02	± 5
2016/7/20	D5GHzV2 (5.8GHz)	1004	Body	1g SAR:	79.9	76.5	-4.26	± 5
				10g SAR:	22.1	21.6	-2.26	± 5

13 RF Output Power Measurement

According to KDB248227D01 802.11 Wi-Fi SAR V02 section 4, the default power measurement procedures are:

- 1) Power must be measured at each transmit antenna port according to the DSSS and OFDM transmission configurations in each standalone and aggregated frequency band.
- 2) Power measurement is required for the transmission mode configuration with the highest maximum output power specified for production units.
 - a) When the same highest maximum output power specification applies to multiple transmission modes, the largest channel bandwidth configuration with the lowest order modulation and lowest data rate is measured.
 - b) When the same highest maximum output power is specified for multiple largest channel bandwidth configurations with the same lowest order modulation or lowest order modulation and lowest data rate, power measurement is required for all equivalent 802.11 configurations with the same maximum output power.
- 3) For each transmission mode configuration, power must be measured for the highest and lowest channels; and at the mid-band channel(s) when there are at least 3 channels. For configurations with multiple mid-band channels, due to an even number of channels, both channels should be measured.

13.1 Wi-Fi (2.4GHz Band)

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Avg. Pwr (dBm)		Maximum Tune-up Pwr (dBm)
					Main	Aux	
2.4	802.11b	1M	1	2412	20.0	20.0	20.0
			6	2437	20.5	20.5	20.5
			11	2462	20.0	20.0	20.0
	802.11g	6M	1	Not Required			17.0
			6				19.5
			11				16.0
	802.11n HT20	MCS0	1				17.0
			6				19.5
			11				16.0
	802.11n HT40	MCS8	3				13.0
			6				18.5
			9				11.5

Note(s):

- Output Power and SAR is not required for 802.11g/n HT20/HT40 channels when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

13.2 Wi-Fi (5GHz Band)

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Avg. Pwr (dBm)		Maximum Tune-up	SAR Test (Yes/No)
					Main	Aux		
5.2 (U-NII 1)	802.11a	6	36-48	5180-5240	Not Required		15.0	No
	802.11n (HT20)	MCS0	36-48	5180-5240			15.0	No
	802.11n (HT40)	MCS0	38-46	5190-5230			15.0	No
	802.11ac VHT20	VHT0	36-48	5180-5240			15.0	No
	802.11ac VHT40	VHT0	38-46	5190-5230			15.0	No
	802.11ac VHT80	VHT80	42	5210			15.0	No
5.3 (U-NII 2A)	802.11a	6	52-60	5260-5300	Not Required		19.0	No
			64	5320			19.0	No
	802.11n (HT20)	MCS0	52-60	5260-5280			19.0	No
			64	5320			17.0	No
	802.11n (HT40)	MCS0	54	5270	18.8	18.8	19.0	Yes
			62	5310	16.9	17.0	17.0	Yes
	802.11ac VHT20	VHT0	52-60	5260-5300	Not Required		19.0	No
			64	5320			17.0	No
	802.11ac VHT40	VHT0	54	5270			19.0	No
			62	5310			17.0	No
	802.11ac VHT80	VHT80	58	5290			12.0	No

Note(s):

- Output Power and SAR measurement is not required for 802.11a /n HT20/ac channels when the specified maximum tune-up powers are the same in 802.11a/n HT20/ac and the measured SAR is ≤ 1.2 W/Kg.
- When the specified maximum output power is the same for both UNII band I and UNII band 2A, begin SAR measurement in UNII band 2A; and if the highest reported SAR for UNII band 2A is
 - ≤ 1.2 W/kg, SAR is not required for UNII band I.
 - > 1.2 W/kg, both bands should be tested independently for SAR.

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Avg. Pwr (dBm)		Maximum Tune-up	SAR Test (Yes/No)
					Main	Aux		
5.5 (U-NII-2C)	802.11a	6	100	5500	Not Required		17.0	No
			104-136	5520-5680			18.0	No
			140	5700			16.5	No
	802.11n (HT20)	MCS0	100	5500			17.0	No
			104-136	5520-5680			18.0	No
			140	5700			16.5	No
	802.11n (HT40)	MCS0	102	5510			17.0	No
			110-134	5550-5670			18.0	No
			142	5710			18.0	No
	802.11ac VHT20	VHT0	100	5500			17.0	No
			104-136	5520-5680			18.0	No
			140	5700			16.5	No
	802.11ac VHT40	VHT0	102	5510			17.0	No
			110-134	5550-5670			18.0	No
			142	5710			18.0	No
	802.11ac VHT80	VHT80	106	5530	14.3	14.4	14.5	Yes
			122	5610	17.8	17.9	18.0	Yes
			138	5690	18.0	17.9	18.0	Yes

Note(s):

- Output Power and SAR measurement is not required for 802.11a/n HT20/n HT40 channels when the specified maximum tune-up powers are the same in 802.1a/n HT20/HT40 and the measured SAR is ≤ 1.2 W/Kg.

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Avg. Pwr (dBm)		Maximum Tune-up	SAR Test (Yes/No)
					Main	Aux		
5.8 (U-NII-3)	802.11a	6	149	5745	Not Required		17.0	No
		6	153-157	5765-5825			19.0	No
	802.11n (HT20)	MCS0	149	5745			17.0	No
			153-165	5765-5825			19.0	No
	802.11n (HT40)	MCS0	151	5755	14.4	14.4	14.5	Yes
			159	5795	19.0	19.0	19.0	Yes
	802.11ac VHT20	VHT0	149	5745	Not Required		17.0	No
			153-165	5765-5825			19.0	No
	802.11ac VHT40	VHT0	151	5755			14.5	No
			159	5795			19.0	No
	802.11ac VHT80	VHT80	155	5775			14.0	No

Note(s):

- Output Power and SAR measurement is not required for 802.11a/n HT20/ac channels when the specified maximum tune-up powers are the same in 802.11a HT20/ac and the measured SAR is ≤ 1.2 W/Kg.

13.3 Bluetooth

Per exclusion calculations in Section 9, SAR testing for Bluetooth is not required.

14 SAR Measurements Results

Wi-Fi (2.4GHz Band):

Test Mode	Band (GHz)	Mode	Dist. (mm)	Test Position	Ch#	Freq. (MHz)	Chain	Power (dBm)		Area Scan 1g. SAR (W/Kg)	Meas. 1g SAR (W/kg)	Reported SAR (W/kg)	Note	Plot No.
								Tune up limit	Meas.					
NB	2.4GHz	802.11b	0	Bottom	6	2437	0	20.5	20.5	1.120	1.010	1.010		1
			0	Bottom	1	2412	0	20.0	20.0	0.873	0.865	0.865	2	
			0	Bottom	6	2437	1	20.5	20.5	0.836	0.918	0.918		2
			0	Bottom	1	2412	1	20.0	20.0	1.150	1.020	1.020	2	
			0	Bottom	6	2437	0	20.5	20.5	0.557	0.707	0.707	Ant2	3
			0	Bottom	1	2412	1	20.0	20.0	0.623	0.681	0.681	Ant2	4
			0	Bottom	6	2437	0	20.5	20.5	0.961	1.010	1.010	3	
			0	Bottom	1	2412	1	20.0	20.0	1.010	1.050	1.050	3	

Note(s):

- Highest reported SAR is > 0.4 W/kg. Due to the highest reported SAR for this test position, other test positions in this exposure condition were evaluated until a SAR ≤ 0.8 W/kg was reported.
- Highest reported SAR is > 0.8 W/kg. Added second highest power channel for this test position.
- Repeated measurements are required only when the measured SAR is ≥ 0.80 W/kg. If the measured SAR values are < 1.45 W/kg with ≤ 20% variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. (Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04)
 - Original SAR = 1.02W/kg, therefore two times repeat SAR is required.
 - Repeat SAR = 1.05 W/kg < 1.45W/kg
 - SAR variation= -2.94 % < 20%
- Antenna 1 and Antenna 2 are the same type and location, so we used the Antenna 1 to performed SAR testing. Antenna 2 was performed the worst channel of Antenna 1 SAR testing only. The measurement SAR is not over limit, so Antenna 2 spot check can be covered test result.

Wi-Fi (5 GHz Band):

Test Mode	Band (GHz)	Mode	Dist. (mm)	Test Position	Ch#	Freq. (MHz)	Chain	Power (dBm)		Area Scan 1g. SAR (W/Kg)	Meas. 1g SAR (W/kg)	Report ed SAR (W/kg)	Note	Plot No.
								Tune up limit	Meas.					
NB	5.3 (U-NII-2A)	802.11n HT40	0	Bottom	54	5270	0	19.0	18.8	0.447	0.748	0.783		5
			0	Bottom	54	5270	1	19.0	18.8	0.788	1.030	1.079		6
			0	Bottom	62	5310	0	17.0	16.9	0.249	0.545	0.558		
			0	Bottom	62	5310	1	17.0	17.0	0.567	0.823	0.823		
	5.5 (U-NII-2C)	802.11ac	0	Bottom	138	5690	0	18.0	18.0	1.120	1.200	1.200		7
			0	Bottom	138	5690	1	18.0	17.9	0.745	1.130	1.156		8
			0	Bottom	138	5690	1	18.0	17.9	1.020	0.985	1.008	3	
			0	Bottom	122	5610	0	18.0	17.8	1.000	1.080	1.131		
			0	Bottom	122	5610	1	18.0	17.9	0.686	1.090	1.115		
			0	Bottom	106	5530	0	14.5	14.3	0.361	0.802	0.840		
	5.8 (U-NII-3)	802.11n HT40	0	Bottom	159	5795	0	19.0	19.0	1.170	1.120	1.120		9
			0	Bottom	159	5795	0	19.0	19.0	0.944	1.220	1.220	3	
			0	Bottom	159	5795	1	19.0	19.0	0.840	1.010	1.010		10
			0	Bottom	151	5755	0	14.5	14.4	0.523	0.950	0.972		
			0	Bottom	151	5755	1	14.5	14.4	0.451	0.627	0.642		
			0	Bottom	159	5795	0	19.0	19.0	0.918	1.160	1.160	Ant2	11
			0	Bottom	151	5755	0	14.5	14.4	0.573	0.645	0.660	Ant2	12
	5.5 (U-NII-2C)	802.11ac	0	Bottom	138	5690	1	18.0	18.0	0.693	1.030	1.030	Ant2	13
			0	Bottom	122	5610	1	18.0	17.9	0.698	0.914	0.935	Ant2	14

Note(s):

- Highest reported SAR is > 0.4 W/kg. Due to the highest reported SAR for this test position, other test positions in this exposure condition were evaluated until a SAR ≤ 0.8 W/kg was reported.
- Highest reported SAR is > 0.8 W/kg. Added second highest power channel for this test position.
- Repeated measurements are required only when the measured SAR is ≥ 0.80 W/kg. If the measured SAR values are < 1.45 W/kg with ≤ 20% variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. (Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04)
 - Original SAR = 1.13 W/kg, therefore two times repeat SAR is required.
 - Repeat SAR = 0.95 W/kg < 1.45W/kg
 - SAR variation= 13.27 % < 20%
- Antenna 1 and Antenna 2 are the same type and location, so we used the Antenna 1 to performed SAR testing. Antenna 2 was performed the worst channel of Antenna 1 SAR testing only. The measurement SAR is not over limit, so Antenna 2 spot check can be covered test result..

15 Simultaneous Transmission SAR Analysis

KDB 447498 D01 General RF Exposure Guidance v06, introduces a new formula for calculating the SAR to Peak Location Ratio (SPLSR) between pairs of simultaneously transmitting antennas:

$$SPLSR = (SAR_1 + SAR_2)^{1.5} / R_i$$

Where:

SAR₁ is the highest Reported or estimated SAR for the first of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition

SAR₂ is the highest Reported or estimated SAR for the second of a pair of simultaneous transmitting antennas, in the same test operating mode and exposure condition as the first

R_i is the separation distance between the pair of simultaneous transmitting antennas. When the SAR is measured, for both antennas in the pair, it is determined by the actual x, y and z coordinates in the 1-g SAR for each SAR peak location, based on the extrapolated and interpolated result in the zoom scan measurement, using the formula of $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$

A new threshold of 0.04 is also introduced in the draft KDB. Thus, in order for a pair of simultaneous transmitting antennas with the sum of 1-g SAR > 1.6 W/kg to qualify for exemption from Simultaneous Transmission SAR measurements, it has to satisfy the condition of:

$$(SAR_1 + SAR_2)^{1.5} / R_i \leq 0.04$$

15.1 Estimated SAR for Simultaneous Transmission SAR Analysis

Considerations for SAR estimation

- When standalone SAR test exclusion applies, standalone SAR must also be estimated to determine simultaneous transmission SAR test exclusion.
- Dedicated Host Approach criteria for SAR test exclusion is likewise applied to SAR estimation, with certain distinctions between test exclusion and SAR estimation:
 - When the separation distance from the antenna to an adjacent edge is ≤ 5 mm, a distance of 5 mm is applied for SAR estimation; this is the same between test exclusion and SAR estimation calculations.
 - When the separation distance from the antenna to an adjacent edge is > 5 mm but ≤ 50 mm, the actual antenna-to-edge separation distance is applied for SAR estimation.
 - When the minimum test separation distance is > 50 mm, the estimated SAR value is 0.4 W/kg

15.1.1 Estimated SAR for Bluetooth

According to section 9, the Bluetooth must be estimated according to following to determine simultaneous transmission SAR test exclusion:

- $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [v_{f(\text{GHz})}/x]$ W/kg for test separation distances ≤ 50 mm; where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
- 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm.

Antenna	Band	Frequency (MHz)	Output Power		Separation Distances(mm)					Estimated 1-g SAR (W/Kg)				
			dBm	mW	Bottom	Edge1	Edge2	Edge3	Edge4	Bottom	Edge1	Edge2	Edge3	Edge4
Wi-Fi Main	2.4GHz	2437	15.5	35	11.0					Measure				
Wi-Fi Main	5.2GHz	5210	15.0	32	11.0					Measure				
Wi-Fi Main	5.3GHz	5270	19.0	79	11.0					Measure				
Wi-Fi Main	5.5GHz	5690	18.0	63	11.0					Measure				
Wi-Fi Main	5.8GHz	5795	19.0	79	11.0					Measure				
Wi-Fi Main	Bluetooth	2402	7.0	5	11.0					0.094				

Antenna	Band	Frequency (MHz)	Output Power		Separation Distances(mm)					Estimated 1-g SAR (W/Kg)				
			dBm	mW	Bottom	Edge1	Edge2	Edge3	Edge4	Bottom	Edge1	Edge2	Edge3	Edge4
Wi-Fi Aux	2.4GHz	2437	15.5	35	11.0					Measure				
Wi-Fi Aux	5.2GHz	5210	15.0	32	11.0					Measure				
Wi-Fi Aux	5.3GHz	5270	19.0	79	11.0					Measure				
Wi-Fi Aux	5.5GHz	5690	18.0	63	11.0					Measure				
Wi-Fi Aux	5.8GHz	5795	19.0	79	11.0					Measure				
Wi-Fi Aux	Bluetooth	2402	7.0	5	11.0					0.094				

15.2 Sum of the SAR for Simultaneous Transmission Analysis

15.2.1 Sum of the SAR for Wi-Fi & Wi-Fi(MIMO)

Wi-Fi 2.4GHz

Test Position	Simultaneous Transmission Scenario		Σ 1-g SAR (W/kg)	SPLSR (Yes/No)
	Wi-Fi Main	Wi-Fi Aux		
Bottom	1.010	1.050	2.060	YES

Note(s):

As the Sum of the SAR is greater than 1.6W/Kg, so SPLSR is required.

Wi-Fi 5GHz

Test Position	Simultaneous Transmission Scenario		Σ 1-g SAR (W/kg)	SPLSR (Yes/No)
	Wi-Fi Main	Wi-Fi Aux		
Bottom	1.220	1.156	2.376	YES

Note(s):

As the Sum of the SAR is greater than 1.6W/Kg, so SPLSR is required

15.2.2 Sum of the SAR for Wi-Fi & Bluetooth

Band	Test Position	Simultaneous Transmission Scenario		Σ 1-g SAR (W/kg)	SPLSR (Yes/No)
		Wi-Fi Main	Bluetooth		
2.4GHz	Bottom	1.010	0.094	1.104	No

Note(s):

As the Sum of the SAR is less than 1.6W/Kg, so SPLSR is not required

Band	Test Position	Simultaneous Transmission Scenario		Σ 1-g SAR (W/kg)	SPLSR (Yes/No)
		Wi-Fi Main	Bluetooth		
5GHz	Bottom	1.220	0.094	1.314	No

Note(s):

As the Sum of the SAR less than 1.6W/Kg, so SPLSR is not required.

15.2.3 Sum of the 1g SAR for Body Exposure Condition

Wi-Fi 2.4GHz

Test Position	Simultaneous Transmission Scenario		Σ 1-g SAR (W/kg)	Calculated distance (cm)	SPLSR	Figure	Simultaneous TX SAR required
	Wi-Fi Main	Wi-Fi Aux					
Bottom	1.010	1.050	2.060	14.36	0.02	1	No

The SPLSR is rounded to two decimal digits and ≤ 0.04 , so SPLSR calculated result is pass.

Wi-Fi 5GHz

Test Position	Simultaneous Transmission Scenario		Σ 1-g SAR (W/kg)	Calculated distance (cm)	SPLSR	Figure	Simultaneous TX SAR required
	Wi-Fi Main	Wi-Fi Aux					
Bottom	1.220	1.156	2.376	13.96	0.03	2	No

The SPLSR is rounded to two decimal digits and ≤ 0.04 , so SPLSR calculated result is pass.

16 Equipment List & Calibration Status

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Cycle(year)	Calibration Due
S-Parameter Network Analyzer	Agilent	E5071C	MY46107234	1	2016/10/13
Electronic Probe kit	Hewlett Packard	85070D	N/A	N/A	N/A
Power Meter	Agilent	4416	GB41291611	1	2016/09/05
Power Sensor	Agilent	8481H	MY41091956	1	2016/09/05
Data Acquisition Electronics (DAE)	SPEAG	DAE4	877	1	2017/3/20
Dosimetric E-Field Probe	SPEAG	EX3DV4	3665	1	2017/05/25
2450 MHz System Validation Dipole	SPEAG	D2450V2	728	1	2017/05/23
5GHz System Validation Dipole	SPEAG	D5GHzV2	1004	1	2016/11/19
Robot	Staubli	RX90L	F02/5T69A1/A/01	N/A	N/A
Amplifier	Mini-Circuit	ZVE-8G	665500309	N/A	N/A
Amplifier	Mini-Circuit	ZHL-1724HLN	D072602#2	N/A	N/A

17 Facilities

All measurement facilities used to collect the measurement data are located at

- ☐ No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang, Taoyuan Hsien, Taiwan, R.O.C.
- ☒ No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)
- ☐ No. 199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

18 Reference

- [1] Federal Communications Commission, \Report and order: Guidelines for evaluating the environmental effects of radiofrequency radiation", Tech. Rep. FCC 96-326, FCC, Washington, D.C. 20554, 1996.
- [2] David L. Means Kwok Chan, Robert F. Cleveland, \Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", Tech. Rep., Federal Communication Commission, Office of Engineering & Technology, Washington, DC, 1997.
- [3] Thomas Schmid, Oliver Egger, and Niels Kuster, \Automated E-field scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105{113, Jan. 1996.
- [4] Niels Kuster, Ralph Kastle, and Thomas Schmid, \Dosimetric evaluation of mobile communications equipment with known precision", IEEE Transactions on Communications, vol. E80-B, no. 5, pp. 645{652, May 1997.
- [5] CENELEC, \Considerations for evaluating of human exposure to electromagnetic fields (EMFs) from mobile telecommunication equipment (MTE) in the frequency range 30MHz - 6GHz", Tech. Rep., CENELEC, European Committee for Electrotechnical Standardization, Brussels, 1997.
- [6] ANSI, ANSI/IEEE C95.1-1992: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992.
- [7] Katja Pokovic, Thomas Schmid, and Niels Kuster, \Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies", in ICECOM '97, Dubrovnik, October 15{17, 1997, pp. 120{124.
- [8] Katja Pokovic, Thomas Schmid, and Niels Kuster, \E-field probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23{25 June, 1996, pp. 172{175.
- [9] Volker Hombach, Klaus Meier, Michael Burkhardt, Eberhard Kuhn, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 900 MHz", IEEE Transactions on Microwave Theory and Techniques, vol. 44, no. 10, pp. 1865{1873, Oct. 1996.
- [10] Klaus Meier, Ralf Kastle, Volker Hombach, Roger Tay, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 1800 MHz", IEEE Transactions on Microwave Theory and Techniques, Oct. 1997, in press.
- [11] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [12] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992..Dosimetric Evaluation of Sample device, month 1998 9
- [13] NIS81 NAMAS, \The treatment of uncertainty in EMC measurement", Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.
- [14] Barry N. Taylor and Christ E. Kuyatt, \Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994. Dosimetric Evaluation of Sample device, month 1998 10

19 Attachments

Exhibit	Content
1	System Performance Check Plots
2	SAR Test Data Plots
3	SPLSR
4	Calibration Data Report
5	T160625W02-A-SF PHOTOS

END OF REPORT