

TUV SUD BABT TCB

Octagon House,
Segensworth Road,
Fareham,
Hampshire,
PO15 5RL

Date: **06/16/2015**

REF: **RF exposure analysis**

Model: **LE70-915** FCC ID: **RI7LE70FH** IC: **5131A-LE70FH**

The device is designed as module to be installed in and used in a mixed mobile and portable exposure host platform. Portable exposure conditions are evaluated in a separate exhibit. The analysis provided in this document only covers mobile exposure conditions and for that the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all the persons and must not be co-located or operating in conjunction with any other antenna or transmitter except in the conditions described in this document.

MPE exposure limits

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure:

Frequency Range (MHz)	Power density (mW/cm ²)	Averaging time (minutes)
300 – 1500	f (MHz) /1500	30

The table below is excerpted from RSS-102, Issue 4, 4.2, titled “RF Limits for Devices used by the General Public”:

Frequency Range (MHz)	Power density (W/m ²)	Averaging time (minutes)
300-6000	0.02619 f ^{0.6834}	6

As all the operating frequencies of this device are higher than 1500 MHz, the applicable maximum permissive exposure is: 1 mW/cm².

Using the equation $S = \frac{PG}{4\pi R^2}$ to calculate the exposure to electromagnetic fields

where: S = power density (in appropriate units, e.g. mW/cm²)
P = power input to the antenna (in appropriate units, e.g., mW)
G = power gain of the antenna in the direction of interest relative to an isotropic radiator
R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Compliance with FCC and IC maximum permissive exposure limits is demonstrated based on the following calculations.

1. Standalone operations analysis

Frequency Band	Mode	Frequency Range (MHz)	Reference frequency (Lowest freq.) (MHz)	Maximum conducted output power (dBm)	Antenna gain (dBi)	Evaluation distance for compliance with MPE limits (cm)	$S = \frac{PG}{4\pi R^2}$ (mW/cm ²)	FCC MPE limit (mW/cm ²)	IC MPE limit (mW/cm ²)	COMPLIANCE (S<S _{Limit})	RELATIVE EXPOSURE MPE ratio (S/S _{Limit})
902-928 MHz	DSS	915,3 - 927,6	915,3	27,11	1,90	20	0,158	0,610	0,277	COMPLIANT	0,5723506
902-928 MHz	DTS	908,88-908,88	908,88	12,65	1,90	20	0,006	0,606	0,275	COMPLIANT	0,0205945

Under all conditions the equipment complies with the FCC/IC MPE limits and the maximum MPE ratio obtained is **0,5723506**.

2. Co-location analysis

2.1. Co-location with other transmitter in mobile exposure conditions

According to KDB 447498 D01 General RF Exposure Guidance v05r2, 7.2:

Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on calculated or measured field strengths or power density, is ≤ 1.0 .

As the maximum calculated MPE ratio for the device is **0,030**, the product can be co-located with other antennas providing that the sum of the MPE ratios for all the other simultaneous transmitting antennas incorporated in a host device, based on calculated or measured field strengths or power density is ≤ 1.0 – **0,5723506 = 0,4276494**.

2.2. Co-location with other transmitter in mixed mobile and portable host platform exposure conditions

According to KDB 447498 D01 General RF Exposure Guidance v05r2, 7.2:

When one of the following test exclusion conditions is satisfied for all combinations of simultaneous transmission configurations, further equipment approval is not required to incorporate transmitter modules in host devices that operate in the mixed mobile and portable host platform exposure conditions. The grantee is responsible for documenting this according to Class I permissive change requirements. Antennas that qualify for standalone SAR test exclusion must apply the estimated standalone SAR to determine simultaneous transmission test exclusion.

- The $[\sum \text{ of (the highest measured or estimated SAR for each standalone antenna configuration, adjusted for maximum tune-up tolerance) / 1.6 W/kg} + [\sum \text{ of MPE ratios}]]$ is ≤ 1.0 .
- The SAR to peak location separation ratios of all simultaneous transmitting antenna pairs operating in portable exposure conditions are all ≤ 0.04 and the $[\sum \text{ of MPE ratios}]$ is ≤ 1.0 .

As the maximum calculated MPE ratio for the device is **0,5723506**, the equipment can be co-located with other transmitters in a mixed mobile and portable conditions providing that the exposure of the co-located transmitter complies with:

- The $\sum$ of (the highest measured or estimated SAR for each standalone antenna configuration, adjusted for maximum tune-up tolerance) / 1.6 W/kg] + $\sum$ of MPE ratios] is $\leq 1.0 - 0,5723506 = 0,4276494$

OR

- The SAR to peak location separation ratios of all simultaneous transmitting antenna pairs operating in portable exposure conditions are all ≤ 0.04 and the $\sum$ of MPE ratios] is $\leq 1.0 - 0,5723506 = 0,4276494$

Yours sincerely,

A handwritten signature in blue ink, appearing to read "B. Tucker", enclosed within a blue oval.

p.a.

Name: Mr Brian Tucker
Position: Global VP, Quality
Company: Telit Communications S.p.A.
Phone: 1-919-439-7977 Ext. 1002
e-mail: brian.tucker@telit.com