

FCC Test Report

Report No.: RF181220E07

FCC ID: I88LTE7480-S905

Test Model: LTE7480-S905

Received Date: Dec. 20, 2018

Test Date: Jan. 19 to Mar. 07, 2019

Issued Date: Mar. 27, 2019

Applicant: Zyxel Communications Corporation

Address: No.2 Industry East RD. IX, Hsinchu Science Park, Hsinchu 30075, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

**FCC Registration /
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	4
1 Certificate of Conformity.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information.....	7
3.1 General Description of EUT	7
3.2 Description of Test Modes	9
3.2.1 Test Mode Applicability and Tested Channel Detail	10
3.3 Duty Cycle of Test Signal	12
3.4 Description of Support Units	13
3.4.1 Configuration of System under Test	14
3.5 General Description of Applied Standards	15
4 Test Types and Results	16
4.1 Radiated Emission and Bandedge Measurement.....	16
4.1.1 Limits of Radiated Emission and Bandedge Measurement	16
4.1.2 Test Instruments	17
4.1.3 Test Procedures.....	19
4.1.4 Deviation from Test Standard	19
4.1.5 Test Setup.....	20
4.1.6 EUT Operating Conditions.....	21
4.1.7 Test Results	22
4.2 Conducted Emission Measurement	36
4.2.1 Limits of Conducted Emission Measurement	36
4.2.2 Test Instruments	36
4.2.3 Test Procedures.....	37
4.2.4 Deviation from Test Standard	37
4.2.5 Test Setup.....	37
4.2.6 EUT Operating Conditions.....	37
4.2.7 Test Results	38
4.3 6dB Bandwidth Measurement	40
4.3.1 Limits of 6dB Bandwidth Measurement	40
4.3.2 Test Setup.....	40
4.3.3 Test Instruments	40
4.3.4 Test Procedure	40
4.3.5 Deviation from Test Standard	40
4.3.6 EUT Operating Conditions.....	40
4.3.7 Test Result.....	41
4.4 Conducted Output Power Measurement.....	43
4.4.1 Limits of Conducted Output Power Measurement	43
4.4.2 Test Setup.....	43
4.4.3 Test Instruments	43
4.4.4 Test Procedures.....	43
4.4.5 Deviation from Test Standard	43
4.4.6 EUT Operating Conditions.....	43
4.4.7 Test Results	44
4.5 Power Spectral Density Measurement.....	46
4.5.1 Limits of Power Spectral Density Measurement	46
4.5.2 Test Setup.....	46
4.5.3 Test Instruments	46
4.5.4 Test Procedure	46
4.5.5 Deviation from Test Standard	46
4.5.6 EUT Operating Condition	46

4.5.7 Test Results	47
4.6 Conducted Out of Band Emission Measurement	49
4.6.1 Limits of Conducted Out of Band Emission Measurement.....	49
4.6.2 Test Setup.....	49
4.6.3 Test Instruments	49
4.6.4 Test Procedure	49
4.6.5 Deviation from Test Standard	49
4.6.6 EUT Operating Condition	49
4.6.7 Test Results	49
5 Pictures of Test Arrangements.....	56
Appendix – Information of the Testing Laboratories	57

Release Control Record

Issue No.	Description	Date Issued
RF181220E07	Original release.	Mar. 27, 2019

1 Certificate of Conformity

Product: LTE-A Pro Outdoor Router

Brand: ZYXEL

Test Model: LTE7480-S905

Sample Status: ENGINEERING SAMPLE


Applicant: Zyxel Communications Corporation

Test Date: Jan. 19 to Mar. 07, 2019

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :  , **Date:** Mar. 27, 2019
Claire Kuan / Specialist

Approved by :  , **Date:** Mar. 27, 2019
May Chen / Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -7.31dB at 0.25156MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -0.6dB at 2390.00MHz, 2483.50MHz
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is iPEX not a standard connector.

Note:

Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ($\pm$)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.84 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	4.87 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.12 dB
	6GHz ~ 18GHz	4.86 dB
	18GHz ~ 40GHz	5.24 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	LTE-A Pro Outdoor Router
Brand	ZYXEL
Test Model	LTE7480-S905
CPU Model No.	MT7621AT
WiFi Chip Model No.	MT7603E
LTE chip Model No.	SDX20
FW version	LTE7480-S905 V2.00(ABQT.0)C0
Status of EUT	ENGINEERING SAMPLE
Power Supply Rating	DC 48V from adapter (POE)
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b: up to 11Mbps 802.11g: up to 54Mbps 802.11n: up to 300Mbps
Operating Frequency	2.412 ~ 2.462GHz
Number of Channel	802.11b, 802.11g, 802.11n (HT20): 11 802.11n (HT40): 7
Output Power	279.693mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	Adapter (POE) x 1
Data Cable Supplied	RJ45 cable (Unshielded, 1.8m)

Note:

1. There are WLAN and WWAN technology used for the EUT. The EUT has below radios as following table:

Radio 1	Radio 2
WLAN (2.4GHz)	WWAN (LTE) / 3G

2. Simultaneously transmission condition.

Condition	Technology	
1	WLAN (2.4GHz)	WWAN (LTE) / 3G

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

3. The EUT must be supplied with a adapter (POE) as following table:

Brand	Model No.	Spec.
SHENZHEN	TPT24S48A-MC	Input: 100-240Vac, 0.5A, 50/60Hz AC input cable: Unshielded 1.8m Output: 48Vdc

4. The antennas provided to the EUT, please refer to the following table:

Chain No.	Antenna Net Gain(dBi)	Frequency range	Antenna Type	Connector Type
WLAN-ANT0	6	2.4 ~ 2.4835GHz	PIFA	iPEX
WLAN-ANT1	5	2.4 ~ 2.4835GHz	PIFA	iPEX
WWAN_0 (TX & RX)	9.85	3550 ~ 3700 MHz	Dipole	iPEX
WWAN_1 (RX only)	9.85	3550 ~ 3700 MHz	Dipole	iPEX
WWAN_2 (RX only)	9.85	3550 ~ 3700 MHz	Dipole	iPEX
WWAN_3 (RX only)	9.85	3550 ~ 3700 MHz	Dipole	iPEX

5. The EUT incorporates a MIMO function.

MODULATION MODE	TX & RX CONFIGURATION	
802.11b	1TX diversity	2RX
802.11g	1TX diversity	2RX
802.11n (HT20)	2TX	2RX
802.11n (HT40)	2TX	2RX

Note: Max. gain was selected for 1TX test.

6. The power setting are list as below:

802.11b		802.11g		802.11n (HT20)		802.11n (HT40)	
Frequency (MHz)	Power Setting	Frequency (MHz)	Power Setting	Frequency (MHz)	Power Setting	Frequency (MHz)	Power Setting
2412	1A	2412	1B	2412	17	2422	13
2437	1A	2437	1B	2437	1B	2437	1A
2462	1A	2462	1B	2462	16	2452	13

7. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

Channel	Frequency	Channel	Frequency
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (HT40):

Channel	Frequency	Channel	Frequency
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE≥1G**: Radiated Emission above 1GHz & Bandedge Measurement

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Note: The EUT had been pre-tested on the 0 degree, Vertical +30 degree, Vertical -30 degree, 0 degree clockwise 45 degree and 0 degree counterclockwise 45 degree. The worst case was found when positioned on 0 degree.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11n (HT20)	1 to 11	6	OFDM	BPSK	6.5

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11n (HT20)	1 to 11	6	OFDM	BPSK	6.5

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY
RE $\geq$ 1G	22deg. C, 68%RH	120Vac, 60Hz	Steven Chiang
RE $<$ 1G	23deg. C, 67%RH	120Vac, 60Hz	Frank Chuang
PLC	23deg. C, 74%RH	120Vac, 60Hz	Andy Ho
APCM	25deg. C, 60%RH	120Vac, 60Hz	Anderson Chen

3.3 Duty Cycle of Test Signal


802.11b: Duty cycle = $8.437/8.5 = 0.993$

802.11g: Duty cycle = $1.396/1.548 = 0.902$


802.11n (HT20): Duty cycle = $1.308/1.362 = 0.96$

802.11n (HT40): Duty cycle = $0.648/0.702 = 0.923$


802.11b




802.11g



802.11n (HT20)



802.11n (HT40)



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	SIM Card	R&S	NA	NA	NA	Provided by Lab
B.	Laptop	DELL	E6420	B92T3R1	FCC DoC	Provided by Lab

Note:

1. All power cords of the above support units are non-shielded (1.8m).

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	RJ-45 Cable	1	10	No	0	Provided by Lab
2.	RJ-45 Cable	1	1.8	No	0	Supplied by client
3.	AC Cable	1	1.8	No	0	Supplied by client
4.	GND Cable	1	2.8	No	0	Provided by Lab

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)
KDB 558074 D01 15.247 Meas Guidance v05
KDB 662911 D01 Multiple Transmitter Output v02r01
ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

For radiated emission below 1GHz:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Keysight	N9038A	MY54450088	July 05, 2018	July 04, 2019
Pre-Amplifier EMCi	EMC001340	980142	Jan. 25, 2019	Jan. 24, 2020
Loop Antenna Electro-Metrics	EM-6879	269	Sep. 07, 2018	Sep. 06, 2019
RF Cable	NA	LOOPCAB-001	Jan. 14, 2019	Jan. 13, 2020
RF Cable	NA	LOOPCAB-002	Jan. 14, 2019	Jan. 13, 2020
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-01	Oct. 30, 2018	Oct. 29, 2019
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-406	Nov. 22, 2018	Nov. 21, 2019
RF Cable	8D	966-4-1	Mar. 21, 2018	Mar. 20, 2019
RF Cable	8D	966-4-2	Mar. 21, 2018	Mar. 20, 2019
RF Cable	8D	966-4-3	Mar. 21, 2018	Mar. 20, 2019
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-4-01	Sep. 27, 2018	Sep. 26, 2019
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 4.
3. The CANADA Site Registration No. is 20331-2
4. Loop antenna was used for all emissions below 30 MHz.
5. Tested Date: Mar. 07, 2019

For other test items:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Keysight	N9038A	MY54450088	July 05, 2018	July 04, 2019
Pre-Amplifier EMC	EMC001340	980142	Feb. 09, 2018	Feb. 08, 2019
Loop Antenna Electro-Metrics	EM-6879	269	Sep. 07, 2018	Sep. 06, 2019
RF Cable	NA	LOOPCAB-001	Jan. 14, 2019	Jan. 13, 2020
RF Cable	NA	LOOPCAB-002	Jan. 14, 2019	Jan. 13, 2020
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-01	Oct. 30, 2018	Oct. 29, 2019
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-406	Nov. 22, 2018	Nov. 21, 2019
RF Cable	8D	966-4-1	Mar. 21, 2018	Mar. 20, 2019
RF Cable	8D	966-4-2	Mar. 21, 2018	Mar. 20, 2019
RF Cable	8D	966-4-3	Mar. 21, 2018	Mar. 20, 2019
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-4-01	Sep. 27, 2018	Sep. 26, 2019
Horn_Antenna SCHWARZBECK	BBHA 9120D	9120D-783	Nov. 25, 2018	Nov. 24, 2019
Pre-Amplifier Mini-Circuits	ZVA-183-S+	AMP-ZVA-03	May 10, 2018	May 09, 2019
RF Cable	EMC104-SM-SM-1200	160923	Jan. 29, 2018	Jan. 28, 2019
RF Cable	EMC104-SM-SM-2000	150318	Jan. 29, 2018	Jan. 28, 2019
RF Cable	EMC104-SM-SM-5000	150321	Jan. 29, 2018	Jan. 28, 2019
Pre-Amplifier EMC	EMC184045SE	980387	Jan. 29, 2018	Jan. 28, 2019
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170608	Nov. 25, 2018	Nov. 24, 2019
RF Cable	EMC102-KM-KM-1200	160925	Jan. 29, 2018	Jan. 28, 2019
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA
Spectrum Analyzer R&S	FSV40	100964	June 20, 2018	June 19, 2019
Power meter Anritsu	ML2495A	1014008	May 09, 2018	May 08, 2019
Power sensor Anritsu	MA2411B	0917122	May 09, 2018	May 08, 2019
Fixed Attenuator Mini-Circuits	MDCS18N-10	MDCS18N-10-01	Apr. 16, 2018	Apr. 15, 2019

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 4.
3. The CANADA Site Registration No. is 20331-2
4. Loop antenna was used for all emissions below 30 MHz.
5. Tested Date: Jan. 19 to 25, 2019

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Connected the EUT with the Laptop is placed on remote site.
- Controlling software (QA Tool (Version: 0.0.1.85)) has been activated to set the EUT on specific status.

4.1.7 Test Results

Above 1GHz Data:

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.4 PK	74.0	-17.6	3.62 H	12	58.4	-2.0
2	2390.00	41.5 AV	54.0	-12.5	3.62 H	12	43.5	-2.0
3	*2412.00	100.9 PK			3.62 H	12	103.0	-2.1
4	*2412.00	98.7 AV			3.62 H	12	100.8	-2.1
5	4824.00	46.2 PK	74.0	-27.8	1.26 H	337	44.2	2.0
6	4824.00	42.7 AV	54.0	-11.3	1.26 H	337	40.7	2.0
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.6 PK	74.0	-17.4	1.13 V	26	58.6	-2.0
2	2390.00	43.1 AV	54.0	-10.9	1.13 V	26	45.1	-2.0
3	*2412.00	102.6 PK			1.13 V	26	104.7	-2.1
4	*2412.00	100.2 AV			1.13 V	26	102.3	-2.1
5	4824.00	47.8 PK	74.0	-26.2	1.48 V	325	45.8	2.0
6	4824.00	44.9 AV	54.0	-9.1	1.48 V	325	42.9	2.0

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	55.1 PK	74.0	-18.9	3.64 H	360	57.1	-2.0
2	2390.00	41.5 AV	54.0	-12.5	3.64 H	360	43.5	-2.0
3	*2437.00	101.2 PK			3.64 H	360	103.4	-2.2
4	*2437.00	98.8 AV			3.64 H	360	101.0	-2.2
5	2483.50	54.2 PK	74.0	-19.8	3.64 H	360	56.4	-2.2
6	2483.50	41.4 AV	54.0	-12.6	3.64 H	360	43.6	-2.2
7	4874.00	45.5 PK	74.0	-28.5	1.26 H	331	43.5	2.0
8	4874.00	42.2 AV	54.0	-11.8	1.26 H	331	40.2	2.0
9	7311.00	45.3 PK	74.0	-28.7	1.65 H	158	36.8	8.5
10	7311.00	34.5 AV	54.0	-19.5	1.65 H	158	26.0	8.5

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	55.7 PK	74.0	-18.3	1.12 V	24	57.7	-2.0
2	2390.00	41.6 AV	54.0	-12.4	1.12 V	24	43.6	-2.0
3	*2437.00	102.8 PK			1.12 V	24	105.0	-2.2
4	*2437.00	100.3 AV			1.12 V	24	102.5	-2.2
5	2483.50	55.2 PK	74.0	-18.8	1.12 V	24	57.4	-2.2
6	2483.50	41.5 AV	54.0	-12.5	1.12 V	24	43.7	-2.2
7	4874.00	47.7 PK	74.0	-26.3	1.47 V	326	45.7	2.0
8	4874.00	44.8 AV	54.0	-9.2	1.47 V	326	42.8	2.0
9	7311.00	46.0 PK	74.0	-28.0	1.36 V	204	37.5	8.5
10	7311.00	38.6 AV	54.0	-15.4	1.36 V	204	30.1	8.5

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	100.9 PK			3.82 H	3	103.1	-2.2
2	*2462.00	98.6 AV			3.82 H	3	100.8	-2.2
3	2483.50	54.5 PK	74.0	-19.5	3.81 H	3	56.7	-2.2
4	2483.50	41.7 AV	54.0	-12.3	3.81 H	3	43.9	-2.2
5	4924.00	45.4 PK	74.0	-28.6	1.20 H	330	43.4	2.0
6	4924.00	41.9 AV	54.0	-12.1	1.20 H	330	39.9	2.0
7	7386.00	45.9 PK	74.0	-28.1	1.61 H	162	37.3	8.6
8	7386.00	34.9 AV	54.0	-19.1	1.61 H	162	26.3	8.6
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	102.7 PK			3.19 V	343	104.9	-2.2
2	*2462.00	100.2 AV			3.19 V	343	102.4	-2.2
3	2483.50	55.6 PK	74.0	-18.4	3.19 V	343	57.8	-2.2
4	2483.50	43.6 AV	54.0	-10.4	3.19 V	343	45.8	-2.2
5	4924.00	47.7 PK	74.0	-26.3	1.52 V	14	45.7	2.0
6	4924.00	46.3 AV	54.0	-7.7	1.52 V	14	44.3	2.0
7	7386.00	46.5 PK	74.0	-27.5	1.82 V	41	37.9	8.6
8	7386.00	38.0 AV	54.0	-16.0	1.82 V	41	29.4	8.6

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.0 PK	74.0	-6.0	3.62 H	2	70.0	-2.0
2	2390.00	51.7 AV	54.0	-2.3	3.62 H	2	53.7	-2.0
3	*2412.00	104.2 PK			3.62 H	2	106.3	-2.1
4	*2412.00	94.8 AV			3.62 H	2	96.9	-2.1
5	4824.00	50.4 PK	74.0	-23.6	2.06 H	26	48.4	2.0
6	4824.00	37.2 AV	54.0	-16.8	2.06 H	26	35.2	2.0

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.4 PK	74.0	-4.6	3.29 V	342	71.4	-2.0
2	2390.00	53.2 AV	54.0	-0.8	3.29 V	342	55.2	-2.0
3	*2412.00	106.0 PK			3.29 V	342	108.1	-2.1
4	*2412.00	96.4 AV			3.29 V	342	98.5	-2.1
5	4824.00	45.8 PK	74.0	-28.2	1.54 V	63	43.8	2.0
6	4824.00	35.2 AV	54.0	-18.8	1.54 V	63	33.2	2.0

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.4 PK	74.0	-19.6	3.67 H	355	56.4	-2.0
2	2390.00	42.1 AV	54.0	-11.9	3.67 H	355	44.1	-2.0
3	*2437.00	103.8 PK			3.67 H	355	106.0	-2.2
4	*2437.00	95.0 AV			3.67 H	355	97.2	-2.2
5	2483.50	54.6 PK	74.0	-19.4	3.67 H	355	56.8	-2.2
6	2483.50	42.2 AV	54.0	-11.8	3.67 H	355	44.4	-2.2
7	4874.00	50.2 PK	74.0	-23.8	2.10 H	12	48.2	2.0
8	4874.00	36.8 AV	54.0	-17.2	2.10 H	12	34.8	2.0
9	7311.00	47.9 PK	74.0	-26.1	1.89 H	125	39.4	8.5
10	7311.00	35.6 AV	54.0	-18.4	1.89 H	125	27.1	8.5

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.5 PK	74.0	-19.5	3.21 V	325	56.5	-2.0
2	2390.00	42.2 AV	54.0	-11.8	3.21 V	325	44.2	-2.0
3	*2437.00	105.2 PK			3.21 V	325	107.4	-2.2
4	*2437.00	96.4 AV			3.21 V	325	98.6	-2.2
5	2483.50	54.7 PK	74.0	-19.3	3.21 V	325	56.9	-2.2
6	2483.50	42.3 AV	54.0	-11.7	3.21 V	325	44.5	-2.2
7	4874.00	45.6 PK	74.0	-28.4	1.50 V	73	43.6	2.0
8	4874.00	34.5 AV	54.0	-19.5	1.50 V	73	32.5	2.0
9	7311.00	48.7 PK	74.0	-25.3	3.33 V	59	40.2	8.5
10	7311.00	37.0 AV	54.0	-17.0	3.33 V	59	28.5	8.5

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	107.7 PK			3.62 H	13	109.9	-2.2
2	*2462.00	95.2 AV			3.62 H	13	97.4	-2.2
3	2483.50	68.2 PK	74.0	-5.8	3.62 H	13	70.4	-2.2
4	2483.50	51.9 AV	54.0	-2.1	3.62 H	13	54.1	-2.2
5	4924.00	50.7 PK	74.0	-23.3	2.10 H	3	48.7	2.0
6	4924.00	37.3 AV	54.0	-16.7	2.10 H	3	35.3	2.0
7	7386.00	47.5 PK	74.0	-26.5	1.96 H	123	38.9	8.6
8	7386.00	35.0 AV	54.0	-19.0	1.96 H	123	26.4	8.6
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	106.1 PK			2.87 V	343	108.3	-2.2
2	*2462.00	96.8 AV			2.87 V	343	99.0	-2.2
3	2483.50	69.3 PK	74.0	-4.7	2.87 V	343	71.5	-2.2
4	2483.50	53.3 AV	54.0	-0.7	2.87 V	343	55.5	-2.2
5	4924.00	45.8 PK	74.0	-28.2	1.47 V	63	43.8	2.0
6	4924.00	34.9 AV	54.0	-19.1	1.47 V	63	32.9	2.0
7	7386.00	48.9 PK	74.0	-25.1	3.34 V	56	40.3	8.6
8	7386.00	37.4 AV	54.0	-16.6	3.34 V	56	28.8	8.6

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11n (HT20)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.4 PK	74.0	-4.6	1.89 H	46	71.4	-2.0
2	2390.00	52.3 AV	54.0	-1.7	1.89 H	46	54.3	-2.0
3	*2412.00	109.2 PK			1.89 H	46	111.3	-2.1
4	*2412.00	99.3 AV			1.89 H	46	101.4	-2.1
5	4824.00	50.1 PK	74.0	-23.9	2.03 H	16	48.1	2.0
6	4824.00	36.8 AV	54.0	-17.2	2.03 H	16	34.8	2.0
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	70.2 PK	74.0	-3.8	3.00 V	351	72.2	-2.0
2	2390.00	53.1 AV	54.0	-0.9	3.00 V	351	55.1	-2.0
3	*2412.00	109.8 PK			3.00 V	351	111.9	-2.1
4	*2412.00	99.9 AV			3.00 V	351	102.0	-2.1
5	4824.00	45.7 PK	74.0	-28.3	1.49 V	68	43.7	2.0
6	4824.00	34.7 AV	54.0	-19.3	1.49 V	68	32.7	2.0

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	55.0 PK	74.0	-19.0	1.89 H	44	57.0	-2.0
2	2390.00	43.1 AV	54.0	-10.9	1.89 H	44	45.1	-2.0
3	*2437.00	111.7 PK			1.89 H	44	113.9	-2.2
4	*2437.00	101.7 AV			1.89 H	44	103.9	-2.2
5	2483.50	55.6 PK	74.0	-18.4	1.89 H	44	57.8	-2.2
6	2483.50	44.0 AV	54.0	-10.0	1.89 H	44	46.2	-2.2
7	4874.00	50.5 PK	74.0	-23.5	2.06 H	13	48.5	2.0
8	4874.00	37.1 AV	54.0	-16.9	2.06 H	13	35.1	2.0
9	7311.00	47.5 PK	74.0	-26.5	1.94 H	126	39.0	8.5
10	7311.00	35.2 AV	54.0	-18.8	1.94 H	126	26.7	8.5

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	55.2 PK	74.0	-18.8	2.70 V	6	57.2	-2.0
2	2390.00	43.3 AV	54.0	-10.7	2.70 V	6	45.3	-2.0
3	*2437.00	112.4 PK			2.70 V	6	114.6	-2.2
4	*2437.00	102.4 AV			2.70 V	6	104.6	-2.2
5	2483.50	55.9 PK	74.0	-18.1	2.70 V	6	58.1	-2.2
6	2483.50	44.4 AV	54.0	-9.6	2.70 V	6	46.6	-2.2
7	4874.00	45.7 PK	74.0	-28.3	1.49 V	76	43.7	2.0
8	4874.00	34.8 AV	54.0	-19.2	1.49 V	76	32.8	2.0
9	7311.00	49.0 PK	74.0	-25.0	3.33 V	45	40.5	8.5
10	7311.00	37.3 AV	54.0	-16.7	3.33 V	45	28.8	8.5

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	110.5 PK			1.86 H	44	112.7	-2.2
2	*2462.00	99.9 AV			1.86 H	44	102.1	-2.2
3	2483.50	68.4 PK	74.0	-5.6	1.86 H	44	70.6	-2.2
4	2483.50	52.5 AV	54.0	-1.5	1.86 H	44	54.7	-2.2
5	4924.00	49.9 PK	74.0	-24.1	2.10 H	1	47.9	2.0
6	4924.00	36.7 AV	54.0	-17.3	2.10 H	1	34.7	2.0
7	7386.00	47.3 PK	74.0	-26.7	1.99 H	123	38.7	8.6
8	7386.00	35.0 AV	54.0	-19.0	1.99 H	123	26.4	8.6
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	111.0 PK			2.71 V	355	113.2	-2.2
2	*2462.00	100.4 AV			2.71 V	355	102.6	-2.2
3	2483.50	68.9 PK	74.0	-5.1	2.71 V	355	71.1	-2.2
4	2483.50	53.2 AV	54.0	-0.8	2.71 V	355	55.4	-2.2
5	4924.00	46.0 PK	74.0	-28.0	1.55 V	71	44.0	2.0
6	4924.00	35.2 AV	54.0	-18.8	1.55 V	71	33.2	2.0
7	7386.00	49.5 PK	74.0	-24.5	3.36 V	37	40.9	8.6
8	7386.00	37.7 AV	54.0	-16.3	3.36 V	37	29.1	8.6

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11n (HT40)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.0 PK	74.0	-6.0	1.89 H	49	70.0	-2.0
2	2390.00	52.7 AV	54.0	-1.3	1.89 H	49	54.7	-2.0
3	*2422.00	102.8 PK			1.89 H	49	104.9	-2.1
4	*2422.00	93.9 AV			1.89 H	49	96.0	-2.1
5	4844.00	50.0 PK	74.0	-24.0	2.09 H	28	48.1	1.9
6	4844.00	36.8 AV	54.0	-17.2	2.09 H	28	34.9	1.9
7	7266.00	47.6 PK	74.0	-26.4	1.96 H	117	39.1	8.5
8	7266.00	35.5 AV	54.0	-18.5	1.96 H	117	27.0	8.5

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.8 PK	74.0	-5.2	3.24 V	249	70.8	-2.0
2	2390.00	53.4 AV	54.0	-0.6	3.24 V	249	55.4	-2.0
3	*2422.00	103.6 PK			3.24 V	249	105.7	-2.1
4	*2422.00	94.7 AV			3.24 V	249	96.8	-2.1
5	4844.00	43.6 PK	74.0	-30.4	1.50 V	92	41.7	1.9
6	4844.00	32.4 AV	54.0	-21.6	1.50 V	92	30.5	1.9
7	7266.00	47.0 PK	74.0	-27.0	3.32 V	33	38.5	8.5
8	7266.00	35.1 AV	54.0	-18.9	3.32 V	33	26.6	8.5

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.4 PK	74.0	-7.6	1.87 H	34	68.4	-2.0
2	2390.00	51.1 AV	54.0	-2.9	1.87 H	34	53.1	-2.0
3	*2437.00	107.2 PK			1.87 H	34	109.4	-2.2
4	*2437.00	97.3 AV			1.87 H	34	99.5	-2.2
5	2483.50	70.0 PK	74.0	-4.0	1.87 H	34	72.2	-2.2
6	2483.50	52.3 AV	54.0	-1.7	1.87 H	34	54.5	-2.2
7	4874.00	50.0 PK	74.0	-24.0	2.03 H	8	48.0	2.0
8	4874.00	36.6 AV	54.0	-17.4	2.03 H	8	34.6	2.0
9	7311.00	47.5 PK	74.0	-26.5	2.00 H	126	39.0	8.5
10	7311.00	35.4 AV	54.0	-18.6	2.00 H	126	26.9	8.5

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.3 PK	74.0	-6.7	2.49 V	8	69.3	-2.0
2	2390.00	52.0 AV	54.0	-2.0	2.49 V	8	54.0	-2.0
3	*2437.00	108.1 PK			2.49 V	8	110.3	-2.2
4	*2437.00	98.2 AV			2.49 V	8	100.4	-2.2
5	2483.50	70.9 PK	74.0	-3.1	2.49 V	8	73.1	-2.2
6	2483.50	53.1 AV	54.0	-0.9	2.49 V	8	55.3	-2.2
7	4874.00	45.4 PK	74.0	-28.6	1.45 V	74	43.4	2.0
8	4874.00	34.5 AV	54.0	-19.5	1.45 V	74	32.5	2.0
9	7311.00	49.5 PK	74.0	-24.5	3.30 V	40	41.0	8.5
10	7311.00	37.7 AV	54.0	-16.3	3.30 V	40	29.2	8.5

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	103.9 PK			1.90 H	43	106.1	-2.2
2	*2452.00	94.1 AV			1.90 H	43	96.3	-2.2
3	2483.50	66.2 PK	74.0	-7.8	1.90 H	43	68.4	-2.2
4	2483.50	52.5 AV	54.0	-1.5	1.90 H	43	54.7	-2.2
5	4904.00	50.9 PK	74.0	-23.1	2.03 H	0	48.9	2.0
6	4904.00	37.4 AV	54.0	-16.6	2.03 H	0	35.4	2.0
7	7356.00	47.2 PK	74.0	-26.8	1.96 H	141	38.7	8.5
8	7356.00	34.8 AV	54.0	-19.2	1.96 H	141	26.3	8.5
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	104.6 PK			2.89 V	358	106.8	-2.2
2	*2452.00	94.8 AV			2.89 V	358	97.0	-2.2
3	2483.50	67.1 PK	74.0	-6.9	2.89 V	358	69.3	-2.2
4	2483.50	53.4 AV	54.0	-0.6	2.89 V	358	55.6	-2.2
5	4904.00	43.1 PK	74.0	-30.9	1.43 V	85	41.1	2.0
6	4904.00	32.4 AV	54.0	-21.6	1.43 V	85	30.4	2.0
7	7356.00	47.6 PK	74.0	-26.4	3.38 V	59	39.1	8.5
8	7356.00	35.8 AV	54.0	-18.2	3.38 V	59	27.3	8.5

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

Below 1GHz Data:


802.11n (HT20)

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	31.29	30.8 QP	40.0	-9.2	2.50 H	266	40.5	-9.7
2	61.74	32.3 QP	40.0	-7.7	2.00 H	360	41.5	-9.2
3	96.52	33.1 QP	43.5	-10.4	2.00 H	248	45.7	-12.6
4	158.23	34.5 QP	43.5	-9.0	2.00 H	282	42.3	-7.8
5	193.76	38.9 QP	43.5	-4.6	1.50 H	271	49.2	-10.3
6	427.19	33.8 QP	46.0	-12.2	2.00 H	3	37.3	-3.5

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	34.97	33.5 QP	40.0	-6.5	1.00 V	155	43.0	-9.5
2	81.80	35.5 QP	40.0	-4.5	1.50 V	322	48.8	-13.3
3	105.56	32.0 QP	43.5	-11.5	1.00 V	360	43.3	-11.3
4	158.91	31.9 QP	43.5	-11.6	2.00 V	360	39.7	-7.8
5	200.50	37.5 QP	43.5	-6.0	1.00 V	360	47.9	-10.4
6	560.30	35.4 QP	46.0	-10.6	1.00 V	6	36.3	-0.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 24, 2018	Oct. 23, 2019
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 22, 2018	Oct. 21, 2019
Line-Impedance Stabilization Network (for Peripheral) R&S	ENV216	100072	June 04, 2018	June 03, 2019
50 ohms Terminator	N/A	3	Oct. 22, 2018	Oct. 21, 2019
RF Cable	5D-FB	COCCAB-001	Sep. 28, 2018	Sep. 27, 2019
Fixed attenuator EMCI	STI02-2200-10	003	Mar. 16, 2018	Mar. 15, 2019
Software BVADT	BVADT_Cond_ V7.3.7.4	NA	NA	NA

Note:

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Conduction 1.
3. Tested Date: Jan. 22, 2019

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.


4.2.7 Test Results

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16562	10.03	37.38	26.66	47.41	36.69	65.18	55.18	-17.77	-18.49
2	0.25156	10.05	38.17	34.35	48.22	44.40	61.71	51.71	-13.49	-7.31
3	8.87500	10.48	34.97	29.81	45.45	40.29	60.00	50.00	-14.55	-9.71
4	13.09766	10.70	36.74	30.49	47.44	41.19	60.00	50.00	-12.56	-8.81
5	17.62891	10.94	34.80	28.95	45.74	39.89	60.00	50.00	-14.26	-10.11
6	22.70313	11.11	33.57	28.41	44.68	39.52	60.00	50.00	-15.32	-10.48

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16562	9.93	29.79	25.99	39.72	35.92	65.18	55.18	-25.46	-19.26
2	0.25547	9.95	37.15	33.21	47.10	43.16	61.58	51.58	-14.48	-8.42
3	8.96094	10.33	33.76	28.42	44.09	38.75	60.00	50.00	-15.91	-11.25
4	12.58203	10.51	36.37	30.24	46.88	40.75	60.00	50.00	-13.12	-9.25
5	18.29688	10.79	35.70	30.76	46.49	41.55	60.00	50.00	-13.51	-8.45
6	20.99609	10.88	34.81	29.75	45.69	40.63	60.00	50.00	-14.31	-9.37

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




4.3 6dB Bandwidth Measurement

4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Result

802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	10.12	0.5	Pass
6	2437	10.09	0.5	Pass
11	2462	9.63	0.5	Pass

802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	16.08	0.5	Pass
6	2437	16.33	0.5	Pass
11	2462	15.79	0.5	Pass

802.11n (HT20)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	17.27	17.63	0.5	PASS
6	2437	17.32	17.65	0.5	PASS
11	2462	16.43	17.02	0.5	PASS

802.11n (HT40)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
3	2422	36.40	36.41	0.5	Pass
6	2437	35.44	35.60	0.5	Pass
9	2452	35.31	35.99	0.5	Pass

Spectrum Plot of Worst Value


802.11b : CH11




802.11g : CH11



802.11n (HT20) / Chain 0 : CH11



802.11n (HT40) / Chain 0 : CH9



4.4 Conducted Output Power Measurement

4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20-MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

Same as Item 4.3.6.

4.4.7 Test Results

FOR PEAK POWER

802.11b

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
1	2412	65.013	18.13	30	Pass
6	2437	66.069	18.20	30	Pass
11	2462	65.313	18.15	30	Pass

802.11g

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
1	2412	126.765	21.03	30	Pass
6	2437	145.881	21.64	30	Pass
11	2462	132.13	21.21	30	Pass

802.11n (HT20)

Chan.	Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	19.12	19.15	163.882	22.15	30	Pass
6	2437	21.57	21.34	279.693	24.47	30	Pass
11	2462	19.20	19.00	162.609	22.11	30	Pass

802.11n (HT40)

Chan.	Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	17.40	17.54	111.708	20.48	30	Pass
6	2437	21.00	20.96	250.631	23.99	30	Pass
9	2452	17.55	17.53	113.509	20.55	30	Pass

FOR AVERAGE POWER

802.11b

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	39.811	16.00
6	2437	43.853	16.42
11	2462	40.644	16.09

802.11g

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	36.392	15.61
6	2437	41.115	16.14
11	2462	37.67	15.76

802.11n (HT20)

Chan.	Frequency (MHz)	Avg. Power (dBm)		Total Power (mW)	Total Power (dBm)
		Chain 0	Chain 1		
1	2412	13.68	13.84	47.545	16.77
6	2437	16.25	16.19	83.761	19.23
11	2462	13.52	13.21	43.432	16.38

802.11n (HT40)


Chan.	Frequency (MHz)	Avg. Power (dBm)		Total Power (mW)	Total Power (dBm)
		Chain 0	Chain 1		
3	2422	12.36	12.38	34.517	15.38
6	2437	15.95	15.81	77.462	18.89
9	2452	12.40	12.28	34.282	15.35

4.5 Power Spectral Density Measurement

4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm in any 3 kHz.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

Same as Item 4.3.6

4.5.7 Test Results

802.11b

Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
1	2412	-8.24	8	Pass
6	2437	-8.34	8	Pass
11	2462	-8.34	8	Pass

802.11g

Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
1	2412	-11.40	8	Pass
6	2437	-10.45	8	Pass
11	2462	-11.19	8	Pass

802.11n (HT20)

Tx chain	Channel	Freq. (MHz)	PSD (dBm/3kHz)	10 log (N=2) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	1	2412	-12.99	3.01	-9.98	5.48	Pass
	6	2437	-10.99	3.01	-7.98	5.48	Pass
	11	2462	-12.32	3.01	-9.31	5.48	Pass
1	1	2412	-12.28	3.01	-9.27	5.48	Pass
	6	2437	-10.52	3.01	-7.51	5.48	Pass
	11	2462	-11.74	3.01	-8.73	5.48	Pass

Note: 1. Directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 8.52\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8 - (8.52 - 6) = 5.48\text{dBm}$


802.11n (HT40)

Tx chain	Channel	Freq. (MHz)	PSD (dBm/3kHz)	10 log (N=2) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	3	2422	-17.03	3.01	-14.02	5.48	Pass
	6	2437	-14.05	3.01	-11.04	5.48	Pass
	9	2452	-17.03	3.01	-14.02	5.48	Pass
1	3	2422	-16.48	3.01	-13.47	5.48	Pass
	6	2437	-14.19	3.01	-11.18	5.48	Pass
	9	2452	-17.25	3.01	-14.24	5.48	Pass


Note: 1. Directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 8.52\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8 - (8.52 - 6) = 5.48\text{dBm}$

Spectrum Plot of Worst Value


802.11b : CH1




802.11g : CH6



802.11n (HT20) / Chain 1 : CH6



802.11n (HT40) / Chain 0 : CH6




4.6 Conducted Out of Band Emission Measurement

4.6.1 Limits of Conducted Out of Band Emission Measurement

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOBE

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition


Same as Item 4.3.6

4.6.7 Test Results


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with

802.11b


CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





802.11g



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





802.11n (HT20)

Chain 0



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





Chain 1



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





802.11n (HT40) Chain 0



CH 3




CH 6




CH 9



CH 3 Band edge





CH 9 Band edge





Chain 1



CH 3




CH 6




CH 9



CH 3 Band edge



CH 9 Band edge



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---