

FCC RF EXPOSURE REPORT

FCC ID: TE7KLM100

Project No. : 1812C029
Equipment : Kasa Light Wi-Fi Module
Model : KLM100
Applicant : TP-Link Technologies Co., Ltd.
Address : Building 24(floors1,3,4,5) and 28(floors1-4)
Central Science and Technology Park,
Shennan Rd, Nanshan, Shenzhen, China

According: : FCC Guidelines for Human Exposure IEEE
C95.1 & FCC Part 2.1091

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan,
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000



Certificate #5123.02

1. GENERAL SUMMARY

Equipment : Kasa Light Wi-Fi Module
 Brand Name : tp-link
 Test Model : KLM100
 Series Model : N/A
 Applicant : TP-Link Technologies Co., Ltd.
 Manufacturer : TP-Link Technologies Co., Ltd.
 Address : Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China
 Factory : TP-Link Technologies Co., Ltd.
 Address : Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China
 Date of Test : Dec. 06, 2018~Dec. 21, 2018
 Test Sample : Engineering Sample
 No.: D181211171 for Conducted, D181211170 for Radiated
 Standards : FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-2-1812C029) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of A2LA according to the ISO/IEC 17025 quality assessment standard and technical standard(s).

2. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:


S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1		N/A	Printed	N/A	1.50

3. TEST RESULTS

Antenna Gain (dBi)	Antenna Gain (numeric)	Average Output Power (dBm)	Average Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
1.5	1.4125	17.96	62.5173	0.01758	1	Complies

Note: the calculated distance is 20 cm.

End of Test Report