



**FCC CFR47 PART 15 SUBPART C
CERTIFICATION**

TEST REPORT

FOR

2.4GHZ TRUE MIMO PC CARD

MODEL NUMBER: AGN1023PC

FCC ID: SA3-AGN1023PC0200

REPORT NUMBER: 04U2913-1

ISSUE DATE: AUGUST 11, 2004

Prepared for

**AIRGO NETWORKS INC.
900 ARASTRADERO ROAD
PALO ALTO, CA 94304, USA**

Prepared by

**COMPLIANCE CERTIFICATION SERVICES
561F MONTEREY ROAD,
MORGAN HILL, CA 95037, USA
TEL: (408) 463-0885
FAX: (408) 463-0888**



TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION.....	3
2. EUT DESCRIPTION.....	4
3. TEST METHODOLOGY	5
4. FACILITIES AND ACCREDITATION	5
5. CALIBRATION AND UNCERTAINTY.....	6
5.1. MEASURING INSTRUMENT CALIBRATION.....	6
5.2. MEASUREMENT UNCERTAINTY.....	6
5.3. TEST AND MEASUREMENT EQUIPMENT.....	7
6. SETUP OF EQUIPMENT UNDER TEST.....	8
7. APPLICABLE LIMITS AND TEST RESULTS	10
7.1. 6 dB BANDWIDTH.....	10
7.2. 99% BANDWIDTH.....	17
7.3. PEAK OUTPUT POWER.....	24
7.4. MAXIMUM PERMISSIBLE EXPOSURE	32
7.5. AVERAGE POWER.....	<i>Error! Bookmark not defined.</i>
7.6. PEAK POWER SPECTRAL DENSITY	33
7.7. CONDUCTED SPURIOUS EMISSIONS.....	40
7.8. RADIATED EMISSIONS.....	53
7.8.1. TRANSMITTER RADIATED SPURIOUS EMISSIONS	53
7.8.2. TRANSMITTER RADIATED EMISSIONS ABOVE 1 GHZ	56
7.8.3. WORST-CASE RADIATED EMISSIONS BELOW 1 GHz.....	74
7.9. POWERLINE CONDUCTED EMISSIONS	78
8. SETUP PHOTOS.....	82

1. TEST RESULT CERTIFICATION

COMPANY NAME: AIRGO NETWORKS INC
900 ARASTRADERO ROAD
PALO ALTO, CA 94304 U.S.A.

EUT DESCRIPTION: 2.4GHz True MIMO PC Card

MODEL: AGN1023PC

DATE TESTED: APRIL 7 – JULY 27, 2004

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 15 SUBPART C	NO NON-COMPLIANCE NOTED

Compliance Certification Services, Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: This document reports conditions under which testing was conducted and results of tests performed. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification Services will constitute fraud and shall nullify the document.

Approved & Released For CCS By:



MICHAEL HECKROTTE
EMC MANAGER
COMPLIANCE CERTIFICATION SERVICES

Tested By:



YAN ZHENG
EMC ENGINEER
COMPLIANCE CERTIFICATION SERVICES

2. EUT DESCRIPTION

The EUT is an 802.11b/g MIMO CardBus employs two transmitters and three receivers on each of two radio cards.

The transmitter has a maximum peak conducted output power as follows:

Frequency Band (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2412 - 2462	802.11b	23.32	214.78
2412 - 2462	802.11g	21.83	152.41

The radio utilizes two MIMO system antennas for diversity, each with a maximum gain of 2 dBi.

3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4/2001, FCC CFR 47 Part 2 and FCC CFR 47 Part 15.

4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 561F Monterey Road, Morgan Hill, California, USA. The sites are constructed in conformance with the requirements of ANSI C63.4, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.



No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government.

5. CALIBRATION AND UNCERTAINTY

5.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

5.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Radiated Emission, 30 to 200 MHz	+/- 3.3 dB
Radiated Emission, 200 to 1000 MHz	+4.5 / -2.9 dB
Radiated Emission, 1000 to 2000 MHz	+4.5 / -2.9 dB
Power Line Conducted Emission	+/- 2.9 dB

Uncertainty figures are valid to a confidence level of 95%.

5.3. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	Cal Due
Peak Power Meter	Agilent	E4416A	GB41291160	11/7/2004
Peak / Average Power Sensor	Agilent	E9327A	US40440755	11/7/2004
EMI Test Receiver	R & S	ESIB40	100192	11/21/2004
Antenna, Horn 1 ~ 18 GHz	EMCO	3117	29301	12/26/2004
Preamplifier, 1 ~ 26 GHz	Miteq	NSP10023988	646456	6/10/2005
EMI Receiver, 9 kHz ~ 2.9 GHz	HP	8542E	3942A00286	11/21/2004
RF Filter Section	HP	85420E	3705A00256	11/21/2004
30MHz---- 2Ghz	Sunol Sciences	JB1 Antenna	A121003	12/22/2004
Antenna, Horn 26 ~ 40 GHz	ARA	MWH-2640/B	1029	38324
Spectrum Analyzer	Agilent	E4446A	MY43360112	1/13/2005
EMI Test Receiver	R & S	ESHS 20	827129/006	7/17/2005
LISN, 10 kHz ~ 30 MHz	FCC	50/250-25-2	114	10/13/2004
LISN, 10 kHz ~ 30 MHz	Solar	8012-50-R-24-BNC	8379443	10/13/2004
AC Power Source, 10KVA	ACS	AFC-10K-AFC-2	J1568	CNR
Site A Line Stabilizer / Conditioner	Tripplite	LC-1800a	A0051681	CNR
PreAmplifier 26-40 GHz	MITEQ	NSP4000-SP2	924343	38139

6. SETUP OF EQUIPMENT UNDER TEST

SUPPORT EQUIPMENT

PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	FCC ID
Laptop PC	Sony	PCG-5312	28315730 3303321	AK8JPN-35452-M5-E


I/O CABLES

I/O CABLE LIST						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length	Remarks
1	AC	1	US115	UNSHIELDED	2m	NO
2	DC	1	DC	UNSHIELDED	2m	NO

TEST SETUP

The EUT is installed in a host laptop computer via a cardbus extender adapter during the tests. Test software exercised the radio card.

SETUP DIAGRAM FOR TESTS



7. APPLICABLE LIMITS AND TEST RESULTS

7.1. 6 dB BANDWIDTH

LIMIT

§15.247 (a) (2) For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to 100 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

RESULTS

No non-compliance noted:


802.11b Mode


Channel	Frequency (MHz)	6 dB Bandwidth (kHz)	Minimum Limit (kHz)	Margin (kHz)
Low	2412	9830	500	9330
Middle	2437	10170	500	9670
High	2462	10420	500	9920


802.11g Mode

Channel	Frequency (MHz)	6 dB Bandwidth (kHz)	Minimum Limit (kHz)	Margin (kHz)
Low	2412	15330	500	14830
Middle	2437	15420	500	14920
High	2462	15580	500	15080


6 DB BANDWIDTH (802.11b MODE)









6 DB BANDWIDTH (802.11g MODE)







7.2. 99% BANDWIDTH

LIMIT

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

RESULTS

No non-compliance noted:


802.11b Mode


Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	14.0609
Middle	2437	14.9469
High	2462	14.7875


802.11g Mode

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	15.289
Middle	2437	15.3962
High	2462	15.2137


99% BANDWIDTH (802.11b MODE)









99% BANDWIDTH (802.11g MODE)







7.3. PEAK OUTPUT POWER

PEAK POWER LIMIT

§15.247 (b) The maximum peak output power of the intentional radiator shall not exceed the following:

§15.247 (b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz , and 5725-5850 MHz bands: 1 watt.

§15.247 (b) (4) Except as shown in paragraphs (b)(4) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

§15.247 (b) (4) (i) Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer and the analyzer's internal channel power integration function is used to integrate the power over a bandwidth greater than or equal to the 99% bandwidth.

RESULTS

The maximum antenna gain is 2 dBi for other than fixed, point-to-point operations, therefore the limit is 30 dBm.

No non-compliance noted:


802.11b Mode


Channel	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Margin (dB)
Low	2412	23.32	30	-6.68
Middle	2437	21.28	30	-8.72
High	2462	20.86	30	-9.14


802.11g Mode

Channel	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Margin (dB)
Low	2412	21.83	30	-8.17
Middle	2437	20.32	30	-9.68
High	2462	19.27	30	-10.73


OUTPUT POWER (802.11b MODE)









OUTPUT POWER (802.11g MODE)







7.4. MAXIMUM PERMISSIBLE EXPOSURE

NOT APPLICABLE. The EUT is a portable device subject to SAR evaluation. SAR test results have been submitted.

7.5. PEAK POWER SPECTRAL DENSITY

LIMIT

§15.247 (d) For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer, the maximum level in a 3 kHz bandwidth is measured with the spectrum analyzer using RBW = 3 kHz and VBW > 3 kHz, sweep time = span / 3 kHz, and video averaging is turned off. The PPSD is the highest level found across the emission in any 3 kHz band.

RESULTS

No non-compliance noted:


802.11b Mode


Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin (dB)
Low	2412	-2.35	8	-10.35
Middle	2437	-4.84	8	-12.84
High	2462	-5.72	8	-13.72


802.11g Mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin (dB)
Low	2412	-5.06	8	-13.06
Middle	2437	-6.81	8	-14.81
High	2462	-7.30	8	-15.30


PEAK POWER SPECTRAL DENSITY (802.11b MODE)









PEAK POWER SPECTRAL DENSITY (802.11g MODE)







7.6. CONDUCTED SPURIOUS EMISSIONS

LIMITS

§15.247 (c) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

RESULTS


No non-compliance noted:


SPURIOUS EMISSIONS, LOW CHANNEL (802.11b MODE)







SPURIOUS EMISSIONS, MID CHANNEL (802.11b MODE)







SPURIOUS EMISSIONS, HIGH CHANNEL (802.11b MODE)







SPURIOUS EMISSIONS, LOW CHANNEL (802.11g MODE)







SPURIOUS EMISSIONS, MID CHANNEL (802.11g MODE)





SPURIOUS EMISSIONS, HIGH CHANNEL (802.11g MODE)





7.7. RADIATED EMISSIONS

7.7.1. TRANSMITTER RADIATED SPURIOUS EMISSIONS

LIMITS

§15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

§15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.


RESULTS

No non-compliance noted:


7.7.2. TRANSMITTER RADIATED EMISSIONS ABOVE 1 GHZ


RESTRICTED BANDEDGE (b MODE, LOW CHANNEL, HORIZONTAL)







RESTRICTED BANDEDGE (b MODE, LOW CHANNEL, VERTICAL)







RESTRICTED BANDEDGE (b MODE, HIGH CHANNEL, HORIZONTAL)





RESTRICTED BANDEDGE (b MODE, HIGH CHANNEL, VERTICAL)







HARMONICS AND SPURIOUS EMISSIONS (b MODE)


07/26/04 High Frequency Measurement Compliance Certification Services, Morgan Hill Open Field Site Test Engr: VIEN TRAN 0412821 Company: AIRGO EUT Descr.: 802.11abg CARDBUS EUT M/N: 1200 Test Target: FCC15 CLASS B Mode Oper: TX 11b L/M/H_HARMONIC & SPUR Test Equipment: <table border="1"><tr><td>EMCO Horn 1-18GHz T73; S/N: 6717 @3m</td><td>Spectrum Analyzer Agilent E4446A Analyzer</td><td>Pre-amplifier 1-26GHz T87 Miteq 924342</td><td>Pre-amplifier 26-40GHz</td><td>Horn >18GHz</td></tr></table> <table border="1"><tr><td colspan="4">Hi Frequency Cables ☒ (2 ft) ☐ (2 ~ 3 ft) ☐ (4 ~ 6 ft) ☒ (12 ft)</td><td colspan="2">Peak Measurements: 1 MHz Resolution Bandwidth 1MHz Video Bandwidth</td><td colspan="2">Average Measurements: 1 MHz Resolution Bandwidth 10Hz Video Bandwidth</td></tr></table>																EMCO Horn 1-18GHz T73; S/N: 6717 @3m	Spectrum Analyzer Agilent E4446A Analyzer	Pre-amplifier 1-26GHz T87 Miteq 924342	Pre-amplifier 26-40GHz	Horn >18GHz	Hi Frequency Cables ☒ (2 ft) ☐ (2 ~ 3 ft) ☐ (4 ~ 6 ft) ☒ (12 ft)				Peak Measurements: 1 MHz Resolution Bandwidth 1MHz Video Bandwidth		Average Measurements: 1 MHz Resolution Bandwidth 10Hz Video Bandwidth	
EMCO Horn 1-18GHz T73; S/N: 6717 @3m	Spectrum Analyzer Agilent E4446A Analyzer	Pre-amplifier 1-26GHz T87 Miteq 924342	Pre-amplifier 26-40GHz	Horn >18GHz																								
Hi Frequency Cables ☒ (2 ft) ☐ (2 ~ 3 ft) ☐ (4 ~ 6 ft) ☒ (12 ft)				Peak Measurements: 1 MHz Resolution Bandwidth 1MHz Video Bandwidth		Average Measurements: 1 MHz Resolution Bandwidth 10Hz Video Bandwidth																						
f GHz	Dist feet	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	HPF	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes													
LOW CH = 2412MHZ																												
4.824	9.8	45.0	31.4	33.4	2.9	-44.7	0.0	1.0	37.5	23.9	74.0	54.0	-36.5	-30.1	V													
4.824	9.8	42.9	30.0	33.4	2.9	-44.7	0.0	1.0	35.4	22.5	74.0	54.0	-38.6	-31.5	H													
MID CH=2437MHZ																												
4.874	9.8	46.2	33.2	33.4	2.9	-44.7	0.0	1.0	38.7	25.7	74.0	54.0	-35.3	-28.3	V													
7.311	9.8	53.0	41.8	35.8	4.2	-44.5	0.0	1.0	49.5	38.3	74.0	54.0	-24.5	-15.7	V													
4.874	9.8	40.4	28.7	33.4	2.9	-44.7	0.0	1.0	32.9	21.2	74.0	54.0	-41.1	-32.8	H													
7.311	9.8	44.0	31.8	35.8	4.2	-44.5	0.0	1.0	40.5	28.3	74.0	54.0	-33.5	-25.7	H													
HI CH = 2462MHZ																												
4.924	9.8	47.0	32.5	33.5	2.9	-44.8	0.0	1.0	39.6	25.1	74.0	54.0	-34.4	-28.9	V													
7.386	9.8	48.8	35.5	36.0	4.3	-44.5	0.0	1.0	45.5	32.2	74.0	54.0	-28.5	-21.8	V													
	9.8						0.0	1.0							V													
4.924	9.8	40.5	29.8	33.5	2.9	-44.8	0.0	1.0	33.1	22.4	74.0	54.0	-40.9	-31.6	H													
7.386	9.8	42.2	30.0	36.0	4.3	-44.5	0.0	1.0	38.9	26.7	74.0	54.0	-35.1	-27.3	H													
NO OTHER TX EMISSION WERE DETECTED AFTER 3RD HARMONIC																												
f	Measurement Frequency		Amp	Preamp Gain		Avg Lim	Average Field Strength Limit																					
Dist	Distance to Antenna		D Corr	Distance Correct to 3 meters		Pk Lim	Peak Field Strength Limit																					
Read	Analyzer Reading		Avg	Average Field Strength @ 3 m		Avg Mar	Margin vs. Average Limit																					
AF	Antenna Factor		Peak	Calculated Peak Field Strength		Pk Mar	Margin vs. Peak Limit																					
CL	Cable Loss		HPF	High Pass Filter																								


RESTRICTED BANDEDGE (g MODE, LOW CHANNEL, HORIZONTAL)







RESTRICTED BANDEDGE (g MODE, LOW CHANNEL, VERTICAL)







RESTRICTED BANDEDGE (g MODE, HIGH CHANNEL, HORIZONTAL)





RESTRICTED BANDEDGE (g MODE, HIGH CHANNEL, VERTICAL)






HARMONICS AND SPURIOUS EMISSIONS (g MODE)

07/26/04 High Frequency Measurement Compliance Certification Services, Morgan Hill Open Field Site																
Test Engr: VIEN TRAN Project #: 0412821 Company: AIRGO EUT Descr.: 802.11abg CARDBUS EUT M/N: 1200 Test Target: FCC15 CLASS B Mode Oper: TX 11g L/M/H_HARMONIC & SPUR																
Test Equipment:																
EMCO Horn 1-18GHz T73; S/N: 6717 @3m		Spectrum Analyzer HP 8593EM Analyzer		Pre-amplifier 1-26GHz T87 Miteq 924342		Pre-amplifier 26-40GHz		Horn > 18GHz								
Hi Frequency Cables ☒ (2 ft) ☐ (2 ~ 3 ft) ☐ (4 ~ 6 ft) ☒ (12 ft)																
Peak Measurements: 1 MHz Resolution Bandwidth 1MHz Video Bandwidth																
Average Measurements: 1 MHz Resolution Bandwidth 10Hz Video Bandwidth																
f GHz	Dist feet	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	HPF	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes	
LOW CH = 2412MHZ																
4.824	9.8	40.6	27.9	33.4	2.9	-44.7	0.0	1.0	33.1	20.4	74.0	54.0	-40.9	-33.6	V	
4.824	9.8	38.8	27.6	33.4	2.9	-44.7	0.0	1.0	31.3	20.1	74.0	54.0	-42.7	-33.9	H	
MID CH=2437																
4.874	9.8	39.9	28.0	33.4	2.9	-44.7	0.0	1.0	32.4	20.5	74.0	54.0	-41.6	-33.5	V	
7.311	9.8	50.0	36.1	35.8	4.2	-44.5	0.0	1.0	46.5	32.6	74.0	54.0	-27.5	-21.4	V	
12.185	9.8	41.0	29.4	39.2	6.2	-42.4	0.0	1.0	45.0	33.4	74.0	54.0	-29.0	-20.6	V	
4.874	9.8	39.0	27.8	33.4	2.9	-44.7	0.0	1.0	31.5	20.3	74.0	54.0	-42.5	-33.7	H	
7.311	9.8	44.0	31.8	35.8	4.2	-44.5	0.0	1.0	40.5	28.3	74.0	54.0	-33.5	-25.7	H	
HI CH = 2462MHZ																
4.924	9.8	39.6	27.4	33.5	2.9	-44.8	0.0	1.0	32.2	20.0	74.0	54.0	-41.8	-34.0	V	
7.386	9.8	43.6	31.0	36.0	4.3	-44.5	0.0	1.0	40.3	27.7	74.0	54.0	-33.7	-26.3	V	
4.924	9.8	39.0	27.2	33.5	2.9	-44.8	0.0	1.0	31.6	19.8	74.0	54.0	-42.4	-34.2	H	
7.386	9.8	42.2	30.0	36.0	4.3	-44.5	0.0	1.0	38.9	26.7	74.0	54.0	-35.1	-27.3	H	
NO OTHER TX EMISSION WERE DETECTED AFTER 3RD HARMONIC																
f	Measurement Frequency					Amp	Preamp Gain					Avg Lim	Average Field Strength Limit			
Dist	Distance to Antenna					D Corr	Distance Correct to 3 meters					Pk Lim	Peak Field Strength Limit			
Read	Analyzer Reading					Avg	Average Field Strength @ 3 m					Avg Mar	Margin vs. Average Limit			
AF	Antenna Factor					Peak	Calculated Peak Field Strength					Pk Mar	Margin vs. Peak Limit			
CL	Cable Loss					HPF	High Pass Filter									

WORST-CASE RADIATED EMISSIONS BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)



HORIZONTAL DATA

	Freq	Remark	Read Level	Factor	Level	Limit Line	Over Limit
	MHz		dBuV	dB	dBuV/m	dBuV/m	dB
1	198.780	QP	27.79	13.58	41.37	43.50	-2.13
2	198.780	Peak	29.79	13.58	43.37	43.50	-0.13
3	225.940	QP	32.05	13.07	45.12	46.00	-0.88
4 *	225.940	Peak	34.25	13.11	47.36	46.00	1.36
5	225.940	QP	32.00	13.07	45.07	46.00	-0.93
6	305.480	Peak	29.46	16.03	45.49	46.00	-0.51
7	305.480	QP	27.46	16.01	43.47	46.00	-2.53
8	332.640	QP	27.40	16.54	43.94	46.00	-2.06
9 *	332.640	Peak	29.64	16.54	46.18	46.00	0.18
10	725.490	Peak	21.71	24.23	45.94	46.00	-0.06
11	725.490	QP	19.50	24.22	43.72	46.00	-2.28
12	856.440	Peak	19.66	25.55	45.21	46.00	-0.79
13	856.440	QP	17.46	25.53	42.99	46.00	-3.01
14	921.430	QP	19.03	26.63	45.66	46.00	-0.34
15 *	921.430	Peak	21.23	26.73	47.97	46.00	1.96


SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)

VERTICAL PLOT



561F Monterey Road
San Jose, CA 95131
Tel: (408) 463-0888
Fax: (408) 463-0885

Data#: 2 File#: BELOW 1GHZ.EMI Date: 07-26-2004 Time: 09:54:00



(Audix ATC)

Trace: 1

Ref Trace:

Condition: FCC CLASS-B SUNOL BILOG 12/22/04 VERTICAL

Test Operator: : VIEN TRAN

Project #: : 04I2821

Company: : AIRGO

EUT: : CARDBUS 802.11abg

Model No: :

Configuration: : EUT / LAPTOP

Target of Test: : FCC-B

Mode of Operation: TX WORST CASE_ 2.4GHZ BAND

Page: 1

VERTICAL DATA

	Freq	Remark	Read Level	Factor	Level	Limit Line	Over Limit
	MHz		dBuV	dB	dBuV/m	dBuV/m	dB
1	43.580	Peak	23.06	13.58	36.64	40.00	-3.36
2	225.940	Peak	30.80	13.11	43.91	46.00	-2.09
3	320.030	Peak	26.04	16.23	42.27	46.00	-3.73
4	332.640	Peak	25.75	16.54	42.29	46.00	-3.71
5	352.040	Peak	25.95	16.91	42.86	46.00	-3.14
6	895.240	Peak	16.19	26.12	42.31	46.00	-3.69
7	902.030	Peak	16.78	26.21	42.99	46.00	-3.01
8	921.430	Peak	17.85	26.73	44.59	46.00	-1.42

7.8. POWERLINE CONDUCTED EMISSIONS

LIMIT

§15.207 (a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal.

The lower limit applies at the boundary between the frequency ranges.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.4.

The resolution bandwidth is set to 9 kHz for both peak detection and quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

Line conducted data is recorded for both NEUTRAL and HOT lines.


RESULTS

No non-compliance noted:


6 WORST EMISSIONS

CONDUCTED EMISSIONS DATA (115VAC 60Hz)									
Freq.	Reading			Closs	Limit	EN B	Margin		Remark
(MHz)	PK (dBuV)	QP (dBuV)	AV (dBuV)	(dB)	QP	AV	QP (dB)	AV (dB)	L1 / L2
0.15	54.70	--	17.33	0.00	66.00	56.00	-11.30	-38.67	L1
0.26	50.04	--	37.84	0.00	62.91	52.91	-12.87	-15.07	L1
6.15	48.14	--	16.74	0.00	60.00	50.00	-11.86	-33.26	L1
0.15	52.24	--	10.89	0.00	66.00	56.00	-13.76	-45.11	L2
5.74	46.66	--	22.17	0.00	60.00	50.00	-13.34	-27.83	L2
0.25	46.60	--	37.26	0.00	63.20	53.20	-16.60	-15.94	L2
6 Worst Data									

LINE 1 RESULTS




LINE 2 RESULTS





8. SETUP PHOTOS

ANTENNA PORT CONDUCTED RF MEASUREMENT SETUP




RADIATED RF MEASUREMENT SETUP





POWERLINE CONDUCTED EMISSIONS MEASUREMENT SETUP



LINE CONDUCTED BACK PHOTO



END OF REPORT