

FCC Test Report

Report No.: RWAQ202400273B

Applicant: Shenzhen Omni Intelligent Technology Co., Ltd.

Address: 11th Floor, Building 31, Phase III, Lianchuang Technology Park,
Nanwan street, Longgang District, Shenzhen, China

Product Name: Sharing scooter IOT

Product Model: M154-IOT

Multiple Models: N/A

Trade Mark: N/A

FCC ID: 2AI2O-M154IOT

Standards: FCC CFR Title 47 Part 15C (§15.247)

Test Date: 2024-06-06 to 2024-06-12

Test Result: Complied

Report Date: 2024-06-13

Reviewed by:

Abel chen

Abel Chen
Project Engineer

Approved by:

Jacob Kong

Jacob Kong
Manager

Prepared by:

World Alliance Testing & Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen,
Guangdong, People's Republic of China



This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk “★”

Announcement

1. This test report shall not be reproduced except in full, without the written approval of World Alliance Testing & Certification (Shenzhen) Co., Ltd
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.
5. The information marked “#” is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

Revision History

Version No.	Issued Date	Description
00	2024-06-13	Original

Contents

1	General Information	4
1.1	Client Information	4
1.2	Product Description of EUT	4
1.3	Antenna information	4
1.4	Related Submittal(s)/Grant(s).....	5
1.5	Measurement Uncertainty	5
1.6	Laboratory Location.....	5
1.7	Test Methodology	5
2	Description of Measurement.....	6
2.1	Test Configuration.....	6
2.2	Test Auxiliary Equipment	6
2.3	Test Setup.....	7
2.4	Test Procedure	9
2.5	Measurement Method.....	10
2.6	Measurement Equipment	10
3	Test Results	12
3.1	Test Summary.....	12
3.2	Limit	13
3.3	AC Line Conducted Emissions Test Data.....	14
3.4	Radiated emission Test Data.....	15
3.5	RF Conducted Test Data	23
3.5.1	6 dB Emission Bandwidth and 99% Occupied Bandwidth.....	23
3.5.2	Maximum Conducted Peak Output Power.....	23
3.5.3	Power Spectral Density.....	23
3.5.4	100 kHz Bandwidth of Frequency Band Edge	23
3.5.5	Duty Cycle	23
4	Test Setup Photo.....	29
5	E.U.T Photo	30

1 General Information

1.1 Client Information

Applicant:	Shenzhen Omni Intelligent Technology Co., Ltd.
Address:	11th Floor, Building 31, Phase III, Lianchuang Technology Park, Nanwan street, Longgang District, Shenzhen, China
Manufacturer:	Shenzhen Omni Intelligent Technology Co., Ltd.
Address:	11th Floor, Building 31, Phase III, Lianchuang Technology Park, Nanwan street, Longgang District, Shenzhen, China

1.2 Product Description of EUT

The EUT is Sharing scooter IOT that contains BLE and LTE radios, this report covers the full testing of the BLE radio.

Sample Serial Number	78-6 for RE test, 78-7 for RF test conducted test (assigned by WATC)
Sample Received Date	2024-05-28
Sample Status	Good Condition
Frequency Range	2402MHz - 2480MHz(BLE1M)
Maximum Conducted Peak Output Power	-3.20dBm
Modulation Technology	GFSK
Spatial Streams	SISO (1TX, 1RX)
Antenna Gain [#]	1.8dBi
Power Supply	DC 3.7V from battery or DC 12~72V
Adapter Information	N/A
Modification	Sample No Modification by the test lab

1.3 Antenna information

15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
Device Antenna information:	
The BLE antenna is an internal antenna which cannot replace by end-user, please see product internal photos for details.	

1.4 Related Submittal(s)/Grant(s)

FCC Part 22H/24E/27, Equipment Class: PCB, FCC ID: 2AI2O-M154IOT

1.5 Measurement Uncertainty

Parameter		Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
AC Power Lines Conducted Emissions		±3.14dB
Emissions, Radiated	Below 30MHz	±2.78dB
	Below 1GHz	±4.84dB
	Above 1GHz	±5.44dB
Emissions, Conducted		1.75dB
Conducted Power		0.74dB
Frequency Error		150Hz
Bandwidth		0.34%
Power Spectral Density		0.74dB
Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.		

1.6 Laboratory Location

World Alliance Testing & Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen, Guangdong, People's Republic of China

Tel: +86-755-29691511, Email: qa@watc.com.cn

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 463912, the FCC Designation No. : CN5040.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0160.

1.7 Test Methodology

FCC CFR 47 Part 2

FCC CFR 47 Part 15

KDB 558074 D01 DTS Meas Guidance v05r02

ANSI C63.10-2013

2 Description of Measurement

2.1 Test Configuration

Operating channels:					
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	19	2440	38	2478
1	2404	20	2442	39	2480
...	...	...	...	/	/
18	2438	...	...	/	/
According to ANSI C63.10-2013 chapter 5.6.1 Table 11 requirement, select lowest channel, middle channel, and highest channel in the frequency range in which device operates for testing. The detailed frequency points are as follows:					
Lowest channel		Middle channel		Highest channel	
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	19	2440	39	2480

Test Mode:				
Transmitting mode:		Keep the EUT in continuous transmitting with modulation		
Exercise software [#] :		DOGO_VP2.3.9		
Mode	Data rate	Power Level Setting [#]		
		Low Channel	Middle Channel	High Channel
BLE 1M	1Mbps	-5	-5	-5
The exercise software and the maximum power setting that provided by manufacturer.				


Worst-Case Configuration:
For radiated emissions, EUT was investigated in three orthogonal orientation, the worst-case orientation was recorded in report
For radiated emission 9kHz-1GHz and above 18GHz were performed with the EUT transmits at the channel with highest output power as worst-case scenario.

2.2 Test Auxiliary Equipment

Manufacturer	Description	Model	Serial Number
UNI-TREND Technology (CHINA) Co., Ltd.	DC Power Supply	UTP1310S	unknown

2.3 Test Setup


1) Conducted emission measurement:




Note: The 0.8 m distance specified between EUT/AE/PSU and AMN/AAN, is applicable only to the EUT being measured. If the device is AE then it shall be >0.8 m.

2) Radiated emission measurement:


Below 30MHz (3m SAC)




30MHz-1GHz (3m SAC)




1GHz-18GHz(3m FAC)



Above 18GHz (3m FAC)



3) RF Conducted Test



2.4 Test Procedure

Conducted emission:

1. The E.U.T is placed on a non-conducting table 40cm from the vertical ground plane and 80cm above the horizontal ground plane (Please refer to the block diagram of the test setup and photographs).
2. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
3. Line conducted data is recorded for both Line and Neutral

Radiated Emission Procedure:

a) For below 30MHz

1. All measurements were made at a test distance of 3 m. The measured data was extrapolated from the test distance (3m) to the specification distance (300 m from 9-490 kHz and 30 m from 490 kHz- 30 MHz) to clearly show the relative levels of fundamental and spurious emissions and demonstrate compliance with the requirement that the level of any spurious emissions be below the level of the intentionally transmitted signal. The extrapolation factor for the limits were $40 \cdot \log(\text{test distance} / \text{specification distance})$.
2. Loop antenna use, investigation was done on the three antenna orientations (parallel, perpendicular, ground-parallel)

b) For 30MHz-1GHz:

1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m.
2. EUT works in each mode of operation that needs to be tested. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.

c) For above 1GHz:

1. The EUT was placed on the tabletop of a rotating table 1.5 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m (1-18GHz) and 1.5 m (above 18GHz).
2. EUT works in each mode of operation that needs to be tested, and having the EUT continuously working. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.
3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.
4. Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

RF Conducted Test:

1. The antenna port of EUT was connected to the RF port of the test equipment (Power Meter or

Spectrum analyzer) through Attenuator and RF cable.

2. The cable assembly insertion loss of 6.5dB (including 6.0dB Attenuator and 0.5dB cable) was entered as an offset in the power meter. Note: Actual cable loss was unavailable at the time of testing, therefore a loss of 0.5dB was assumed as worst case. This was later verified to be true by laboratory. (if the RF cable provided by client, the cable loss declared by client)
3. The EUT is keeping in continuous transmission mode and tested in all modulation modes.

2.5 Measurement Method

Description of Test	Measurement Method
AC Line Conducted Emissions	ANSI C63.10-2013 Section 6.2
Maximum Conducted Output Power	ANSI C63.10-2013 Section 11.9.1.1
Power Spectral Density	ANSI C63.10-2013 Section 11.10.2
6 dB Emission Bandwidth	ANSI C63.10-2013 Section 11.8.1
99% Occupied Bandwidth	ANSI C63.10-2013 Section 6.9.3
100kHz Bandwidth of Frequency Band Edge	ANSI C63.10-2013 Section 6.10
Radiated emission	ANSI C63.10-2013 Section 11.11&11.12.1
Duty Cycle	ANSI C63.10-2013 Section 11.6

2.6 Measurement Equipment

Manufacturer	Description	Model	Management No.	Calibration Date	Calibration Due Date
Radiated Emission Test					
R&S	EMI test receiver	ESR3	102758	2023/7/3	2024/7/2
ROHDE& SCHWARZ	SPECTRUM ANALYZER	FSV40-N	101608	2023/7/3	2024/7/2
SONOMA INSTRUMENT	Low frequency amplifier	310	186014	2023/7/12	2024/7/11
COM-POWER	preamplifier	PAM-118A	18040152	2023/8/21	2024/8/20
COM-POWER	Amplifier	PAM-840A	461306	2023/8/8	2024/8/7
BACL	Loop Antenna	1313-1A	4010611	2024/2/7	2027/2/6
SCHWARZBECK	Log - periodic wideband antenna	VULB 9163	9163-872	2023/7/7	2024/7/6
Astro Antenna Ltd	Horn antenna	AHA-118S	3015	2023/7/6	2024/7/5
Ducommun technologies	Horn Antenna	ARH-4223-02	1007726-03	2023/7/10	2024/7/9

Oulitong	Band Reject Filter	OBSF-2400-248 3.5-50N	OE02103119	2023/9/15	2024/9/14
N/A	Coaxial Cable	N/A	NO.9	2023/8/8	2024/8/7
N/A	Coaxial Cable	N/A	NO.10	2023/8/8	2024/8/7
N/A	Coaxial Cable	N/A	NO.11	2023/8/8	2024/8/7
Audix	Test Software	E3	191218 V9	/	/
RF Conducted Test					
ROHDE& SCHWARZ	SPECTRUM ANALYZER	FSU-26	200680/026	2023/7/12	2024/7/11
narda	6dB attenuator	603-06-1	N/A	2023/7/26	2024/7/25

Note: All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or International standards.

3 Test Results

3.1 Test Summary

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
-	99% Occupied Bandwidth	Report only
§15.247(d)	100kHz Bandwidth of Frequency Band Edge	Compliance
§15.205, §15.209, §15.247(d)	Radiated emission	Compliance
-	Duty Cycle	Report only

3.2 Limit

Test items	Limit
AC Line Conducted Emissions	See details §15.207 (a)
Conducted Output Power	For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.
6dB Emission Bandwidth	The minimum 6 dB bandwidth shall be at least 500 kHz.
Power Spectral Density	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
Spurious Emissions, 100kHz Bandwidth of Frequency Band Edge	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.3 AC Line Conducted Emissions Test Data

Not Applicable, the device is for vehicle use.

3.4 Radiated emission Test Data


9 kHz-30MHz:

Test Date:	2024-06-12	Test By:	Luke Li
Environment condition:	Temperature: 23.1°C; Relative Humidity:72%; ATM Pressure: 99.9kPa		

For radiated emissions below 30MHz, there were no emissions found within 20dB of limit.

30MHz-1GHz:

Test Date:	2024-06-12	Test By:	Luke Li
Environment condition:	Temperature: 23.1°C; Relative Humidity:72%; ATM Pressure: 99.9kPa		




Project No. : RWAQ202400273
 Test Mode : Transmitting
 Test Voltage : DC 36V
 Environment : 23.1°C/72%R.H./99.9kPa
 Tested by : Luke Li
 Polarization : horizontal
 Remark : BLE 1M low channel

--No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector

1	108.855	41.28	-13.58	27.70	43.50	-15.80	Peak
2	172.940	38.79	-15.73	23.06	43.50	-20.44	Peak
3	191.958	36.84	-13.81	23.03	43.50	-20.47	Peak
4	349.051	39.18	-8.61	30.57	46.00	-15.43	Peak
5	403.912	37.22	-7.31	29.91	46.00	-16.09	Peak
6	437.458	36.82	-7.00	29.82	46.00	-16.18	Peak

Remarks: Factor = Antenna factor + Cable loss - Preamp gain



Project No. : RWAQ202400273
Test Mode : Transmitting
Test Voltage : DC 36V
Environment : 23.1°C/72%R.H./99.9kPa
Tested by : Luke Li
Polarization : vertical
Remark : BLE 1M low channel

--No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector
1	39.352	41.61	-13.68	27.93	40.00	-12.07	Peak
2	53.556	43.20	-12.30	30.90	40.00	-9.10	Peak
3	57.548	44.84	-13.17	31.67	40.00	-8.33	Peak
4	110.538	37.67	-13.76	23.91	43.50	-19.59	Peak
5	152.695	43.79	-16.89	26.90	43.50	-16.60	Peak
6	439.380	35.21	-7.00	28.21	46.00	-17.79	Peak

Remarks: Factor = Antenna factor + Cable loss - Preamp gain

Remark:

Result = Reading + Factor

Factor = Antenna factor + Cable loss – Amplifier gain

Over Limit = Result – Limit

Above 1GHz:

Test Date:	2024-06-06	Test By:	Bard Huang
Environment condition:	Temperature: 23.8°C; Relative Humidity:65%; ATM Pressure: 101.1kPa		

Frequency (MHz)	Reading level (dBμV)	Polar	Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
BLE 1M							
Low Channel							
2389.697	37.19	horizontal	7.18	44.37	54.00	-9.63	Average
2389.697	52.23	horizontal	7.18	59.41	74.00	-14.59	Peak
2389.650	36.27	vertical	7.18	43.45	54.00	-10.55	Average
2389.650	50.05	vertical	7.18	57.23	74.00	-16.77	Peak
4804.000	47.90	horizontal	-0.21	47.69	74.00	-26.31	Peak
4804.000	48.78	vertical	-0.21	48.57	74.00	-25.43	Peak
Middle Channel							
4880.000	47.72	horizontal	0.08	47.80	74.00	-26.20	Peak
4880.000	48.13	vertical	0.08	48.21	74.00	-25.79	Peak
High Channel							
2483.504	36.83	horizontal	7.25	44.08	54.00	-9.92	Average
2483.504	61.15	horizontal	7.25	68.40	74.00	-5.60	Peak
2483.617	36.31	vertical	7.25	43.56	54.00	-10.44	Average
2483.617	57.41	vertical	7.25	64.66	74.00	-9.34	Peak
4960.000	47.20	horizontal	0.28	47.48	74.00	-26.52	Peak
4960.000	47.12	vertical	0.28	47.40	74.00	-26.60	Peak

Remark:

Corrected Amplitude= Reading level + corrected Factor

Corrected Factor = Antenna factor + Cable loss – Amplifier gain


Margin = Corrected Amplitude – Limit


For the test result of Peak below the Peak limit more than 20dB, which can compliance with the average limit, just the Peak level was recorded.

The emission levels of other frequencies that were lower than the limit 20dB, not show in test report.

For emissions in 18GHz-25GHz range, all emissions were investigated and in the noise floor level.

Test plot for example as below:







Project No. : RWAQ202400273
 Test Mode : Transmitting
 Test Voltage : DC 36V
 Environment : 23.8°C/65%R.H./101.1kPa
 Tested by : Bard Huang
 Polarization : horizontal
 Remark : BLE 1M low channel

--No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Detector
1	19890.950	54.20	-7.29	46.91	74.00	-27.09	Peak
2	21809.900	53.92	-6.97	46.95	74.00	-27.05	Peak
3	24884.440	53.08	-3.58	49.50	74.00	-24.50	Peak

Remarks: Factor = Antenna factor + Cable loss - Preamp gain





Project No. : RWAQ202400273
Test Mode : Transmitting
Test Voltage : DC 36V
Environment : 23.8°C/65%R.H./101.1kPa
Tested by : Bard Huang
Polarization : vertical
Remark : BLE 1M low channel

--No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Detector
1	18836.920	52.67	-6.54	46.13	74.00	-27.87	Peak
2	21921.960	54.03	-6.80	47.23	74.00	-26.77	Peak
3	24488.740	53.43	-5.77	47.66	74.00	-26.34	Peak

Remarks: Factor = Antenna factor + Cable loss - Preamp gain

3.5 RF Conducted Test Data

Test Date:	2024-06-12	Test By:	Ryan Zhang
Environment condition:	Temperature: 25.7°C; Relative Humidity:55%; ATM Pressure: 100.5kPa		

3.5.1 6 dB Emission Bandwidth and 99% Occupied Bandwidth

Test Mode	Channel [MHz]	6dB BW [MHz]	99% OBW[MHz]	6dB BW Limit[MHz]	Verdict
BLE 1M	2402	0.680	1.020	0.5	pass
	2440	0.688	1.024	0.5	pass
	2480	0.692	1.024	0.5	pass

3.5.2 Maximum Conducted Peak Output Power

Test Mode	Channel [MHz]	Result [dBm]	Limit [dBm]	Verdict
BLE 1M	2402	-3.20	30	Pass
	2440	-3.48	30	Pass
	2480	-3.80	30	Pass

3.5.3 Power Spectral Density

Test Mode	Channel [MHz]	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
BLE 1M	2402	-19.70	8	Pass
	2440	-20.03	8	Pass
	2480	-20.33	8	Pass

3.5.4 100 kHz Bandwidth of Frequency Band Edge

Test Mode	Channel [MHz]	Result	Limit	Verdict
BLE 1M	2402	Refer test plot	Refer test plot	Pass
	2480	Refer test plot	Refer test plot	Pass




3.5.5 Duty Cycle

Test Mode	Channel [MHz]	Ton (ms)	Ton+off (ms)	Duty Cycle [%]	1/T [kHz]	VBW setting [Hz]
BLE 1M	2440	2.265	2.500	90.60	0.442	500




6 dB Emission Bandwidth:

Page 24 of 30

99% Occupied Bandwidth:

BLE 1M	/
Lowest channel	/
 Ref: 25 dBm Offset: 6.3 dB Att: 25 dB RBW: 20 kHz VBW: 50 kHz SWF: 20 ms Marker 1 [T1] -6.25 dBm 2.402000000 GHz Center: 2.402 GHz 200 kHz/ Span 2 MHz Date: 12.JUN.2024 15:46:54	/
Middle channel	/
 Ref: 25 dBm Offset: 6.3 dB Att: 25 dB RBW: 20 kHz VBW: 50 kHz SWF: 20 ms Marker 1 [T1] -6.55 dBm 2.440000000 GHz Center: 2.44 GHz 200 kHz/ Span 2 MHz Date: 12.JUN.2024 15:48:15	/
High channel	/
 Ref: 25 dBm Offset: 6.3 dB Att: 25 dB RBW: 20 kHz VBW: 50 kHz SWF: 20 ms Marker 1 [T1] -6.95 dBm 2.480000000 GHz Center: 2.48 GHz 200 kHz/ Span 2 MHz Date: 12.JUN.2024 15:49:16	/


Maximum Conducted Peak Output Power:

BLE 1M	/
Lowest channel	/
 Ref: 25 dBm Offset: 6.3 dB Att: 25 dB RBW: 3 MHz VBW: 10 MHz SWF: 2.5 ms Marker 1 [T1] -3.20 dBm 2.401880000 GHz Center: 2.402 GHz 1 MHz/ Span: 10 MHz Date: 12.JUN.2024 15:47:13	/
Middle channel	/
 Ref: 25 dBm Offset: 6.3 dB Att: 25 dB RBW: 3 MHz VBW: 10 MHz SWF: 2.5 ms Marker 1 [T1] -3.48 dBm 2.439700000 GHz Center: 2.44 GHz 1 MHz/ Span: 10 MHz Date: 12.JUN.2024 15:48:34	/
High channel	/
 Ref: 25 dBm Offset: 6.3 dB Att: 25 dB RBW: 3 MHz VBW: 10 MHz SWF: 2.5 ms Marker 1 [T1] -3.80 dBm 2.479600000 GHz Center: 2.48 GHz 1 MHz/ Span: 10 MHz Date: 12.JUN.2024 15:49:29	/


Power Spectral Density:

BLE 1M	/
Lowest channel	/
Ref: 25 dBm Offset: 6.3 dB Att: 25 dB RBW: 3 kHz VBW: 10 kHz SWT: 115 ms Marker 1 [T1] -19.70 dBm 2.40385720 GHz Center: 2.402 GHz 102 kHz/ Span: 1.02 MHz Date: 12.JUN.2024 15:47:20	/
Middle channel	/
Ref: 25 dBm Offset: 6.3 dB Att: 25 dB RBW: 3 kHz VBW: 10 kHz SWT: 115 ms Marker 1 [T1] -20.03 dBm 2.439833059 GHz Center: 2.44 GHz 103.05 kHz/ Span: 1.0305 MHz Date: 12.JUN.2024 15:48:41	/
High channel	/
Ref: 25 dBm Offset: 6.3 dB Att: 25 dB RBW: 3 kHz VBW: 10 kHz SWT: 120 ms Marker 1 [T1] -20.33 dBm 2.479831844 GHz Center: 2.48 GHz 103.8 kHz/ Span: 1.038 MHz Date: 12.JUN.2024 15:49:35	/

100kHz Bandwidth of Frequency Band Edge:



Duty cycle:



4 Test Setup Photo

Please refer to the attachment RWAQ202400273B Test Setup photo.

5 E.U.T Photo

Please refer to the attachment RWAQ202400273 External photo and RWAQ202400273 Internal photo.

---End of Report---