

RF TEST REPORT



Report No.: 16070340-FCC-R

Supersede Report No.: N/A

Applicant	Bytech NY Inc.	
Product Name	Bluetooth Speaker	
Model No.	BY-AU-SW-100-BK	
Serial No.	CL-AU-SW-100-BK	
Test Standard	FCC Part 15.247: 2015, ANSI C63.10: 2013	
Test Date	March 30 to April 11, 2016	
Issue Date	April 12, 2016	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification <input checked="" type="checkbox"/>		
Equipment did not comply with the specification <input type="checkbox"/>		
<i>Winnie Zhang</i>	<i>David Huang</i>	
Winnie Zhang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	16070340-FCC-R
Page	3 of 57

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	7
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	8
6.1 ANTENNA REQUIREMENT	8
6.2 CHANNEL SEPARATION	9
6.3 20DB BANDWIDTH	13
6.4 PEAK OUTPUT POWER	17
6.5 NUMBER OF HOPPING CHANNEL	21
6.6 TIME OF OCCUPANCY (DWEIL TIME)	23
6.7 BAND EDGE	27
6.8 AC POWER LINE CONDUCTED EMISSIONS	35
6.9 RADIATED SPURIOUS EMISSIONS	41
ANNEX A. TEST INSTRUMENT	46
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	47
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT	52
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	56
ANNEX E. DECLARATION OF SIMILARITY	57

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16070340-FCC-R	NONE	Original	April 12, 2016

2. Customer information

Applicant Name	Bytech NY Inc.
Applicant Add	2585 West 13th Street,Brooklyn NY 11223
Manufacturer	Bytech NY Inc.
Manufacturer Add	2585 West 13th Street,Brooklyn NY 11223

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT:	Bluetooth Speaker
Main Model:	BY-AU-SW-100-BK
Serial Model:	CL-AU-SW-100-BK
Date EUT received:	March 29, 2016
Test Date(s):	March 30 to April 11, 2016
Equipment Category :	DSS
Antenna Gain:	0dBi
Type of Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
RF Operating Frequency (ies):	2402-2480 MHz
Max. Output Power:	5.629 dBm
Number of Channels:	Bluetooth: 79CH
Port:	USB Port, Power Port, AUX-IN
Input Power:	Battery: Spec: DC 3.7V 1000mAh 3.7Wh USB Port:5V
Trade Name :	N/A
FCC ID:	2AHN6AUSW100BK

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)	20 dB Bandwidth	Compliance
§15.247(b)(1)	Peak Output Power	Compliance
§15.247(a)(1)(iii)	Number of Hopping Channel	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(d)	Band Edge	Compliance
§15.207(a)	AC Line Conducted Emissions	N/A
§15.205, §15.209, §15.247(d)	Radiated Emissions	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 1 antenna:

A permanently attached PCB antenna for Bluetooth, the gain is 0dBi for Bluetooth



The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 Channel Separation

Temperature	22°C
Relative Humidity	57%
Atmospheric Pressure	1005mbar
Test date :	April 05, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(a)(1)	a)	Channel Separation < 20dB BW and 20dB BW < 25KHz ; Channel Separation Limit=25KHz Chanel Separation < 20dB BW and 20dB BW > 25kHz ; Channel Separation Limit=2/3 20dB BW	
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings:</p> <ul style="list-style-type: none"> - The EUT must have its hopping function enabled - Span = wide enough to capture the peaks of two adjacent channels - Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span - Video (or Average) Bandwidth (VBW) ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot. 		

Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Channel Separation measurement result


Type/ Modulation	CH	CH Freq (MHz)	CH Separation (MHz)	Limit (MHz)	Result
CH Separation GFSK	Low Channel	2402	1.005	0.699	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.005	0.699	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.005	0.692	Pass
	Adjacency Channel	2479			
CH Separation $\pi/4$ DQPSK	Low Channel	2402	1.005	0.909	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.005	0.899	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.005	0.897	Pass
	Adjacency Channel	2479			
CH Separation 8DPSK	Low Channel	2402	1.005	0.897	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.005	0.903	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.005	0.902	Pass
	Adjacency Channel	2479			

Test Plots


Channel Separation measurement result




Test Report	16070340-FCC-R
Page	12 of 57



8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

6.3 20dB Bandwidth

Temperature	22°C
Relative Humidity	57%
Atmospheric Pressure	1005mbar
Test date :	April 05, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)	a)	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings:</p> <ul style="list-style-type: none"> - Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel - RBW \geq 1% of the 20 dB bandwidth - VBW \geq RBW - Sweep = auto - Detector function = peak - Trace = max hold. - The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference 		

Test Report	16070340-FCC-R
Page	14 of 57

	marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Measurement result


Modulation	CH	CH Freq (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GFSK	Low	2402	1.049	0.9381
	Mid	2441	1.049	0.9321
	High	2480	1.038	0.9355
π /4 DQPSK	Low	2402	1.364	1.2206
	Mid	2441	1.348	1.2162
	High	2480	1.346	1.2175
8DPSK	Low	2402	1.346	1.2277
	Mid	2441	1.354	1.2241
	High	2480	1.353	1.2307

Test Plots


20dB Bandwidth measurement result




Test Report	16070340-FCC-R
Page	16 of 57



8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

6.4 Peak Output Power

Temperature	22°C
Relative Humidity	57%
Atmospheric Pressure	1005mbar
Test date :	April 05, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	<input checked="" type="checkbox"/>
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	<input checked="" type="checkbox"/>
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with ≥ 25 & < 50 channels: ≤ 0.25 Watt	<input type="checkbox"/>
	f)	DTS in 902-928MHz, 2400-2483.5MHz: ≤ 1 Watt	<input type="checkbox"/>

Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>
------------	--

Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings:</p> <ul style="list-style-type: none"> - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel - RBW > the 20 dB bandwidth of the emission being measured - VBW \geq RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize.
----------------	--

Test Report	16070340-FCC-R
Page	18 of 57

	<p>- Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (see the note above regarding external attenuation and cable loss). The limit is specified in one of the subparagraphs of this Section. Submit this plot. A peak responding power meter may be used instead of a spectrum analyzer.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


Peak Output Power measurement result

Type	Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Limit (mW)	Result
Output power	GFSK	Low	2402	5.629	125	Pass
		Mid	2441	4.820	125	Pass
		High	2480	3.797	125	Pass
	π /4 DQPSK	Low	2402	5.575	125	Pass
		Mid	2441	3.032	125	Pass
		High	2480	3.204	125	Pass
	8DPSK	Low	2402	5.319	125	Pass
		Mid	2441	4.038	125	Pass
		High	2480	3.696	125	Pass


Test Plots

Output Power measurement result






8DPSK Output power - Low CH 2402



8DPSK Output power - Mid CH 2441




8DPSK Output power - High CH 2480

6.5 Number of Hopping Channel

Temperature	22°C
Relative Humidity	57%
Atmospheric Pressure	1005mbar
Test date :	April 05, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	FHSS in 2400-2483.5MHz \geq 15 channels	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer settings:</u> The EUT must have its hopping function enabled.</p> <ul style="list-style-type: none"> - Span = the frequency band of operation - RBW \geq 1% of the span - VBW \geq RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow trace to fully stabilize. - It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s). 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Number of Hopping Channel measurement result

Type	Modulation	Frequency Range	Number of Hopping Channel	Limit
Number of Hopping Channel	GFSK	2400-2483.5	79	15
	$\pi/4$ DQPSK	2400-2483.5	79	15
	8-DPSK	2400-2483.5	79	15

Test Plots


Number of Hopping Channels measurement result



6.6 Time of Occupancy (Dwell Time)

Temperature	22°C
Relative Humidity	57%
Atmospheric Pressure	1005mbar
Test date :	April 05, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	Dwell Time < 0.4s	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer</u></p> <ul style="list-style-type: none"> - Span = zero span, centered on a hopping channel - RBW = 1 MHz - VBW ≥ RBW - Sweep = as necessary to capture the entire dwell time per hopping channel - Detector function = peak - Trace = max hold - use the marker-delta function to determine the dwell time 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		


Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A


Type	Modulation	CH	Pulse Width (ms)	Dwell Time (ms)	Limit (ms)	Result
Dwell Time	GFSK	Low	2.750	293.333	400	Pass
		Mid	2.750	293.333	400	Pass
		High	2.875	306.667	400	Pass
	π /4 DQPSK	Low	2.775	296.000	400	Pass
		Mid	2.775	296.000	400	Pass
		High	2.950	314.667	400	Pass
	8DPSK	Low	2.800	298.667	400	Pass
		Mid	2.825	301.333	400	Pass
		High	2.775	296.000	400	Pass
Note: Dwell time=Pulse Time (ms) × (1600 ÷ 6 ÷ 79) ×31.6						

Test Plots


Dwell Time measurement result




Test Report	16070340-FCC-R
Page	26 of 57



8DPSK - Low CH 2402



8DPSK - Mid CH 2441




8DPSK - High CH 2480

6.7 Band Edge

Temperature	24°C
Relative Humidity	59%
Atmospheric Pressure	1007mbar
Test date :	April 07, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Radiated Method Only</p> <ul style="list-style-type: none"> 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, 		

Test Report	16070340-FCC-R
Page	28 of 57


	<p>and make sure the instrument is operated in its linear range.</p> <ul style="list-style-type: none"> - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: <ul style="list-style-type: none"> a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☐ Yes ☒ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Test Plots


GFSK Mode:




GFSK-Hopping Left Side-PK
Note: F1 is frequency 2400MHz





GFSK-Hopping Right Side-PK
Note: F1 is frequency 2483.5MHz



GFSK-Hopping Left Side-AV



GFSK-Hopping Right Side-AV





GFSK-Left Side-PK

Note: F1 is frequency 2400MHz

GFSK-Right Side-PK

Note: F1 is frequency 2483.5MHz



GFSK-Left Side-AV


GFSK-Right Side-AV

Top-Left Plot: $\pi/4$ DQPSK-Hopping Left Side-PK
 Note: F1 is frequency 2400MHz
 Att: 5 dB, RBW: 1 MHz, VBW: 3 MHz, Ref: 102.0 dBμV, SWT: 2.5ms
 M2[1]: 46.49 dBμV, 2.373440000 GHz
 M1[1]: 60.41 dBμV, 2.400000000 GHz
 Limit-L 74
 Start: 2.31 GHz, Stop: 2.44 GHz
 Date: 7.APR.2016 15:36:36

Top-Right Plot: $\pi/4$ DQPSK-Hopping Right Side-PK
 Note: F1 is frequency 2483.5MHz
 Att: 5 dB, RBW: 1 MHz, VBW: 3 MHz, Ref: 102.0 dBμV, SWT: 2.5ms
 M1[1]: 55.48 dBμV, 2.483770000 GHz
 Limit-R 74
 Start: 2.44 GHz, Stop: 2.5 GHz
 Date: 7.APR.2016 15:41:27


Bottom-Left Plot: $\pi/4$ DQPSK-Hopping Left-AV
 Att: 5 dB, RBW: 1 MHz, VBW: 3 MHz, Ref: 102.0 dBμV, SWT: 2.5ms
 M2[1]: 39.83 dBμV, 2.382270000 GHz
 M1[1]: 51.89 dBμV, 2.400000000 GHz
 Limit-L 54
 Start: 2.31 GHz, Stop: 2.44 GHz
 Date: 7.APR.2016 15:37:49

Bottom-Right Plot: $\pi/4$ DQPSK-Hopping Right-AV
 Att: 5 dB, RBW: 1 MHz, VBW: 3 MHz, Ref: 102.0 dBμV, SWT: 2.5ms
 M1[1]: 44.47 dBμV, 2.484010000 GHz
 Limit-R 54
 Start: 2.44 GHz, Stop: 2.5 GHz
 Date: 7.APR.2016 15:39:49




$\pi/4$ DQPSK-Left Side-PK

Note: F1 is frequency 2400MHz




$\pi/4$ DQPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz





$\pi/4$ DQPSK-Left Side-AV





$\pi/4$ DQPSK-Right Side-AV

8DPSK Mode:




8DPSK-Hopping Left Side-PK
Note: F1 is frequency 2400MHz

8DPSK--Hopping Right Side-PK
Note: F1 is frequency 2483.5MHz




8DPSK--Hopping Left-AV

8DPSK--Hopping Right-AV



Date: 7.APR.2016 15:03:32




Date: 7.APR.2016 15:19:45

8DPSK--Left Side-PK


Note: F1 is frequency 2400MHz

8DPSK--Right Side-PK

Note: F1 is frequency 2483.5MHz



Date: 7.APR.2016 15:04:20



Date: 7.APR.2016 15:18:09

8DPSK--Left Side-AV

8DPSK--Right Side-AV

6.8 AC Power Line Conducted Emissions

Temperature	23°C
Relative Humidity	58%
Atmospheric Pressure	1006mbar
Test date :	April 06, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable		
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	<div><input checked="" type="checkbox"/></div>		
		Frequency ranges (MHz)		Limit (dBµV)	
				QP	Average
		0.15 ~ 0.5		66 – 56	56 – 46
		0.5 ~ 5		56	46
5 ~ 30	60	50			

Test Setup	<p>Note: 1. Support units were connected to second LISN. 2. Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>
------------	--

Procedure	<ol style="list-style-type: none"> The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss
-----------	---


Test Report	16070340-FCC-R
Page	36 of 57

	<p>coaxial cable.</p> <ol style="list-style-type: none"> 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Bluetooth Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.9456	31.25	QP	10.03	41.28	56.00	-14.72
2	L1	0.9456	18.98	AVG	10.03	29.01	46.00	-16.99
3	L1	1.8426	33.96	QP	10.04	44.00	56.00	-12.00
4	L1	1.8426	20.53	AVG	10.04	30.57	46.00	-15.43
5	L1	2.7669	29.56	QP	10.05	39.61	56.00	-16.39
6	L1	2.7669	11.84	AVG	10.05	21.89	46.00	-24.11
7	L1	3.6903	25.89	QP	10.06	35.95	56.00	-20.05
8	L1	3.6903	9.65	AVG	10.06	19.71	46.00	-26.29
9	L1	4.7199	7.67	QP	10.08	17.75	56.00	-38.25
10	L1	4.7199	-0.96	AVG	10.08	9.12	46.00	-36.88
11	L1	5.4960	27.68	QP	10.09	37.77	60.00	-22.23
12	L1	5.4960	10.69	AVG	10.09	20.78	50.00	-29.22

Test Mode: Bluetooth Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.9495	30.47	QP	10.03	40.50	56.00	-15.50
2	N	0.9495	20.07	AVG	10.03	30.10	46.00	-15.90
3	N	1.8816	33.49	QP	10.04	43.53	56.00	-12.47
4	N	1.8816	21.10	AVG	10.04	31.14	46.00	-14.86
5	N	2.8410	34.46	QP	10.05	44.51	56.00	-11.49
6	N	2.8410	20.29	AVG	10.05	30.34	46.00	-15.66
7	N	3.7878	33.18	QP	10.06	43.24	56.00	-12.76
8	N	3.7878	18.09	AVG	10.06	28.15	46.00	-17.85
9	N	4.7394	29.37	QP	10.07	39.44	56.00	-16.56
10	N	4.7394	12.41	AVG	10.07	22.48	46.00	-23.52
11	N	5.6598	25.54	QP	10.08	35.62	60.00	-24.38
12	N	5.6598	14.49	AVG	10.08	24.57	50.00	-25.43

Test Mode: Bluetooth Mode




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	L1	0.9183	32.90	QP	10.03	42.93	56.00	-13.07
2	L1	0.9183	22.43	AVG	10.03	32.46	46.00	-13.54
3	L1	1.3707	16.99	QP	10.03	27.02	56.00	-28.98
4	L1	1.3707	6.73	AVG	10.03	16.76	46.00	-29.24
5	L1	1.8387	33.74	QP	10.04	43.78	56.00	-12.22
6	L1	1.8387	17.90	AVG	10.04	27.94	46.00	-18.06
7	L1	2.7630	30.98	QP	10.05	41.03	56.00	-14.97
8	L1	2.7630	17.97	AVG	10.05	28.02	46.00	-17.98
9	L1	3.6552	27.81	QP	10.06	37.87	56.00	-18.13
10	L1	3.6552	15.70	AVG	10.06	25.76	46.00	-20.24
11	L1	0.9183	32.90	QP	10.03	42.93	56.00	-13.07
12	L1	0.9183	22.43	AVG	10.03	32.46	46.00	-13.54

Test Mode: Bluetooth Mode



Test Data


Phase Neutral Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.9456	39.80	QP	10.03	49.83	56.00	-6.17
2	N	0.9456	26.23	AVG	10.03	36.26	46.00	-9.74
3	N	1.8426	39.93	QP	10.04	49.97	56.00	-6.03
4	N	1.8426	26.46	AVG	10.04	36.50	46.00	-9.50
5	N	2.7630	39.06	QP	10.05	49.11	56.00	-6.89
6	N	2.7630	24.85	AVG	10.05	34.90	46.00	-11.10
7	N	3.7878	38.16	QP	10.06	48.22	56.00	-7.78
8	N	3.7878	24.25	AVG	10.06	34.31	46.00	-11.69
9	N	4.7316	37.10	QP	10.07	47.17	56.00	-8.83
10	N	4.7316	21.50	AVG	10.07	31.57	46.00	-14.43
11	N	5.6754	35.88	QP	10.08	45.96	60.00	-14.04
12	N	5.6754	20.20	AVG	10.08	30.28	50.00	-19.72

6.9 Radiated Spurious Emissions

Temperature	23°C
Relative Humidity	58%
Atmospheric Pressure	1006mbar
Test date :	April 06, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable											
47CFR§15.205, §15.209, §15.247(d)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges												
		<table><tr><th>Frequency range (MHz)</th><th>Field Strength (µV/m)</th></tr><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></table>		Frequency range (MHz)	Field Strength (µV/m)	30 – 88	100	88 – 216	150	216 960	200	Above 960	500	
		Frequency range (MHz)		Field Strength (µV/m)										
		30 – 88		100										
		88 – 216		150										
		216 960		200										
Above 960	500													

Test Setup	
------------	--

Procedure	<ol style="list-style-type: none"> The EUT was switched on and allowed to warm up to its normal operating condition. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:
-----------	---

Test Report	16070340-FCC-R
Page	42 of 57


	<p>a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen.</p> <p>b. The EUT was then rotated to the direction that gave the maximum emission.</p> <p>c. Finally, the antenna height was adjusted to the height that gave the maximum emission.</p> <p>3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</p> <p>4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</p> <p>5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Bluetooth Mode

Below 1GHz




Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	H	177.5092	43.13	peak	-9.69	33.44	43.50	-10.06	100	142
2	H	311.0867	45.64	peak	-6.58	39.06	46.00	-6.94	100	281
3	H	400.4319	42.98	peak	-4.29	38.69	46.00	-7.31	100	255
4	H	489.0269	41.34	peak	-1.99	39.35	46.00	-6.65	100	153
5	H	578.6699	38.13	peak	-0.34	37.79	46.00	-8.21	100	131
6	H	758.0408	37.44	QP	2.54	39.98	46.00	-6.02	100	120

Below 1GHz



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	V	52.0251	47.53	QP	-13.42	34.11	40.00	-5.89	100	306
2	V	489.0269	43.05	QP	-1.99	41.06	46.00	-4.94	100	1
3	V	668.1423	40.30	QP	1.02	41.32	46.00	-4.68	100	29
4	V	758.0408	40.93	QP	2.54	43.47	46.00	-2.53	100	186
5	V	845.0878	38.52	QP	3.75	42.27	46.00	-3.73	100	164
6	V	935.5463	35.90	QP	5.01	40.91	46.00	-5.09	100	220

Test Mode:	Transmitting Mode
------------	-------------------

Mode: GFSK (Worst Case)

Low Channel (2402 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4804	38.51	AV	V	33.83	6.86	31.72	47.48	54	-6.52
4804	38.19	AV	H	33.83	6.86	31.72	47.16	54	-6.84
4804	51.25	PK	V	33.83	6.86	31.72	60.22	74	-13.78
4804	50.83	PK	H	33.83	6.86	31.72	59.8	74	-14.2

Middle Channel (2441 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4882	38.44	AV	V	33.86	6.82	31.82	47.3	54	-6.7
4882	38.07	AV	H	33.86	6.82	31.82	46.93	54	-7.07
4882	51.19	PK	V	33.86	6.82	31.82	60.05	74	-13.95
4882	50.63	PK	H	33.86	6.82	31.82	59.49	74	-14.51

High Channel (2480 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4960	38.61	AV	V	33.9	6.76	31.92	47.35	54	-6.65
4960	38.15	AV	H	33.9	6.76	31.92	46.89	54	-7.11
4960	51.37	PK	V	33.9	6.76	31.92	60.11	74	-13.89
4960	50.54	PK	H	33.9	6.76	31.92	59.28	74	-14.72

Note:

- 1, The testing has been conformed to 10*2480MHz=24,800MHz
- 2, All other emissions more than 30 dB below the limit

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191106	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191107	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
LISN	ISN T800	34373	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
Transient Limiter	LIT-153	531118	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Positioning Controller	UC3000	MF780208282	11/19/2015	11/18/2016	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/21/2015	09/20/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo




Whole package - Front View




EUT - Front View



EUT - Rear View



EUT - Top View



EUT - Bottom View



EUT - Left View




EUT - Left View


Annex B.ii. Photograph: EUT Internal Photo




Cover Off - Top View




Small Mainboard - Front View



Small Mainboard - Rear View




Mainboard - Front View




Mainboard - Rear View



Battery - Front View



Battery - Rear View




BT - Antenna View

Annex B.iii. Photograph: Test Setup Photo




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below
1GHz




Radiated Spurious Emissions Test Setup Above
1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for Conducted Emissions



Block Configuration Diagram for Radiated Emission (Below 1GHz) .



Block Configuration Diagram for Radiated Emission (Above 1GHz) .



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Lenovo	Lenovo Laptop	E40	LR-1EHRX
Lenovo	Mobile phone	X1	XT2001

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	ST22100

Test Report	16070340-FCC-R
Page	56 of 57

Annex D. User Manual / Block Diagram / Schematics / Partlist

N/A

Test Report	16070340-FCC-R
Page	57 of 57

Annex E. DECLARATION OF SIMILARITY

N/A