

司南微电子（深圳）有限公司

SINAWELL Electronics(Shenzhen) Co., Ltd.

Customer Name	Shenzhen cannice Technology Co., Ltd
Product Name	A1101-10-L
Customer Item Number	300012000317
Project name	A1101-10-L
Product brand	SN
Product model	SN1229-BT-L

Appendix	☒ cover	☒ buleprint	☐ FAI report	☐ CPK report告
	☒ Reliability Test Report	☐ 3D model	☒ RoHS	☐ UN38.3

Supplier	Make	Audit	Approval
Signature	Chen de	Li xiao long	Zhang ping

Customer	Make	Audit	Approval
Signature			

Admit condition	☐ admit	☐ Denial of recognition
	☐ Conditional recognition	Conditions to be satisfied:
	☐ Provisional recognition	limit____PCS

Supplier Information:	
Name : SINAWELL Electronics(Shenzhen) Co., Ltd.	Contacts : Zhang wen feng
ADD: 708-718, Jinfulai Building, 49-1 Dabao Road, Xin'an 28 District, Bao'an District, Shenzhen	
TLE : 0755-29988460	Fax : 0755-29988470
EMAIL: zwf@sinawell.cn	

Rev: B

The Main Antenna Sample Confirmation

Customer	Shenzhen CANNICE Technology Co., Ltd.		
Project Name	A1101-10-L		Date2024-07-03
Project NO.	SN1229-BT-L	Notes	FPC
Frequency Range	BT		
Designed By	RF Engineer	Structural Engineer	
Checked By	Engineering Manager		
Client' s Approval			

Designer: SINAWELL Electronics(Shenzhen) Co., Ltd.

Add: 712-717, Block A Jinfulai Building,49-1 Dabao Road,Xinan 28th area,Baoan District,Shenzhen,China

Table of Contents

Specification description.....	1
1. Summary of specifications.....	1
2. Appearance.....	3
3. Electrical performance.....	3
3.1. Antenna band.....	3
3.2. Matching circuit.....	3
3.3. Return Loss.....	4
3.4. Antenna Gain.....	4
4. Appearance structure.....	5
4.1. Antenna Material.....	5
5. Remarks.....	6
Appendix I (Mechanical drawing).....	6
Appendix II (Performance Report)	7-10
6. Size Report	11
7. Salt fog report.....	12
8. Explanation of FPC Preservation Period	13
9. Base material shipment report.....	14
12. Quality Assurance.....	15
13. Product raw material list.....	16

1. Specification description

This specification describes the status of the A1101-10-L internal antenna with a frequency band of 2400MHz-2500MHz.

2. Antenna appearance



3. Electrical performance

3.1. Antenna band


	BT
Transmitting band(MHz)	2400MHz-2500MHz

3.2. Matching Circuit

After the test point is at the antenna connector (RF test port), see the figure below.

1. BT antenna matching.

Element	Value
E1(0402)	NC
E2(0402)	0 Ω
E3(0402)	NC
E4(0402)	0 Ω



3.3. Return Loss

BT VSWR+ Return

	Resonant Point Range(MHz)	Frequency point(MHz)/Maximum Echo Loss(dB)		
	2400-2500		2400	2500
		VSWR	1.3	1.6
		Return loss	-17.69	-12.74

3.4. Antenna Gain

Freq	Effi	Effi	Gain
(MHz)	(%)	(dB)	(dBi)
2400	15.15	-8.2	-1.19
2410	18.49	-7.33	-0.43
2420	19.9	-7.01	-0.24
2430	22.03	-6.57	0.14
2440	24.29	-6.15	0.54
2450	25.78	-5.89	0.78
2460	26.98	-5.69	0.95
2470	26.23	-5.81	0.89
2480	26.97	-5.69	0.99
2490	25.56	-5.92	0.81
2500	25.11	-6	0.92

4. Appearance structure

4.1. Antenna Material

5. Notes

(Electrical Performance Test Report)


In the electrical performance test report, the 3D darkroom data for manufacturers are provided.

The following table format

Appendix 1: (Mechanical drawing)

Appendix II (Performance report)




FPC Mechanical drawing(Annex I)

1	2	3	4	5	6	7	8																								
		<table border="1" style="font-size: 8px;"> <tr> <th colspan="4">The third person</th> </tr> <tr> <td>0~10</td> <td>±0.05</td> <td>○</td> <td>0.02</td> </tr> <tr> <td>10~18</td> <td>±0.10</td> <td>●</td> <td>0.03</td> </tr> <tr> <td>18~30</td> <td>±0.12</td> <td>⊥</td> <td>0.02</td> </tr> <tr> <td>30~40</td> <td>±0.15</td> <td>∠</td> <td>0.04</td> </tr> <tr> <td>40~</td> <td>±0.20</td> <td>Angle</td> <td>±0.5°</td> </tr> </table>						The third person				0~10	±0.05	○	0.02	10~18	±0.10	●	0.03	18~30	±0.12	⊥	0.02	30~40	±0.15	∠	0.04	40~	±0.20	Angle	±0.5°
The third person																															
0~10	±0.05	○	0.02																												
10~18	±0.10	●	0.03																												
18~30	±0.12	⊥	0.02																												
30~40	±0.15	∠	0.04																												
40~	±0.20	Angle	±0.5°																												
A							A																								
B							B																								
C							C																								
Notes: 1. "*" is the key dimension ; 2. Please refer to the drawing if no dimension is indicated; 3. Meet rohs2.0, reach environmental protection requirements.																															
<table border="1" style="width:100%;"> <tr> <td style="width:10%;">B</td> <td style="width:70%;">Film change</td> <td style="width:10%;">Date</td> <td style="width:10%;">Remarks</td> </tr> <tr> <td>Rev.</td> <td>Modify the content</td> <td></td> <td></td> </tr> </table>				B	Film change	Date	Remarks	Rev.	Modify the content			<table border="1" style="width:100%;"> <tr> <td style="width:10%;">1</td> <td style="width:40%;">BT antenna</td> <td style="width:30%;">Electrolytic copper</td> <td style="width:10%;">Black</td> <td style="width:10%;">Gold Finger Plating</td> </tr> <tr> <td>No.</td> <td>Part name</td> <td>Material</td> <td>Color</td> <td>Thickness</td> </tr> </table>				1	BT antenna	Electrolytic copper	Black	Gold Finger Plating	No.	Part name	Material	Color	Thickness						
B	Film change	Date	Remarks																												
Rev.	Modify the content																														
1	BT antenna	Electrolytic copper	Black	Gold Finger Plating																											
No.	Part name	Material	Color	Thickness																											
司南微电子(深圳)有限公司 SINAWELL Electronics (Shenzhen) Co., LTD <table border="1" style="width:100%;"> <tr> <td style="width:40%;">Project name</td> <td style="width:20%;">AI101-10(SN1229)</td> <td style="width:20%;">Date</td> <td style="width:20%;">2024-07-03</td> </tr> <tr> <td>Product name</td> <td>BT antenna</td> <td>ME</td> <td></td> </tr> <tr> <td>Material no.</td> <td>SN1229-BT-L</td> <td>RF</td> <td></td> </tr> <tr> <td>Material</td> <td></td> <td>Project</td> <td></td> </tr> <tr> <td colspan="2"></td> <td>Company</td> <td>mm Scale 1:1 Rev. B</td> </tr> </table>								Project name	AI101-10(SN1229)	Date	2024-07-03	Product name	BT antenna	ME		Material no.	SN1229-BT-L	RF		Material		Project				Company	mm Scale 1:1 Rev. B				
Project name	AI101-10(SN1229)	Date	2024-07-03																												
Product name	BT antenna	ME																													
Material no.	SN1229-BT-L	RF																													
Material		Project																													
		Company	mm Scale 1:1 Rev. B																												
D							D																								
1	2	3	4	5	6	7	8																								

Focus on size




NO	Size(mm)	Tolerance(mm)	Notes
1	14.22	±0.2	
2	23.67	±0.2	
3	0.12	±0.02	
4			
5			
6			




3DTest Report (FS)

BT	Channel	3DCoupling Test	Field strength map
TRP	0	2	Bluetooth 0 TRP 
TIS	0	-87.49	Bluetooth 0 TIS 
TRP	39	4.47	Bluetooth 39 TRP 

TIS	39	-87.85	Bluetooth 39 TIS
TRP	78	3.87	Bluetooth 78 TRP
TIS	78	-87.09	Bluetooth 78 TIS

3DTest Report (BH)

BT	Channel	3DCoupling Test	Field strength map
TRP	0	-0.69	 Bluetooth 0 TRP
TIS	0	-81.89	 Bluetooth 0 TIS
TRP	39	1.98	 Bluetooth 39 TRP

TIS	39	-83.86	Bluetooth 39 TIS 
TRP	78	2.94	Bluetooth 78 TRP 
TIS	78	-83.77	Bluetooth 78 TIS 

Size Report

	Customer	cannice	Project Name	A1101-10-BT-L		Measurement Date	2024-07-03	
	Supplier	sinawell	Measurement Tool	Quadratic		Unit	mm	
NO	dimension	Toleranca	Measure 1	Measure 2	Measure 3	Measure 4	Measure 5	determine
1	14. 22	±0. 2	14.26	14.28	14.26	14.27	14.26	OK
2	23. 67	±0. 2	23.70	23.68	23.71	23.70	23.72	OK
3	0. 12	±0. 02	0.11	0.11	0.11	0.11	0.11	OK
4								
5								
6								
7								
8								
9								
10								
11								
12								
13								
14								
15								
16								
17								
18								
19								
20								
21								
22								

DRAWN BY: shimeng yang

APPROVED BY: De Chen

Salt fog Report

Customer Name	CANNICE	Corax	A1101-10-BT-L	Tester	shimeng yang
Test Quantity	5PCS	Test Item	Salt fog	Test Date	2024-07-03
Test conditions	1.Temperature: 35℃				
	2.Humidity: 98%, PH: 6.5-7.2				
	3.Temperature in the box: 37℃				
	4.Test duration: 24hours				
	5.Drug concentration: 5%NaCl				
Testing procedure	1.Put the product in the salt mist box.				
	2.Place the product at the right angle.				
	3.set the relevant parameters and start the spray.				
	4.Complete the removal of the experimental product. Before inspection, wash the product with clean water and place it at room temperature for two hours.				
TEST	Projects	Before testing	After testing	test result	remarks
	Coating	Well	Well	qualified	
	Conductivity	Well	Well	qualified	
	Resistance	Well	Well	qualified	
	Cohesion	Well	Well	qualified	

DRAWN BY: shimeng yang

APPROVED BY: De Chen

Explanation of FPC Preservation Period

I .Preservation conditions: temperature 21 +4; humidity 60% H +10%.

II . Exit Guarantee

1.Appearance Guarantee: No oxidation occurs during 12 months of storage in original packaging.

2.Functional Assurance

A:One year to ensure good welding continuity.

B:Ensure good conductivity within two years.

III、 Points for Attention in FPC Welding

1. FC itself has hygroscopicity. It is suggested to preheat the three-layer plate (including) for 30 minutes before use, and bake it for 120 minutes at 100 in order to avoid bursting due to hygroscopicity and rapid oxidation during operation.

2. HOT BAR jobs

A: FPC is used for cooked pressing. CVI should be crossed over glass to avoid suspension, resulting in fracture of copper during bending.

B: FPC avoids the use of dead angle and is liable to cause fracture.

3: SMT operation: The plating part should be shielded to prevent atomization in flow welding.

4: Hand welding operation: the working temperature of soldering iron should not exceed 290 C, and the time of soldering iron staying on the plate surface should not exceed 10 seconds.



覆铜板检验报告
PI CCL Quality Test Report

日期 (DATE) : 2023-11-09

品名 (Product Name)	SHISE252018FY1
PI 厚度 (PI film Thickness) μm	25
接着剂厚 (Adhesive Thickness) μm	20
铜箔厚度 (Copper Foil Thickness) μm	18
幅宽 (Width) mm	250
生产日期 (P/Date)	2023-11-08
保质期 (Shelf life)	2023-11-08-2024-11-07


工厂地址: 江苏省太仓市太平北路 168 号
TEL: 0512-53378333 FAX: 0512-53378355
Factory Address: No. 168 Taping North Road,
TaiCang City, JiangSu Province, China.

测试项目 Item		品质标准 (Spec)	测试结果 (Result)			测试方法 (Test Method)
			生产批号 (LOT NO.):			
			23B08A**	***		
厚度 Thickness (μm)		±10%	63	***		SERENGETI SPEC
剥离强度 Peel Strength(kgf/cm)	A 面	≥0.7	1.22	***		IPC-TM-650 2.4.9
	B 面					
尺寸安定性 Dimensional Stability(%)	MD	≤±0.2%	-0.0853	Nothing		IPC-TM-650 2.2.4
	TD		0.0873	Follows		
焊锡耐热性 Solder Resistance		300℃*10SEC 无分层起泡	PASS	***		IPC-TM-650 2.4.13
外观 Appearance		无凸点、撞损、裁切不良、皱痕等等	OK	***		SERENGETI SPEC

注: 1、保存条件: 常温常湿保存一年 (Deadline of reserve is 1 year in normal condition)。

2、以上测试项目仅供参考 (Above test for reference only)。

苏州蔡伦格蒂电子材料有限公司

审核:  

Quality Assurance Certificate

Customer Name: Shenzhen Kenaixin Technology Co., Ltd

Our commitment A1101-10-BT-L product, Has been produced and inspected according to your company's technical quality indicators or supply quality agreement, All indicators are qualified, Factory approval.

Product raw material list

Category	Name of material	Material specifications	Suppliers
FPC	Substrate	A pair and a half of electrolytic copper with glue	Cai Rengedi
	Back Glue	3M 9471 LE	3M
	Positive ink	Black oil (PSM-800)	U-LI
	Character ink	White characters (KTM-150F)	Glory
	Gold plated	1 U	Get Rich