

FCC TEST REPORT

 REPORT NO.:
 RF931008L02B

 MODEL NO.:
 8193URF

 RECEIVED:
 Oct. 08, 2004

 TESTED:
 Oct. 19, 2004 ~ Jan. 18, 2005

 ISSUED:
 Jan. 20, 2005

APPLICANT: BEHAVIOR TECH COMPUTER CORP.

ADDRESS: 2F, 51, Tung Hsing Rd., Taipei, Taiwan, R.O.C.

- **ISSUED BY:** Advance Data Technology Corporation
- **LAB ADDRESS:** No. 47, 14th Lin, Chiapau Tsun, Linko, Taipei, Taiwan, R.O.C.
- **TEST LOCATION:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 22 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agency. The test results in the report only apply to the tested sample.







Table of Contents

1	CERTIFICATION	3
2	SUMMARY OF TEST RESULTS	4
2.1	MEASUREMENT UNCERTAINTY	4
3	GENERAL INFORMATION	5
3.1	GENERAL DESCRIPTION OF EUT	5
3.2	DESCRIPTION OF TEST MODES	6
3.2.1	CONFIGURATION OF SYSTEM UNDER TEST	6
3.2.2	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	8
3.4	DESCRIPTION OF SUPPORT UNITS	8
4.1	CONDUCTED EMISSION MEASUREMENT	9
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	9
4.1.2	TEST INSTRUMENTS	9
4.1.3	TEST PROCEDURES	10
4.1.4	DEVIATION FROM TEST STANDARD	10
4.1.5	TEST SETUP	11
4.1.6	EUT OPERATING CONDITIONS	11
4.1.7	TEST RESULTS	12
4.2	RADIATED EMISSION MEASUREMENT	14
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	14
4.2.2	TEST INSTRUMENT	15
4.2.3	TEST PROCEDURE	16
4.2.4	DEVATION FROM TEST STANDARD	16
4.2.5	TEST SETUP	17
4.2.6	EUT OPERATING CONDITION	17
4.2.7	TEST RESULTS	18
4	PHOTOGRAPHS OF THE TEST CONFIGURATION	20
5	INFORMATION ON THE TESTING LABORATORIES	22



1 CERTIFICATION

PRODUCT NAME : Wireless Transceiver
BRAND NAME : BTC
MODEL NO. : 8193URF
APPLICANT : BEHAVIOR TECH COMPUTER CORP.
TEST SAMPLE : PROTOTYPE
TESTED : Oct. 19, 2004 ~ Jan. 18, 2005
STANDARDS : FCC Part 15, Subpart C (15.227) ANSI C63.4-2003

The above equipment has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY	: <u>Andrea Hora</u> (Andrea Hsia)	, DATE: Jan. 20, 2005
TECHNICAL ACCEPTANCE Responsible for RF	: <u>Glan (Jang</u>)	, DATE: Jan. 20, 2005
APPROVED BY	: (Cody Chang / Deputy Manager)	, DATE: Jan. 20, 2005



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C						
STANDARD PARAGRAPH	TEST TYPE	RESULT	REMARK			
15.207	Conducted Emission Test	PASS	Meet the requirement of limit Minimum passing margin is –11.63dB at 0.228 MHz			
15.227 15.209	Radiated Emission Test	PASS	Meet the requirement of limit Minimum passing margin is –7.66 dB at 360.46 MHz			

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

Measurement	Frequency	Uncertainty
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.63 dB
	200MHz ~1000MHz	3.65 dB
	1GHz ~ 18GHz	2.20 dB
	18GHz ~ 40GHz	1.88 dB



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Wireless Transceiver	
MODEL NO.	8193URF	
POWER SUPPLY	5Vdc from host equipment	
MODULATION TYPE	FSK	
CARRIER FREQUENCY OF EACH CHANNEL	26.995, 27.045, 27.095, 27.145, 27.195MHz	
NUMBER OF CHANNEL	5	
ANTENNA TYPE	Loop antenna	
DATA CABLE	1.2m non-shielded without core.	
I/O PORTS	USB	

NOTE:

1. The EUT was designed with transmission and receiving functions.

2. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



3.2 DESCRIPTION OF TEST MODES

Five channels were provided in this EUT.

CHANNEL	FREQUENCY
1	26.995 MHz
2	27.045 MHz
3	27.095 MHz
4	27.145 MHz
5	27.195 MHz

*Channel 3 was the worst case and chosen for final test.

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST





3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:

EUT	Applicable to		Description	
mode	PLC	RE<1G		
1	Х	х	NA	

Where PLC: Power Line Conducted Emission

RE<1G RE: Radiated Emission below 1GHz

Power Line Conducted Emission Test:

Following channel(s) was (were) selected for the final test as listed below.

EUT	Available Channels	Tested Channel	Modulation Type
Receiver	1 to 5	3	FSK

Radiated Emission Test (Below 1 GHz):

Following channel(s) was (were) selected for the final test as listed below.

EUT	Available Channels	Tested Channel	Modulation Type
Receiver	1 to 5	3	FSK



3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is the transmitter part of a Wireless Receiver. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.227)

ANSI C63.4-2003

All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP05L	12130898320	E2K24CLNS
2	PRINTER	EPSON	LQ-300+	DCGY047265	FCC DoC Approved
3	MODEM	ACEEX	1414V/3	0401008248	IFAXDM1414
4	WIRELESS KEYBOARD	BTC	8193URF	NA	E5XKB8193URF

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core
3	1.2 m braid shielded w/o core.
4	NA

NOTE: All power cords of the above support units are non shielded (1.8m).



4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTE	ΓED LIMIT (dBμV)	
0 15 0 5	Quasi-peak	Average	
0.5-5 5-30	66 to 56 56 60	56 to 46 46 50	

NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL	
Test Receiver	560630	100299	Nov 06 2005	
ROHDE & SCHWARZ	E3C330	100200	NOV. 06, 2005	
RF signal cable		Cable HyCO2 01	Mar. 07, 2005	
Woken	30-гв	Cable-HyC02-01		
LISN		100100	Mar 10, 2005	
ROHDE & SCHWARZ	E3HZ-Z3	100100	Mar. 10, 2005	
LISN		100211	Mar. 04, 2005	
ROHDE & SCHWARZ	ESH3-25	100311	Mar. 04, 2005	
Software	ADT Cond 1/2	NIA	NA	
ADT		INA	NA	

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 2.

3. The VCCI Site Registration No. is C-2047.



4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit 20dB) was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation



4.1.5 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item in this test report - Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

- a. Connected the EUT (transmitter part) with a notebook system on the testing table.
- b. Checked if the transmitter part (EUT) was set at the same channel.
- c. Set the EUT for under transmitting condition at specific channel.
- d. The notebook system sent "H" messages on its monitor.
- e. The notebook system sent "H" messages to modem.
- f. The notebook system sent "H" messages to printer and the printer prints them on paper.
- g. Repeated d ~ f.



4.1.7 TEST RESULTS Conducted Worst-Case Data

EUT	Wireless Transceiver	MODEL	8193URF					
INPUT POWER		6dB						
(SYSTEM)	120 vac, 00 112	BANDWIDTH	SKI IZ					
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH, 991hPa	PHASE	Line (L)					
TESTED BY	Leo Hung							

	Freq.	Corr.	Reading	g Value	Emission Level		Limit		Margin	
No		Factor	[dB ((uV)]	[dB ((uV)]	[dB	(uV)]	(dl	3)
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.158	0.10	37.33	-	37.43	-	65.58	55.58	-28.14	-
2	0.228	0.10	44.52	-	44.62	-	62.52	52.52	-17.90	-
3	0.349	0.11	31.35	-	31.46	-	58.98	48.98	-27.52	-
4	1.809	0.26	21.78	-	22.04	-	56.00	46.00	-33.96	-
5	3.855	0.31	22.67	_	22.98	_	56.00	46.00	-33.02	-
6	10.582	0.55	34.72	-	35.27	-	60.00	50.00	-24.73	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

- 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
- 3. The emission levels of other frequencies were very low against the limit.
- 4. Margin value = Emission level Limit value
- 5. Correction factor = Insertion loss + Cable loss
- 6. Emission Level = Correction Factor + Reading Value.





EUT	Wireless Transceiver	MODEL	8193URF
INPUT POWER (SYSTEM)	120Vac, 60 Hz	6dB BANDWIDTH	9kHz
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH, 991hPa	PHASE	Neutral (N)
TESTED BY	Leo Hung		

	Freq.	Corr.	Readin	g Value	Emission Level		ion Limit el		Margin	
No		Factor	[dB	(uV)]	[dB	[dB (uV)] [dB (uV)]		(uV)]	(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.228	0.10	44.79	-	44.89	-	62.52	52.52	-17.63	-
2	0.345	0.11	33.36	-	33.47	-	59.07	49.07	-25.60	-
3	0.584	0.15	24.59	-	24.74	-	56.00	46.00	-31.26	-
4	1.848	0.25	30.46	-	30.71	-	56.00	46.00	-25.29	-
5	3.711	0.30	25.75	-	26.05	-	56.00	46.00	-29.95	-
6	10.352	0.49	35.33	-	35.82	-	60.00	50.00	-24.18	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

- 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
- 3. The emission levels of other frequencies were very low against the limit.
- 4. Margin value = Emission level Limit value
- 5. Correction factor = Insertion loss + Cable loss
- 6. Emission Level = Correction Factor + Reading Value.





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

According to 15.227 the field strength of Emissions from intentional radiators operated under these frequencies bands shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (dBuV/m)				
26.96-27.28	Peak	Average			
	100	80			

Field strength limits are at the distance of 3 meters, Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any Emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENT

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL	
Test Receiver	ESIB7	100188	Dec 19 2005	
ROHDE & SCHWARZ	20127		DC0. 10, 2000	
Spectrum Analyzer	FSP40	100039	Nov 21 2005	
ROHDE & SCHWARZ				
BILOG Antenna	VI II B9168	9168-157	Feb 03 2005	
SCHWARZBECK	VOLDOTOO		1 00. 00, 2000	
HORN Antenna	BBHA 9120 D	0120D_407	Feb 03 2005	
SCHWARZBECK	DDHAGIZOD	51200-401	1 65. 65, 2005	
HORN Antenna	BBHA 9170	BBHA 9170241	Feb. 23, 2005	
SCHWARZBECK	BBIIAGING			
Loop Antenna	HFH2-Z2	100070	Nov. 14, 2005	
Preamplifier	8440B	3008401061	Nov. 09, 2005	
Agilent	0449D	3000401901		
Preamplifier	84470	2044010620	Nov. 09, 2005	
Agilent	04470	2944A10029		
RF signal cable		218182/4	Mar 04 2005	
HUBER+SUHNER	SOCOLEEX 104	210102/4	Mai: 04, 2000	
RF signal cable	SUCOELEX 104	218194/4	Mar 04 2005	
HUBER+SUHNER		210134/4	Mai: 04, 2000	
Software	ADT Radiated V/5 14	NΔ	ΝΔ	
ADT.				
Antenna Tower	AT100	AT03021702	ΝΑ	
ADT.	ALIO	A193021702		
Turn Table	TT100	TT03021702	ΝΔ	
ADT.	11100.	1133021702	NA	
Controller	SC100	SC03021702	NA	
ADT.	50100.	3033021702	NA	

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 1.

3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.

4. The IC Site Registration No. is IC4924-2.



4.2.3 TEST PROCEDURE

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected Emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the Emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the Emissions that did not have 10 dB margin would be retested one by one using the quasi-peak method or average method as specified and then reported in Data sheet peak mode and QP mode.

NOTE:

The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.

4.2.4 DEVATION FROM TEST STANDARD

No deviation.



4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item in this test report - Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITION

Same as 4.1.6



4.2.7 TEST RESULTS Frequency 27.095MHz Worst-Case Data

EUT	Wireless Transceiver	MODEL	8193URF
INPUT POWER	5 Vdc	FREQUENCY RANGE	Below 1000 MHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 54% RH, 991 hPa	DETECTOR FUNCTION	Peak / Average
TESTED BY	Match Tsui		

	TEST DISTANCE: 3 M							
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*27.095	54.89 PK	100.00	-45.11	1.60	217	41.11	13.78
2	*27.095	47.41 AV	80.00	-32.59	1.60	217	33.63	13.78
2 *27.095 47.41 AV 80.00 -32.59 1.60 217 33.63 13.78 REMARKS: 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m) 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) 3. The other Emission levels were very low against the limit. 4. Margin value = Emission level – Limit value. 5. "*" = Fundamental frequency 6. Loop Antenna was used for all frequency below 30MHz.								



EUT	Wireless Transceiver	MODEL	8193URF
INPUT POWER	5 Vdc	FREQUENCY RANGE	Below 1000 MHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 54% RH, 991 hPa	DETECTOR FUNCTION	Quasi-Peak
TESTED BY	Match Tsui		

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)	
1	53.33	24.65 QP	40.00	-15.35	1.25 H	181	10.26	14.38	
2	133.03	29.44 QP	43.50	-14.06	1.50 H	40	15.52	13.92	
3	214.67	30.61 QP	43.50	-12.89	1.00 H	37	18.89	11.72	
4	300.20	30.86 QP	46.00	-15.14	1.50 H	22	16.32	14.54	
5	319.64	32.94 QP	46.00	-13.06	1.00 H	340	17.95	14.98	
6	346.85	31.75 QP	46.00	-14.25	1.25 H	10	16.14	15.60	
7	360.46	38.34 QP	46.00	-7.66	1.00 H	181	22.43	15.91	
8	426.55	35.45 QP	46.00	-10.55	1.00 H	193	17.93	17.51	
9	479.04	29.91 QP	46.00	-16.09	2.00 H	220	11.42	18.49	
10	514.03	34.97 QP	46.00	-11.03	1.50 H	253	15.94	19.03	
11	533.47	30.51 QP	46.00	-15.49	1.50 H	82	11.08	19.43	
12	585.95	33.25 QP	46.00	-12.75	1.25 H	130	12.51	20.73	
13	640.38	35.24 QP	46.00	-10.76	1.25 H	79	13.59	21.65	
14	745.35	30.26 QP	46.00	-15.74	1.00 H	220	6.78	23.48	
15	768.68	32.86 QP	46.00	-13.14	1.00 H	58	9.17	23.69	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M									
No.	Freq. (MHz)	Emission	Limit (dBuV/m)	Margin (dB)	Antenna	Table	Raw	Correction	
		Level			Height	Angle	Value	Factor	
		(dBuV/m)			(m)	(Degree)	(dBuV)	(dB/m)	
1	64.99	26.30 QP	40.00	-13.70	1.25 V	244	13.15	13.15	
2	119.42	33.95 QP	43.50	-9.55	1.00 V	1	20.97	12.97	
3	154.41	26.35 QP	43.50	-17.15	1.25 V	334	11.61	14.73	
4	228.28	25.29 QP	46.00	-20.71	1.00 V	4	12.93	12.36	
5	323.53	28.23 QP	46.00	-17.77	1.50 V	70	13.16	15.07	
6	360.46	27.04 QP	46.00	-18.96	1.25 V	10	11.13	15.91	
7	405.17	29.30 QP	46.00	-16.70	1.25 V	292	12.36	16.95	
8	426.55	28.59 QP	46.00	-17.41	1.75 V	232	11.07	17.51	
9	514.03	30.47 QP	46.00	-15.53	1.00 V	211	11.44	19.03	
10	640.38	27.76 QP	46.00	-18.24	1.50 V	256	6.10	21.65	
11	768.68	27.77 QP	46.00	-18.23	1.75 V	208	4.08	23.69	
12	863.93	29.96 QP	46.00	-16.04	1.50 V	262	5.40	24.56	

REMARKS: 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)

2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)

3. The other emission levels were very low against the limit.

4. Margin value = Emission level – Limit value.



4 PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST







5 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025

USA	FCC, NVLAP, UL , A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA, CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: <u>www.adt.com.tw/index.5/phtml</u>. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab Tel: 886-2-26052180 Fax: 886-2-26052943 Hsin Chu EMC/RF Lab Tel: 886-3-5935343 Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab Tel: 886-3-3183232 Fax: 886-3-3185050

Linko RF Lab. Tel: 886-3-3270910 Fax: 886-3-3270892

Web Site: <u>www.adt.com.tw</u>

The address and road map of all our labs can be found in our web site also.