



**FCC CFR47 CERTIFICATION
CLASS II PERMISSIVE CHANGE
TEST REPORT**

FOR

PCI Express 802.11a/b/g transceiver

MODEL NUMBER: PA3503U-1MPC

FCC ID: CJ6UPA3503WL

REPORT NUMBER: 05U3822-1

ISSUE DATE: JANUARY 16, 2006

Prepared for
**TOSHIBA CORPORATION
DIGITAL MEDIA NETWORK COMPANY
2-9 SUEHIRO-CHO, OME
TOKYO, 198-8710, JAPAN**

Prepared by
**COMPLIANCE CERTIFICATION SERVICES
561F MONTEREY ROAD,
MORGAN HILL, CA 95037, USA
TEL: (408) 463-0885
FAX: (408) 463-0888**

NVLAP[®]
LAB CODE:200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
A	1/16/06	Initial Issue	DG

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. CALIBRATION AND UNCERTAINTY.....	5
4.1. MEASURING INSTRUMENT CALIBRATION	5
4.2. MEASUREMENT UNCERTAINTY.....	5
5. EQUIPMENT UNDER TEST.....	6
5.1. DESCRIPTION OF EUT	6
5.2. DESCRIPTION OF AVAILABLE ANTENNAS.....	6
5.3. DESCRIPTION OF CLASS II PERMISSIVE CHANGE.....	6
5.4. SOFTWARE AND FIRMWARE	6
5.5. WORST-CASE CONFIGURATION AND MODE.....	6
5.6. DESCRIPTION OF TEST SETUP	6
6. TEST AND MEASUREMENT EQUIPMENT	9
7. LIMITS AND RESULTS	10
7.1. CHANNEL TESTS FOR THE 2400 TO 2483.5 MHz BAND	10
7.1.1. AVERAGE POWER.....	10
7.2. CHANNEL TESTS FOR THE 5725 TO 5850 MHz BAND	11
7.2.1. AVERAGE POWER.....	11
7.3. RADIATED EMISSIONS.....	12
7.3.1. TRANSMITTER RADIATED SPURIOUS EMISSIONS	12
7.3.2. TRANSMITTER ABOVE 1 GHz FOR 2400 TO 2483.5 MHz BAND	15
7.3.3. TRANSMITTER ABOVE 1 GHz FOR 5725 TO 5850 MHz BAND	33
7.3.4. WORST-CASE RADIATED EMISSIONS BELOW 1 GHz	34
7.4. POWERLINE CONDUCTED EMISSIONS	42
8. SETUP PHOTOS	45

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: TOSHIBA CORPORATION
DIGITAL MEDIA NETWORK COMPANY
2-9 SUEHIRO-CHO, OME
TOKYO, 198-8710, JAPAN

EUT DESCRIPTION: PCI Express 802.11a/b/g transceiver

MODEL: PA3503U-1MPC

SERIAL NUMBER: 6159Y031916

DATE TESTED: DECEMBER 19, 2005 – JANUARY 6, 2006

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 15 SUBPART C	NO NON-COMPLIANCE NOTED

Compliance Certification Services, Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification Services will constitute fraud and shall nullify the document. No part of this report may be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any government agency.

Approved & Released For CCS By:

Tested By:



DAVID GARCIA
EMC SUPERVISOR
COMPLIANCE CERTIFICATION SERVICES



FRANK IBRAHIM
EMC ENGINEER
COMPLIANCE CERTIFICATION SERVICES

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2003, FCC CFR 47 Part 2 and FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 561F Monterey Road, Morgan Hill, California, USA. The sites are constructed in conformance with the requirements of ANSI C63.4, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Radiated Emission, 30 to 200 MHz	+/- 3.3 dB
Radiated Emission, 200 to 1000 MHz	+4.5 / -2.9 dB
Radiated Emission, 1000 to 2000 MHz	+4.5 / -2.9 dB
Power Line Conducted Emission	+/- 2.9 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is an 802.11a/b/g transceiver

The radio module is manufactured by Atheros Communications Inc.

5.2. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes two Integrated Omni-directional antennas for diversity; model HTL017 antenna has a maximum gain of 3.2 dBi for 5.8 GHz band, and model WNC001 has a maximum gain of 1.8 dBi for 2.4 GHz band. Additional antennas of same type and lower gain are used with this radio and listed in the FCC submission.

5.3. DESCRIPTION OF CLASS II PERMISSIVE CHANGE

1. The radio module has a limited module approval and is installed in a portable condition.
2. Add new antenna models:
Hitachi: HTL017 & HFT40
Tyco: TIAN01 & TBN001
WNC: WNC001

Full antenna details are included in separate exhibit.

5.4. SOFTWARE AND FIRMWARE

The EUT driver software installed in the host support equipment during testing was Atheros Radio Test, Revision 5.3 Build #11.

The test utility software used during testing was ART-V53_build 13.

5.5. WORST-CASE CONFIGURATION AND MODE

Radiated emissions tests above 1 GHz were performed on each applicable L/M/H channel.

The worst-case channel is determined as the channel with the highest output power. The highest measured output power was at 2437 MHz in 11g mode. The worst-case data rate for this channel is determined to be 6 Mb/s, based on previous experience with Atheros WLAN product design architectures.

Thus worst-case radiated emissions below 1 GHz and power line conducted emissions tests were made at 2437 MHz in the 802.11g mode, at 6 Mb/s.

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	FCC ID
Laptop	Toshiba	Portege M400	05B-012	DoC
AC/DC Adapter	Toshiba	PA3283U-1ACA	03X19218	DoC


I/O CABLES

I/O CABLE LIST						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length	Remarks
1	AC	1	AC	Unshielded	2m	N/A
2	DC	1	DC	Unshielded	2m	N/A

TEST SETUP

The EUT is installed in a host laptop computer. Test software exercised the radio card.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	Cal Due
Spectrum Analyzer 3 Hz ~ 44 GHz	Agilent	E4446A	MY43360112	03/28/06
Antenna, Horn 1 ~ 18 GHz	EMCO	3115	6717	04/22/06
Preamplifier, 1 ~ 26.5 GHz	HP	8449B	3008A00369	08/17/06
EMI Test Receiver	R & S	ESHS 20	827129/006	06/03/06
LISN, 10 kHz ~ 30 MHz	FCC	LISN-50/250-25-2	2023	08/30/06
LISN, 10 kHz ~ 30 MHz	Solar	8012-50-R-24-BNC	8379443	08/30/06
Peak Power Meter	Agilent	E4416A	GB41291160	02/09/06
Peak / Average Power Sensor	Agilent	E9327A	US40440755	02/10/06
2.4-2.5 GHz Reject Filter	Micro-Tronics	BRM50702	002	C.N.R.
4.0 GHz High Pass Filter	Micro-Tronics	HPM13351	002	C.N.R.
Antenna, Horn 1 ~ 18 GHz	ETS	3117	29301	04/22/06
5.725-5.825 GHz Reject Filter	Micro-Tronics	BRC13192	002	C.N.R.
7.6 GHz High Pass Filter	Micro-Tronics	HPM13195	001	C.N.R.
Preamplifier, 26 ~ 40 GHz	Miteq	NSP4000-SP2	924343	08/18/06
Antenna, Horn 18 ~ 26 GHz	ARA	MWH-1826/B	1049	09/12/06
Antenna, Horn 26 ~ 40 GHz	ARA	MWH-2640/B	1029	12/29/06
Spectrum Analyzer, 26.5 GHz	HP	8593EM	3710A00205	01/06/06
Antenna, Bilog 30 MHz ~ 2 GHz	Sunol Sciences	JB1	A121003	03/03/06
Preamplifier, 1300 MHz	HP	8447D	1937A02062	01/07/06

7. LIMITS AND RESULTS

7.1. CHANNEL TESTS FOR THE 2400 TO 2483.5 MHz BAND

7.1.1. AVERAGE POWER

AVERAGE POWER LIMIT

None: for reporting purposes only. The average power for each channel was set to the average power specified in the original filing.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

No non-compliance noted:

The cable assembly insertion loss of 11.6 dB (including 10 dB pad and 1.6 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

802.11b Mode

Channel	Frequency (MHz)	Power (dBm)
Low	2412	17.40
Middle	2437	17.40
High	2462	17.60

802.11g Mode

Channel	Frequency (MHz)	Power (dBm)
Low	2412	16.00
Middle	2437	19.20
High	2462	14.70

7.2. CHANNEL TESTS FOR THE 5725 TO 5850 MHz BAND

7.2.1. AVERAGE POWER

AVERAGE POWER LIMIT

None: for reporting purposes only. The average power for each channel was set to the average power specified in the original filing.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

No non-compliance noted:

The cable assembly insertion loss of 12.2 dB (including 10 dB pad and 2.2 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

802.11a Mode

Channel	Frequency (MHz)	Average Power (dBm)
Low	5745	17.80
Middle	5785	17.70
High	5825	17.50

7.3. RADIATED EMISSIONS

7.3.1. TRANSMITTER RADIATED SPURIOUS EMISSIONS

LIMITS

§15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

§15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.


The spectrum from 30 MHz to 25 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.


The spectrum from 30 MHz to 40 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each 5 GHz band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.


7.3.2. TRANSMITTER ABOVE 1 GHz FOR 2400 TO 2483.5 MHz BAND


RESTRICTED BANDEDGE (b MODE, LOW CHANNEL, HORIZONTAL)







RESTRICTED BANDEDGE (b MODE, LOW CHANNEL, VERTICAL)







RESTRICTED BANDEDGE (b MODE, HIGH CHANNEL, HORIZONTAL)





RESTRICTED BANDEDGE (b MODE, HIGH CHANNEL, VERTICAL)







HARMONICS AND SPURIOUS EMISSIONS (b MODE)

12/20/05 High Frequency Measurement Compliance Certification Services, Morgan Hill Open Field Site																	
Test Engr:		Frank Ibrahim															
Project #:		05U3822															
Company:		Toshiba															
EUT Descrip.:		Mini PCExpress 802.11 a/b/g transceiver															
EUT M/N:		AR5BXB6															
Test Target:		FCC 15.247															
Configuration:		Stand Alone EUT															
Mode Oper:		TX ON in 11b mode															
Power Settings:		Conducted Average Power: Low(17.4 dBm), Mid(17.4 dBm), High(17.6 dBm)															
Test Equipment:																	
Horn 1-18GHz T119; S/N: 29301 @3m				Pre-amplifier 1-26GHz T34 HP 8449B				Pre-amplifier 26-40GHz				Horn > 18GHz T125; ARA 18-26GHz; S/N:1007					
Hi Frequency Cables																	
2 foot cable				3 foot cable Frank 177080001				12 foot cable Frank 187209001				HPF		Reject Filter R_001		Peak Measurements RBW=VBW=1MHz Average Measurements RBW=1MHz; VBW=10Hz	
f GHz	Dist (m)	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Fldr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)		
11b Low Channel																	
1.060	3.0	63.3	42.4	27.6	2.1	-38.2	0.0	0.0	54.8	33.9	74	54	-19.2	-20.1	V		
4.824	3.0	50.3	46.0	34.0	4.0	-34.8	0.0	0.0	53.5	49.2	74	54	-20.5	-4.8	V		
1.060	3.0	60.0	42.0	27.6	2.1	-38.2	0.0	0.0	51.5	33.5	74	54	-22.5	-20.5	H		
4.824	3.0	49.4	45.0	34.0	4.0	-34.8	0.0	0.0	52.5	48.1	74	54	-21.5	-5.9	H		
11b Mid Channel																	
4.874	3.0	50.5	46.8	34.1	4.0	-34.8	0.0	0.0	53.7	50.1	74	54	-20.3	-3.9	V		
7.311	3.0	50.6	44.7	35.6	4.6	-34.1	0.0	0.0	56.7	50.9	74	54	-17.3	-3.1	V		
4.874	3.0	48.6	43.3	34.1	4.0	-34.8	0.0	0.0	51.8	46.6	74	54	-22.2	-7.4	H		
7.311	3.0	52.0	46.9	35.6	4.6	-34.1	0.0	0.0	58.2	53.0	74	54	-15.8	-1.0	H		
11b High Channel																	
4.924	3.0	52.9	50.2	34.1	4.0	-34.8	0.0	0.0	56.2	53.5	74	54	-17.8	-0.5	V		
7.386	3.0	49.6	42.6	35.7	4.6	-34.1	0.0	0.0	55.8	48.8	74	54	-18.2	-5.2	V		
4.924	3.0	52.8	50.1	34.1	4.0	-34.8	0.0	0.0	56.1	53.4	74	54	-17.9	-0.6	H		
7.386	3.0	52.0	46.8	35.7	4.6	-34.1	0.0	0.0	58.2	53.0	74	54	-15.8	-1.0	H		
f	Measurement Frequency					Amp	Preamp Gain					Avg Lim	Average Field Strength Limit				
Dist	Distance to Antenna					D Corr	Distance Correct to 3 meters					Pk Lim	Peak Field Strength Limit				
Read	Analyzer Reading					Avg	Average Field Strength @ 3 m					Avg Mar	Margin vs. Average Limit				
AF	Antenna Factor					Peak	Calculated Peak Field Strength					Pk Mar	Margin vs. Peak Limit				
CL	Cable Loss					HPF	High Pass Filter										


EUT was scanned from 1 GHz to 25 GHz, no other signals above noise floor were found.


RESTRICTED BANDEDGE (g MODE, LOW CHANNEL, HORIZONTAL)







RESTRICTED BANDEDGE (g MODE, LOW CHANNEL, VERTICAL)







RESTRICTED BANDEDGE (g MODE, HIGH CHANNEL, HORIZONTAL)





RESTRICTED BANDEDGE (g MODE, HIGH CHANNEL, VERTICAL)





HARMONICS AND SPURIOUS EMISSIONS (g MODE)

12/20/05 High Frequency Measurement Compliance Certification Services, Morgan Hill Open Field Site																	
Test Engr:		Frank Ibrahim															
Project #:		05U3822															
Company:		Toshiba															
EUT Descrip.:		Mini PCExpress 802.11 a/b/g transceiver															
EUT M/N:		AR5BXB6															
Test Target:		FCC 15.247															
Configuration:		Stand Alone EUT															
Mode Oper:		TX ON in 11g mode															
Power Settings:		Conducted Average Power: Low(16 dBm), Mid(19.2 dBm), High(14.7 dBm)															
Test Equipment:																	
Horn 1-18GHz T119; S/N: 29301 @3m				Pre-amplifier 1-26GHz T34 HP 8449B				Pre-amplifier 26-40GHz				Horn > 18GHz T125; ARA 18-26GHz; S/N:1007					
Hi Frequency Cables																	
2 foot cable				3 foot cable Frank 177080001				12 foot cable Frank 187209001				HPF		Reject Filter R_001		Peak Measurements RBW=VBW=1MHz Average Measurements RBW=1MHz; VBW=10Hz	
f GHz	Dist (m)	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Filtr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)		
11g Low Channel																	
4.824	3.0	45.5	33.3	34.0	4.0	-34.8	0.0	0.0	48.7	36.5	74	54	-25.3	-17.5	V		
4.824	3.0	46.4	32.6	34.0	4.0	-34.8	0.0	0.0	49.5	35.8	74	54	-24.5	-18.2	H		
11g Mid Channel																	
4.874	3.0	49.1	36.3	34.1	4.0	-34.8	0.0	0.0	52.3	39.5	74	54	-21.7	-14.5	V		
7.311	3.0	50.4	38.4	35.6	4.6	-34.1	0.0	0.0	56.6	44.5	74	54	-17.4	-9.5	V		
4.874	3.0	49.6	36.1	34.1	4.0	-34.8	0.0	0.0	52.8	39.3	74	54	-21.2	-14.7	H		
7.311	3.0	54.9	42.3	35.6	4.6	-34.1	0.0	0.0	61.0	48.4	74	54	-13.0	-5.6	H		
11g High Channel																	
4.924	3.0	45.9	33.1	34.1	4.0	-34.8	0.0	0.0	49.3	36.4	74	54	-24.7	-17.6	V		
7.386	3.0	47.8	34.6	35.7	4.6	-34.1	0.0	0.0	54.0	40.8	74	54	-20.0	-13.2	V		
4.924	3.0	46.7	34.7	34.1	4.0	-34.8	0.0	0.0	50.0	38.0	74	54	-24.0	-16.0	H		
7.386	3.0	50.3	37.5	35.7	4.6	-34.1	0.0	0.0	56.5	43.7	74	54	-17.5	-10.3	H		
f	Measurement Frequency		Amp	Preamp Gain		Avg Lim		Average Field Strength Limit									
Dist	Distance to Antenna		D Corr	Distance Correct to 3 meters		Pk Lim		Peak Field Strength Limit									
Read	Analyzer Reading		Avg	Average Field Strength @ 3 m		Avg Mar		Margin vs. Average Limit									
AF	Antenna Factor		Peak	Calculated Peak Field Strength		Pk Mar		Margin vs. Peak Limit									
CL	Cable Loss		HPF	High Pass Filter													

EUT was scanned from 1 GHz to 25 GHz, no other signals above noise floor were found.

7.3.3. TRANSMITTER ABOVE 1 GHz FOR 5725 TO 5850 MHz BAND

HARMONICS AND SPURIOUS EMISSIONS (802.11a MODE)

12/14/05 High Frequency Measurement Compliance Certification Services, Morgan Hill Open Field Site																			
Test Engr:		Frank Ibrahim																	
Project #:		05U3822																	
Company:		Toshiba																	
EUT Descr.:		Mini PCExpress 802.11 a/b/g transceiver																	
EUT M/N:		AR5BXB6																	
Test Target:		FCC 15.247																	
Configuration:		Stand Alone EUT																	
Mode Oper:		TX ON in 11a mode																	
Power Settings:		Conducted Average Power: Low(17.83 dBm), Mid(17.70 dBm), High(17.50 dBm)																	
Test Equipment:																			
Horn 1-18GHz				Pre-amplifier 1-26GHz				Pre-amplifier 26-40GHz				Horn > 18GHz							
T73; S/N: 6717 @3m				T34 HP 8449B				T88 Miteq 26-40GHz				T125; ARA 18-26GHz; S/N:1007							
Hi Frequency Cables																			
2 foot cable				3 foot cable				12 foot cable				HPF				Reject Filter			
				Frank 177080001				Frank 187209001				HPF_7.6GHz							
Peak Measurements RBW=VBW=1MHz																			
Average Measurements RBW=1MHz ; VBW=10Hz																			
f GHz	Dist (m)	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Fltr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)				
11a Low Channel																			
11.490	3.0	51.8	38.5	38.3	5.2	-32.5	0.0	0.7	63.5	50.2	74	54	-10.5	-3.8	V				
11.490	3.0	46.8	33.6	38.3	5.2	-32.5	0.0	0.7	58.5	45.3	74	54	-15.5	-8.7	H				
11a Mid Channel																			
11.570	3.0	51.8	38.3	38.3	5.2	-32.5	0.0	0.7	63.5	50.0	74	54	-10.5	-4.0	V				
11.570	3.0	53.1	39.6	38.3	5.2	-32.5	0.0	0.7	64.8	51.3	74	54	-9.2	-2.7	H				
11a High Channel																			
11.650	3.0	54.1	42.0	38.4	5.3	-32.5	0.0	0.7	65.9	53.8	74	54	-8.1	-0.2	V				
11.650	3.0	54.8	42.1	38.4	5.3	-32.5	0.0	0.7	66.6	53.9	74	54	-7.4	-0.1	H				
f Measurement Frequency Amp Preamp Gain Avg Lim Average Field Strength Limit																			
Dist Distance to Antenna D Corr Distance Correct to 3 meters Pk Lim Peak Field Strength Limit																			
Read Analyzer Reading Avg Average Field Strength @ 3 m Avg Mar Margin vs. Average Limit																			
AF Antenna Factor Peak Calculated Peak Field Strength Pk Mar Margin vs. Peak Limit																			
CL Cable Loss HPF High Pass Filter																			
EUT scanned from 1 GHz to 40 GHz, no other signals were found above noise floor in this frequency range.																			

7.3.4. WORST-CASE RADIATED EMISSIONS BELOW 1 GHz


SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, 11g, HORIZONTAL)

HORIZONTAL PLOT



561F Monterey Road
Morgan Hill, CA 95037
Tel: (408) 463-0888
Fax: (408) 463-0885

Data#: 7 File#: rad 1219.EMI Date: 12-19-2005 Time: 19:40:30



(Auxil ATC)

Trace: 6

Ref Trace:

Condition: FCC CLASS-B HORIZONTAL
Test Operator: : Frank Ibrahim
Project #: : 05u3822
Company: : Toshiba
EUT: : Mini PCIexpress 802.11 a/b/g transceiver
Model No.: : AR5BXB6
Configuration: : Stand-Alone
Mode of operation: TX ON at Mid Channel in 11g mode
Target of Test : FCC B

HORIZONTAL DATA

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	216.240	54.95	-15.26	39.69	46.00	-6.31	Peak
2	240.490	53.08	-14.06	39.02	46.00	-6.98	Peak
3	324.880	53.95	-11.18	42.77	46.00	-3.23	Peak
4	378.230	49.94	-10.00	39.94	46.00	-6.06	Peak
5	434.490	45.28	-8.67	36.61	46.00	-9.39	Peak
6	921.430	39.51	-0.79	38.72	46.00	-7.28	Peak

VERTICAL DATA

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	33.880	48.00	-8.87	39.13	40.00	-0.87	QP
2 *	33.880	51.28	-8.87	42.41	40.00	2.41	Peak
3	41.640	53.20	-13.67	39.53	40.00	-0.47	QP
4 *	41.640	56.59	-13.02	43.57	40.00	3.57	Peak
5	242.430	58.26	-13.99	44.27	46.00	-1.73	Peak
6	378.230	52.00	-10.00	42.00	46.00	-4.00	Peak
7	434.490	51.12	-8.67	42.45	46.00	-3.55	Peak
8	866.140	42.57	-1.25	41.32	46.00	-4.68	Peak


SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, 11a, HORIZONTAL)

HORIZONTAL PLOT



561F Monterey Road
Morgan Hill, CA 95037
Tel: (408) 463-0888
Fax: (408) 463-0885

Data#: 6 File#: rad 1220.EMI Date: 12-20-2005 Time: 19:30:08



(Auxil ATC)

Trace: 5

Ref Trace:

Condition: FCC CLASS-B HORIZONTAL
Test Operator: : Frank Ibrahim
Project #: : 05U3822
Company: : Toshiba
EUT: : Mini PCIexpress 802.11 a/b/g transceiver
Model No.: : AR5BXB6
Configuration: : EUT Stand Alone
Mode of operation: TX ON at Low Channel (5745 MHz), 11a
Target of Test : FCC Class B

HORIZONTAL DATA

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	216.240	51.81	-15.26	36.55	46.00	-9.45	Peak
2	246.310	53.87	-13.84	40.02	46.00	-5.98	Peak
3	324.880	46.88	-11.18	35.70	46.00	-10.30	Peak
4	378.230	44.18	-10.00	34.18	46.00	-11.82	Peak
5	434.490	38.36	-8.67	29.69	46.00	-16.31	Peak
6	803.090	36.33	-1.76	34.57	46.00	-11.43	Peak


SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, 11a, VERTICAL)

VERTICAL PLOT



561F Monterey Road
Morgan Hill, CA 95037
Tel: (408) 463-0888
Fax: (408) 463-0885

Data#: 4 File#: rad 1220.EMI Date: 12-20-2005 Time: 19:20:14



(Auxiliary ATC)

Trace: 1

Ref Trace:

Condition: FCC CLASS-B VERTICAL
Test Operator: : Frank Ibrahim
Project #: : 05U3822
Company: : Toshiba
EUT: : Mini PCIexpress 802.11 a/b/g transceiver
Model No.: : AR5BXB6
Configuration: : EUT Stand Alone
Mode of operation: TX ON at Low Channel (5745 MHz), 11a
Target of Test : FCC Class B

VERTICAL DATA

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	36.790	48.92	-10.51	38.41	40.00	-1.59	QP
2 *	36.790	51.63	-10.51	41.12	40.00	1.12	Peak
3 *	41.640	53.21	-13.02	40.19	40.00	0.19	Peak
4	41.640	52.45	-13.02	39.43	40.00	-0.57	QP
5	247.280	54.35	-13.84	40.50	46.00	-5.50	QP
6	247.280	59.81	-13.84	45.96	46.00	-0.04	Peak
7	324.880	50.58	-11.18	39.40	46.00	-6.60	Peak
8	378.230	51.73	-10.00	41.73	46.00	-4.27	Peak
9	756.530	43.68	-2.47	41.21	46.00	-4.79	Peak

7.4. POWERLINE CONDUCTED EMISSIONS

LIMIT

§15.207 (a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal.

The lower limit applies at the boundary between the frequency ranges.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.4.

The resolution bandwidth is set to 9 kHz for both peak detection and quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

No non-compliance noted:

6 WORST EMISSIONS

CONDUCTED EMISSIONS DATA (115VAC 60Hz)									
Freq.	Reading			Closs	Limit	EN B	Margin		Remark
(MHz)	PK (dBuV)	QP (dBuV)	AV (dBuV)	(dB)	QP	AV	QP (dB)	AV (dB)	L1 / L2
0.17	51.80	--	--	0.00	64.91	54.91	-13.11	-3.11	L1
0.37	38.36	--	--	0.00	58.61	48.61	-20.25	-10.25	L1
3.04	37.56	--	--	0.00	56.00	46.00	-18.44	-8.44	L1
0.17	49.42	--	--	0.00	64.77	54.77	-15.35	-5.35	L2
0.36	44.90	--	--	0.00	58.82	48.82	-13.92	-3.92	L2
0.54	44.48	--	--	0.00	56.00	46.00	-11.52	-1.52	L2
6 Worst Data									

11g mode

LINE 1 AND LINE 2 RESULTS

