

FCC PART 15.225


TEST REPORT

For

Advanced Card Systems Limited

Units 4108 - 4110, 41st Floor, Manhattan Place, 23 Wang Tai Road, Kowloon Bay, Hong Kong

FCC ID: V5MACR1255

Report Type: Class II Permissive Change	Product Type: NFC Bluetooth Smart Card Reader
Report Number: RSZ180605001-00C	
Report Date: 2018-06-26	
Rocky Kang 	
Reviewed By: RF Engineer	
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY	4
SYSTEM TEST CONFIGURATION.....	5
JUSTIFICATION	5
EUT EXERCISE SOFTWARE	5
EQUIPMENT MODIFICATIONS	5
LOCAL SUPPORT EQUIPMENT	5
EXTERNAL I/O CABLE.....	5
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
TEST EQUIPMENT LIST	8
FCC§15.203 - ANTENNA REQUIREMENT.....	9
APPLICABLE STANDARD	9
ANTENNA CONNECTED CONSTRUCTION	9
FCC §15.207 – AC LINE CONDUCTED EMISSION	10
APPLICABLE STANDARD	10
EUT SETUP	10
EMI TEST RECEIVER SETUP.....	10
TEST PROCEDURE	11
CORRECTED FACTOR & MARGIN CALCULATION	11
TEST RESULTS SUMMARY	11
TEST DATA	11
FCC§15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST	14
APPLICABLE STANDARD	14
EUT SETUP	14
EMI TEST RECEIVER SETUP.....	14
CORRECTED AMPLITUDE & MARGIN CALCULATION	15
TEST RESULTS SUMMARY	15
TEST DATA	15
FCC§15.225(E) - FREQUENCY STABILITY.....	19
APPLICABLE STANDARD	19
TEST PROCEDURE	19
TEST DATA	19
FCC§15.215(C) - 20DB EMISSION BANDWIDTH	20
REQUIREMENT	20
TEST PROCEDURE	20
TEST DATA	20

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Advanced Card Systems Limited's* product, model number: *ACR1255 (FCC ID: V5MACR1255)* or the "EUT" in this report was a *NFC Bluetooth Smart Card Reader*, which was measured approximately: 8.5 cm (L) x 5.4 cm (W) x 1.1cm (H), rated with input voltage: DC 3.7 V battery.

**All measurement and test data in this report was gathered from production sample serial number: 180605001. (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2018-06-05.*

Objective

This Type approval report is prepared on behalf of *Advanced Card Systems Limited* in accordance with Part 2- Subpart J, and Part 15-Subparts A and C of the Federal Communication Commissions rules.

The objective is to determine the compliance of the EUT with FCC rules, section 15.203, 15.205, 15.207, 15.209 and 15.225.

This is a CIIPC application of the device; the differences between the original device and the current one are as follows:

1. Change the NFC antenna.
2. Change the power unit.
3. Change the produce type.
4. Change the appearance silkscreen.
5. Change the company address to "Units 4108 - 4110, 41st Floor, Manhattan Place, 23 Wang Tai Road, Kowloon Bay, Hong Kong".
6. Remove the USB cable

For the change made to the device, the all test item were performed.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS submissions with FCC ID: V5MACR1255.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter	uncertainty
Occupied Channel Bandwidth	±5%
RF Output Power with Power meter	±0.5dB
RF conducted test with spectrum	±1.5dB
AC Power Lines Conducted Emissions	±1.95dB
All emissions, radiated	±4.88dB
Temperature	±3°C
Humidity	±6%
Supply voltages	±0.4%

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

EUT Exercise Software

“ADPU” exercise software was used.

Equipment Modifications

No modification on the EUT.


Local Support Equipment

Manufacturer	Description	Model	Serial Number
DELL	PC	VOSTRO 220S	127BP2X
TCL	Monitor	TFT1560PS	ALA560806C160409
Microsoft	Keyboard	1406	0200706128743
Microsoft	Mouse	1405	0204608630856
SAST	Modem	AEM-2100	0293
Longway	Adapter	TYP60-1207000Z	LW516654

External I/O Cable

Cable Description	Length (m)	From/Port	To
Shielding Detachable RS232 cable	1.0	PC	Modem
Shielding Detachable VGA cable	1.0	PC	Monitor
Un-shielding Un-detachable DC cable	0.5	Adapter	Modem
Shielding Un-detachable USB cable	1.2	Keyboard	PC
Shielding Un-detachable USB cable	1.2	Mouse	PC
Un-shielding detachable AC cable	1.2	Monitor	LISN 1
Un-shielding detachable AC cable	1.2	PC	LISN 1
Un-shielding detachable AC cable	1.2	Adapter 2	LISN 2
Shielding Un-detachable USB cable	1.0	EUT	PC

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207	AC Line Conducted Emission	Compliance
§15.225 §15.209 §15.205	Radiated Emission Test	Compliance
§15.225(e)	Frequency Stability	Compliance
§15.215(c)	20dB Emission Bandwidth	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2017-08-04	2018-08-04
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2017-12-21	2018-12-21
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2018-05-21	2018-11-19
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
N/A	Conducted Emission Cable	N/A	UF A210B-1-0720-504504	2018-05-12	2018-11-12
Radiated Emission Test					
HP	Amplifier	HP8447E	1937A01046	2018-05-21	2018-11-19
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2018-01-11	2019-01-11
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
ETS	Passive Loop Antenna	6512	00029604	2018-03-07	2021-03-06
Sonoma instrument	Amplifier	310N	186238	2018-05-21	2018-11-19
Ducommun technologies	RF Cable	UFA210A-1-4724-30050U	MFR64369 223410-001	2018-05-21	2018-11-19
Ducommun technologies	RF Cable	104PEA	218124002	2018-05-21	2018-11-19
Fluke	Digital Multimeter	287	19000011	2018-04-09	2019-04-09
instek	DC Power Supply	GPS-3030DD	EM832096	NCR	NCR
ESPEC	Temperature & Humidity Chamber	EL-10KA	9107726	2017-12-21	2018-12-21

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Antenna Connected Construction


The EUT has a printed antenna on PCB, which was permanently attached, the antenna gain is 0 dBi, fulfill the requirement of this section. Please see EUT photo for details.

FCC §15.207 – AC LINE CONDUCTED EMISSION

Applicable Standard

FCC§15.207

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the PC was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa


The testing was performed by Bibo Zhang on 2018-06-22.

EUT operation mode: Transmitting

AC 120 V/60 Hz, Line:



Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.205500	47.1	20.1	63.4	16.3	QP
0.221500	45.5	20.1	62.8	17.3	QP
0.309410	39.6	20.1	60.0	20.4	QP
0.340930	45.5	20.1	59.2	13.7	QP
0.352630	41.4	20.1	58.9	17.5	QP
0.958630	35.6	20.0	56.0	20.4	QP
0.205500	42.5	20.1	53.4	10.9	Ave.
0.221500	40.3	20.1	52.8	12.5	Ave.
0.309410	31.3	20.1	50.0	18.7	Ave.
0.340930	34.1	20.1	49.2	15.1	Ave.
0.352630	31.5	20.1	48.9	17.4	Ave.
0.958630	29.9	20.0	46.0	16.1	Ave.

AC 120V/60 Hz, Neutral:

Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.313290	40.5	20.1	59.9	19.4	QP
0.347130	40.7	20.1	59.0	18.3	QP
0.352690	41.2	20.1	58.9	17.7	QP
1.021090	35.4	20.0	56.0	20.6	QP
1.050370	34.8	20.0	56.0	21.2	QP
21.558630	31.2	20.0	60.0	28.8	QP
0.313290	30.3	20.1	49.9	19.6	Ave.
0.347130	34.7	20.1	49.0	14.3	Ave.
0.352690	29.9	20.1	48.9	19.0	Ave.
1.021090	29.1	20.0	46.0	16.9	Ave.
1.050370	28.0	20.0	46.0	18.0	Ave.
21.558630	25.6	20.0	50.0	24.4	Ave.

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude


FCC§15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST

Applicable Standard

As per FCC Part 15.225

- (a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- (b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- (c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

EUT Setup



Note: Antenna is set up at 1m during test for below 30MHz.

The radiated emission tests were performed in the 3-meter chamber a test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC Part Subpart C limits.

EMI Test Receiver Setup

According to FCC Rules, 47 CFR 15.33, the EUT emissions were investigated up to 1000 MHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
9 kHz – 150 kHz	300 Hz	1 kHz	/	QP
150 kHz – 30 MHz	10 kHz	30 kHz	/	QP
30 MHz – 1000 MHz	100 kHz	300 kHz	/	QP

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain

Corrected Amplitude = Meter Reading + Corrected Factor

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.209.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa


The testing was performed by Bibo Zhang on 2018-06-08.

Test mode: Transmitting

1) Spurious Emissions (9 kHz~30 MHz):

Indicated		Table Angle Degree	Antenna Height (m)	Detector	Correction Factor			Corrected Amplitude (dBμV/m) @3m	FCC part 15.225	
Freq. (MHz)	Reading (dBμV/m) @3m				Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)		Limit (dBμV/m) @3m	Result
0.009	-0.2	0	1	QP	88.0	0.2	30.2	57.80	128.05	Pass
0.329	30.61	0	1	QP	56.8	0.2	30.2	57.41	104.08	Pass


9 kHz~150 kHz



EUT

Date: 8.JUN.2018 20:36:59


150 kHz~30 MHz



EUT

Date: 8.JUN.2018 20:42:17

2) Spurious Emissions (30 MHz~1GHz):



Frequency (MHz)	Corrected Amplitude (dBμV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
36.527250	19.62	109.0	V	113.0	-3.5	40.00	20.38
88.326375	16.43	107.0	V	129.0	-10.9	43.50	27.07
148.557375	17.08	240.0	V	47.0	-4.6	43.50	26.42
632.981750	36.06	102.0	H	237.0	4.0	46.00	9.94
786.448625	35.97	100.0	V	268.0	9.0	46.00	10.03
894.920250	39.68	105.0	H	205.0	10.1	46.00	6.32

Note:

- 1) Correction Factor = Antenna factor(Rx) + Cable Loss – Amplifier factor
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

3) Inband:

Indicated			Table Angle Degree	Antenna Height (m)	Detector	Correction Factor			Corrected Amplitude (dBμV/m) @3m	FCC part 15.225	
Frequency Range (MHz)	Mark Point (MHz)	Reading (dBμV/m) @3m				Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)		Limit (dBμV/m) @3m	Result
13.110-13.410	13.404	69.18	0	1	QP	32	0.2	30.2	67.18	80.5	Pass
13.410-13.553	13.549	70.95	0	1.3	QP	32	0.2	30.2	68.95	90.5	Pass
13.553-13.567	13.562	70.94	0	1.2	QP	32	0.2	30.2	69.94	124.0	Pass
13.567-13.710	13.702	68.59	0	1.2	QP	32	0.2	30.2	68.59	90.5	Pass
13.710-14.010	13.984	68.19	0	1	QP	32	0.2	30.2	68.19	80.5	Pass

FCC§15.225(e) - FREQUENCY STABILITY

Applicable Standard

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to PC, then to an external AC power supply and inductive antenna was connected to a Spectrum Analyzer. The EUT was placed inside the temperature chamber.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the Spectrum Analyzer.

Frequency Stability vs. Voltage: An external variable AC power supply Source. The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the end point. The output frequency was recorded for each voltage.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Bibo Zhang on 2018-06-11.

Test Mode: Transmitting

Test Result: Pass

Voltage Supply (V _{DC})	Temperature (°C)	Measured Frequency (MHz)	Frequency Error (%)	Part 15.225 Limit
5.0	-20	13.55946	-0.00398	$\pm 0.01\%$
	-10	13.55947	-0.00391	$\pm 0.01\%$
	0	13.55966	-0.00251	$\pm 0.01\%$
	10	13.55979	-0.00155	$\pm 0.01\%$
	20	13.55989	-0.00081	$\pm 0.01\%$
	30	13.55947	-0.00391	$\pm 0.01\%$
	40	13.55982	-0.00133	$\pm 0.01\%$
	50	13.55917	-0.00612	$\pm 0.01\%$

FCC§15.215(c) - 20dB EMISSION BANDWIDTH

Requirement

Per 15.215 (c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the table of the chamber, Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.

Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Bibo Zhang on 2018-06-08.

Test Mode: Transmitting

Test Result: Pass

20 dB Emission Bandwidth



EUT

Date: 8.JUN.2018 20:49:27

***** END OF REPORT *****