



FCC RF Test Report

APPLICANT : Lenovo(Shanghai) Electronics
Technology Co., Ltd.
EQUIPMENT : Portable Tablet Computer
BRAND NAME : Lenovo
MODEL NAME : Lenovo TB-X704Y
FCC ID : O57TBX704Y
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Feb.22, 2017 and testing was completed on Jun.07, 2017. We, SPORTON International (ShenZhen) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON International (ShenZhen) INC., the test report shall not be reproduced except in full.

Prepared by: Eric Shih / Manager

Approved by: Jones Tsai / Manager



SPORTON International (ShenZhen) INC.

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan District, Shenzhen City,
Guangdong Province, China**



TABLE OF CONTENTS

1	GENERAL DESCRIPTION	5
1.1	Applicant	5
1.2	Manufacturer	5
1.3	Product Feature of Equipment Under Test.....	5
1.4	Product Specification of Equipment Under Test.....	6
1.5	Component List.....	6
1.6	Modification of EUT	6
1.7	Testing Location	7
1.8	Applicable Standards.....	8
2	TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1	Carrier Frequency and Channel	9
2.2	Test Mode.....	10
2.3	Connection Diagram of Test System.....	11
2.4	Support Unit used in test configuration and system	12
2.5	EUT Operation Test Setup	12
2.6	Measurement Results Explanation Example.....	13
3	TEST RESULT	14
3.1	6dB and 99% Bandwidth Measurement	14
3.2	Output Power Measurement.....	16
3.3	Power Spectral Density Measurement	17
3.4	Conducted Band Edges and Spurious Emission Measurement	19
3.5	Radiated Band Edges and Spurious Emission Measurement	32
3.6	AC Conducted Emission Measurement.....	36
3.7	Antenna Requirements.....	40
4	LIST OF MEASURING EQUIPMENT	41
5	UNCERTAINTY OF EVALUATION	42
APPENDIX A. CONDUCTED TEST RESULTS		
APPENDIX B. RADIATED SPURIOUS EMISSION		
APPENDIX C. DUTY CYCLE PLOTS		
APPENDIX D. SETUP PHOTOGRAPHS		



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR722203-01C	Rev. 01	Initial issue of report	Jun. 26, 2017



SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	RSS-247 5.2(a)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	RSS-Gen 6.6	99% Bandwidth	-	Pass	-
3.2	15.247(b)	RSS-247 5.4(d)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	RSS-247 5.2(b)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	RSS-247 5.5	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
			Conducted Spurious Emission		Pass	-
3.5	15.247(d)	RSS-247 5.5	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 7.23 dB at 30.000 MHz
3.6	15.207	RSS-GEN 8.8	AC Conducted Emission	15.207(a)	Pass	Under limit 7.40 dB at 17.850 MHz
3.7	15.203 & 15.247(b)	N/A	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

Lenovo(Shanghai) Electronics Technology Co., Ltd.

NO.68 BUILDING, 199 FENJU RD, China (Shanghai) Pilot Free Trade Zone, 200131, CHINA

1.2 Manufacturer

Lenovo PC HK Limited

23/F, Lincoln House, Taikoo Place, 979 King's Road, Quarry Bay, Hong Kong

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Portable Tablet Computer
Brand Name	Lenovo
Model Name	Lenovo TB-X704Y
FCC ID	O57TBX704Y
EUT supports Radios application	WLAN2.4GHz802.11 b/g/nHT20/HT40 WLAN2.4GHz802.11 a/nHT20/HT40 WLAN5GHz802.11ac VHT20/VHT40/HT80 Bluetooth v3.0+EDR/ Bluetooth v4.0LE Bluetooth v4.1LE/ Bluetooth v4.2LE
HW Version	Lenovo Tablet TB-X704Y
SW Version	TB-X704Y_RF01_20170420
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	802.11b : 17.79 dBm (0.0601 W) 802.11g : 24.38 dBm (0.2742 W) 802.11n HT20 : 24.18 dBm (0.2618 W) 802.11n HT40 : 25.07 dBm (0.3214 W)
99% Occupied Bandwidth	802.11b : 13.29MHz 802.11g : 18.53MHz 802.11n HT20 : 19.23MHz 802.11n HT40 : 36.66MHz
Antenna Type / Gain	PIFA Antenna type with gain 0.63 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Component List

Note: There are two types of EUT, please refer to the following table for the difference between them.

According to the difference, we choose sample 1 to perform full test, and sample 2 to verify worst case.

Component	Sample 1	Sample 2
CPU	Qualcomm APQ-8053-1-857NSP-TR-01-0-AB	Qualcomm APQ-8053-1-857NSP-TR-01-0-AB
BT/WIFI Module	Qualcomm WCN-3680B-0-79BWLNSP-TR-05-1	Qualcomm WCN-3680B-0-79BWLNSP-TR-05-1
RAM/EMMC	2G+16G Samsung KMQE10013M-B318 MCP_16GB+16Gb,LPDDR3	2G+16G Hynix H9TQ17ABJTBCUR-KUM MCP_16GB+16Gb,LPDDR3
LCD	INX: P101KDA-AF0	BOE: TV101WUM-NL1
Battery	SCUD: L16D2P31, 3.85V/7000mAh	Celxpert: L16D2P31, 3.85V/7000mAh
Camera front	Q Tech: F5695AK	AVC: BFL05006
Camera rear	Q Tech: FX219BH	film: L8856A10

1.6 Modification of EUT

No modifications are made to the EUT during all test items.



1.7 Testing Location

Test Site	SPORTON International (ShenZhen) INC.	
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan District, Shenzhen City, Guangdong Province, China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
Test Site No.	Sporton Site No.	
	TH01-SZ	CO01-SZ

Test Site	SPORTON International (ShenZhen) INC.	
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
Test Site No.	Sporton Site No.	FCC/IC Registration No.
	03CH03-SZ	565805/4086F

Note: The test site complies with ANSI C63.4 2014 requirement.



1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Test Mode


Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0


Test Cases	
AC Conducted Emission	Mode 1 : Bluetooth Link + WLAN(2.4G) Link + Adapter1 + Earphone + USB Cable 1 for sample1
	Mode 2 : Bluetooth Link + WLAN(2.4G) Link + Adapter2 + Earphone + USB Cable 2 for sample2
Remark: 1. For radiated TCS; the tests were performed with adapter, earphone and USB cable. 2. The worst case of conducted emission is mode 2; only the test data of it was reported.	

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Earphone	Lenovo	SH100	FCC DoC	Unshielded,1.6m	N/A
2.	WLAN AP	Dlink	DIR-820L	KA2IR820LA1	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	E540	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Nokia	BH-108	PYAHS-107W	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN function, the engineering test program was provided and enabled to make EUT (connect with Bluetooth base station to) continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.0 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 5.0 + 10 = 15.0 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures


1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup








3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz Low	Relative Humidity :	50 ~ 53 %
Test Channel :	01	Test Engineer :	Wilson Chen





Test Mode :	802.11b	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz Mid	Relative Humidity :	50 ~ 53 %
Test Channel :	06	Test Engineer :	Wilson Chen


WLAN 802.11b Channel 06**100kHz PSD reference Level****Spurious Emission 30MHz~3GHz****Spurious Emission 2GHz~25GHz**



Test Mode :	802.11b	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz High	Relative Humidity :	50 ~ 53 %
Test Channel :	11	Test Engineer :	Wilson Chen


WLAN 802.11b Channel 11

100kHz PSD reference Level




Date: 12.MAY.2017 17:32:27

High Channel Plot




Date: 12.MAY.2017 17:33:17

Spurious Emission 30MHz~3GHz



Date: 13.JUN.2017 17:52:17

Spurious Emission 2GHz~25GHz




Date: 12.MAY.2017 17:35:50




Test Mode :	802.11g	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz Low	Relative Humidity :	50 ~ 53 %
Test Channel :	01	Test Engineer :	Wilson Chen

WLAN 802.11g Channel 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11g	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz Mid	Relative Humidity :	50 ~ 53 %
Test Channel :	06	Test Engineer :	Wilson Chen

WLAN 802.11g Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11g	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz High	Relative Humidity :	50 ~ 53 %
Test Channel :	11	Test Engineer :	Wilson Chen

WLAN 802.11g Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz








Test Mode :	802.11n HT20	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz Low	Relative Humidity :	50 ~ 53 %
Test Channel :	01	Test Engineer :	Wilson Chen









Test Mode :	802.11n HT20	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz Mid	Relative Humidity :	50 ~ 53 %
Test Channel :	06	Test Engineer :	Wilson Chen

WLAN 802.11n HT20 Channel 06**100kHz PSD reference Level****Spurious Emission 30MHz~3GHz****Spurious Emission 2GHz~25GHz**




Test Mode :	802.11n HT20	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz High	Relative Humidity :	50 ~ 53 %
Test Channel :	11	Test Engineer :	Wilson Chen

WLAN 802.11n HT20 Channel 11**100kHz PSD reference Level****High Channel Plot****Spurious Emission 30MHz~3GHz****Spurious Emission 2GHz~25GHz**






Test Mode :	802.11n HT40	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz Low	Relative Humidity :	50 ~ 53 %
Test Channel :	03	Test Engineer :	Wilson Chen






Test Mode :	802.11n HT40	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz Mid	Relative Humidity :	50 ~ 53 %
Test Channel :	06	Test Engineer :	Wilson Chen

WLAN 802.11n HT40 Channel 06**100kHz PSD reference Level****Spurious Emission 30MHz~3GHz****Spurious Emission 2GHz~25GHz**



Test Mode :	802.11n HT40	Temperature :	24 ~ 26 °C
Test Band :	2.4GHz High	Relative Humidity :	50 ~ 53 %
Test Channel :	09	Test Engineer :	Wilson Chen



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Duty Cycle

Please refer to Appendix C.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

For terminal test result, the testing follows FCC KDB 174176.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 2	Temperature :	21~23℃
Test Engineer :	Tao Cheng	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	Bluetooth Link + WLAN(2.4G) Link + Adapter2 + Earphone + USB Cable 2 for sample2		




Site : C001-SZ
Condition: FCC 15C QP LISN_20170301_L LINE

Mode : Mode 2

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.15	47.24	-8.76	56.00	36.80	0.03	10.41	Average
2	0.15	50.74	-15.26	66.00	40.30	0.03	10.41	QP
3	0.20	38.35	-15.27	53.62	28.10	0.03	10.22	Average
4	0.20	40.85	-22.77	63.62	30.60	0.03	10.22	QP
5	0.71	22.99	-23.01	46.00	12.80	0.02	10.17	Average
6	0.71	35.39	-20.61	56.00	25.20	0.02	10.17	QP
7	2.19	23.29	-22.71	46.00	13.00	0.12	10.17	Average
8	2.19	36.29	-19.71	56.00	26.00	0.12	10.17	QP
9	2.64	23.54	-22.46	46.00	13.20	0.14	10.20	Average
10	2.64	34.94	-21.06	56.00	24.60	0.14	10.20	QP
11	18.82	37.73	-12.27	50.00	26.00	1.15	10.58	Average
12	18.82	50.53	-9.47	60.00	38.80	1.15	10.58	QP



Test Mode :	Mode 2	Temperature :	21~23°C
Test Engineer :	Tao Cheng	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Bluetooth Link + WLAN(2.4G) Link + Adapter2 + Earphone + USB Cable 2 for sample2		



Site : CO01-SZ
Condition: FCC 15C_QP LISN_20170301_N NEUTRAL

Mode : Mode 2

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15	46.24	-9.76	56.00	35.80	0.03	10.41	Average
2	0.15	49.74	-16.26	66.00	39.30	0.03	10.41	QP
3	0.20	35.65	-18.02	53.67	25.40	0.03	10.22	Average
4	0.20	38.35	-25.32	63.67	28.10	0.03	10.22	QP
5	0.72	18.59	-27.41	46.00	8.41	0.02	10.16	Average
6	0.72	30.79	-25.21	56.00	20.61	0.02	10.16	QP
7	2.82	16.14	-29.86	46.00	5.91	0.03	10.20	Average
8	2.82	27.74	-28.26	56.00	17.51	0.03	10.20	QP
9	4.18	20.71	-25.29	46.00	10.39	0.06	10.26	Average
10	4.18	31.81	-24.19	56.00	21.49	0.06	10.26	QP
11 *	17.85	42.60	-7.40	50.00	31.60	0.48	10.52	Average
12	17.85	47.90	-12.10	60.00	36.90	0.48	10.52	QP

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	9kHz~40GHz	Apr.20.2017	May 12, 2017~ May 13, 2017	Apr.19.2018	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1207253	30MHz~40GHz	Jan. 06, 2017	May 12, 2017~ May 13, 2017	Jan. 05, 2018	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Jan. 06, 2017	May 12, 2017~ May 13, 2017	Jan. 05, 2018	Conducted (TH01-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Jan. 06, 2017	May 14, 2017	Jan. 05, 2018	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Jan. 05, 2017	May 14, 2017	Jan. 04, 2018	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	MessTec	3816/2SH	00103892	9kHz~30MHz	Jan. 05, 2017	May 14, 2017	Jan. 04, 2018	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000 891	100Vac~250Vac	Jul. 16, 2016	May 14, 2017	Jul. 15, 2017	Conduction (CO01-SZ)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY544500 83	20Hz~8.4GHz	Apr. 20, 2017	Jun. 07, 2017	Apr. 19, 2018	Radiation (03CH03-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY551502 46	10Hz~44GHz;	Apr.20, 2017	Jun. 07, 2017	Apr. 19, 2018	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 14, 2017	Jun. 07, 2017	May 13, 2018	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	May 14, 2017	Jun. 07, 2017	May 13, 2018	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBE CK	BBHA 9120D	9120D-128 5	1GHz~18GHz	Jan. 12, 2017	Jun. 07, 2017	Jan. 11, 2018	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Aug.10, 2016	Jun. 07, 2017	Aug. 09, 2017	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102210	0.01Hz ~3000MHz	Oct. 11, 2016	Jun. 07, 2017	Oct. 10, 2017	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	AMF-7D-0010 1800-30-10P- R	1943528	1GHz~18GHz	Oct. 11, 2016	Jun. 07, 2017	Oct. 10, 2017	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY395013 02	500MHz~26.5G Hz	Jan. 06, 2017	Jun. 07, 2017	Jan. 05, 2018	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	TTA1840-35- HG	1871923	18GHz~40GHz	Jul. 16. 2016	Jun. 07, 2017	Jul. 15. 2017	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010001 985	N/A	NCR	Jun. 07, 2017	NCR	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jun. 07, 2017	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jun. 07, 2017	NCR	Radiation (03CH03-SZ)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.5dB
--	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1G MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1 dB
--	--------

Uncertainty of Radiated Emission Measurement (1G MHz ~ 18G MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
--	--------

Uncertainty of Radiated Emission Measurement (18G MHz ~ 40G MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
--	--------



Appendix A. Conducted Test Results

A1 - DTS Part

Test Engineer:	Wilson Chen	Temperature:	24 ~ 26	°C
Test Date:	2017/5/12~2017/5/13	Relative Humidity:	50 ~ 53	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	13.19	8.05	0.50	Pass
11b	1Mbps	1	6	2437	13.19	8.53	0.50	Pass
11b	1Mbps	1	11	2462	13.29	8.55	0.50	Pass
11g	6Mbps	1	1	2412	18.33	16.34	0.50	Pass
11g	6Mbps	1	6	2437	18.43	16.34	0.50	Pass
11g	6Mbps	1	11	2462	18.53	16.38	0.50	Pass
HT20	MCS0	1	1	2412	19.23	17.56	0.50	Pass
HT20	MCS0	1	6	2437	19.18	17.58	0.50	Pass
HT20	MCS0	1	11	2462	19.08	17.58	0.50	Pass
HT40	MCS0	1	3	2422	36.36	35.09	0.50	Pass
HT40	MCS0	1	6	2437	36.46	35.45	0.50	Pass
HT40	MCS0	1	9	2452	36.66	35.45	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	17.79	30.00	0.63	18.42	36.00	Pass
11b	1Mbps	1	6	2437	17.31	30.00	0.63	17.94	36.00	Pass
11b	1Mbps	1	11	2462	16.26	30.00	0.63	16.89	36.00	Pass
11g	6Mbps	1	1	2412	24.38	30.00	0.63	25.01	36.00	Pass
11g	6Mbps	1	6	2437	23.85	30.00	0.63	24.48	36.00	Pass
11g	6Mbps	1	11	2462	22.50	30.00	0.63	23.13	36.00	Pass
HT20	MCS0	1	1	2412	24.18	30.00	0.63	24.81	36.00	Pass
HT20	MCS0	1	6	2437	23.61	30.00	0.63	24.24	36.00	Pass
HT20	MCS0	1	11	2462	22.71	30.00	0.63	23.34	36.00	Pass
HT40	MCS0	1	3	2422	25.07	30.00	0.63	25.70	36.00	Pass
HT40	MCS0	1	6	2437	24.41	30.00	0.63	25.04	36.00	Pass
HT40	MCS0	1	9	2452	23.43	30.00	0.63	24.06	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.09	15.01
11b	1Mbps	1	6	2437	0.09	14.44
11b	1Mbps	1	11	2462	0.09	13.40
11g	6Mbps	1	1	2412	0.60	14.32
11g	6Mbps	1	6	2437	0.60	13.76
11g	6Mbps	1	11	2462	0.60	12.94
HT20	MCS0	1	1	2412	0.62	14.31
HT20	MCS0	1	6	2437	0.62	13.57
HT20	MCS0	1	11	2462	0.62	12.99
HT40	MCS0	1	3	2422	1.19	14.66
HT40	MCS0	1	6	2437	1.19	14.28
HT40	MCS0	1	9	2452	1.19	13.58

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-5.75	0.63	8.00	Pass
11b	1Mbps	1	6	2437	-7.19	0.63	8.00	Pass
11b	1Mbps	1	11	2462	-7.53	0.63	8.00	Pass
11g	6Mbps	1	1	2412	-10.96	0.63	8.00	Pass
11g	6Mbps	1	6	2437	-9.55	0.63	8.00	Pass
11g	6Mbps	1	11	2462	-11.51	0.63	8.00	Pass
HT20	MCS0	1	1	2412	-10.97	0.63	8.00	Pass
HT20	MCS0	1	6	2437	-11.86	0.63	8.00	Pass
HT20	MCS0	1	11	2462	-11.55	0.63	8.00	Pass
HT40	MCS0	1	3	2422	-13.60	0.63	8.00	Pass
HT40	MCS0	1	6	2437	-13.75	0.63	8.00	Pass
HT40	MCS0	1	9	2452	-14.94	0.63	8.00	Pass



Appendix B. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2387.49	42.1	-31.9	74	42.36	27.43	5.64	33.33	191	118	P	H
		2390	32.03	-21.97	54	32.28	27.43	5.64	33.32	191	118	A	H
	*	2412	99.18	-	-	99.37	27.49	5.64	33.32	191	118	P	H
	*	2412	96.15	-	-	96.34	27.49	5.64	33.32	191	118	A	H
		2337.615	41.83	-32.17	74	42.39	27.24	5.53	33.33	173	266	P	V
		2390	32.07	-21.93	54	32.32	27.43	5.64	33.32	173	266	A	V
	*	2412	99.79	-	-	99.98	27.49	5.64	33.32	173	266	P	V
	*	2412	96.64	-	-	96.83	27.49	5.64	33.32	173	266	A	V
802.11b CH 06 2437MHz		2375.52	41.66	-32.34	74	42.03	27.37	5.59	33.33	244	307	P	H
		2389.66	31.28	-22.72	54	31.54	27.43	5.64	33.33	244	307	A	H
	*	2437	99.21	-	-	99.23	27.61	5.68	33.31	244	307	P	H
	*	2437	94.16	-	-	94.18	27.61	5.68	33.31	244	307	A	H
		2497.76	42.6	-31.4	74	42.38	27.8	5.72	33.3	244	307	P	H
		2484.6	31.85	-22.15	54	31.7	27.74	5.72	33.31	244	307	A	H
		2366.98	41.6	-32.4	74	42.04	27.3	5.59	33.33	150	266	P	V
		2389.52	31.65	-22.35	54	31.91	27.43	5.64	33.33	150	266	A	V
	*	2437	99.44	-	-	99.46	27.61	5.68	33.31	150	266	P	V
	*	2437	96.03	-	-	96.05	27.61	5.68	33.31	150	266	A	V
		2484.6	42.81	-31.19	74	42.66	27.74	5.72	33.31	150	266	P	V
		2483.69	32.23	-21.77	54	32.08	27.74	5.72	33.31	150	266	A	V



802.11b CH 11 2462MHz	*	2462	99.17	-	-	99.12	27.68	5.68	33.31	208	123	P	H
	*	2462	95.89	-	-	95.84	27.68	5.68	33.31	208	123	A	H
		2484.32	43.6	-30.4	74	43.45	27.74	5.72	33.31	208	123	P	H
		2486.56	33.52	-20.48	54	33.37	27.74	5.72	33.31	208	123	A	H
	*	2462	98.75	-	-	98.7	27.68	5.68	33.31	150	292	P	V
	*	2462	95.47	-	-	95.42	27.68	5.68	33.31	150	292	A	V
		2485.96	43.07	-30.93	74	42.92	27.74	5.72	33.31	150	292	P	V
		2486.36	33.15	-20.85	54	33	27.74	5.72	33.31	150	292	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		4824	42.7	-31.3	74	59.99	31.49	7.82	56.6	250	0	P	H
		4824	42.9	-31.1	74	60.19	31.49	7.82	56.6	250	0	P	V
802.11b CH 06 2437MHz		4874	41.25	-32.75	74	58.73	31.61	7.82	56.91	250	0	P	H
		7311	43.29	-30.71	74	55.95	36.17	9.17	58	250	0	P	H
		4874	41.09	-32.91	74	58.57	31.61	7.82	56.91	250	0	P	V
		7311	43.22	-30.78	74	55.88	36.17	9.17	58	250	0	P	V
802.11b CH 11 2462MHz		4924	43.98	-30.02	74	60.51	31.73	7.82	56.08	250	0	P	H
		7386	43.2	-30.8	74	55.72	36.28	9.21	58.01	250	0	P	H
		4924	43.71	-30.29	74	60.24	31.73	7.82	56.08	250	0	P	V
		7386	44.01	-29.99	74	56.53	36.28	9.21	58.01	250	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2389.905	53.28	-20.72	74	53.53	27.43	5.64	33.32	250	336	P	H
		2389.8	39.03	-14.97	54	39.28	27.43	5.64	33.32	250	336	A	H
	*	2412	103.25	-	-	103.44	27.49	5.64	33.32	250	336	P	H
	*	2412	94.27	-	-	94.46	27.49	5.64	33.32	250	336	A	H
		2389.8	54.81	-19.19	74	55.06	27.43	5.64	33.32	150	86	P	V
		2390	38.54	-15.46	54	38.79	27.43	5.64	33.32	150	86	A	V
	*	2412	101.63	-	-	101.82	27.49	5.64	33.32	150	86	P	V
	*	2412	94.08	-	-	94.27	27.49	5.64	33.32	150	86	A	V
802.11g CH 06 2437MHz		2383.92	42.05	-31.95	74	42.42	27.37	5.59	33.33	250	338	P	H
		2384.76	32.99	-21.01	54	33.31	27.37	5.64	33.33	250	338	A	H
	*	2437	101.83	-	-	101.85	27.61	5.68	33.31	250	338	P	H
	*	2437	93.98	-	-	94	27.61	5.68	33.31	250	338	A	H
		2483.97	43.06	-30.94	74	42.91	27.74	5.72	33.31	250	338	P	H
		2488.87	33.39	-20.61	54	33.18	27.8	5.72	33.31	250	338	A	H
		2344.44	41.78	-32.22	74	42.34	27.24	5.53	33.33	150	293	P	V
		2385.04	32.81	-21.19	54	33.13	27.37	5.64	33.33	150	293	A	V
	*	2437	101	-	-	101.02	27.61	5.68	33.31	150	293	P	V
	*	2437	93.35	-	-	93.37	27.61	5.68	33.31	150	293	A	V
		2484.74	42.65	-31.35	74	42.5	27.74	5.72	33.31	150	293	P	V
		2489.36	33.18	-20.82	54	32.97	27.8	5.72	33.31	150	293	A	V



802.11g CH 11 2462MHz	*	2462	100.79	-	-	100.74	27.68	5.68	33.31	235	336	P	H
	*	2462	93.17	-	-	93.12	27.68	5.68	33.31	235	336	A	H
		2483.92	51.15	-22.85	74	51	27.74	5.72	33.31	235	336	P	H
		2483.52	39	-15	54	38.85	27.74	5.72	33.31	235	336	A	H
	*	2462	99.58	-	-	99.53	27.68	5.68	33.31	150	293	P	V
	*	2462	91.99	-	-	91.94	27.68	5.68	33.31	150	293	A	V
		2484.24	49.01	-24.99	74	48.86	27.74	5.72	33.31	150	293	P	V
		2483.52	37.98	-16.02	54	37.83	27.74	5.72	33.31	150	293	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4824	41.71	-32.29	74	59	31.49	7.82	56.6	250	0	P	H
		4824	42.55	-31.45	74	59.84	31.49	7.82	56.6	250	0	P	V
802.11g CH 06 2437MHz		4874	40.04	-33.96	74	57.52	31.61	7.82	56.91	250	0	P	H
		7311	43.32	-30.68	74	55.98	36.17	9.17	58	250	0	P	H
		4874	40.97	-33.03	74	58.45	31.61	7.82	56.91	250	0	P	V
		7311	43.06	-30.94	74	55.72	36.17	9.17	58	250	0	P	V
802.11g CH 11 2462MHz		4924	43.5	-30.5	74	60.03	31.73	7.82	56.08	250	0	P	H
		7386	43.24	-30.76	74	55.76	36.28	9.21	58.01	250	0	P	H
		4924	43.14	-30.86	74	59.67	31.73	7.82	56.08	250	0	P	V
		7386	42.67	-31.33	74	55.19	36.28	9.21	58.01	250	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2389.695	56.58	-17.42	74	56.84	27.43	5.64	33.33	250	336	P	H
		2389.905	40.12	-13.88	54	40.37	27.43	5.64	33.32	250	336	A	H
	*	2412	102.34	-	-	102.53	27.49	5.64	33.32	250	336	P	H
	*	2412	94.27	-	-	94.46	27.49	5.64	33.32	250	336	A	H
		2389.905	53.32	-20.68	74	53.57	27.43	5.64	33.32	150	84	P	V
		2390	38.68	-15.32	54	38.93	27.43	5.64	33.32	150	84	A	V
	*	2412	101.23	-	-	101.42	27.49	5.64	33.32	150	84	P	V
	*	2412	93.07	-	-	93.26	27.49	5.64	33.32	150	84	A	V
802.11n HT20 CH 06 2437MHz		2385.88	42.23	-31.77	74	42.49	27.43	5.64	33.33	150	344	P	H
		2385.18	33.57	-20.43	54	33.89	27.37	5.64	33.33	150	344	A	H
	*	2437	101.13	-	-	101.15	27.61	5.68	33.31	150	344	P	H
	*	2437	93.41	-	-	93.43	27.61	5.68	33.31	150	344	A	H
		2484.32	42.94	-31.06	74	42.79	27.74	5.72	33.31	150	344	P	H
		2488.45	33.97	-20.03	54	33.76	27.8	5.72	33.31	150	344	A	H
		2385.18	42.73	-31.27	74	43.05	27.37	5.64	33.33	150	84	P	V
		2385.32	32.84	-21.16	54	33.16	27.37	5.64	33.33	150	84	A	V
	*	2437	100.12	-	-	100.14	27.61	5.68	33.31	150	84	P	V
	*	2437	92.44	-	-	92.46	27.61	5.68	33.31	150	84	A	V
		2485.16	43.1	-30.9	74	42.95	27.74	5.72	33.31	150	84	P	V
		2488.73	33.51	-20.49	54	33.3	27.8	5.72	33.31	150	84	A	V



802.11n HT20 CH 11 2462MHz	*	2462	99.68	-	-	99.63	27.68	5.68	33.31	217	119	P	H
	*	2462	91.78	-	-	91.73	27.68	5.68	33.31	217	119	A	H
		2484.2	51.52	-22.48	74	51.37	27.74	5.72	33.31	217	119	P	H
		2483.52	37.98	-16.02	54	37.83	27.74	5.72	33.31	217	119	A	H
	*	2462	99.04	-	-	98.99	27.68	5.68	33.31	150	288	P	V
	*	2462	91.49	-	-	91.44	27.68	5.68	33.31	150	288	A	V
		2483.84	50.37	-23.63	74	50.22	27.74	5.72	33.31	150	288	P	V
		2483.52	37.81	-16.19	54	37.66	27.74	5.72	33.31	150	288	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		4824	42.46	-31.54	74	59.75	31.49	7.82	56.6	250	0	P	H
		4824	43.09	-30.91	74	60.38	31.49	7.82	56.6	250	0	P	V
802.11n HT20 CH 06 2437MHz		4874	40.22	-33.78	74	57.7	31.61	7.82	56.91	250	0	P	H
		7311	43.01	-30.99	74	55.67	36.17	9.17	58	250	0	P	H
		4874	40.12	-33.88	74	57.6	31.61	7.82	56.91	250	0	P	V
		7311	42.98	-31.02	74	55.64	36.17	9.17	58	250	0	P	V
802.11n HT20 CH 11 2462MHz		4924	43.91	-30.09	74	60.44	31.73	7.82	56.08	250	0	P	H
		7386	44.49	-29.51	74	57.01	36.28	9.21	58.01	250	0	P	H
		4924	43.51	-30.49	74	60.04	31.73	7.82	56.08	250	0	P	V
		7386	43.08	-30.92	74	55.6	36.28	9.21	58.01	250	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 03 2422MHz		2389.94	54.05	-19.95	74	54.3	27.43	5.64	33.32	250	120	P	H
		2389.8	38.15	-15.85	54	38.4	27.43	5.64	33.32	250	120	A	H
	*	2422	102.12	-	-	102.24	27.55	5.64	33.31	250	120	P	H
	*	2422	94.78	-	-	94.9	27.55	5.64	33.31	250	120	A	H
		2489.43	43.98	-30.02	74	43.77	27.8	5.72	33.31	250	120	P	H
		2484.32	33.64	-20.36	54	33.49	27.74	5.72	33.31	250	120	A	H
		2389.38	51.81	-22.19	74	52.07	27.43	5.64	33.33	150	103	P	V
		2389.8	35.21	-18.79	54	35.46	27.43	5.64	33.32	150	103	A	V
	*	2422	99.6	-	-	99.72	27.55	5.64	33.31	150	103	P	V
	*	2422	91.86	-	-	91.98	27.55	5.64	33.31	150	103	A	V
		2494.4	42.41	-31.59	74	42.19	27.8	5.72	33.3	150	103	P	V
		2483.55	33.97	-20.03	54	33.82	27.74	5.72	33.31	150	103	A	V
802.11n HT40 CH 06 2437MHz		2389.94	47.27	-26.73	74	47.52	27.43	5.64	33.32	150	164	P	H
		2389.94	34.39	-19.61	54	34.64	27.43	5.64	33.32	150	164	A	H
	*	2437	101.6	-	-	101.62	27.61	5.68	33.31	150	164	P	H
	*	2437	93	-	-	93.02	27.61	5.68	33.31	150	164	A	H
		2483.5	45.55	-28.45	74	45.4	27.74	5.72	33.31	150	164	P	H
		2483.5	34.29	-19.71	54	34.14	27.74	5.72	33.31	150	164	A	H
		2389.1	42.52	-31.48	74	42.78	27.43	5.64	33.33	150	146	P	V
		2389.66	32.75	-21.25	54	33.01	27.43	5.64	33.33	150	146	A	V
	*	2437	100.15	-	-	100.17	27.61	5.68	33.31	150	146	P	V
	*	2437	92.74	-	-	92.76	27.61	5.68	33.31	150	146	A	V
		2483.83	45.98	-28.02	74	45.83	27.74	5.72	33.31	150	146	P	V
		2484.18	33.8	-20.2	54	33.65	27.74	5.72	33.31	150	146	A	V



802.11n HT40 CH 09 2452MHz		2348.22	41.69	-32.31	74	42.19	27.24	5.59	33.33	150	165	P	H
		2389.94	33.91	-20.09	54	34.16	27.43	5.64	33.32	150	165	A	H
	*	2452	102.16	-	-	102.18	27.61	5.68	33.31	150	165	P	H
	*	2452	94.1	-	-	94.12	27.61	5.68	33.31	150	165	P	H
		2483.9	50.51	-23.49	74	50.36	27.74	5.72	33.31	150	165	P	H
		2485.86	38.05	-15.95	54	37.9	27.74	5.72	33.31	150	165	A	H
		2365.72	41.45	-32.55	74	41.89	27.3	5.59	33.33	150	145	P	V
		2389.8	33.02	-20.98	54	33.27	27.43	5.64	33.32	150	145	A	V
	*	2452	100.29	-	-	100.31	27.61	5.68	33.31	150	145	P	V
	*	2452	91.7	-	-	91.72	27.61	5.68	33.31	150	145	A	V
		2484.18	50.72	-23.28	74	50.57	27.74	5.72	33.31	150	145	P	V
		2483.69	36	-18	54	35.85	27.74	5.72	33.31	150	145	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n		4844	42.93	-31.07	74	60.16	31.53	7.82	56.58	150	360	P	H
HT40		7266	44.86	-29.14	74	57.86	36.13	9.14	58.27	150	360	P	H
CH 03		4844	42.18	-31.82	74	59.41	31.53	7.82	56.58	150	360	P	V
2422MHz		7266	44.45	-29.55	74	57.45	36.13	9.14	58.27	150	360	P	V
802.11n		4874	40.75	-33.25	74	58.23	31.61	7.82	56.91	150	360	P	H
HT40		7311	42.43	-31.57	74	55.09	36.17	9.17	58	150	360	P	H
CH 06		4874	41.92	-32.08	74	59.4	31.61	7.82	56.91	150	360	P	V
2437MHz		7311	43.27	-30.73	74	55.93	36.17	9.17	58	150	360	P	V
802.11n		4904	43.83	-30.17	74	60.67	31.69	7.82	56.35	150	360	P	H
HT40		7356	41.17	-32.83	74	53.71	36.23	9.19	57.96	150	360	P	H
CH 09		4904	41.93	-32.07	74	58.77	31.69	7.82	56.35	150	360	P	V
2452MHz		7356	41.64	-32.36	74	54.18	36.23	9.19	57.96	150	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz WIFI 802.11n HT40 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT40 LF		30.97	24.98	-15.02	40	31.97	24.52	0.27	31.78	100	121	P	H
		107.6	25.03	-18.47	43.5	38.76	16.73	1.09	31.55	-	-	P	H
		214.3	22.22	-21.28	43.5	35.96	15.88	1.64	31.26	-	-	P	H
		488.81	26.14	-19.86	46	32.17	22.73	2.4	31.16	-	-	P	H
		556.71	27.01	-18.99	46	31.24	24.39	2.58	31.2	-	-	P	H
		750.71	28.18	-17.82	46	30.36	26.02	3.03	31.23	-	-	P	H
		30	32.77	-7.23	40	38.8	25.1	0.65	31.78	100	0	P	V
		119.24	26.54	-16.96	43.5	40.98	17.08	0	31.52	-	-	P	V
		172.59	22.8	-20.7	43.5	36.28	16.69	1.17	31.34	-	-	P	V
		341.37	21.62	-24.38	46	31.39	20	1.52	31.29	-	-	P	V
		510.15	25.99	-20.01	46	32.01	23.34	1.8	31.16	-	-	P	V
		675.05	27.68	-18.32	46	33.46	25.45	0	31.23	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.




Appendix C. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(KHz)	VBW Setting
802.11b	97.94	8.261	0.121	300Hz
802.11g	87.04	1.362	0.734	1KHz
802.11n HT20	86.67	1.281	0.781	1KHz
802.11n HT40	76.04	0.635	1.575	3KHz




802.11b






802.11g





802.11n HT20





802.11n HT40

