

Königswinkel 10 32825 Blomberg Germany Phone +49 5235 9500-0 Fax +49 5235 9500-10

TEST REPORT

Test Report Reference: R61924 Edition 1, 2nd Version

Equipment under Test: cB-0902-0201

Serial Number: none

FCC ID: PVH090202S

Applicant: connectBlue AB

Manufacturer: connectBlue AB

Test Laboratory (CAB) accredited by DATech e.V. in compliance with DIN EN ISO/IEC 17025 under the Reg. No. DAT-P-105/99-21 and FCC Test site registration number 90877



Contents: Pa	ige
1 IDENTIFICATION	3
1.1 APPLICANT	3
1.2 MANUFACTURER	3
1.3 DATES	3
1.4 TEST LABORATORY	4
1.5 RESERVATION	4
1.6 NORMATIVE REFERENCES	4
1.7 TEST RESULTS	4
2 TECHNICAL DATA OF EQUIPMENT	5
2.1 DEVICE UNDER TEST	5
2.2 PERIPHERY DEVICES	6
3 OPERATIONAL STATES AND PHYSICAL BOUNDARIES	6
4 ADDITIONAL INFORMATION	7
5 LIST OF MEASUREMENTS	7
6 TEST RESULTS	8
6.1 RADIATED EMISSIONS (TRANSMITTER)	8
6.1.1 METHOD OF MEASUREMENT (RADIATED EMISSIONS)	8
6.1.2 TEST RESULTS (RADIATED EMISSIONS) 6.1.2.1 PRELIMINARY MEASUREMENT WITH ADDITIONAL ANTENNA (9 kHz to 25	14
GHz)	14
6.1.2.2 FINAL MEASUREMENT WITH ADDITIONAL ANTENNA (1 GHz to 25 GHz)	23
7 TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS	26
8 LIST OF ANNEXES	30



1 IDENTIFICATION

1.1 APPLICANT

Name:	connectBlue AB	
Address:	Norra Vallgatan 64 3V	
	Malmö SE-211 19	
Country:	Sweden	
Name for contact purposes:	Mr. Martin Engdahl	
Tel:	+ 46 40 63 07 100	
Fax:	+ 46 40 23 71 37	
e-mail address:	martin.engdahl@connectblue.se	

1.2 MANUFACTURER

Name:	connectBlue AB	
Address:	Norra Vallgatan 64 3V	
	Malmö SE-211 19	
Country:	Sweden	
Name for contact purposes:	Mr. Martin Engdahl	
Tel:	+ 46 40 63 07 100	
Fax:	+ 46 40 23 71 37	
e-mail address:	martin.engdahl@connectblue.se	

1.3 DATES

Date of receipt of test sample:	04 October 2006
Start of test:	05 October 2006
End of test:	05 October 2006



1.4 TEST LABORATORY

PHOENIX TESTLAB GmbH Königswinkel 10 D-32825 Blomberg Germany

+49 (0) 52 35 / 95 00-0 +49 (0) 52 35 / 95 00-10

accredited by DATech GmbH in compliance with DIN EN ISO/IEC 17025 under Reg. No. DAT-P-105/99-21, FCC Test site registration number 90877 and Industry Canada Test site registration IC3469

Phone:

Fax:

Test engineer:	Thomas KÜHN	T. Li	23 October 2006
	Name	Signature	Date
Test report checked:	Frank EIKERMANN	7.Epsueun	23 October 2006
	Name	Signature	Date
		PHOENIX TESTLAB GmbH Königswinkel 10 32825 Blomberg Tel. 0 52 35 / 95 00-0 Fax 0 52 35 / 95 00-10	
		Stamp	

1.5 RESERVATION

This test report is only valid in its original form.

Any reproduction of its contents without written permission of the accredited test laboratory PHOENIX TESTLAB GmbH is prohibited.

The test results herein refer only to the tested sample. PHOENIX TESTLAB GmbH is not responsible for any generalisations or conclusions drawn from these test results concerning further samples. Any modification of the tested samples is prohibited and leads to the invalidity of this test report. Each page necessarily contains the PHOENIX TESTLAB Logo and the TEST REPORT REFERENCE.

1.6 NORMATIVE REFERENCES

- [1] **ANSI C63.4-2003** American National Standard for Methods of Measuring of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.
- [2] FCC CFR 47 Part 15 (February 2006) Radio Frequency Devices
- [3] FCC Public Notice DA 00-705 (March 2000)

1.7 TEST RESULTS

The requirements of this test document are fulfilled by the equipment under test. The complete test results are presented in the following.



2 TECHNICAL DATA OF EQUIPMENT

2.1 DEVICE UNDER TEST

Type of equipment: *	Bluetooth module	
Type designation: *	cB-0902-0201	
FCC ID: *	PVH090202S	
Antenna type: *	Internal or external	
Antenna gain: *	Refer table below	
Antenna connector: *	With internal antenna, no antenna connector is mounted. Using an external antenna, a UFL connector is used.	
Power supply: *	3.0 V DC to 6.0 V DC	
Type of modulation: *	FHSS (GFSK)	
Operating frequency range:*	2.402 to 2.480 GHz	
Number of channels: *	79	
Temperature range: *	-30 °C to +85 °C	

*: declared by the applicant

Used antennas:

model name*	Antenna type	Rated Antenna gain*
INWAVE BTAB-2450	external	+2.0 dBi

*: declared by the applicant

The following external I/O cables were used:

Cable	Length	Shielding	Connector
DC in	2 m *	No	6.3 mm jack plug
-	-	-	-

*: Length during the test if no other specified.



2.2 PERIPHERY DEVICES

The following equipment was used as control unit and ancillary equipment:

- The Bluetooth module was connected to a carrier board (cB-0903-02), which was delivered by the applicant. The carrier board was supplied via an external power supply with 5.0 V DC.
- A personal computer with a terminal-software was used, connected temporary to the carrier board, for setting the equipment into the necessary operation mode. During the measurement procedures the personal computer was disconnected.

3 OPERATIONAL STATES AND PHYSICAL BOUNDARIES

The EUT is intended to be used in several bluetooth applications. Because the cB-0902-0201 is a module, which will be implemented in a final application, it was mounted on a carrier board to change the operation modes of the EUT from a Laptop with test software. The tests were carried out with a unmodified sample with the external antenna INWAVE BTAB-2450 connected to the antenna connector.

During the tests the test sample was powered by an external power supply via the carrier board with 5.0 V DC.

If not otherwise stated, for modulating the transmitter, a pseudo random bit sequence with a length of 27 byte and with a pattern type DH5 was used.

For selecting an operation mode, a personal computer with a software delivered by the applicant was connected to the carrier board. After adjusting the operating mode, the personal computer was removed. To do this the test-engineer was instructed by the applicant.

During the tests, the EUT was not labelled with a FCC-label.

The following operation modes were used during the tests:

Operation mode	Description of the operation mode
1	Continuous transmitting on 2402 MHz
2	Continuous transmitting on 2441 MHz
3	Continuous transmitting on 2480 MHz

Physical boundary of the EUT





4 ADDITIONAL INFORMATION

The cB-0902-0201 is already tested under PHOENIX-TESTLAB test report reference R51984_A. The reason for this report is the additional antenna INWAVE BTAB-2450, which should be listed in combination with the cB-0902-0201. With this antenna the radiated spurious emission measurement was carried out to show the compliance with the requirements. The measurements were carried out with the same test sample than the measurements, which were carried out under R51984_A.

Application	Frequency range [MHz]	FCC 47 CFR Part 15 section	Status	Refer page
20 dB bandwitdh	General	15.247 (a) (1)	Reported under R51984_A	9 et seq. (R51984_A)
Carrier frequency separation	General	15.247 (a) (1)	Reported under R51984_A	13 et seq. (R51984_A)
Number of hopping channels	2400.0 - 2483.5	15.247 (a) (1) (iii)	Reported under R51984_A	16 et seq. (R51984_A)
Dwell time	2400.0 - 2483.5	15.247 (a) (1) (iii)	Reported under R51984_A	18 et seq. (R51984_A)
Maximum peak output power	2400.0 - 2483.5	15.247 (b) (1)	Reported under R51984_A	21 et seq. (R51984_A)
Power spectral density	2441	15.247 (e)	Reported under R51984_A	25 et seq. (R51984_A)
Band edge compliance	2400.0 - 2483.5	15.247 (d)	Reported under R51984 A	28 et seq. (R51984_A)
Conducted emissions (transmitter)	0.009 - 25,000	15.247 (d)	Reported under R51984_A	32 et seq. (R51984_A)
Radiated emissions (transmitter)	0.009 - 25,000	15.205 (a) 15.209 (a)	Passed	8 et seq. (this report)
Conducted emissions on supply line	0.15 - 30	15.207 (a)	Reported under R51984_A	67 et seq. (R51984_A)

5 LIST OF MEASUREMENTS



6 TEST RESULTS

6.1 RADIATED EMISSIONS (TRANSMITTER)

6.1.1 METHOD OF MEASUREMENT (RADIATED EMISSIONS)

The radiated emission measurement is subdivided into four stages.

- A preliminary measurement carried out in a fully anechoic chamber with a fixed antenna height in the frequency range 9 kHz to 1 GHz.
- A final measurement carried out on an outdoor test side without reflecting ground plane and a fixed antenna height in the frequency range 9 kHz to 30 MHz.
- A final measurement carried out on an open area test side with reflecting ground plane and various antenna height in the frequency range 30 MHz to 1 GHz.
- A final measurement carried out in a fully anechoic chamber with a fixed antenna height in the frequency range 1 GHz to 25 GHz.

All measurements will be carried out with the EUT working on the middle and upper and lower edge of the assigned frequency band. For this reason the hopping function of the EUT has to be disenabled.

Preliminary measurement (9 kHz to 30 MHz):

In the first stage a preliminary measurement will be performed in a shielded room with a measuring distance of 3 meters. Tabletop devices will set up on a non-conducting support with a size of 1 m by 1.5 m and a height of 80 cm. Floor-standing devices will be placed directly on the turntable/ground plane. The set up of the Equipment under test will be in accordance to ANSI C63.4-2003 [1].

The frequency range 9 kHz to 30 MHz will be monitored with a spectrum analyser while the system and its cables will be manipulated to find out the configuration with the maximum emission levels if applicable. The EMI Receiver will be set to MAX Hold mode. The EUT and the measuring antenna will be rotated around their vertical axis to found the maximum emissions.

The resolution bandwidth of the spectrum analyser will be set to the following values:

Frequency range	Resolution bandwidth
9 kHz to 150 kHz	200 Hz
150 kHz to 30 MHz	10 kHz





Preliminary measurement procedure:

Prescans were performed in the frequency range 9 kHz to 150 kHz and 150 kHz to 30 MHz.

The following procedure will be used:

- 1) Monitor the frequency range at horizontal polarisation and a EUT azimuth of 0 °.
- 2) Manipulate the system cables within the range to produce the maximum level of emission.
- 3) Rotate the EUT by 360 ° to maximize the detected signals.
- 4) Make a hardcopy of the spectrum.
- 5) Measure the frequencies of highest detected emission with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
- 6) Repeat steps 1) to 4) with the other orthogonal axes of the EUT.
- 7) Rotate the measuring antenna and repeat steps 1) to 5).

Final measurement (9 kHz to 30 MHz):

In the second stage a final measurement will be performed on an open area test site with no conducting ground plane in a measuring distances of 3 m, 10 m and 30 m. In the case where larger measuring distances are required the results will be extrapolated based on the values measured on the closer distances according to Section 15.31 (f) (2) [2]. The final measurement will be performed with a EMI Receiver set to Quasi Peak detector except for the frequency bands 9 kHz to 90 kHz and 110 kHz to 490 kHz where an average detector will be used according Section 15.209 (d) [2].

On the during the preliminary measurement detected frequencies the final measurement will be performed while rotating the EUT and the measuring antenna in the range of 0 ° to 360 ° around their vertical axis until the maximum value is found.

The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth			
9 kHz to 150 kHz	200 Hz			
150 kHz to 30 MHz	9 kHz			





Final measurement procedure:

The following procedure will be used:

- 1) Monitor the frequency range with the measuring antenna at vertical orientation parallel to the EUT at an azimuth of 0 °.
- 2) Rotate the EUT by 360 ° to maximize the detected signals and note the azimuth and orientation.
- 3) Rotate the measuring antenna to find the maximum and note the value.
- 4) Rotate the measuring antenna and repeat steps 1) to 3) until the maximum value is found.
- 5) Repeat steps 1) to 4) with the other orthogonal axes of the EUT if applicable (handheld equipment).

Preliminary measurement (30 MHz to 1 GHz)

In the first stage a preliminary measurement will be performed in a fully anechoic chamber with a measuring distance of 3 meter. Tabletop devices will set up on a non-conducting support with a size of 1 m by 1.5 m and a height of 80 cm. Floor-standing devices will be placed directly on the turntable/ground plane. The set up of the Equipment under test will be in accordance to ANSI C63.4-2003 [1].

The frequency range 30 MHz to 1 GHz will be measured with an EMI Receiver set to MAX Hold mode and a resolution bandwidth of 100 kHz. The measurement will be performed in horizontal and vertical polarisation of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 ° to 360 °.

The resolution bandwidth of the EMI Receiver will be set to the following values:







Procedure preliminary measurement:

Prescans were performed in the frequency range 30 MHz to 230 MHz and 230 MHz to 1 GHz. The following procedure will be used:

- 1. Monitor the frequency range at horizontal polarisation and a EUT azimuth of 0°.
- 2. Manipulate the system cables within the range to produce the maximum level of emission.
- 3. Rotate the EUT by 360 ° to maximize the detected signals.
- Make a hardcopy of the spectrum.
 Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase
- 6. Repeat 1) to 4) with the other orthogonal axes of the EUT if handheld equipment.
- 7. Repeat 1) to 5) with the vertical polarisation of the measuring antenna.

Final measurement (30 MHz to 1 GHz)

A final measurement on an open area test site will be performed on selected frequencies found in the preliminary measurement. During this test the EUT will be rotated in the range of

0 ° to 360 °, the measuring antenna will be set to horizontal and vertical polarisation and raised and lowered in the range from 1 m to 4 m to find the maximum level of emissions.

The resolution bandwidth of the EMI Receiver will be set to the following values:





Procedure final measurement:

The following procedure will be used:

- 1) Measure on the selected frequencies at an antenna height of 1 m and a EUT azimuth of 23 °.
- 2) Move the antenna from 1 m to 4 m and note the maximum value at each frequency.
- 3) Rotate the EUT by 45 ° and repeat 2) until an azimuth of 337 ° is reached.
- 4) Repeat 1) to 3) for the other orthogonal antenna polarization.
- 5) Move the antenna and the turntable to the position where the maximum value is detected.
- 6) Measure while moving the antenna slowly +/- 1 m.
- 7) Set the antenna to the position where the maximum value is found.
- 8) Measure while moving the turntable +/- 45° .
- 9) Set the turntable to the azimuth where the maximum value is found.
- 10) Measure with Final detector (QP and AV) and note the value.
- 11) Repeat 5) to 10) for each frequency.
- 12) Repeat 1) to 11) for each orthogonal axes of the EUT if handheld equipment.

Final measurement (1 GHz to 25 GHz)

This measurement will be performed in a fully anechoic chamber with a measuring distance of 3 meter. Tabletop devices will set up on a non-conducting support with a size of 1 m by 1.5 m and a height of 80 cm. Floor-standing devices will be placed directly on the turntable/ground plane. The set up of the Equipment under test will be in accordance to ANSI C63.4-2003 [1].

Preliminary measurement (1 GHz to 25 GHz)

The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to MAX Hold mode and a resolution bandwidth of 100 kHz. The measurement will be performed in horizontal and vertical polarisation of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 ° to 360 °. If the EUT is larger than the antenna beam width, the antenna will be moved to various positions, to cover the whole surface of the EUT. It might be possible to shorter the measuring distance to higher the measurement sensitivity.

The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth
1 GHz to 4 GHz	100 kHz
4 GHz to 12 GHz	100 kHz
12 GHz to 18 GHz	100 kHz
18 GHz to 25 GHz	100 kHz

Final measurement (1 GHz to 25 GHz)

The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to MAX Hold mode and a resolution bandwidth of 1 MHz. The measurement will be performed in horizontal and vertical polarisation of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 ° to 360 °. If the EUT is larger than the antenna beam width, the antenna will be moved to various positions, to cover the whole surface of the EUT. It might be possible to shorter the measuring distance to higher the measurement sensitivity.



The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth
1 GHz to 4 GHz	1 MHz
4 GHz to 12 GHz	1 MHz
12 GHz to 18 GHz	1 MHz
18 GHz to 25 GHz	1 MHz



Procedure of measurement:

The measurements were performed in the frequency range 1 GHz to 4 GHz, 4 GHz to 12 GHz, 12 GHz to 18 GHz and 18 GHz to 25 GHz.

The following procedure will be used:

- 1) Monitor the frequency range at horizontal polarisation and a EUT azimuth of 0 °.
- Rotate the EUT by 360 ° to maximize the detected signals.
- 3) Change the antenna polarisation.
- 4) Rotate the EUT by 360 ° to maximize the detected signals.
- 5) Make a hardcopy of the spectrum.
- 6) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
- 7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarisation and azimuth and the peak and average detector, which causes the maximum emission.
- 8) Repeat steps 1) to 7) with the other orthogonal axes of the EUT if handheld equipment.
- 9) Repeat steps 1) to 8) for the next antenna spot if the EUT is lager than the antenna beamwidth.

Step 1) to 6) are defined as preliminary measurement.



6.1.2 TEST RESULTS (RADIATED EMISSIONS)

6.1.2.1 PRELIMINARY MEASUREMENT WITH ADDITIONAL ANTENNA (9 kHz to 25 GHz)

Ambient temperature		22 °C	Relative humidity	60 %
Position of EUT:	The EUT w between El	as set-up on a non-co JT and antenna was 3	onducting table of a height of 3 m.	0.8 m. The distance
Cable guide:	The cable of the cable g	of the EUT was fixed out of the EUT was fixed out of the picture o	on the non-conducting table. res in annex A of this test rep	For further information of port.
Test record:	Where not there was r	otherwise stated the t to difference to the ot	test was carried out in test m her test modes. All results ar	ode 2 of the EUT, because e shown in the following.
Supply voltage:	During all n	neasurements the EU	IT was supplied with 5.0 V D	C via the carrier board.
Remark:	The emissi system and	ons found around 32 I not from the EUT.	kHz, 63 kHz and 95 kHz cau	sed by the measuring

61924_12.wmf: Spurious emissions from 9 kHz to 150 kHz:



TEST EQUIPMENT USED FOR THE TEST:

29, 31 – 37, 39, 43, 46, 49 – 51, 54



61924_13.wmf: Spurious emissions from 150 kHz to 1 MHz:



61924_14.wmf: Spurious emissions from 1 MHz to 30 MHz:



No significant frequencies above the noise floor of the system were found during the preliminary radiated emission test, so no measurements were carried out on the outdoor test site.



61924_1.wmf: Spurious emissions from 30 MHz to 230 MHz:



61924_2.wmf: Spurious emissions from 230 MHz to 1 GHz:



No significant frequencies above the noise floor of the system were found during the preliminary radiated emission test, so no measurements were carried out on the open area test site.



Transmitter operates at the lower end of the assigned frequency band (operation mode 1)

61924_19.wmf: Spurious emissions from 1 GHz to 4 GHz:



61924_23.wmf: Spurious emissions from 4 GHz to 12 GHz:





61924_24.wmf: Spurious emissions from 12 GHz to 18 GHz:



61924_25.wmf: Spurious emissions from 18 GHz to 25 GHz:



The following frequencies were found inside the restricted bands during the preliminary radiated emission test: - 12.010 GHz.

The following frequencies were found outside the restricted bands during the preliminary radiated emission test:

- 2.402 GHz, 7.206 GHz, 9.608 GHz and 14.412 GHz.

These frequencies have to be measured in a final measurement. The results were presented in the following.



Transmitter operates at the middle of the assigned frequency band (operation mode 2)

61924_18.wmf: Spurious emissions from 1 GHz to 4 GHz:



61924_22.wmf: Spurious emissions from 4 GHz to 12 GHz:





61924_27.wmf: Spurious emissions from 12 GHz to 18 GHz:



61924_26.wmf: Spurious emissions from 18 GHz to 25 GHz:



The following frequencies were found inside the restricted bands during the preliminary radiated emission test:

- 4.882 GHz, 7.323 GHz and 12.205 GHz.

The following frequencies were found outside the restricted bands during the preliminary radiated emission test:

- 2.441 GHz and 14.646 GHz.

These frequencies have to be measured in a final measurement. The results were presented in the following.



Transmitter operates at the upper end of the assigned frequency band (operation mode 3)

61924_20.wmf: Spurious emissions from 1 GHz to 4 GHz:



61924_21.wmf: Spurious emissions from 4 GHz to 12 GHz:





61924_28.wmf: Spurious emissions from 12 GHz to 18 GHz:



61924_29.wmf: Spurious emissions from 18 GHz to 25 GHz:



The following frequencies were found inside the restricted bands during the preliminary radiated emission test: 4.960 GHz, 7.440 GHz and 12.400.

The following frequencies were found outside the restricted bands during the preliminary radiated emission test: 2.480 GHz and 14.880 GHz.

These frequencies have to be measured in a final measurement. The results were presented in the following.



6.1.2.2 FINAL MEASUREMENT WITH ADDITIONAL ANTENNA (1 GHz to 25 GHz)

Ambient temperature		22 °C		Relative humidity	60 %
Position of EUT:	The EUT w between El	as set-up on a nor JT and antenna wa	n-cond as 3 m	lucting table of a height of 0.8 n.	3 m. The distance
Cable guide:	The cable of the cable g	of the EUT was fixe uide refer to the pi	ed on ctures	the non-conducting table. For in annex A of this test report	r further information of t.
Supply voltage:	During all n	neasurements the	EUT ۱	was supplied with 5.0 V DC v	ia the carrier board.
Resolution bandwidth:	For all mea	surements a resol	ution I	pandwidth of 1 MHz was used	d.

Transmitter operates at the lower end of the assigned frequency band (operation mode 1)

Result measured with the peak detector:

Frequency	Corr. value	Limit	Margin	Readings	Antenna factor	Preamp	Cable loss	Height	Pol.	Restr. Band
GHz	dBµV/m	dBµV/m	dB	dBµV	1/m	dB	dB	cm		
2.402	99.3	-	-	68.0	28.5	0.0	2.8	150	Vert.	-
7.206	57.7	79.3	21.6	41.1	36.3	24.6	4.9	150	Vert.	No
9.608	51.5	79.3	27.8	31.8	37.9	23.9	5.7	150	Vert.	No
12.010	46.1	74.0	27.9	37.4	33.6	25.9	1.0	100	Vert.	Yes
14.412	45.1	79.3	34.2	36.6	33.6	26.3	1.2	100	Hor.	No

Result measured with the average detector:

Frequency	Corr. value	Limit	Margin	Readings	Antenna factor	Preamp	Cable loss	Height	Pol.	Restr. Band
GHz	dBµV/m	dBµV/m	dB	dBµV	1/m	dB	dB	cm		
2.402	91.9	-	-	60.6	28.5	0.0	2.8	150	Vert.	-
7.206	49.5	71.9	22.4	32.6	36.3	24.6	4.9	150	Vert.	No
9.608	39.1	71.9	32.8	19.4	37.9	23.9	5.7	150	Vert.	No
12.010	33.0	54.0	21.0	24.3	33.6	25.9	1.0	100	Vert.	Yes
14.412	31.6	71.9	40.3	23.1	33.6	26.3	1.2	100	Hor.	No



Transmitter operates at the middle of the assigned frequency band (operation mode 2)

Result measured with the peak detector:

Frequency	Corr. value	Limit	Margin	Readings	Antenna factor	Preamp	Cable loss	Height	Pol.	Restr. Band
GHz	dBµV/m	dBµV/m	dB	dBµV	1/m	dB	dB	cm		
2.441	98.1	-	-	66.6	28.7	0.0	2.8	150	Vert.	-
4.882	46.4	74.0	27.6	34.9	33.4	25.7	3.8	150	Vert.	Yes
7.323	52.7	74.0	21.3	36.1	36.3	24.6	4.9	150	Vert.	Yes
12.205	47.6	74.0	26.4	38.8	33.6	25.8	1.0	100	Hor.	Yes
14.646	47.8	78.1	30.3	39.6	33.6	26.6	1.2	100	Hor.	No

Result measured with the average detector:

Frequency	Corr.	Limit	Margin	Readings	Antenna	Preamp	Cable	Height	Pol.	Restr.
	value				factor		loss			Band
GHz	dBµV/m	dBµV/m	dB	dBµV	1/m	dB	dB	cm		
2.441	90.6	-	-	59.1	28.7	0.0	2.8	150	Vert.	-
4.882	38.1	54.0	15.9	25.6	33.4	25.7	3.8	150	Vert.	Yes
7.323	42.8	54.0	11.2	26.2	36.3	24.6	4.9	150	Vert.	Yes
12.205	33.9	54.0	20.1	25.1	33.6	25.8	1.0	100	Hor.	Yes
14.646	35.8	70.6	34.8	27.6	33.6	26.6	1.2	100	Hor.	No



Transmitter operates at the upper end of the assigned frequency band (operation mode 3)

Result measured with the peak detector:

Frequency	Corr. value	Limit	Margin	Readings	Antenna factor	Preamp	Cable loss	Height	Pol.	Restr. Band
GHz	dBµV/m	dBµV/m	dB	dBµV	1/m	dB	dB	cm		
2.480	97.0	-	-	65.5	28.7	0.0	2.8	150	Vert.	-
4.960	47.1	74.0	26.9	35.4	33.5	25.6	3.8	150	Vert.	Yes
7.440	54.0	74.0	20.0	37.2	36.3	24.5	5.0	150	Vert.	Yes
12.400	44.3	74.0	29.7	35.4	33.7	25.8	1.0	100	Hor.	Yes
14.880	47.6	77.0	29.4	39.6	33.7	26.9	1.2	100	Vert.	No

Result measured with the average detector:

Frequency	Corr. value	Limit	Margin	Readings	Antenna factor	Preamp	Cable loss	Height	Pol.	Restr. Band
GHz	dBµV/m	dBµV/m	dB	dBµV	1/m	dB	dB	cm		
2.480	89.3	-	-	57.8	28.7	0.0	2.8	150	Vert.	-
4.960	36.4	54.0	17.6	24.7	33.5	25.6	3.8	150	Vert.	Yes
7.440	44.8	54.0	9.2	28.0	36.3	24.5	5.0	150	Vert.	Yes
12.400	31.1	54.0	22.9	22.2	33.7	25.8	1.0	100	Hor.	Yes
14.880	35.4	69.3	33.9	27.4	33.7	26.9	1.2	100	Vert.	No

Test: Passed

TEST EQUIPMENT USED FOR THE TEST:

29, 31 – 37, 39, 43, 46, 49 – 51, 54



7 TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS



Emiss	Emission measurement at AC mains and DC in / out ports at M4												
No.	Test equipment	Туре	Manufacturer	Serial No.	PM-No								
1	Shielded chamber M4	-	Siemens	B83117S1-X158	480088								
2	Measuring receiver	ESAI	Rohde & Schwarz	831953/001 833181/018	480025 480026								
3	LISN	NSLK8128	Schwarzbeck	8128155	480058								
4	DC-filter	B84266-A21- E13	Siemens	940164525	480099								
5	AC-filter	B84299-D87- E3	Siemens	930262292	480097								
6	EMI-Software	ES-K1	Rohde & Schwarz	-	480111								

Radiated emission measurement at M5					
No.	Test equipment	Туре	Manufacturer	Serial No.	PM-No
7	Fully anechoic chamber M5	-	Siemens	B83177-S1-X156	480073
8	Measuring receiver	ESVS30	Rohde & Schwarz	829673/012	480024
9	Controller	HD100	Deisel	100/324	480067
10	Antenna support	MA240	Deisel	228/314	480069
11	Turntable	DS412	Deisel	412/317	480070
12	Antenna	CBL6112C	Chase	2689	480327
13	EMI Software	ES-K1	Rohde & Schwarz	-	480111

Radiated emission measurement at M6					
No.	Test equipment	Туре	Manufacturer	Serial No.	PM-No
14	Open area test site	-	Phoenix Test-Lab	-	480085
15	Measuring receiver	ESVS30	Rohde & Schwarz	829673/012	480024
16	Controller	HD100	Deisel	100/670	480139
17	Turntable	DS420HE	Deisel	420/620/80	480087
18	Antenna support	AS615P	Deisel	615/310	480086
19	Antenna	CBL6111 A	Chase	1643	480147
20	EMI Software	ES-K1	Rohde & Schwarz	-	480111



Radiated emission measurement at M8						
No.	Test equipment	Туре	Manufacturer	Serial No.	PM-No	
21	Fully anechoic chamber M8	-	Siemens	B83117-E7019- T231	480190	
22	Measuring receiver	ESMI	Rohde & Schwarz	843977/001 843530/018	480179 480180	
23	Measuring receiver	ESCS 30	Rohde & Schwarz	828985/014	480270	
24	Controller	HD100	Deisel	100/427	480181	
25	Turntable	DS420	Deisel	420/435/97	480186	
26	Antenna support	AS615P	Deisel	615/310	480187	
27	Antenna	CBL6112 A	Chase	2034	480185	
28	EMI Software	ES-K1	Rohde & Schwarz	-	480111	

Radiated emission measurement at M20					
No.	Test equipment	Туре	Manufacturer	Serial No.	PM-No
29	Fully anechoic chamber M20	-	Albatross Projects	B83107-E2439- T232	480303
30	Measuring receiver	ESMI	Rohde & Schwarz	843977/001 843530/018	480179 480180
31	Measuring receiver	ESI 40	Rohde & Schwarz	100064	480355
32	Controller	HD100	Deisel	100/670	480326
33	Turntable	DS420HE	Deisel	420/620/80	480315
34	Antenna support	AS615P	Deisel	615/310	480187
35	Antenna	CBL6112 B	Chase	2688	480328
36	Antenna	3115 A	EMCO	9609-4918	480183
37	Standard Gain Horn 11.9GHz – 18GHZ	18240-20	Flann Microwave	483	480294
38	Standard Gain Horn 11.9GHz – 18GHZ	18240-20	Flann Microwave	482	480295
39	Standard Gain Horn 17.9GHz – 26.7GHZ	20240-20	Flann Microwave	411	480297
40	Standard Gain Horn 17.9GHz – 26.7GHZ	20240-20	Flann Microwave	410	480296
41	Standard Gain Horn 26.4GHz – 40.1GHZ	22240-20	Flann Microwave	469	480299



		1			
No.	Test equipment	Туре	Manufacturer	Serial No.	PM-No
42	Standard Gain Horn 26.4GHz – 40.1GHZ	22240-20	Flann Microwave	468	480298
43	RF-cable No. 30	RTK 081	Rosenberger	-	410141
44	RF-cable No. 31	RTK 081	Rosenberger	-	410142
45	RF-cable 1m	KPS-1533- 400-KPS	Insulated Wire	-	480300
46	RF-cable 1m	KPS-1533- 400-KPS	Insulated Wire	-	480301
47	RF-cable 2m	KPS-1533- 400-KPS	Insulated Wire	-	480302
48	RF-cable No. 5	RTK 081	Rosenberger		410097
49	Preamplifier	JS3- 00101200- 23-5A	Miteq	681851	480337
50	Preamplifier	JS3- 12001800- 16-5A	Miteq	571667	480343
51	Preamplifier	JS3- 18002600- 20-5A	Miteq	658697	480342
52	Preamplifier	JS3- 26004000- 25-5A	Miteq	563593	480344
53	EMI Software	ES-K1	Rohde & Schwarz	-	480111

Ancillary equipment used for testing					
No.	Test equipment	Туре	Manufacturer	Serial No.	PM-No
54	Power supply	TOE 8852	Toellner	51712	480233
I	-	-	-	-	-
-	-	-	-	-	-
-	-	_	_	-	-

All used measurement equipment was calibrated (if necessary). The calibration intervals and the calibration history will be given out on request.



8 LIST OF ANNEXES

Annex APhotographs of the test set-ups:4 pages

cB-0902-0201 with additional antenna, test set-up fully anechoic chamber 61924_5.jpg cB-0902-0201 with additional antenna, test set-up fully anechoic chamber 61924_1.jpg cB-0902-0201 with additional antenna, test set-up fully anechoic chamber 61924_3.jpg cB-0902-0201 with additional antenna, test set-up fully anechoic chamber 61924_6.jpg

ANNEX B	INTERNAL PHOTOGRAPHS OF THE TEST SAMPLE:	7 pages	
	cB-0902-0201 on carrier board	61924_d.jpg	
	cB-0902-0201 Sample "12", top view	61924_a.jpg	
	cB-0902-0201 bottom view	61924_g.jpg	
	cB-0901-02 carrier board, top view	61924_c.jpg	
	cB-0902-0201 carrier board, bottom view	61924_b.jpg	
	INWAVE BTAB-2450, 3-D.view	61924_f.jpg	
	INWAVE BTAB-2450, bottom view	61924_h.jpg	

ANNEX C EXTERNAL PHOTOGRAPHS OF THE TEST SAMPLE:

- pages

Because the EUT is a module, which is intended to be implemented inside a final application, no external photographs were available