



RF TEST REPORT

Report No.: Q200102S012-FCC-R4

Supersede Report No.: N/A

| | |
|--|--|
| Applicant | ZTE Corporation |
| Product Name | 3G Smart Feature Phone |
| Model No. | Z2317 |
| Serial No. | N/A |
| Test Standard | FCC Part 15.247, ANSI C63.10: 2013 |
| Test Date | Sep 02 to 09, 2019 |
| Issue Date | Jan. 21, 2020 |
| Test Result | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail |
| Equipment complied with the specification | <input checked="" type="checkbox"/> |
| Equipment did not comply with the specification | <input type="checkbox"/> |
|  |  |
| Aaron Liang Test Engineer | David Huang Checked By |
| This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only | |

Issued by:

BUREAU VERITAS (SHENZHEN) CONSUMER PRODUCTS SERVICES CO., LTD

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn



| | |
|-----------------|--------------------|
| Test Report No. | Q200102S012-FCC-R4 |
| Page | 2 of 39 |

This page has been left blank intentionally.

CONTENTS

| | |
|---|-----------|
| 1. REPORT REVISION HISTORY | 4 |
| 2. CUSTOMER INFORMATION | 4 |
| 3. TEST SITE INFORMATION | 4 |
| 4. EQUIPMENT UNDER TEST (EUT) INFORMATION | 5 |
| 5. TEST SUMMARY | 7 |
| 6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS | 8 |
| 6.1 ANTENNA REQUIREMENT | 8 |
| 6.2 DTS (6 DB) CHANNEL BANDWIDTH | 9 |
| 6.3 MAXIMUM OUTPUT POWER | 12 |
| 6.4 POWER SPECTRAL DENSITY | 15 |
| 6.5 BAND-EDGE & UNWANTED EMISSIONS INTO RESTRICTED FREQUENCY BANDS..... | 17 |
| 6.6 AC POWER LINE CONDUCTED EMISSIONS | 20 |
| 6.7 RADIATED EMISSIONS & RESTRICTED BAND | 24 |
| ANNEX A. TEST INSTRUMENT | 32 |
| ANNEX B. TEST SETUP AND SUPPORTING EQUIPMENT | 35 |
| ANNEX C. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST/ DECLARATION OF SIMILARITY..... | 39 |

1. Report Revision History


| Report No. | Report Version | Description | Issue Date |
|--------------------|----------------|-------------|---------------|
| Q200102S012-FCC-R4 | NONE | Original | Jan. 21, 2020 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

2. Customer information

| | |
|------------------|---|
| Applicant Name | ZTE Corporation |
| Applicant Add | ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R. China |
| Manufacturer | ZTE Corporation |
| Manufacturer Add | ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R. China |

3. Test site information

| | |
|----------------------|---|
| Lab performing tests | BUREAU VERITAS (SHENZHEN) CONSUMER PRODUCTS SERVICES CO., LTD |
| Lab Address | Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108 |
| FCC Test Site No. | 535293 |
| IC Test Site No. | 4842E-1 |
| Test Software | Radiated Emission Program-To Shenzhen v2.0 |



| | |
|-------------------------------|---|
| Description of EUT: | 3G Smart Feature Phone |
| Main Model: | Z2317 |
| Serial Model: | N/A |
| Date EUT received: | Aug 28, 2019 |
| Test Date(s): | Sep 02 to 09, 2019 |
| Equipment Category : | DTS |
| Antenna Gain: | GSM850: -1dBi PCS1900: -1.5dBi UMTS-FDD Band V: -1dBi UMTS-FDD Band II: -1.5dBi WIFI: 0dBi Bluetooth/BLE: 0dBi |
| Antenna Type: | PIFA antenna |
| Type of Modulation: | GSM / GPRS: GMSK EGPRS: GMSK UMTS-FDD: QPSK 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK GPS:BPSK |
| RF Operating Frequency (ies): | GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz; RX: 1932.4 ~ 1987.6 MHz WIFI: 802.11b/g/n(20M): 2412-2462 MHz WIFI: 802.11n(40M): 2422-2452 MHz Bluetooth& BLE: 2402-2480 MHz |



| | |
|-----------------|--------------------|
| Test Report No. | Q200102S012-FCC-R4 |
| Page | 6 of 39 |

GPS: 1575.42 MHz

Max. Output Power: -0.29dBm

Number of Channels: GSM 850: 124CH
PCS1900: 299CH
UMTS-FDD Band V: 102CH
UMTS-FDD Band II: 277CH
WIFI :802.11b/g/n(20M): 11CH
WIFI :802.11n(40M): 7CH
Bluetooth: 79CH
BLE: 40CH
GPS:1CH

Port: Please refer to the user's manual

Trade Name : ZTE

Adapter 1:
Model: TPA-97050050U01
Input: AC100-240V~50/60Hz,0.15A
Output: DC 5.0V, 500mA

Input Power: Adapter 2:
Model: 50.069MX03
Input: AC100-240V~50/60Hz,0.2A
Output: DC 5.0V, 500mA

Battery :
Model: 5C1001
Spec: 3.7V, 1000mAh/3.7Wh
Limited charge voltage: 4.2

FCC ID: SRQ-ZTEZ2317

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

| FCC Rules | Description of Test | Result |
|---------------------------------|---|------------|
| §15.203 | Antenna Requirement | Compliance |
| §15.247 (a)(2) | DTS (6 dB) CHANNEL BANDWIDTH | Compliance |
| §15.247(b)(3) | Conducted Maximum Output Power | Compliance |
| §15.247(e) | Power Spectral Density | Compliance |
| §15.247(d) | Band-Edge & Unwanted Emissions into Restricted Frequency Bands | Compliance |
| §15.207 (a), | AC Power Line Conducted Emissions | Compliance |
| §15.205, §15.209, §15.247(d) | Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands | Compliance |

Measurement Uncertainty

| Emissions | | |
|--|---|---------------|
| Test Item | Description | Uncertainty |
| Band-Edge & Unwanted Emissions into Restricted Frequency Bands and Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands | Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m) | +5.6dB/-4.5dB |
| - | - | - |

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 2 antennas:

A permanently attached PIFA antenna for Bluetooth/BLE/WIFI/GPS, the gain is 0dBi for Bluetooth/BLE, the gain is 0dBi for WIFI.


A permanently attached PIFA antenna for GSM/PCS/UMTS, the gain is -1dBi for GSM850, -1.5dBi for PCS1900, -1dBi for UMTS-FDD Band V, -1.5dBi for UMTS-FDD Band II.

The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 DTS (6 dB) Channel Bandwidth

| | |
|----------------------|---------------|
| Temperature | 25°C |
| Relative Humidity | 57% |
| Atmospheric Pressure | 1024mbar |
| Test date : | Sep 05 , 2019 |
| Tested By : | Aaron Liang |

| Spec | Item | Requirement | Applicable |
|----------------|---|---|-------------------------------------|
| § 15.247(a)(2) | a) | 6dB BW ≥ 500kHz; | <input checked="" type="checkbox"/> |
| RSS Gen(4.6.1) | b) | 99% BW: For FCC reference only; required by IC. | <input checked="" type="checkbox"/> |
| Test Setup |  Spectrum Analyzer EUT | | |
| Test Procedure | 558074 D01 DTS MEAS Guidance v05r02, 8.1 DTS bandwidth <u>6dB Emission bandwidth measurement procedure</u> <ul style="list-style-type: none"> - Set RBW = 100 kHz. - Set the video bandwidth (VBW) ≥ 3 RBW. - Detector = Peak. - Trace mode = max hold. - Sweep = auto couple. - Allow the trace to stabilize. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. | | |
| Remark | | | |
| Result | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail | | |

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

6dB Bandwidth measurement result


Test Data

| CH | Frequency (MHz) | 6dB Bandwidth (kHz) | 99% Occupied Bandwidth (MHz) |
|------|-----------------|---------------------|------------------------------|
| Low | 2402 | 0.704 | 1.0224 |
| Mid | 2440 | 0.696 | 1.0216 |
| High | 2480 | 0.696 | 1.0185 |


Test Plots




6dB Bandwidth - Low CH 2402




6dB Bandwidth - Mid CH 2440




6dB Bandwidth - High CH 2480



99% Occupied Bandwidth - Low CH 2402



99% Occupied Bandwidth - Mid CH 2440




99% Occupied Bandwidth - High CH 2480

6.3 Maximum Output Power

| | |
|----------------------|---------------|
| Temperature | 25°C |
| Relative Humidity | 57% |
| Atmospheric Pressure | 1024mbar |
| Test date : | Sep 07 , 2019 |
| Tested By : | Aaron Liang |

Requirement(s):

| Spec | Item | Requirement | Applicable |
|------------------------------------|---|--|-------------------------------------|
| §15.247(b) (3),RSS210 (A8.4) | a) | FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt | <input type="checkbox"/> |
| | b) | FHSS in 5725-5850MHz: ≤ 1 Watt | <input type="checkbox"/> |
| | c) | For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt. | <input type="checkbox"/> |
| | d) | FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt | <input type="checkbox"/> |
| | e) | FHSS in 902-928MHz with ≥ 25 & <50 channels: ≤ 0.25 Watt | <input type="checkbox"/> |
| | f) | DTS in 902-928MHz, 2400-2483.5MHz: ≤ 1 Watt | <input checked="" type="checkbox"/> |
| Test Setup |  <p style="text-align: center;">Spectrum Analyzer EUT</p> | | |
| Test Procedure | <p>558074 D01 DTS MEAS Guidance v05r02, 9.1.2 Integrated band power method Maximum output power measurement procedure</p> <p>a) Set the RBW \geq DTS bandwidth. b) Set VBW $\geq 3 \times$ RBW. c) Set span $\geq 3 \times$ RBW d) Sweep time = auto couple. e) Detector = peak. f) Trace mode = max hold. g) Allow trace to fully stabilize. h) Use peak marker function to determine the peak amplitude level.</p> | | |
| Remark | | | |
| Result | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail | | |



| | |
|-----------------|--------------------|
| Test Report No. | Q200102S012-FCC-R4 |
| Page | 13 of 39 |

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Output Power measurement result


Test Data

| Type | CH | Frequency (MHz) | Conducted Power (dBm) | Limit (dBm) | Result |
|--------------|------|-----------------|-----------------------|-------------|--------|
| Output power | Low | 2402 | -0.30 | 30 | Pass |
| | Mid | 2440 | 0.14 | 30 | Pass |
| | High | 2480 | 0.11 | 30 | Pass |


Test Plots



PK Output power - Low CH 2402



PK Output power - Mid CH 2440



PK Output power - High CH 2480



| | |
|-----------------|--------------------|
| Test Report No. | Q200102S012-FCC-R4 |
| Page | 14 of 39 |


Average OUTPUT POWER(FOR REFERENCE)

Test Data

| CH | Frequency (MHz) | Average Power (dBm) |
|------|--------------------|------------------------|
| Low | 2402 | -0.63 |
| Mid | 2441 | -0.29 |
| High | 2480 | -0.63 |

6.4 Power Spectral Density

| | |
|----------------------|-------------------|
| Temperature | 25°C |
| Relative Humidity | 57% |
| Atmospheric Pressure | 1024mbar |
| Test date : | November 24, 2018 |
| Tested By : | Aaron Liang |

| Spec | Item | Requirement | Applicable |
|----------------|---|--|-------------------------------------|
| §15.247(e) | a) | The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. | <input checked="" type="checkbox"/> |
| Test Setup |  <p style="text-align: center;">Spectrum Analyzer EUT</p> | | |
| Test Procedure | <p>558074 D01 DTS MEAS Guidance v05r02, 10.2 power spectral density method power spectral density measurement procedure</p> <ul style="list-style-type: none"> - a) Set analyzer center frequency to DTS channel center frequency. - b) Set the span to 1.5 times the DTS bandwidth. - c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. - d) Set the VBW $\geq 3 \times \text{RBW}$. - e) Detector = peak. - f) Sweep time = auto couple. - g) Trace mode = max hold. - h) Allow trace to fully stabilize. - i) Use the peak marker function to determine the maximum amplitude level within the RBW. - j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat. | | |
| Remark | | | |
| Result | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail | | |

Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A




| | |
|-----------------|--------------------|
| Test Report No. | Q200102S012-FCC-R4 |
| Page | 16 of 39 |

Power Spectral Density measurement result


Test Data

| Type | CH | Freq (MHz) | PSD (dBm) | Limit (dBm) | Result |
|------|------|------------|-----------|-------------|--------|
| PSD | Low | 2402 | -16.01 | 8 | Pass |
| | Mid | 2440 | -15.53 | 8 | Pass |
| | High | 2480 | -15.49 | 8 | Pass |


Test Plots



PSD - Low CH 2402



PSD - Mid CH 2440




PSD - High CH 2480

6.5 Band-Edge & Unwanted Emissions into Restricted Frequency Bands

| | |
|----------------------|---------------|
| Temperature | 26°C |
| Relative Humidity | 55% |
| Atmospheric Pressure | 1010mbar |
| Test date : | Sep 05 , 2019 |
| Tested By : | Aaron Liang |

Requirement(s):


| Spec | Item | Requirement | Applicable |
|----------------|---|---|-------------------------------------|
| §15.247(d) | a) | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. | <input checked="" type="checkbox"/> |
| Test Setup |  | | |
| Test Procedure | <p>Radiated Method Only</p> <ul style="list-style-type: none"> 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range. | | |

| | |
|--------|---|
| | <ul style="list-style-type: none"> - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: <ul style="list-style-type: none"> a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete. |
| Remark | |
| Result | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail |

Test Data ☐ Yes ☒ N/A
 Test Plot ☒ Yes (See below) ☐ N/A


Test Plots

Band Edge measurement result




Band Edge, Left Side (Peak)

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz




Band Edge, Right Side (Peak)

Note: F1 is frequency 2483.5MHz



Band Edge, Left Side-AV



Band Edge, Right Side-AV


Note: Both Horizontal and vertical polarities were investigated.

6.6 AC Power Line Conducted Emissions

| | |
|----------------------|---------------|
| Temperature | 26°C |
| Relative Humidity | 55% |
| Atmospheric Pressure | 1010mbar |
| Test date : | Sep 05 , 2019 |
| Tested By : | Aaron Liang |

Requirement(s):

| Spec | Item | Requirement | Applicable | | | | | | | | | | | | | | |
|-----------------------------|------|--|--|------------------------|--------------|--|----|---------|------------|---------|---------|---------|----|----|--------|----|----|
| 47CFR§15.207, RSS210 (A8.1) | a) | For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges. | <div><input checked="" type="checkbox"/></div> | | | | | | | | | | | | | | |
| | | <table><tr><th rowspan="2">Frequency ranges (MHz)</th><th colspan="2">Limit (dBµV)</th></tr><tr><th>QP</th><th>Average</th></tr><tr><td>0.15 ~ 0.5</td><td>66 – 56</td><td>56 – 46</td></tr><tr><td>0.5 ~ 5</td><td>56</td><td>46</td></tr><tr><td>5 ~ 30</td><td>60</td><td>50</td></tr></table> | | Frequency ranges (MHz) | Limit (dBµV) | | QP | Average | 0.15 ~ 0.5 | 66 – 56 | 56 – 46 | 0.5 ~ 5 | 56 | 46 | 5 ~ 30 | 60 | 50 |
| | | Frequency ranges (MHz) | | | Limit (dBµV) | | | | | | | | | | | | |
| | | | | QP | Average | | | | | | | | | | | | |
| | | 0.15 ~ 0.5 | | 66 – 56 | 56 – 46 | | | | | | | | | | | | |
| 0.5 ~ 5 | 56 | 46 | | | | | | | | | | | | | | | |
| 5 ~ 30 | 60 | 50 | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |

| | |
|------------|---|
| Test Setup |  <p>Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p> |
|------------|---|

| | |
|-----------|---|
| Procedure | <ol style="list-style-type: none"> The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss |
|-----------|---|




| | |
|-----------------|--------------------|
| Test Report No. | Q200102S012-FCC-R4 |
| Page | 21 of 39 |

| | |
|--------|--|
| | <p>coaxial cable.</p> <ol style="list-style-type: none">4. All other supporting equipment were powered separately from another main supply.5. The EUT was switched on and allowed to warm up to its normal operating condition.6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz.8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power). |
| Remark | |
| Result | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail |

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Transmitting Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

| No. | P/L | Frequency (MHz) | Reading (dBμV) | Detector | Corrected (dB) | Result (dBμV) | Limit (dBμV) | Margin (dB) |
|-----|-----|-----------------|----------------|----------|----------------|---------------|--------------|-------------|
| 1 | L1 | 0.1578 | 37.41 | QP | 10.12 | 47.53 | 65.58 | -18.05 |
| 2 | L1 | 0.1578 | 23.56 | AVG | 10.12 | 33.68 | 55.58 | -21.90 |
| 3 | L1 | 0.4074 | 41.41 | QP | 10.10 | 51.51 | 57.70 | -6.19 |
| 4 | L1 | 0.4074 | 30.11 | AVG | 10.10 | 40.21 | 47.70 | -7.49 |
| 5 | L1 | 0.5751 | 34.71 | QP | 10.10 | 44.81 | 56.00 | -11.19 |
| 6 | L1 | 0.5751 | 24.65 | AVG | 10.10 | 34.75 | 46.00 | -11.25 |
| 7 | L1 | 0.9768 | 36.03 | QP | 10.13 | 46.16 | 56.00 | -9.84 |
| 8 | L1 | 0.9768 | 22.94 | AVG | 10.13 | 33.07 | 46.00 | -12.93 |
| 9 | L1 | 2.5017 | 35.56 | QP | 10.16 | 45.72 | 56.00 | -10.28 |
| 10 | L1 | 2.5017 | 19.49 | AVG | 10.16 | 29.65 | 46.00 | -16.35 |
| 11 | L1 | 4.1388 | 34.17 | QP | 10.18 | 44.35 | 56.00 | -11.65 |
| 12 | L1 | 4.1388 | 16.04 | AVG | 10.18 | 26.22 | 46.00 | -19.78 |

Test Mode: Transmitting Mode



Test Data

Phase Neutral Plot at 120Vac, 60Hz

| No. | P/L | Frequency (MHz) | Reading (dBμV) | Detector | Corrected (dB) | Result (dBμV) | Limit (dBμV) | Margin (dB) |
|-----|-----|-----------------|----------------|----------|----------------|---------------|--------------|-------------|
| 1 | N | 0.1617 | 38.08 | QP | 10.14 | 48.22 | 65.38 | -17.16 |
| 2 | N | 0.1617 | 23.31 | AVG | 10.14 | 33.45 | 55.38 | -21.93 |
| 3 | N | 0.4152 | 40.66 | QP | 10.12 | 50.78 | 57.54 | -6.76 |
| 4 | N | 0.4152 | 30.86 | AVG | 10.12 | 40.98 | 47.54 | -6.56 |
| 5 | N | 0.8364 | 34.45 | QP | 10.14 | 44.59 | 56.00 | -11.41 |
| 6 | N | 0.8364 | 18.68 | AVG | 10.14 | 28.82 | 46.00 | -17.18 |
| 7 | N | 1.6632 | 33.00 | QP | 10.16 | 43.16 | 56.00 | -12.84 |
| 8 | N | 1.6632 | 18.10 | AVG | 10.16 | 28.26 | 46.00 | -17.74 |
| 9 | N | 4.4352 | 35.04 | QP | 10.20 | 45.24 | 56.00 | -10.76 |
| 10 | N | 4.4352 | 20.63 | AVG | 10.20 | 30.83 | 46.00 | -15.17 |
| 11 | N | 17.2896 | 25.73 | QP | 10.34 | 36.07 | 60.00 | -23.93 |
| 12 | N | 17.2896 | 13.36 | AVG | 10.34 | 23.70 | 50.00 | -26.30 |


6.7 Radiated Emissions & Restricted Band

| | |
|----------------------|---------------|
| Temperature | 26°C |
| Relative Humidity | 55% |
| Atmospheric Pressure | 1010mbar |
| Test date : | Sep 05 , 2019 |
| Tested By : | Aaron Liang |

Requirement(s):

| Spec | Item | Requirement | Applicable | | | | | | | | | | | | | | | | |
|--------------------------------------|---|---|---|-------------------------------------|-----------------------|-------------|-------------|-------------|--------------|------------|----|---------|-----|----------|-----|---------|-----|-----------|-----|
| 47CFR§15.247(d), RSS210 (A8.5) | a) | Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges | <input checked="" type="checkbox"/> | | | | | | | | | | | | | | | | |
| | | <table><tr><th>Frequency range (MHz)</th><th>Field Strength (µV/m)</th></tr><tr><td>0.009~0.490</td><td>2400/F(KHz)</td></tr><tr><td>0.490~1.705</td><td>24000/F(KHz)</td></tr><tr><td>1.705~30.0</td><td>30</td></tr><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></table> | | Frequency range (MHz) | Field Strength (µV/m) | 0.009~0.490 | 2400/F(KHz) | 0.490~1.705 | 24000/F(KHz) | 1.705~30.0 | 30 | 30 – 88 | 100 | 88 – 216 | 150 | 216 960 | 200 | Above 960 | 500 |
| | | Frequency range (MHz) | | Field Strength (µV/m) | | | | | | | | | | | | | | | |
| | | 0.009~0.490 | | 2400/F(KHz) | | | | | | | | | | | | | | | |
| | | 0.490~1.705 | | 24000/F(KHz) | | | | | | | | | | | | | | | |
| | | 1.705~30.0 | | 30 | | | | | | | | | | | | | | | |
| | | 30 – 88 | | 100 | | | | | | | | | | | | | | | |
| | | 88 – 216 | | 150 | | | | | | | | | | | | | | | |
| | 216 960 | 200 | | | | | | | | | | | | | | | | | |
| | Above 960 | 500 | | | | | | | | | | | | | | | | | |
| b) | For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required <input checked="" type="checkbox"/> 20 dB down <input type="checkbox"/> 30 dB down | <input checked="" type="checkbox"/> | | | | | | | | | | | | | | | | | |
| | c) | | or restricted band, emission must also comply with the radiated emission limits specified in 15.209 | <input checked="" type="checkbox"/> | | | | | | | | | | | | | | | |

Test Setup



Procedure

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:
 - a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen.
 - b. The EUT was then rotated to the direction that gave the maximum emission.
 - c. Finally, the antenna height was adjusted to the height that gave the maximum emission.
3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.



| | |
|-----------------|--------------------|
| Test Report No. | Q200102S012-FCC-R4 |
| Page | 26 of 39 |

| | |
|--------|--|
| | The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. 5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured. |
| Remark | |
| Result | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail |

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Result:

| | |
|------------|-------------------|
| Test Mode: | Transmitting Mode |
|------------|-------------------|

Frequency range: 9KHz - 30MHz

| Freq. (MHz) | Detection value | Factor (dB/m) | Reading (dBuV/m) | Result (dBuV/m) | Limit@3m (dBuV/m) | Margin (dB) |
|----------------|--------------------|------------------|---------------------|--------------------|----------------------|----------------|
| -- | -- | -- | -- | -- | -- | >20 |
| -- | -- | -- | -- | -- | -- | >20 |

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

Test Mode: Transmitting Mode

30MHz -1GHz




Test Data

Vertical Polarity Plot @3m

| No. | P/L | Frequency | Reading | Ant_F | PA_G | Cab_L | Result | Limit | Margin | Height | Degr ee |
|-----|-----|-----------|----------|--------|-------|-------|----------|----------|--------|--------|---------|
| | | (MHz) | (dBuV/m) | (dB/m) | (dB) | (dB) | (dBuV/m) | (dBuV/m) | (dB) | (cm) | (°) |
| 1 | H | 34.8500 | 36.02 | 17.00 | 22.25 | 0.15 | 30.92 | 40.00 | -9.08 | S | 169 |
| 2 | H | 199.7500 | 31.65 | 11.50 | 22.38 | 1.55 | 22.32 | 43.50 | -21.18 | 100 | 143 |
| 3 | H | 700.2700 | 24.63 | 21.50 | 21.36 | 2.41 | 27.18 | 46.00 | -18.82 | 200 | 217 |
| 4 | H | 896.2100 | 29.44 | 23.73 | 20.89 | 2.65 | 34.93 | 46.00 | -11.07 | 100 | 139 |
| 5 | H | 920.4600 | 26.62 | 23.49 | 20.84 | 2.67 | 31.94 | 46.00 | -14.06 | 100 | 143 |
| 6 | H | 993.2100 | 24.20 | 24.21 | 20.70 | 2.75 | 30.46 | 54.00 | -23.54 | 200 | 90 |

30MHz -1GHz



Test Data

Horizontal Polarity Plot @3m

| N o. | P/ L | Frequency (MHz) | Reading (dBuV/m) | Ant_F (dB/m) | PA_G (dB) | Cab_L (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Degr ee (°) |
|---------|---------|--------------------|---------------------|-----------------|--------------|---------------|--------------------|-------------------|----------------|----------------|-------------------|
| 1 | V | 34.8500 | 35.11 | 17.00 | 22.25 | 0.15 | 30.01 | 40.00 | -9.99 | 100 | 130 |
| 2 | V | 199.7500 | 32.03 | 11.50 | 22.38 | 1.55 | 22.70 | 43.50 | -20.80 | 100 | 74 |
| 3 | V | 790.4800 | 27.67 | 22.11 | 21.17 | 2.54 | 31.15 | 46.00 | -14.85 | 100 | 42 |
| 4 | V | 885.5400 | 27.35 | 23.26 | 20.92 | 2.64 | 32.33 | 46.00 | -13.67 | 100 | 19 |
| 5 | V | 935.0100 | 26.89 | 23.52 | 20.81 | 2.69 | 32.29 | 46.00 | -13.71 | 100 | 301 |
| 6 | V | 999.0300 | 25.79 | 24.37 | 20.69 | 2.76 | 32.23 | 54.00 | -21.77 | 100 | 68 |

Above 1GHz

| | |
|------------|-------------------|
| Test Mode: | Transmitting Mode |
|------------|-------------------|

Low Channel: GFSK Mode (Worst Case) (2402 MHz)

| ANTENNA POLARITY & test distance: HORIZONTAL at 3 m | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4804 | 49.87PK | 74 | -24.13 | 270 | 220 | 63.62 | -13.75 |
| 2 | 4804 | 34.86AV | 54 | -19.14 | 326 | 180 | 48.61 | -13.75 |
| ANTENNA POLARITY & test distance: Vertical at 3 m | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4804 | 49.68PK | 74 | -24.32 | 311 | 275 | 63.43 | -13.75 |
| 2 | 4804 | 34.87AV | 54 | -19.13 | 202 | 64 | 48.62 | -13.75 |

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)-Preamplifier Gain.
3. Only emissions significantly above equipment noise floor are reported.
4. Margin value = Emission level – Limit value.
5. The testing has been conformed to $10 \times 2402 \text{ MHz} = 24,020 \text{ MHz}$
6. X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

Middle Channel: GFSK Mode (Worst Case) (2440 MHz)

| ANTENNA POLARITY & test distance: HORIZONTAL at 3 m | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4804 | 49.65PK | 74 | -15.4 | 357 | 356 | 62.35 | -3.75 |
| 2 | 4804 | 34.77AV | 54 | -3.77 | 131 | 314 | 53.98 | -3.75 |
| ANTENNA POLARITY & test distance: Vertical at 3 m | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4804 | 49.76 PK | 74 | -24.24 | 221 | 57 | 63.51 | -13.75 |
| 2 | 4804 | 34.65 AV | 54 | -19.35 | 357 | 183 | 48.4 | -13.75 |

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)-Preamplifier Gain.
3. Only emissions significantly above equipment noise floor are reported.
4. Margin value = Emission level – Limit value.
5. The testing has been conformed to $10 \times 2440 \text{ MHz} = 24,400 \text{ MHz}$
6. X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

High Channel: GFSK Mode (Worst Case) (2480 MHz)

| ANTENNA POLARITY & test distance: HORIZONTAL at 3 m | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4960 | 50.47PK | 74 | -23.53 | 239 | 316 | 64.22 | -13.75 |
| 2 | 4960 | 35.59AV | 54 | -18.41 | 224 | 152 | 49.34 | -13.75 |
| ANTENNA POLARITY & test distance: Vertical at 3 m | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4960 | 50.14PK | 74 | -23.86 | 325 | 353 | 63.89 | -13.75 |
| 2 | 4960 | 35.26AV | 54 | -18.74 | 115 | 3 | 49.01 | -13.75 |

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)-Preamplifier Gain.
3. Only emissions significantly above equipment noise floor are reported.
4. Margin value = Emission level – Limit value.
5. The testing has been conformed to $10 \times 2462 \text{ MHz} = 24,620 \text{ MHz}$
- 6, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

Annex A. TEST INSTRUMENT

RE& RSE

Frequency Range Below 1GHz

| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Next Cal. |
|--------------------------|----------------|-----------|------------------------|-------------|-------------|
| EMI Test Receiver | Rohde&Schwarz | ESL6 | 1300.5001K06-100262-eQ | Apr. 04, 19 | Apr. 03, 20 |
| Bilog Antenna | Sunol Sciences | JB6 | A110712 | Apr. 08, 19 | Apr. 07, 20 |
| Active Antenna | CMO-POWER | AL-130 | 121031 | Mar. 27, 19 | Mar. 26, 20 |
| Signal Amplifier | HP | 8447E | 443008 | Mar. 28, 19 | Mar. 27, 20 |
| 3m Semi-anechoic Chamber | SAEMC | 9m*6m*6m | N/A | Oct. 18,18 | Oct. 17,21 |
| Test Software | EZ-EMC | ICP-03A1 | N/A | N/A | N/A |

RE& RSE

Frequency Range Above 1GHz

| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Next Cal. |
|---------------------|--------------|-----------|------------|-------------|-------------|
| Spectrum | Agilent | E4446A | MY46180622 | 8-May-19 | 7-May-20 |
| MXA signal analyzer | Agilent | N9020A | MY49100060 | Mar. 28, 19 | Mar. 27, 20 |
| Horn Antenna | COM-POWER | HAH-118 | 71259 | Mar. 22, 19 | Mar. 21, 20 |
| Horn Antenna | COM-POWER | HAH-118 | 71283 | Mar. 20, 19 | Mar. 19, 20 |



| | |
|-----------------|--------------------|
| Test Report No. | Q200102S012-FCC-R4 |
| Page | 33 of 39 |

| | | | | | |
|------------------|-----------------------------|-----------|-------------|-------------|-------------|
| SHF-EHF Horn | Schwarzbeck | BBHA9170 | BBHA9170147 | Jun. 30, 19 | Jun. 29, 20 |
| SHF-EHF Horn | Schwarzbeck | BBHA9170 | BBHA9170242 | Jun. 30, 19 | Jun. 29, 20 |
| AMPLIFIER | EM Electornic Corporation | EM01G26G | 60613 | Mar. 28, 19 | Mar. 27, 20 |
| AMPLIFIER | Emc Instruments Corporation | Emc012645 | 980077 | Jan. 04, 19 | Jan. 03,20 |
| 3m Semi-anechoic | SAEMC | 9m*6m*6m | N/A | Oct. 18,18 | Oct. 17,21 |
| Test Software | EZ-EMC | ICP-03A1 | N/A | N/A | N/A |

Antenna Port Conducted RF measurement

| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Next Cal. |
|----------------------------|--------------|--------------|--------------|-------------|-------------|
| Wireless Connectivity | R&S | CMW270 | 1201.0002K75 | Nov. 29, 18 | Nov. 28, 19 |
| MXA VEXTOR SIGNAL | Agilent | n5182a | MY50140530 | Mar. 28,19 | Mar. 27,20 |
| MXA signal analyzer | Agilent | n9020a | MY49100060 | Mar. 28,19 | Mar. 27,20 |
| RF Control Unit | Tonscend | JS0806-2 | 188060112 | Mar. 28,19 | Mar. 27,20 |
| Signal Generation | Agilent | E4421B | US40051152 | Nov. 29, 18 | Nov. 28, 19 |
| DC Power Supply | Agilent | E3640A | MY40004013 | Mar. 28,19 | Mar. 27,20 |
| Programmable Temperature & | Hongjin | HYC-TH-225DH | DG-180746 | Mar. 28,19 | Mar. 27,20 |




| | |
|-----------------|--------------------|
| Test Report No. | Q200102S012-FCC-R4 |
| Page | 34 of 39 |

| | | | | | |
|---------------------------------|---------------|---------------|-----------------------------|-------------|----------------|
| Test System | Tonscend | JS 1120- 3 | N/A | N/A | N/A |
| Power Splitter | Weinschel | 1580-1 | TL177 | Mar. 20,19 | Mar. 19,20 |
| Universal Radio Communication | ROHDE&SCHWARZ | CMU200 | 112012 | Mar. 28,19 | Mar. 27,20 |
| Universal Radio Communication | ROHDE&SCHWARZ | CMU200 | 121393 | Mar. 28,19 | Mar. 27,20 |
| Wireless Communication Test Set | ROHDE&SCHWARZ | CMW500 | 1201.0002K500- 155842-Gd | Aug. 06, 19 | Aug. 05, 20 |


Annex B. TEST SETUP AND SUPPORTING EQUIPMENT

Annex B.i. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions (Below 1GHz) .



Block Configuration Diagram for Radiated Emissions (Above 1GHz) .



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

| Manufacturer | Equipment Description | Model | Serial No |
|--------------|-----------------------|-------|-----------|
| N/A | N/A | N/A | N/A |

Supporting Cable:

| Cable type | Shield Type | Ferrite Core | Length | Serial No |
|------------|-------------|--------------|--------|-----------|
| N/A | N/A | N/A | N/A | N/A |



| | |
|-----------------|--------------------|
| Test Report No. | Q200102S012-FCC-R4 |
| Page | 39 of 39 |

Annex C. User Manual / Block Diagram / Schematics / Partlist/ DECLARATION OF SIMILARITY

Please see the attachment