

# RF EXPOSURE REPORT

## FOR

<b>Applicant</b>	:	Shenzhen KunHong Electronics Co., Ltd
<b>Address</b>	:	Suites 2108-2110, Tower C, Times Square Excellence, Baoan Center, Shenzhen, China
<b>Equipment under Test</b>	:	Bluetooth headset
<b>Model No.</b>	:	Eco IPX7 Earbuds
<b>Trade Mark</b>	:	N/A
<b>FCC ID</b>	:	2ATNH-AB2
<b>Manufacturer</b>	:	Qenla Electronic Technology (DongGuan) Co., Ltd.
<b>Address</b>	:	Qenla Industrial Park, No. 8 Qingfeng Road, Qinghutou Village, Tangxia Town, Dongguan, China

**Issued By: Dongguan Dongdian Testing Service Co., Ltd.**

**Add:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan  
City, Guangdong Province, China, 523808

**Tel:** +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

# REPORT

TABLE OF CONTENTS

Test report declares.....3

1. General information..... 5

1.1. Description of Equipment ..... 5

1.2. Assess laboratory ..... 5

2. RF Exposure evaluation ..... 5

## TEST REPORT DECLARE

<b>Applicant</b>	:	Shenzhen KunHong Electronics Co., Ltd
<b>Address</b>	:	Suites 2108-2110, Tower C, Times Square Excellence, Baoan Center, Shenzhen, China
<b>Equipment under Test</b>	:	Bluetooth headset
<b>Model No.</b>	:	Eco IPX7 Earbuds
<b>Trade mark</b>	:	N/A
<b>Manufacturer</b>	:	Qenla Electronic Technology (DongGuan) Co., Ltd.
<b>Address</b>	:	Qenla Industrial Park, No. 8 Qingfeng Road, Qinghutou Village, Tangxia Town, Dongguan, China

**Standard Used:** KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above.

The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

**After evaluation, our opinion is that the equipment In Accordance with above standard.**

<b>Report No:</b>	DDT-R21050721-2E04		
<b>Date of Receipt:</b>	May 14, 2021	<b>Date of Test:</b>	May 14, 2021 ~ May 25, 2021

**Prepared By:**

*Johnny Wang*

**Johnny Wang/Engineer**

**Approved By:**



**Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

### Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	May 26, 2021	

## 1. General information

### 1.1. Description of Equipment

EUT* Name	: Bluetooth headset
Model Number	: Eco IPX7 Earbuds
EUT function description	: Please reference user manual of this device
Power supply	: DC 5V by external AC Adapter : DC 3.7V by Polymer Li-ion built-in battery
Radio Specification	: Bluetooth V5.0
Operation frequency	: 2402MHz-2480MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK
Data rate	: 1 Mbps, 2 Mbps, 3 Mbps
Antenna Type	: PCB layout antenna, maximum PK gain: -0.58 dBi
Sample Type	: Series production

### 1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,  
Guangdong Province, China, 523808

Tel: +86-0769-38826678, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com)

## 2. RF Exposure evaluation

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

[2402MHz, 9 dBm, 7.94 mW(Tune up power)]

$(7.94/5) \cdot [\sqrt{2.402(\text{GHz})}] = 2.46 < 3.0$  for 1-g SAR

Worse case is as below: [2402MHz, 8.36 dBm, 6.85 mW (output power)]

$(6.85/5) \cdot [\sqrt{2.402(\text{GHz})}] = 2.12 < 3.0$  for 1-g SAR

Then SAR evaluation is not required.

**END OF REPORT**