

# FCC PART 15.225

# **TEST REPORT**

For

# **Advanced Card Systems Limited**

Units 4107 - 4110, 41st Floor, Manhattan Place, 23 Wang Tai Road, Kowloon Bay, Hong Kong

## FCC ID: V5MAMR220-C

Report Type:		Product Type:
Original Report		mPOS Reader
Report Number:	RSZ171010002	-00C
Report Date:	2017-11-03	
	Candy Li	Candry . Li
Reviewed By:	RF Engineer	0
Prepared By:	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

**Note**: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

## **TABLE OF CONTENTS**

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	
RELATED SUBMITTAL(S)/GRANT(S)	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY	
IESI FACILITY	4
SYSTEM TEST CONFIGURATION	5
JUSTIFICATION	5
EUT Exercise Software	5
EQUIPMENT MODIFICATIONS	5
EVERNAL VO CADIE	
BLOCK DIAGRAM OF TEST SETUR	
SUMMARY OF TEST RESULTS	
TEST EQUIPMENT LIST	8
ECOSIS 202 ANTENNIA DEOLIDEMENT	0
FCC§15.203 - ANTENNA REQUIREMENT	······9
APPLICABLE STANDARD	9
ANTENNA CONNECTED CONSTRUCTION	
FCC §15.207 – AC LINE CONDUCTED EMISSION	
APPLICABLE STANDARD	
EUT SETUP	10
EMI TEST RECEIVER SETUP	
1 EST PROCEDURE	
CORRECTED FACTOR & MARGIN CALCULATION	
TEST DATA	
ECC215 225 815 205 8 815 200 DADIATED EMICCIONS TEST	14
FCC915.225, 915.205 & 915.209 - KADIATED EMISSIONS TEST	
APPLICABLE STANDARD	
EUI SEIUP	
CORRECTED AMPLITUDE & MARGIN CALCULATION	15
Test Results Summary	
TEST DATA	16
FCC815.225(E) - FREOUENCY STABILITY	
Applicable Standard	18
Test Procedure	18
Test Data	
FCC815.215(C) - 20DB EMISSION BANDWIDTH	
REQUIREMENT	19
Test Procedure	
TEST DATA	

FCC Part 15.225

### **GENERAL INFORMATION**

#### **Product Description for Equipment under Test (EUT)**

The *Advanced Card Systems Limited's* product, model number: AMR220-C (*FCC ID: V5MAMR220-C*) or the "EUT" in this report was a *mPOS Reader*, which was measured approximately: 7.0 cm (L) \* 7.0 cm (W) \*1.5 cm (H), rated with input voltage: DC 3.7 V from battery or DC 5V from USB port.

\*All measurement and test data in this report was gathered from production sample serial number: 1702204 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2017-10-10.

#### Objective

This Type approval report is prepared on behalf of *Advanced Card Systems Limited* in accordance with Part 2- Subpart J, and Part 15-Subparts A and C of the Federal Communication Commissions rules.

The objective is to determine the compliance of the EUT with FCC rules, section 15.203, 15.205, 15.207, 15.209 and 15.225.

#### **Related Submittal(s)/Grant(s)**

Part 15.247 DTS submissions with FCC ID: V5MAMR220-C.

#### **Test Methodology**

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

#### **Measurement Uncertainty**

Parameter	uncertainty
Occupied Channel Bandwidth	±5%
RF Output Power with Power meter	±0.5dB
RF conducted test with spectrum	±1.5dB
AC Power Lines Conducted Emissions	±1.95dB
All emissions, radiated	±4.88dB
Temperature	±3°C
Humidity	±6%
Supply voltages	±0.4%

#### **Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

Bay Area Compliance Laboratories Corp. (Shenzhen) has been accredited to ISO/IEC 17025 by CNAS(Lab code: L2408). And accredited to ISO/IEC 17025 by NVLAP(Lab code: 200707-0), the FCC Designation No. CN5001 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Shenzhen) was registered with ISED Canada under ISED Canada Registration Number 3062B.

## SYSTEM TEST CONFIGURATION

#### Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

#### **EUT Exercise Software**

"SscomE32.exe" Exercise Software was used.

#### **Equipment Modifications**

No modification on the EUT.

### **Local Support Equipment**

Manufacturer	Description	Model	Serial Number
N/A	Contactless card	N/A	N/A
Xinsu	Adapter	XSG0501000CN	N/A

#### External I/O Cable

Cable Description	Length (m)	From/Port	То
Un-shielding Detachable USB Cable	1.0	EUT	Adapter

Report No.: RSZ171010002-00C

#### **Block Diagram of Test Setup**

For conducted emission



For radiated emission:



## SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207	AC Line Conducted Emission	Compliance
\$15.225 \$15.209 \$15.205	Radiated Emission Test	Compliance
§15.225(e)	Frequency Stability	Compliance
§15.215(c)	20dB Emission Bandwidth	Compliance

#### Report No.: RSZ171010002-00C

## **TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date		
Conducted Emissions Test							
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2017-08-04	2018-08-04		
Rohde & Schwarz	LISN	ENV216	3560.6650.12- 101613-Yb	2016-12-07	2017-12-07		
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2017-05-21	2017-11-19		
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR		
N/A	Conducted Emission Cable	N/A	UF A210B-1- 0720-504504	2017-05-12	2017-11-12		
Radiated Emission Test							
HP	Amplifier	HP8447E	1937A01046	2017-05-21	2017-11-19		
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2016-12-07	2017-12-07		
Sunol Sciences	Bi-log Antenna	JB1	A040904-2	2014-12-17	2017-12-16		
ETS	Passive Loop Antenna	6512	00029604	2014-12-24	2017-12-23		
Ducommun technologies	RF Cable	UFA210A-1- 4724-30050U	MFR64369 223410-001	2017-05-21	2017-11-19		
Ducommun technologies	RF Cable	104PEA	218124002	2017-05-21	2017-11-19		
Fluke	Digital Multimeter	287	19000011	2017-04-09	2018-04-09		
instek	DC Power Supply	GPS-3030DD	EM832096	NCR	NCR		
ESPEC	Temperature & Humidity Chamber	EL-10KA	09107726	2016-11-22	2017-11-22		

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## FCC§15.203 - ANTENNA REQUIREMENT

#### **Applicable Standard**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### **Antenna Connected Construction**

The EUT has an internal antenna arrangement, which was permanently attached, the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to EUT photos for details.

## FCC §15.207 – AC LINE CONDUCTED EMISSION

#### **Applicable Standard**

FCC§15.207

#### **EUT Setup**



2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

#### **EMI Test Receiver Setup**

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W	
150 kHz – 30 MHz	9 kHz	

#### **Test Procedure**

During the conducted emission test, the host PC was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

#### **Corrected Factor & Margin Calculation**

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

#### **Test Results Summary**

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_{\rm m} + U_{(Lm)} \le L_{\rm lim} + U_{\rm cispr}$$

In BACL,  $U_{(Lm)}$  is less than  $U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.

#### **Test Data**

#### **Environmental Conditions**

Temperature:	26 °C
<b>Relative Humidity:</b>	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Dylan Li on 2017-11-01.

Report No.: RSZ171010002-00C

EUT operation mode: Transmitting

#### AC 120 V/60 Hz, Line:



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.411790	40.7	20.2	57.6	16.9	QP
0.464870	25.2	20.2	56.6	31.4	QP
0.912410	32.4	20.1	56.0	23.6	QP
0.916350	32.7	20.1	56.0	23.3	QP
1.085890	31.8	20.1	56.0	24.2	QP
1.164690	28.5	20.1	56.0	27.5	QP
0.411790	35.2	20.2	47.6	12.4	Ave.
0.464870	18.3	20.2	46.6	28.3	Ave.
0.912410	25.3	20.1	46.0	20.7	Ave.
0.916350	24.8	20.1	46.0	21.2	Ave.
1.085890	24.9	20.1	46.0	21.1	Ave.
1.164690	23.6	20.1	46.0	22.4	Ave.



#### AC 120V/60 Hz, Neutral:

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.352750	40.0	20.2	58.9	18.9	QP
0.356570	38.0	20.2	58.8	20.8	QP
0.407910	39.3	20.2	57.7	18.4	QP
0.431430	32.8	20.2	57.2	24.4	QP
0.991210	36.0	20.1	56.0	20.0	QP
1.046370	34.5	20.1	56.0	21.5	QP
0.352750	29.5	20.2	48.9	19.4	Ave.
0.356570	26.6	20.2	48.8	22.2	Ave.
0.407910	32.1	20.2	47.7	15.6	Ave.
0.431430	24.5	20.2	47.2	22.7	Ave.
0.991210	28.2	20.1	46.0	17.8	Ave.
1.046370	28.4	20.1	46.0	17.6	Ave.

#### Note:

1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation

2) Corrected Amplitude = Reading + Correction Factor3) Margin = Limit - Corrected Amplitude

FCC Part 15.225

## FCC§15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST

#### **Applicable Standard**

As per FCC Part 15.225

(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

#### **EUT Setup**



Note: Antenna is set up at 1m during test for below 30MHz.

The radiated emission tests were performed in the 3-meter chamber a test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC Part Subpart C limits.

#### **EMI Test Receiver Setup**

According to FCC Rules, 47 CFR 15.33, the EUT emissions were investigated up to 1000 MHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
9 kHz – 150 kHz	300 Hz	1 kHz	/	QP
150 kHz –30 MHz	10 kHz	30 kHz	/	QP
30 MHz – 1000 MHz	100 kHz	300 kHz	/	QP

#### **Corrected Amplitude & Margin Calculation**

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Factor = Antenna Factor + Cable Loss- Amplifier Gain Corrected Amplitude = Meter Reading + Corrected Factor

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

#### **Test Results Summary**

According to the data in the following table, the EUT complied with the FCC §15.209.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL,  $U_{(Lm)}$  is less than  $U_{\text{cispr}}$ , if  $L_{\text{m}}$  is less than  $L_{\text{lim}}$ , it implies that the EUT complies with the limit.

#### Report No.: RSZ171010002-00C

#### **Test Data**

#### **Environmental Conditions**

Temperature:	26 °C
<b>Relative Humidity:</b>	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Dylan Li on 2017-10-10.

Test mode: Transmitting

1) Spurious Emissions (9 kHz~30 MHz):

Ind	icated		Correction Factor			Corrected	FCC Part 15.225	
Frequency	Maximum	im Detector Ai g PK/QP/Ave. Fac ) (d)	ector Ant. C	Cable	Cable Pre-Amp.	Amplitude (dBµV/m) @3m	Limit	
Range (MHz)	RangeReading(MHz)(dBµV)(@3m		Factor (dB)	Loss (dB)	Gain (dB)		(dBµV/m) @3m	Result
0.124	2.15	QP	64.5	0.10	0	66.75	105.74	Pass
26.54	11.95	QP	30.5	0.32	0	42.77	69.54	Pass
13.389	13.41	QP	32.1	0.2	0	45.71	80.5	Pass
13.552	17.14	QP	32.1	0.2	0	49.44	90.5	Pass
13.560	32.78	QP	32.1	0.2	0	65.08	124	Pass
13.568	16.24	QP	32.1	0.2	0	48.54	90.5	Pass
13.839	12.63	QP	32.1	0.2	0	44.93	80.5	Pass

Report No.: RSZ171010002-00C

#### 2) Spurious Emissions (Above 30 MHz):



Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
30.004062	22.64	307.0	Н	268.0	0.3	40.00	17.36
40.699250	29.89	100.0	V	135.0	-6.6	40.00	10.11
528.810125	34.96	105.0	V	170.0	4.1	46.00	11.04
691.689375	28.55	361.0	Н	191.0	6.3	46.00	17.45
794.822875	31.14	108.0	Н	242.0	8.9	46.00	14.86
986.179125	31.46	225.0	Н	330.0	9.6	46.00	14.54

#### Note:

1) Correction Factor =Antenna factor(Rx) + Cable Loss - Amplifier factor

2) Corrected Amplitude = Reading + Correction Factor
3) Margin = Limit - Corrected Amplitude

## FCC§15.225(e) - FREQUENCY STABILITY

#### **Applicable Standard**

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

#### **Test Procedure**

Frequency Stability vs. Temperature: The equipment under test was connected to PC, then to an external AC power supply and inductive antenna was connected to a Spectrum Analyzer. The EUT was placed inside the temperature chamber.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the Spectrum Analyzer.

Frequency Stability vs. Voltage: An external variable AC power supply Source. The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the end point. The output frequency was recorded for each voltage.

#### **Test Data**

#### **Environmental Conditions**

Temperature:	26 °C
<b>Relative Humidity:</b>	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Dylan Li on 2017-11-01.

Test Mode: Transmitting

Test Result: Pass

Voltage Supply (V <sub>DC</sub> )	Temperature (℃)	Measured Frequency (MHz)	Frequency Error (%)	Part 15.225 Limit
	-20	13.55923	-0.00568	±0.01%
	-10	13.55934	-0.00487	±0.01%
	0	13.55953	-0.00347	±0.01%
3.7	10	13.55973	-0.00199	±0.01%
	20	13.55962	-0.00280	±0.01%
	30	13.55961	-0.00288	±0.01%
	40	13.55982	-0.00133	±0.01%
	50	13.55919	-0.00597	±0.01%
3.15	20	13.55987	-0.00096	±0.01%
4.25	20	13.55922	-0.00575	±0.01%

FCC Part 15.225

## FCC§15.215(c) - 20dB EMISSION BANDWIDTH

#### Requirement

Per 15.215 (c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

#### **Test Procedure**

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT on the table of the chamber, Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.

#### **Test Data**

#### **Environmental Conditions**

Temperature:	26 °C
<b>Relative Humidity:</b>	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Dylan Li on 2017-10-17.

Test Mode: Transmitting

#### Test Result: Pass



#### 20 dB Emission Bandwidth

EUT Date: 17.0CT.2017 17:51:33

#### \*\*\*\*\* END OF REPORT \*\*\*\*\*

FCC Part 15.225

#### Report No.: RSZ171010002-00C